

# INTERNATIONAL STANDARD

# NORME INTERNATIONALE



**Electroacoustics – Audio-frequency induction loop systems for assisted hearing –  
Part 1: Methods of measuring and specifying the performance of system components**

**Électroacoustique – Systèmes de boucles d'induction audiofréquences pour améliorer l'audition –**

**Partie 1: Méthodes de mesure et de spécification des performances des composants de systèmes**





**THIS PUBLICATION IS COPYRIGHT PROTECTED**  
**Copyright © 2017 IEC, Geneva, Switzerland**

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland

Tel.: +41 22 919 02 11  
Fax: +41 22 919 03 00  
[info@iec.ch](mailto:info@iec.ch)  
[www.iec.ch](http://www.iec.ch)

#### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

#### About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

#### IEC Catalogue - [webstore.iec.ch/catalogue](http://webstore.iec.ch/catalogue)

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

#### IEC publications search - [www.iec.ch/searchpub](http://www.iec.ch/searchpub)

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

#### IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

#### Electropedia - [www.electropedia.org](http://www.electropedia.org)

The world's leading online dictionary of electronic and electrical terms containing 20 000 terms and definitions in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

#### IEC Glossary - [std.iec.ch/glossary](http://std.iec.ch/glossary)

65 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

#### IEC Customer Service Centre - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: [csc@iec.ch](mailto:csc@iec.ch).

#### A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

#### A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

#### Catalogue IEC - [webstore.iec.ch/catalogue](http://webstore.iec.ch/catalogue)

Application autonome pour consulter tous les renseignements bibliographiques sur les Normes internationales, Spécifications techniques, Rapports techniques et autres documents de l'IEC. Disponible pour PC, Mac OS, tablettes Android et iPad.

#### Recherche de publications IEC - [www.iec.ch/searchpub](http://www.iec.ch/searchpub)

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études,...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

#### IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

#### Electropedia - [www.electropedia.org](http://www.electropedia.org)

Le premier dictionnaire en ligne de termes électroniques et électriques. Il contient 20 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans 16 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

#### Glossaire IEC - [std.iec.ch/glossary](http://std.iec.ch/glossary)

65 000 entrées terminologiques électrotechniques, en anglais et en français, extraites des articles Termes et Définitions des publications IEC parues depuis 2002. Plus certaines entrées antérieures extraites des publications des CE 37, 77, 86 et CISPR de l'IEC.

#### Service Clients - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: [csc@iec.ch](mailto:csc@iec.ch).



IEC 62489-1

Edition 1.2 2017-11  
CONSOLIDATED VERSION

# INTERNATIONAL STANDARD

# NORME INTERNATIONALE



**Electroacoustics – Audio-frequency induction loop systems for assisted hearing –  
Part 1: Methods of measuring and specifying the performance of system components**

**Électroacoustique – Systèmes de boucles d'induction audiofréquences pour améliorer l'audition –**

**Partie 1: Méthodes de mesure et de spécification des performances des composants de systèmes**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

COMMISSION  
ELECTROTECHNIQUE  
INTERNATIONALE

ICS 17.140.50

ISBN 978-2-8322-5103-4

**Warning! Make sure that you obtained this publication from an authorized distributor.  
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**



# REDLINE VERSION

# VERSION REDLINE



**Electroacoustics – Audio-frequency induction loop systems for assisted hearing –  
Part 1: Methods of measuring and specifying the performance of system components**

**Électroacoustique – Systèmes de boucles d'induction audiofréquences pour améliorer l'audition –**

**Partie 1: Méthodes de mesure et de spécification des performances des composants de systèmes**

## CONTENTS

FOREWORD.....	4
1 Scope.....	6
2 Normative references .....	6
3 Terms and definitions .....	7
4 Rated values .....	7
5 Amplifiers .....	8
5.1 General.....	8
5.2 Rated conditions and standard measuring conditions .....	8
5.2.1 Rated conditions.....	8
5.2.2 Standard measurement conditions.....	9
5.3 Pre-conditioning .....	9
5.4 Characteristics to be specified, methods of measurement and presentation of results.....	9
5.4.1 Rated source impedance .....	9
5.4.2 Rated source e.m.f. ....	9
5.4.3 Rated load.....	10
5.4.4 Rated temperature-limited output current.....	10
5.4.5 Rated time for delivery of rated distortion-limited output current .....	10
5.4.6 Rated total harmonic distortion of the output current.....	10
5.4.7 Maximum (distortion-limited) output current .....	11
5.4.8 Compliance voltage .....	11
5.4.9 Noise.....	12
5.4.10 Magnetic field strength .....	13
5.4.11 Loop dimensions .....	13
5.4.12 Frequency response .....	14
5.4.13 Automatic gain control and compression.....	14
5.4.14 Phase error of quadrature networks for phased loop arrays .....	15
5.4.15 Installation.....	15
5.4.16 Physical characteristics .....	15
6 Microphones.....	16
6.1 General.....	16
6.2 Characteristics to be specified, methods of measurement and presentation of results.....	16
7 Other components .....	19
7.1 General.....	19
7.2 Characteristics to be specified, methods of measurement and presentation of results .....	19
8 Measurement uncertainty .....	19
9 Neck loops .....	16
9.1 Input voltage .....	16
9.1.1 Characteristic to be specified.....	16
9.1.2 Method of measurement .....	16
9.2 Input impedance.....	16
9.2.1 Characteristic to be specified.....	16
9.2.2 Method of measurement .....	16
9.2.3 Recommended values .....	16

9.3	Frequency response.....	17
9.3.1	Characteristic to be specified.....	17
9.3.2	Method of measurement.....	17
9.3.3	Presentation of results.....	17
9.3.4	Connector.....	17
10	Monitoring devices.....	17
10.1	General.....	17
10.2	Recommendations for fixed devices.....	17
10.3	Recommendations for portable devices.....	19
Annex A (informative)	Automatic gain control and compression.....	20
Annex B (informative)	Loop conductors and some typical impedance values.....	21
Annex C (informative)	Microphones.....	24
Annex D (normative)	Neck loops.....	25
Annex E (normative)	Test jig for measuring the performance of neck loops.....	27
Annex F (normative)	Specifications for loop listeners and assistive listening devices (ALDs).....	28
Bibliography.....		30
Figure A.1	– Typical steady-state output/input characteristics.....	20
Figure E.1	– Side view.....	27
Figure E.2	– Front view.....	27
Figure E.3	– Back view.....	27
Figure E.4	– Arrangement of the neck loop on the jig.....	27
Figure F.1	– Target frequency response.....	28
Table 1	– Types of fixed monitoring device.....	18
Table B.1	– Typical loop characteristics.....	22
Table B.2	– Cable characteristics.....	23
Table D.1	– Examples of performance of type 1 neck loop design.....	25

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

---

**ELECTROACOUSTICS –  
AUDIO-FREQUENCY INDUCTION LOOP  
SYSTEMS FOR ASSISTED HEARING –****Part 1: Methods of measuring and specifying  
the performance of system components**

## FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

**This consolidated version of the official IEC Standard and its amendments has been prepared for user convenience.**

**IEC 62489-1 edition 1.2 contains the first edition (2010-01) [documents 29/667/CDV and 29/668/RVC], its amendment 1 (2014-12) [documents 29/853/FDIS and 29/860/RVD] and its amendment 2 (2017-11) [documents 29/955/CDV and 29/963/RVC].**

**In this Redline version, a vertical line in the margin shows where the technical content is modified by amendments 1 and 2. Additions are in green text, deletions are in strikethrough red text. A separate Final version with all changes accepted is available in this publication.**



International Standard IEC 62489-1 has been prepared by IEC technical committee 29: Electroacoustics.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

This standard is to be used in conjunction with IEC 60118-4:2006, *Electroacoustics – Hearing aids – Part 4: Induction loop systems for hearing aid purposes – Magnetic field strength*.

A list of all the parts in the IEC 62489 series, under the general title *Electroacoustics – Audio-frequency induction loop systems for assisted hearing*, can be found on the IEC website.

The committee has decided that the contents of the base publication and its amendments will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

iTeh Standards  
(<https://standards.iteh.ai>)

**IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.**

[IEC 62489-1:2010](#)

<https://standards.iteh.ai/catalog/standards/iec/25540007-6607-454d-b007-d4d6763d6879/iec-62489-1-2010>

# ELECTROACOUSTICS – AUDIO-FREQUENCY INDUCTION LOOP SYSTEMS FOR ASSISTED HEARING –

## Part 1: Methods of measuring and specifying the performance of system components

### 1 Scope

This part of the IEC 62489 series applies to the components of audio-frequency induction-loop systems for assisted hearing. It may also be applied to such systems used for other purposes, as far as it is applicable. This standard is intended to encourage accurate and uniform presentation of manufacturers' specifications, which can be verified by standardized methods of measurement. It is intended for type testing.

The components considered are the following:

- amplifiers;
- microphones;
- other components, such as playback equipment.

This standard does not deal with safety, for which IEC 60065 applies. It also does not deal with EMC (Electromagnetic compatibility) and EMF (Electromagnetic fields, in the context of human exposure).

### 2 Normative references

[IEC 62489-1:2010](#)

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60118-4:~~2006~~ 2014, *Electroacoustics – Hearing aids – Part 4: Induction loop systems for hearing aid purposes – ~~Magnetic field strength~~ System performance requirements*

IEC 60268-1:1985, *Sound system equipment – Part 1: General*

IEC 60268-2:1987, *Sound system equipment – Part 2: Explanation of general terms and calculation methods*

IEC 60268-3:~~2000~~ 2013, *Sound system equipment – Part 3: Amplifiers*

IEC 60268-4:~~2004~~ 2014, *Sound system equipment – Part 4: Microphones*

IEC 60417, *Graphical symbols for use on equipment* (available at <http://www.graphical-symbols.info/equipment>)

IEC 60603-11:1992, *Connectors for frequencies below 3 MHz for use with printed boards – Part 11: Detail specification for concentric connectors (dimensions for free connectors and fixed connectors)*

IEC 61938:2013, ~~Audio, video and audiovisual Multimedia systems – Interconnections and matching values – Preferred matching values of analogue signals~~ *Guide to the recommended characteristics of analogue interfaces to achieve interoperability*

ISO/IEC Guide 98-3, *Uncertainty of measurement – Part 3: Guide to the expression of uncertainty in measurement (GUM:1995)*

### 3 Terms and definitions

For the purposes of this document, the following definition applies.

#### 3.1

##### **useful magnetic field volume**

volume within which the system provides hearing-aid users with a signal of acceptable quality (see 6.7 of IEC 60118-4:2006 2014)

#### 3.2

##### **phased loop array**

system of neighbouring loops in which the currents are not in phase with each other

#### 3.3

##### **neck loop**

small induction loop intended to be worn around the neck

NOTE See Annex D.

#### 3.4

##### **telecoil**

magnetic pickup coil intended to receive signals from an induction-loop system in accordance with IEC 60118-4

NOTE A telecoil can be part of a hearing aid or of any other device for receiving signals for an induction-loop system in accordance with IEC 60118-4.

#### 3.5

##### **loop listener**

system consisting of a portable amplifier incorporating a telecoil and headphones or earphones, intended to receive signals from an induction-loop system in accordance with IEC 60118-4

NOTE The functions of loop listener and assistive listening device (see 3.6) can be combined.

#### 3.6

##### **assistive listening device**

##### **ALD**

system consisting of a microphone, a portable amplifier and headphones, earphone or a neck loop

NOTE 1 This device is not the portable receiver described in Annex E of IEC 60118-4:2014, which includes measurement of magnetic field strength but no compensation for frequency-dependent hearing loss and AGC.

NOTE 2 This note applies to the French language only.

### 4 Rated values

The term “rated” means the value stated by the manufacturer. Rated values are of two kinds; rated conditions, fundamental values that can be determined only by the manufacturer, and others that can be measured. See 5.2.1. For a full explanation, see IEC 60268-2.

## 5 Amplifiers

### 5.1 General

In most systems, the amplifier(s) accepts input from microphone(s) and delivers current to the induction loop(s). If there are separate preamplifier or mixer and final amplifier components, the methods described can be used with the interpretation that input signals are applied to the preamplifier or mixer and measurements of output characteristics are made at the output of the final amplifier.

The characteristics to be specified are consistent with the lists in Annex C of IEC 60118-4:2006 2014.

NOTE For characteristics not mentioned in this standard, the provisions of IEC 60268-3 can be applied, with the provisions of 5.2 of this standard replacing those of 3.1 of IEC 60268-3:2000 2013.

### 5.2 Rated conditions and standard measuring conditions

#### 5.2.1 Rated conditions

The rated conditions for amplifiers are the following:

- rated power supply voltage;
- rated source impedance;
- rated source e.m.f. (electromotive force);
- rated load;
- rated temperature-limited output current;
- rated maximum time for delivery of rated distortion-limited output current (see below);
- rated total harmonic distortion of the output current;
- rated mechanical and climatic conditions.

NOTE 1 Total harmonic distortion and (distortion-limited) output current are interdependent. Both cannot be taken as rated conditions simultaneously because normally a given sample amplifier produces less than rated total harmonic distortion at rated output current.

NOTE 2 If the power supply frequency is critical, it is also a rated condition.

NOTE 3 The rated temperature-limited output current and the rated maximum time for delivery of rated distortion-limited output current need not be included in published specifications, provided they are supplied on request.

To obtain the correct conditions for measurements, the values for the above-mentioned rated conditions shall be taken from the manufacturer's specification. These values themselves are not subject to verification, but they constitute the basis for measuring the other characteristics.

Methods of measurement for these other characteristics are given in this standard and the manufacturer is required or permitted to state rated values for these characteristics in the specification of the equipment. These include

- rated maximum distortion limited output current;
- rated equivalent noise source e.m.f., or a measure of noise performance related to it.

An amplifier, considered as a four-terminal network with regard to a specified pair of input terminals and a specified pair of output terminals, shall be understood to be working under rated conditions when the following conditions are fulfilled:

- a) the amplifier is connected to its rated power supply;
- b) the source e.m.f. is connected in series with the rated source impedance to the input terminals;

- c) the output terminals are terminated with the rated load;
- d) the terminals which are not used during the measurement are terminated, if necessary, as specified by the manufacturer;
- e) the source e.m.f. is a sinusoidal voltage equal to the rated source e.m.f. at 1 000 Hz according to IEC 60268-1;
- f) the volume control, if any, is set to such a position that the rated distortion-limited output current appears at the output terminals;
- g) the tone controls, if any, are set to a specified position to give as flat a frequency response as possible;
- h) other controls, if any, are set to their normal positions as specified by the manufacturer;
- i) the climatic conditions given in Clause 8 of IEC 60268-1:1985 are complied with.

Amplifiers for which the rated distortion-limited output current exceeds the rated temperature-limited output current are likely to be subject to unacceptable effects when operated under rated conditions for an extended period of time. For these amplifiers, rated conditions shall be maintained for no longer than can be tolerated by the amplifier.

### 5.2.2 Standard measurement conditions

Standard measurement conditions are obtained by bringing the amplifier under rated conditions (see 5.2.1) and then reducing the output current to a level of –10 dB referred to the rated output current.

NOTE 1 Since testing for temperature rise is carried out according to IEC 60065 under conditions normally requiring an input source e.m.f. greater than that specified above, it is not expected that amplifier would overheat under standard measuring conditions.

NOTE 2 Many amplifiers have an output current control that can be adjusted for the above purpose. For an amplifier without such a control, the source e.m.f. can be adjusted instead.

### 5.3 Pre-conditioning

Immediately before any measurements are made, the amplifier shall be operated under standard measuring conditions for at least 10 min. The measurements may be made in any order.

### 5.4 Characteristics to be specified, methods of measurement and presentation of results

NOTE 5.4.1 to 5.4.5 describe rated conditions, which can be determined only by the manufacturer. See 5.2.1.

#### 5.4.1 Rated source impedance

##### 5.4.1.1 Characteristic to be specified

For each input, the internal impedance of the signal source, or range of acceptable impedances, stated by the manufacturer. This is a rated condition.

NOTE The relevant provisions of IEC 61938:2013 should be applied.

##### 5.4.1.2 Presentation of results

The value or range shall be stated in ohms or a suitable SI multiple, and is assumed to be a pure resistance unless otherwise stated.

#### 5.4.2 Rated source e.m.f.

##### 5.4.2.1 Characteristic to be specified

For each input, the e.m.f. of the signal source, stated by the manufacturer, which, when connected through the rated source impedance to the input, produces rated output current

into the rated load impedance, with all controls set as specified in 5.2.1. This is a rated condition.

NOTE The signal levels and impedance values given in IEC 61938:2013 should be applied.

#### **5.4.2.2 Presentation of results**

The value for each input shall be stated in volts or millivolts, or as a level in decibels referred to 1 V or 0,775 V. See IEC 60268-1.

#### **5.4.3 Rated load**

##### **5.4.3.1 Characteristic to be specified**

The load, stated by the manufacturer, to which the amplifier output shall be connected for measurement purposes. This is a rated condition.

NOTE 1 Example of values for typical loops are given in Annex B.

NOTE 2 It is essential that both the resistor and the inductor do not introduce amplitude distortion, and are able to carry the output current without overheating or changing in value. The inductor can usually be made as an air-cored component of acceptable size for use in measurements.

##### **5.4.3.2 Presentation of results**

The load shall be stated as a series combination of resistance and inductance.

#### **5.4.4 Rated temperature-limited output current**

##### **5.4.4.1 Characteristic to be specified**

The maximum output current, stated by the manufacturer, that can be delivered for an indefinite period to the rated load without unacceptable effects. This is a rated condition.

##### **5.4.4.2 Presentation of results**

[IEC 62489-1:2010](https://standards.iteh.ai/catalog/standards/iec/235a6ec9-68d9-45ed-b0b7-dad67b3d8f79/iec-62489-1-2010)

<https://standards.iteh.ai/catalog/standards/iec/235a6ec9-68d9-45ed-b0b7-dad67b3d8f79/iec-62489-1-2010>

The value is expressed in amperes.

#### **5.4.5 Rated time for delivery of rated distortion-limited output current**

##### **5.4.5.1 Characteristic to be specified**

The time, stated by the manufacturer, for which rated distortion-limited output current can be delivered to the rated load without unacceptable effects.

##### **5.4.5.2 Presentation of results**

The value is expressed in seconds or minutes.

NOTE A value of less than 30 s is likely to make some measurements difficult.

#### **5.4.6 Rated total harmonic distortion of the output current**

##### **5.4.6.1 Characteristic to be specified**

The value of total harmonic distortion, stated by the manufacturer, which is not exceeded when delivering the rated maximum (distortion-limited) current to the rated load. This is a rated condition.