

SLOVENSKI STANDARD SIST ISO 8301:1997

01-december-1997

Hcd`chbU']nc`UWJ^U'!'8c`c Ub^Y`hcd`chbY`i dcfbcgh]']b`gcfcXb]\``Ughbcgh]'j ghUMJcbUfbYa `ghUb1` !'AYf]`b]_'hcd`chbY[U'hc_U

Thermal insulation -- Determination of steady-state thermal resistance and related properties -- Heat flow meter apparatus

iTeh STANDARD PREVIEW

Isolation thermique -- Détermination de la résistance thermique et des propriétés connexes en régime stationnaire -- Méthode fluxmétrique

SIST ISO 8301:1997

Ta slovenski standard je istoveten z: 524ec/sist/4d3f63cc-6e0a-4046-944d-150 8301:1991

ICS:

27.220 Rekuperacija toplote. Toplotna izolacija Heat recovery. Thermal insulation

SIST ISO 8301:1997

en



iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ISO 8301:1997 https://standards.iteh.ai/catalog/standards/sist/4d3f63cc-6e0a-4046-944d-0e34fb5524ec/sist-iso-8301-1997



INTERNATIONAL STANDARD

ISO 8301

First edition 1991-08-01

Thermal insulation — Determination of steady-state thermal resistance and related properties — Heat flow meter apparatus

iTeh STANDARD PREVE Isolation thermique — Détermination de la résistance thermique et des propriétés connexes en régime stationnaire — Méthode fluxmétrique

SIST ISO 8301:1997 https://standards.iteh.ai/catalog/standards/sist/4d3f63cc-6e0a-4046-944d-0e34fb5524ec/sist-iso-8301-1997



Reference number ISO 8301:1991(E)

ISO 8301:1991(E)

Contents

	F	age				
Secti	ion 1 General	. 1				
1.1	Scope	. 1				
1.2	Normative references	. 1				
1.3	Definitions	. 1				
1.4	Symbols and units	. 3				
1.5	Significance	. 5				
1.6	Principle	6				
1.7	Limitations due to apparatus	6				
1.8	Limitations due to the specimens	. 7				
Section 2 Apparatus and calibration 9						
2.1	General (standards.iteh.a	9 1				
2.2	Apparatus SIST ISO 8301:1997	. 9				
2.3	Guidelines for apparlatus/designs.iteh.aj/catalog/standards/sist/4d3f63c 0e34fb5524ec/sist-iso-8301-199	c-16e0a-4046-944d- 7				
2.4	Calibration	16				
2.5	Performance check	19				
Secti	on 3 Test procedures	21				
3.1	General	21				
3.2	Test specimens	21				
3.3	Test method	23				
3.4	Procedures requiring multiple measurements	24				
3.5	Calculations	26				
3.6	Test report	27				

© ISO 1991 All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization Case Postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

Annexes

ļ	Limit values for apparatus performance and testing conditions 2	9
E	B Heat flow meters 3	2
C	Guidelines for estimation of maximum thickness of specimens in heat flow meter apparatus	4
C	Thermocouples	5
Ē	Bibliography	7

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ISO 8301:1997 https://standards.iteh.ai/catalog/standards/sist/4d3f63cc-6e0a-4046-944d-0e34fb5524ec/sist-iso-8301-1997

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

ISO/TC 163, Thermal insulation.

International Standard ISO 8301 was prepared by Technical Committee (standards.iteh.ai)

Annex A forms an integral part of this International Standard. Annexes B, C, D and E are for information only. SIST ISO 8301:1997

https://standards.iteh.ai/catalog/standards/sist/4d3f63cc-6e0a-4046-944d-0e34fb5524ec/sist-iso-8301-1997

SIST ISO 8301:1997

Introduction

0.1 Document subdivision

This International Standard is divided into three sections representing the most comprehensive assembly of information required to use the heat flow meter apparatus:

Section 1: General considerations

Section 2: Apparatus and calibration

Section 3: Test procedures

iTch ST section 3 for test purposes, he must also be familiar with the other two in order to obtain accurate and precise results. He must be particularly St knowledgeable about the general requirements. Section 2 is directed towards the constructor of the apparatus, but he also, in order to build good apparatus, must be familiar with the other sections.

https://standards.iteh.ai/catalog/standards/sist/4d3f63cc-6e0a-4046-944d-

0.2 Heat transfer and measured properties

A large number of tests are run on light-density porous materials. In such cases the actual heat transfer within them can involve a complex combination of different contributions of

- radiation;
- conduction both in the solid and in the gas phase;
- convection (in some operating conditions);

plus their interaction, together with mass transfer, especially in moist materials. Therefore, the heat transfer property, very often improperly called "thermal conductivity", calculated from a defined formula and the results of measurements of heat transfer rate, temperature difference and dimensions for a specimen may be not an intrinsic property of the material itself. This property, in accordance with ISO 9288, should therefore be called the "transfer factor" as it may depend on the test conditions (the transfer factor is often referred to elsewhere as apparent or effective thermal conductivity). The transfer factor may have a significant dependence on the thickness of the specimen and/or on the temperature difference for the same mean test temperature.

Heat transfer by radiation is the first source of dependence of the transfer factor on specimen thickness. As a consequence, not only the material properties but also the radiative characteristics of the surfaces bounding the specimen influence results. Thermal resistance is therefore the property that better describes the thermal behaviour of the specimen, provided that it is accompanied by information on the bounding surfaces.

If there is any possibility of the onset of convection within the specimen (e.g. in light mineral wool for low temperatures), the apparatus orientation, the thickness and the temperature difference can influence both the transfer factor and the thermal resistance. In such cases, as a minimum it is required that the geometry and the boundary conditions of the specimen tested be fully specified, even though information supplied in the test procedures does not cover these test conditions in detail. In addition, it will take considerable knowledge to evaluate the measurement as such, especially when applying the measured values in practice.

The influence of moisture within a specimen on the heat transfer during a measurement is also a very complex matter. Dried specimens only therefore ought to be tested according to standard procedures. Measurements on moist materials need additional precautions not covered in detail in this International Standard.

The knowledge of the physical principles is also extremely important when a heat transfer property, determined by this test method, is used to predict the thermal behaviour of a specific material in a practical application even though other factors such as workmanship can influence this behaviour.

0.3 Background required

The design and subsequent correct operation of a heat flow meter (HFM) apparatus (see 1.6.1 and 2.2.2) to obtain correct results and the interpretation of experimental results is a complex subject requiring great care. It is recommended that the designer, operator and user of measured data of the HFM apparatus should have a thorough background of knowledge of heat transfer mechanisms in the materials products and systems being evaluated, coupled with experience of electrical and temperature measurements particularly at low signal levels. Good laboratory practice in accordance with general test procedures should also be maintained.

The in-depth knowledge in each area cited may be different for the designer, operator, and data user.

0.4 Design, size, and national standards

Many different designs of heat flow meter apparatus exist worldwide to conform to present national standards. Continuing research and development is in progress to improve the apparatus and measurement techniques. Thus it is not practical to mandate a specific design or size of apparatus especially as total requirements may vary quite widely.

0.5 Guidelines supplied

Considerable latitude both in the temperature range and in the geometry of the apparatus is given to the designer of new equipment since various forms have been found to give comparable results. It is recommended that designers of new apparatus carefully read the comprehensive literature cited in annex E. After completion of new apparatus it is recommended that it should be checked by undertaking tests on one or more of the various reference materials of different thermal resistance levels now available. This International Standard outlines only the mandatory requirements necessary to design and operate heat flow meter apparatus in order to provide correct results. A table summarizing limit values for the apparatus performance and testing conditions stated in this International Standard is supplied in annex A. It also includes recommended procedures and practices plus suggested specimen dimensions which together should enhance general measurement levels and assist in improving inter-laboratory comparison and collaborative measurement programmes.

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST ISO 8301:1997</u> https://standards.iteh.ai/catalog/standards/sist/4d3f63cc-6e0a-4046-944d-0e34fb5524ec/sist-iso-8301-1997



iTeh This page Intentionally left blankEVIEW (standards.iteh.ai)

<u>SIST ISO 8301:1997</u> https://standards.iteh.ai/catalog/standards/sist/4d3f63cc-6e0a-4046-944d-0e34fb5524ec/sist-iso-8301-1997

Thermal insulation — Determination of steady-state thermal resistance and related properties — Heat flow meter apparatus

Section 1: General

1.1 Scope

1.1.1 This International Standard defines the use of the heat flow meter method (see 2.2.2) to measure the steady-state heat transfer through flat slab specimens and the calculation of the heat transfer properties of specimens.

This is a secondary or relative method since the ratio of the thermal resistance of the speciments) to the speciment of a standard speciment of a standard speciment is in a standard speciment of a

Reports conforming to this standard test method shall refer to specimens with thermal resistance greater than $0,1 \text{ m}^2 \text{-} \text{K/W}$ provided that thickness limits given in 1.7.2 are not exceeded.

1.1.2 If the specimens satisfy the requirements outlined in 1.8.1, the resultant properties shall be described as the thermal conductance and thermal resistance of the specimen.

1.1.3 If the specimens satisfy the requirements of 1.8.2, the resultant properties shall be described as the mean thermal conductivity of the specimen being evaluated.

1.1.4 If the specimens satisfy the requirements of 1.8.3, the resultant property may be described as the thermal conductivity or the transmissivity of the material being evaluated.

1.2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions

of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 8302:1991, Thermal insulation -- Determination of steady-state thermal resistance and related properties -- Guarded hot plate apparatus.

ISO 9229:--¹¹, Thermal insulation -- Materials, products and systems -- Vocabulary.

ISO 9251:1987, Thermal insulation — Heat transfer conditions and properties of materials — Vocabulary.

ISO 9288:1989, Thermal insulation — Heat transfer by radiation — Physical quantities and definitions.

ISO 9346:1987, Thermal insulation – Mass transfer – Physical quantities and definitions.

1.3 Definitions

For the purposes of this International Standard, the following definitions apply.

The following quantities are defined in ISO 7345 or ISO 9251:

¹⁾ To be published.

Quantity	Symbol	Units
Heat flow-rate	Φ	W
Density of heat flow-rate	9	W/m ²
Thermal resistance ¹⁾	R	m² ·K/W
Thermal conductance	Λ	W/(m² ⋅K)
Thermal conductivity ²⁾	λ	W/(m·K)
Thermal resistivity	r	m∙K/W
Porosity	ξ	
Local porosity	ξ	

1) In some cases it may be necessary to consider also the temperature difference divided by the heat flow rate; no special symbol is assigned to this quantity, sometimes also called resistance.

2) In the most general case \vec{q} and grad T do not

have the same orientation ($\vec{\lambda}$ is not defined through a single constant λ but through a matrix of constants); moreover conductivity changes while changing position within the body, while changing the temperature and changes with time.

The following definitions related to material properties are given in ISO 9251:

porous medium homogeneous medium hoterogeneous porous medium isotropic medium anisotropic medium stable medium parallel, flat isothermal faces and by adiabatic edges perpendicular to the faces, that is made of a material thermally homogeneous, isotropic (or anisotropic with a symmetry axis perpendicular to the faces), stable only within the precision of a measurement and the time required to execute it,

and with thermal conductivity λ or $\begin{bmatrix} \vec{\lambda} \\ \vec{\lambda} \end{bmatrix}$ constant or a linear function of temperature.

1.3.5 transfer factor of a specimen: Is defined by

$$\mathscr{T} = \frac{qd}{\Delta T} = \frac{d}{R} W(\mathbf{m} \cdot \mathbf{K})$$

It depends on experimental conditions and characterizes a **specimen** in relation with the combined conduction and radiation heat transfer. It is often referred to elsewhere as measured, equivalent, apparent or effective thermal conductivity of a **specimen**.

1.3.6 thermal transmissivity of a material: It is defined by

$$\lambda_{\rm t} = \frac{\Delta d}{\Delta R} \, {\rm W}/({\rm m} \cdot {\rm K})$$

iTeh STANDARD PREVIEW when Δd/ΔR is independent of the thickness d. It is independent of experimental conditions and characterizes an insulating material in relation with combined conduction and radiation. Thermal SIST ISO 8 transmissivity can be seen as the limit reached by https://standards.iteh.ai/catalog/standardhes/transfer factor in thick layers where combined 0e34fb5524ec/sist-conduction/and radiation heat transfer takes place.

Other terms not defined in ISO 7345 or ISO 9251:

1.3.1 thermally homogeneous medium: Is one in

which thermal conductivity $[\vec{\lambda}]$ is not a function of the position within the medium but may be a function of direction, time and temperature.

1.3.2 thermally isotropic medium: Is one in which

thermal conductivity $\begin{bmatrix} \lambda \\ \lambda \end{bmatrix}$ is not a function of direction but may be a function of the position with the me-

dium, of time and of the temperature ($[\vec{\lambda}]$ is defined through a single value λ in each point).

1.3.3 thermally stable medium: Is one in which

thermal conductivity λ or $[\vec{\lambda}]$ is not a function of time, but may be a function of the co-ordinates, of the temperature and, when applicable, of the direction.

1.3.4 mean thermal conductivity of a specimen: Is the property defined in steady-state conditions in a body that has the form of a slab bounded by two

It is often referred to elsewhere as equivalent, apparent or effective thermal conductivity of a material.

1.3.7 steady-state heat transfer property: Generic term to identify one of the following properties: thermal resistance, transfer factor, thermal conductivity, thermal resistivity, thermal transmissivity, thermal conductance, mean thermal conductivity.

1.3.8 room temperature: Generic term to identify a mean test temperature of a measurement such that a man in a room would regard it comfortable if it were the temperature of that room.

1.3.9 ambient temperature: Generic term to identify the temperature in the vicinity of the edge of the specimen or in the vicinity of the whole apparatus. This temperature is the temperature within the cabinet where the apparatus is enclosed or that of the laboratory for non-enclosed apparatus.

1.3.10 operator: Person responsible for carrying out the test on a heat flow meter apparatus and for the presentation through a report of measured results.

1.3.11 data user: Person involved in the application and interpretation of measured results to judge material or system performance.

1.3.12 designer: Person who develops the constructional details of an apparatus in order to

1.4 Symbols and units

meet predefined performance limits for the apparatus in assigned test conditions and who identifies test procedures to verify the predicted apparatus accuracy.

Symbol	Quantity	Units
Λ	Area measured on a selected isothermal surface, or metering area	m²
C _s	Specific heat capacity	J/(kg⁻K)
d	Thickness of specimen measured along a path normal to isothermal surfaces	m
d, d''	Thickness for each specimen in a two-specimen configuration HFM ap- paratus	m
$d_{\sf m}$	Mean thickness of a pair of two specimens	m
d_1 , d_2 ,, d_5	Thickness of specimens designated s_1 , s_2 ,, s_5	m
Dt	Maximum allowable distance between hot and cold plates during the test	m
e	Heat flow meter output	mV
f	Calibration factor of the heat flow meter	W/(mV·m²)
L	Length of the side of heat flow meter(s)	m
L_{m}	Length of the side of heat flow meter metering area	m
m _c	Relative mass change after conditioning	_
m _d	Relative mass change due to conditioning after drying	_
m _r	Relative mass change after drying	—
m _w	Relative mass change of a specimen during the test	
M_1	Mass in as-received condition	kg
M_2 http:	Mass after drying s://standards.iteh.ai/catalog/standards/sist/4d3f63cc-6e0a-4046-944d-	kg
M ₃	Mass after conditioning US4105524ec/sist-iso-8301-1997	kg
M_{4}	Mass after test	kg
M_5	Mass of dried or conditioned material, immediately before test	kg
q	Density of heat flow-rate	W/m ²
q', q"	Density of heat flow-rate for each specimen in a two-specimen config- uration HFM apparatus	W/m ²
r	Thermal resistivity	m [.] K/W
r _{avg}	Average thermal resistivity in a two-specimen configuration HFM appa- ratus	m·K/W
R	Thermal resistance	m² ⋅K/W
R _s	Thermal resistance of the standard specimen	m² ∙K/W
R _u	Thermal resistance of the unknown specimen	m² ∙K/W
R _t	Total thermal resistance in a two-specimen configuration HFM apparatus	m² ⋅K/W
<i>S</i> ₁ , <i>S</i> ₂ ,, <i>S</i> ₅	Set of specimens of different thicknesses	
T	Transfer factor of a specimen	W/(m·K)
$T_{\rm m} = (T_1 + T_2)/2$	Mean temperature	к
<i>T</i> ″ ₁ , <i>T</i> ″′ ₁	Hot side temperatures for each specimen in a two-specimen configura- tion HFM apparatus	к
T'_2 , T''_2	Cold side temperature for each specimen in a two-specimen configura- tion HFM apparatus	ĸ
T'm	Mean temperature of specimen (') in a two-specimen configuration HFM apparatus	к
<i>T"</i> ′ _m	Mean temperature of specimen ('') in a two-specimen configuration HFM apparatus	к