

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Maritime navigation and radiocommunication equipment and systems – Marine speed and distance measuring equipment (SDME) – Performance requirements, methods of testing and required test results

Matériels et systèmes de navigation et de radiocommunication maritimes – Equipements de mesurage de la vitesse et de la distance (SDME) – Exigences de performance, méthodes de test et résultats exigibles



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2007 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in 15 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

More than 60 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Catalogue IEC - webstore.iec.ch/catalogue

Application autonome pour consulter tous les renseignements bibliographiques sur les Normes internationales, Spécifications techniques, Rapports techniques et autres documents de l'IEC. Disponible pour PC, Mac OS, tablettes Android et iPad.

Recherche de publications IEC - www.iec.ch/searchpub

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études,...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire en ligne de termes électroniques et électriques. Il contient plus de 30 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans 15 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

Glossaire IEC - std.iec.ch/glossary

Plus de 60 000 entrées terminologiques électrotechniques, en anglais et en français, extraites des articles Termes et Définitions des publications IEC parues depuis 2002. Plus certaines entrées antérieures extraites des publications des CE 37, 77, 86 et CISPR de l'IEC.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: csc@iec.ch.

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Maritime navigation and radiocommunication equipment and systems – Marine speed and distance measuring equipment (SDME) – Performance requirements, methods of testing and required test results

Matériels et systèmes de navigation et de radiocommunication maritimes – Equipements de mesurage de la vitesse et de la distance (SDME) – Exigences de performance, méthodes de test et résultats exigibles

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 47.020.70

ISBN 978-2-8322-2190-7

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

CONTENTS

CONTENTS	2
FOREWORD.....	3
1 Scope.....	5
2 Normative references.....	5
3 Abbreviations.....	5
4 Minimum performance requirements	6
4.1 General	6
4.2 Methods of presentation	6
4.3 Accuracy of measurement	7
4.4 Roll and pitch	7
4.5 Construction and installation	7
5 Methods of testing and required test results	7
5.1 General	7
5.2 Test arrangements	7
5.3 Minimum depth	8
5.4 General requirements	8
5.5 SDME configuration.....	8
5.6 Optional facilities	8
5.7 System configuration	9
5.8 Methods of presentation	9
5.8.1 Speed.....	9
5.8.2 Distance run	9
5.8.3 Display	9
5.9 Distance run external output	9
5.9.1 Contact closure.....	9
5.9.2 Digital interface.....	10
5.10 Mode selection and indication	10
5.11 Additional speed indications.....	10
5.12 Accuracy of measurement	10
5.12.1 Indication of speed.....	10
5.12.2 Indication of distance run	11
5.13 Effects of environment.....	11
5.14 Roll and pitch	11
5.15 Construction and installation	11
Annex A (informative) Cross-references – IMO Resolution MSC.96(72) and the tests in this standard	13
Figure 1 – Ship speed velocity vectors.....	12

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**MARITIME NAVIGATION AND RADIOCOMMUNICATION
EQUIPMENT AND SYSTEMS –
MARINE SPEED AND DISTANCE MEASURING EQUIPMENT (SDME) –
PERFORMANCE REQUIREMENTS,
METHODS OF TESTING AND REQUIRED TEST RESULTS**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61023 has been prepared by IEC technical committee 80: Maritime navigation and radiocommunication equipment and systems.

This third edition cancels and replaces the second edition published in 1999. It constitutes a technical revision.

The main technical changes with regard to the previous edition are listed below:

- amendments resulting from changes to the IMO performance standards for SDME agreed in resolution MSC.96(72) in 2000. The amendments reduce the minimum depth of water under the keel for correct operation of the SDME to 2 m for a ground based equipment, reduce the accuracy required of analogue displays and add a requirement for a serial interface.

This bilingual version (2015-01) corresponds to the English version, published in 2007-06.

The text of this standard is based on the following documents:

FDIS	Report on voting
80/478/FDIS	80/484/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

The French version of this standard has not been voted upon.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

IEC 61023:2007

<https://standards.iteh.ai/catalog/standards/sist/53108259-8e21-4e9e-922e-f42df480bff6/iec-61023-2007>

MARITIME NAVIGATION AND RADIOCOMMUNICATION EQUIPMENT AND SYSTEMS – MARINE SPEED AND DISTANCE MEASURING EQUIPMENT (SDME) – PERFORMANCE REQUIREMENTS, METHODS OF TESTING AND REQUIRED TEST RESULTS

1 Scope

This International Standard specifies the minimum performance requirements, methods of testing and required test results of devices to indicate speed and distance – speed and distance measuring equipment (SDME) required by Regulation 19 of Chapter V of the International Convention for the Safety of Life at Sea (SOLAS), 1974, as amended, and which is associated with IEC 60945.

This standard is based upon the requirements of IMO Resolution MSC.96(72). The clause numbering of that resolution is indicated in parentheses in Clause 4 and all subclauses whose meaning is identical to that in the resolution are printed in italics.

In the tests of Clause 5, the corresponding requirement of Clause 4 is indicated in parentheses. The cross-references between the IMO performance standards in Resolution MSC.96(72) and the tests of this standard are summarized in Annex A.

2 Normative references

[IEC 61023:2007](http://standards.iteh.ai/IEC/61023-2007)

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60945:2002, *Maritime navigation and radiocommunication equipment and systems – General requirements – Methods of testing and required test results*

IEC 61162-1, *Maritime navigation and radiocommunication equipment and systems – Digital interfaces – Part 1: Single talker and multiple listeners*

IMO A.694(17), *General requirements for shipborne radio equipment forming part of the global maritime distress and safety system (GMDSS) and for electronic navigational aids*

IMO MSC.96(72), *Performance standards for devices to measure and indicate speed and distance*

3 Abbreviations

IMO International Maritime Organization
VBW Dual ground/water speed
VLW Distance travelled through the water

4 Minimum performance requirements

4.1 General

- a) (MSC.96(72)/A1.1/2) *Devices to measure and indicate speed and distance are intended for general navigational and ship manoeuvring use. The minimum requirement is to provide information on the distance run and the forward speed of the ship through the water or over the ground. Additional information on ship's motions other than in the forward axis may be provided. The equipment shall fully comply with this performance standard at forward speeds up to the maximum speed of the ship. Devices measuring speed and distance through the water shall meet the performance standard in water of depth greater than 3 m beneath the keel. Devices measuring speed and distance over the ground shall meet the performance standard in water of depth greater than 2 m beneath the keel.*

Radar plotting aids/track control equipment require a device capable of providing speed through the water in the fore-and-aft direction.

- b) (MSC.96(72)/A1.3) *In addition to the general requirements in Resolution A.694(17) as detailed in IEC 60945, devices to indicate speed and distance shall comply with the minimum performance requirements of this standard.*
- c) *Where SDME information is generated by one unit of equipment and is displayed on another unit, the combination of the two units shall be regarded as forming the SDME and shall be tested as an entity.*
- d) *Any facility provided by the equipment which is additional to the minimum requirements of this standard shall be tested to ensure that its operation (and, as far as is reasonably practicable, its malfunction) does not degrade the performance of the equipment.*
- e) *The system shall consist of a sensor and the necessary processing unit to convert the output signal of the sensor to speed and distance for display and for transmission to other equipment.*

4.2 Methods of presentation

IEC 61023:2007

- a) (MSC.96(72)/A2.1) *Speed information may be presented in either analogue or digital form. Where a digital display is used, its incremental steps shall not exceed 0,1 knots. Analogue displays shall be graduated at least every 0,5 knots and be marked with figures at least every 5 knots. If the display can present the speed of the ship in other than the forward direction, the direction of movement shall be indicated unambiguously.*
- b) (MSC.96(72)/A2.2) *Distance run information shall be presented in digital form. The display shall cover the range from 0 to not less than 9 999,9 nautical miles and the incremental steps shall not exceed 0,1 nautical miles. Where practicable, means shall be provided for resetting a read-out to zero.*
- c) (MSC.96(72)/A2.3) *The display shall be easily readable by day and by night.*
- d) (MSC.96(72)/A2.4) *Means shall be provided for transmitting measured speed and distance run information to other equipment fitted on board.*
- (i) (MSC.96(72)/A2.4.2) *When the equipment is used for measuring forward speed, then the information may be transmitted using closing contacts and, if so, this shall be in the form of one contact closure each 0,005 nautical miles run.*

The minimum contact closure time or equivalent pulse width shall be 50 ms.

(ii) (MSC.96(72)/A2.4.1) *The information on all speed and distance parameters, including direction, shall be transmitted in accordance with the relevant international marine interface standards.*

The equipment shall support at least the sentences VBW and VLW to IEC 61162-1.

- e) (MSC.96(72)/A2.5) *If equipment is capable of being operated in either the "speed through the water" or "speed over the ground" mode, mode selection and mode indication shall be provided.*

Where automatic mode selection is provided, the mode in use shall be indicated.

- f) (MSC.96(72)/A2.6) *If the equipment has provision for indicating speeds other than on a single fore-and-aft direction, then both the forward and athwart speeds shall be provided*

either through the water or over the ground. Resultant speed and direction information may be provided as a display-selectable option. All such information shall clearly indicate the direction, mode and validity status of the displayed information.

4.3 Accuracy of measurement

- a) (MSC.96(72)/A3.1) *Errors in measured and indicated speed, when the ship is operating free from shallow-water effect and from the effects of wind, sea bottom type, current and tide, shall not exceed the following:*
- *for a digital display – 2 % of the speed of the ship, or 0,2 knots whichever is greater;*
 - *for an analogue display – 2,5 % of the speed of the ship, or 0,25 knots, whichever is greater; and*
 - *for output data transmission – 2 % of the speed of the ship, or 0,2 knots, whichever is greater.*
- b) (MSC.96(72)/A3.2) *Errors in the indicated distance run, when the ship is operating free from shallow water effect and from the effects of wind, sea bottom type, current and tide, shall not exceed 2 % of the distance run by the ship in 1 h or 0,2 nautical miles in each hour whichever is the greater.*
- c) (MSC.96(72)/A3.3) *If the accuracy of devices to indicate speed and distance run can be affected by certain conditions (e.g. sea state and its effects, water temperature, salinity, sound velocity in water, depth of water under the keel, heel and trim of ship), details of possible effects shall be included in the equipment handbook.*

4.4 Roll and pitch

(MSC.96(72)/A4) *The performance of the equipment shall be such that it will meet the requirements of this standard when the ship is rolling up to $\pm 10^\circ$ and pitching up to $\pm 5^\circ$.*

Any degradation of performance at roll and pitch angles greater than those above shall be included in the equipment handbook.

4.5 Construction and installation

(MSC.96(72)/A5.1) *The system shall be so designed that neither the method of attachment of parts of the equipment to the ship nor damage occurring to any part of the equipment which penetrates the hull could result in the ingress of water to the ship.*

(MSC.96(72)/A5.2) *Where any part of the system is designed to extend from and retract into the hull of the ship, the design shall ensure that it can be extended, operated normally and retracted at all speeds up to the maximum speed of the ship. Its extended and retracted positions shall be clearly indicated at the display position.*

The handbook shall include the manufacturer's recommendations on the installation of the SDME, in particular the positioning of the sensor, as it affects the overall accuracy of the SDME.

5 Methods of testing and required test results

5.1 General

The manufacturer shall, unless otherwise agreed, set up the equipment and ensure that it is operating normally before testing commences.

5.2 Test arrangements

The general arrangements for the tests shall be as follows:

- a) where applicable, the units of the equipment shall be inter-connected by the longest electrical links for which the equipment has been designed. A link may be real or simulated;
- b) for tests to determine speed and distance measurement accuracy, the signals normally received from the sensor shall be simulated as applicable to the particular type of device being tested. Where practicable, the output of the sensor shall be measured to determine the characteristics of its output signal;
- c) where realistic simulation is not practicable, the manufacturer shall demonstrate, to the satisfaction of the laboratory or test house, that the equipment shall satisfy the accuracy requirements. At the discretion of the laboratory or test house, this may be carried out by demonstration or by installation on a ship at sea.

5.3 Minimum depth

(See 4.1.a).)

If the sensor technology used is sensitive to the water depth, the test signals used to verify speed and distance measurement accuracy of the equipment shall be created in such a way that the influence of water depth is simulated.

The speed and distance accuracy tests shall be carried out at non-critical depth conditions (depending upon the sensor type) and at various depths greater than and including 3 m beneath the keel for devices measuring speed and distance through the water and if applicable, 2 m for devices measuring speed and distance over the ground.

5.4 General requirements

(See 4.1.b).)

The equipment shall be tested to fulfil all applicable requirements of IEC 60945.

The relevant clauses/subclauses are the following:

- General – Operational (Clause 6), power supply (Clause 7)
- Environment – Dry heat (8.2), damp heat (8.3), low temperature (8.4), vibration (8.7)
 - For exposed units of the equipment – Rain (8.8)
 - For transducers – Immersion (8.9.1)
- EMC – Conducted (9.2), radiated (9.3), immunity (10.2 to 10.9)

NOTE Not 9.3, 10.4 and 10.9 for transducers.
- Special purpose (acoustic, etc.) (Clause 11), safety (Clause 12), maintenance (Clause 13), manuals (Clause 14), marking (Clause 15)

5.5 SDME configuration

(See 4.1.c).)

By inspection.

5.6 Optional facilities

(See 4.1.d).)

All components of the possible six speed components that are sensed (see Figure 1) by any specific SDME shall be tested for speed and distance accuracy as defined in 4.3 according to the table below.

Component (see explanation of symbols in Figure 1)	Speed accuracy	Distance accuracy (sailed distance)
V_{xg}	0,2 kn or 2 % of V_g	0,2 nm or 2 % over the ground
V_{yg}	0,2 kn or 2 % of V_g	0,2 nm or 2 % over the ground
V_g	0,2 kn or 2 % of V_g	0,2 nm or 2 % over the ground
V_{xw}	0,2 kn or 2 % of V_w	0,2 nm or 2 % through the water
V_{yw}	0,2 kn or 2 % of V_w	0,2 nm or 2 % through the water
V_w	0,2 kn or 2 % of V_w	0,2 nm or 2 % through the water

Any restrictions for the availability (for example water depth) of combinations of the optional speed/distance components shall be clearly stated in the manufacturer's handbook.

5.7 System configuration

(See 4.1.e.)

By inspection.

5.8 Methods of presentation

(See 4.2.)

5.8.1 Speed

(See 4.2.a.)

By inspection and during the tests for accuracy of measurement.

5.8.2 Distance run

(See 4.2.b.)

By inspection and during the tests for accuracy of measurement.

5.8.3 Display

(See 4.2.c.)

By inspection and during the tests for accuracy of measurement.

5.9 Distance run external output

(See 4.2.d.)

5.9.1 Contact closure

(See 4.2.d) (i.)

5.9.1.1 Method of test

The equipment shall be set up in accordance with 5.2 and the closures of each set of output contacts shall be recorded accurately while the simulated sensor signals are applied. A constant forward speed of at least 10 kn shall be applied during which a series of not less than 10 consecutive contact closures shall be recorded.

5.9.1.2 Results required

The contact closure time or equivalent pulse width shall be not less than 50 ms. The interval in distance between the occurrence of the leading edge of one contact closure and the next for at least 10 consecutive contact closures shall be within 2 % of 0,005 nautical miles.

5.9.2 Digital interface

(See 4.2.d) (ii).)

5.9.2.1 Method of test

The equipment shall be set up in accordance with 5.2. Test equipment fulfilling the requirements of IEC 61162-1 and capable of decoding correct messages and indication of all deviations from the correct message syntax shall be provided. A constant forward speed of at least 10 kn shall be applied, during which at least 1 000 consecutive messages shall be recorded.

If any operational status affects the message type or adds any proprietary message for instance for diagnostics, all relevant combinations of such status shall be used.

5.9.2.2 Results required

All characters of all received messages shall comply with VBW of IEC 61162-1. For systems where the total distance through the water counter value is stored in a central processing unit, the VLW message shall also be used for setting any connected distance counter(s).

If additional proprietary messages are generated in any operational mode, these messages shall comply with the proprietary message syntax of IEC 61162-1 and the composition be specified in detail in the equipment manual. The addition of such messages shall not in any way degrade the standard message(s).

5.10 Mode selection and indication

(See 4.2.e).)

By inspection.

5.11 Additional speed indications

(See 4.2.f).)

By inspection.

5.12 Accuracy of measurement

(See 4.3.)

5.12.1 Indication of speed

(See 4.3.a).)

5.12.1.1 Method of test

The equipment shall be set up in accordance with 5.2, and all outputs indicating speed shall be monitored while the sensor simulated signals are applied. A constant forward speed of 1 kn shall be applied for a period of not less than 15 min. This procedure shall then be repeated with the simulated speed being increased by increments of 1 kn up to a speed of 5 kn and thereafter by increments of 5 kn up to the maximum speed for which the equipment is designed.