

INTERNATIONAL STANDARD

NORME INTERNATIONALE



**Optical fibre cables –
Part 2-20: Indoor cables – Family specification for multi-fibre optical distribution
cables**

**Câbles à fibres optiques –
Partie 2-20: Câbles intérieurs – Spécification de famille pour les câbles de
distribution optiques multifibres**



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2008 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de la CEI ou du Comité national de la CEI du pays du demandeur.

Si vous avez des questions sur le copyright de la CEI ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de la CEI de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland
Email: inmail@iec.ch
Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: www.iec.ch/online_news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: www.iec.ch/webstore/custserv

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch
Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00

A propos de la CEI

La Commission Electrotechnique Internationale (CEI) est la première organisation mondiale qui élabore et publie des normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications CEI

Le contenu technique des publications de la CEI est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

- Catalogue des publications de la CEI: www.iec.ch/searchpub/cur_fut-f.htm

Le Catalogue en-ligne de la CEI vous permet d'effectuer des recherches en utilisant différents critères (numéro de référence, texte, comité d'études,...). Il donne aussi des informations sur les projets et les publications retirées ou remplacées.

- Just Published CEI: www.iec.ch/online_news/justpub

Restez informé sur les nouvelles publications de la CEI. Just Published détaille deux fois par mois les nouvelles publications parues. Disponible en-ligne et aussi par email.

- Electropedia: www.electropedia.org

Le premier dictionnaire en ligne au monde de termes électroniques et électriques. Il contient plus de 20 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans les langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International en ligne.

- Service Clients: www.iec.ch/webstore/custserv/custserv_entry-f.htm

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions, visitez le FAQ du Service clients ou contactez-nous:

Email: csc@iec.ch
Tél.: +41 22 919 02 11
Fax: +41 22 919 03 00

INTERNATIONAL STANDARD

NORME INTERNATIONALE



**Optical fibre cables –
Part 2-20: Indoor cables – Family specification for multi-fibre optical distribution
cables**

**Câbles à fibres optiques –
Partie 2-20: Câbles intérieurs – Spécification de famille pour les câbles de
distribution optiques multifibres**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

PRICE CODE
CODE PRIX

T

ICS 33.180.01

ISBN 978-2-88912-615-6

CONTENTS

| | |
|---|----|
| FOREWORD..... | 4 |
| 1 Scope..... | 6 |
| 2 Normative references | 6 |
| 3 Construction..... | 6 |
| 3.1 General..... | 6 |
| 3.2 Optical fibres and primary coating | 7 |
| 3.3 Buffer..... | 7 |
| 3.4 Ruggedised fibre..... | 7 |
| 3.5 Slotted core..... | 7 |
| 3.6 Tube..... | 7 |
| 3.7 Stranded tube..... | 7 |
| 3.8 Ribbon structure..... | 8 |
| 3.9 Strength and anti-buckling members | 8 |
| 3.10 Ripcord | 8 |
| 3.11 Sheath | 8 |
| 3.12 Sheath marking | 8 |
| 3.13 Identification..... | 8 |
| 3.14 Examples of cable constructions | 8 |
| 4 Tests..... | 8 |
| 4.1 Dimensions | 8 |
| 4.2 Mechanical requirements..... | 9 |
| 4.2.1 Cable tensile performance..... | 9 |
| 4.2.2 Cable crush..... | 9 |
| 4.2.3 Cable impact..... | 9 |
| 4.2.4 Cable bending..... | 10 |
| 4.2.5 Cable repeated bending | 10 |
| 4.2.6 Cable bending under tension | 10 |
| 4.2.7 Cable bending at low temperature | 10 |
| 4.2.8 Cable flexing..... | 10 |
| 4.2.9 Cable torsion..... | 10 |
| 4.2.10 Cable kink | 11 |
| 4.3 Environmental requirements – Temperature cycling | 11 |
| 4.4 Transmission requirements | 11 |
| 4.5 Fire performance..... | 11 |
| Annex A (informative) Examples of cable constructions | 13 |
| Annex B (informative) Family specification for multi-fibre optical distribution cables – Blank detail specification and minimum requirements | 18 |
| Bibliography..... | 24 |
| Figure A.1 – Example of cross-section of a 12 fibre distribution cable | 13 |
| Figure A.2 – Example of cross-section of a 36 fibre distribution cable | 13 |
| Figure A.3 – Example of cross-section of a 6 fibre break-out cable | 14 |
| Figure A.4 – Example of cross-section of a 24 fibre break-out cable | 14 |
| Figure A.5 – Example of cross-section of a slotted core type indoor cable with 4 fibre ribbons | 15 |

| | |
|--|----|
| Figure A.6 – Example of cross-section of an SZ (reverse oscillating lay) slotted core type indoor cable with 2 fibre ribbons | 15 |
| Figure A.7 – Example of cross-section of an SZ (reverse oscillating lay) slotted core type indoor cable with 4 fibre bundles | 16 |
| Figure A.8 – Example of multi-fibre unitube cable | 16 |
| Figure A.9 – Example of multi-fibre cable | 17 |
| Table 1 – Dimensions of buffered fibres | 7 |
| Table 2 – Sample temperature cycling values | 11 |
| Table B.1 – Cable description | 18 |
| Table B.2 – Cable element | 19 |
| Table B.3 – Cable construction | 20 |
| Table B.4 – Installation and operating conditions | 20 |
| Table B.5 – Tests applicable | 21 |
| Table B.6 – Specifications for industrial premises installations as defined in ISO/IEC 24702 | 22 |

iTeh STANDARD PREVIEW
(standards.iteh.ai)

IEC 60794-2-20:2008

[https://standards.iteh.ai/catalog/standards/sist/294828eb-8dec-414d-99bd-b396bdc6ac73/iec-](https://standards.iteh.ai/catalog/standards/sist/294828eb-8dec-414d-99bd-b396bdc6ac73/iec-60794-2-20-2008)

60794-2-20-2008

INTERNATIONAL ELECTROTECHNICAL COMMISSION

OPTICAL FIBRE CABLES –

**Part 2-20: Indoor cables –
Family specification for multi-fibre optical distribution cables**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60794-2-20 has been prepared by subcommittee 86A: Fibres and cables, of IEC technical committee 86: Fibre optics.

This second edition cancels and replaces the first edition published in 2003. It constitutes a technical revision.

The main changes from the previous edition include:

- cable crush to be measured both during and after load;
- cable torsion test length parameter correlated to cable outer diameter;
- cable description and construction blank detail specification annexes;
- MICE environment blank detail specification is addressed in Annex B.

This standard is to be used in conjunction with IEC 60794-1-1 and IEC 60794-1-2, and IEC 60794-2.

This bilingual version, published in 2011-07, corresponds to the English version.

The text of this standard is based on the following documents:

| CDV | Report on voting |
|--------------|------------------|
| 86A/1187/CDV | 86A/1221/RVC |

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

The French version of this standard has not been voted upon.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of IEC 60794 series, published under the general title *Optical fibre cables*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

OPTICAL FIBRE CABLES –

Part 2-20: Indoor cables – Family specification for multi-fibre optical distribution cables

1 Scope

This part of IEC 60794 is a family specification covering multi-fibre optical distribution cables for indoor use. The requirements of the sectional specification IEC 60794-2 are applicable to cables covered by this standard.

Annex B contains requirements that supersede the normal requirements in case the cables are intended to be used in installation governed by the MICE table of ISO/IEC 24702 (i.e. industrial premises).

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

They complete the normative references already listed in the generic specification (IEC 60794-1-1, Clause 2, and IEC 60794-1-2, Clause 2).

IEC 60189-1, *Low-frequency cables and wires with PVC insulation and PVC sheath – Part 1: General test and measuring methods*

IEC 60304, *Standard colours for insulation for low-frequency cables and wires*

IEC 60793-2-10, *Optical fibres – Part 2-10: Product specifications – Sectional specification for category A1 multimode fibres*

IEC 60793-2-50, *Optical fibres – Part 2-50: Product specifications – Sectional specification for class B single-mode fibres*

IEC 60794-2, *Optical fibre cables – Part 2: Indoor cables – Sectional specification*

IEC 60811-1-4, *Common test methods for insulating and sheathing materials of electric cables – Part 1: Methods for general application – Section four: Tests at low temperature*

IEC 62222, *Fire performance of communication cables installed in buildings*

3 Construction

3.1 General

In addition to the constructional requirements in IEC 60794-2, the following considerations apply to multi-fibre indoor cables.

The cable shall be designed and manufactured for an expected operating lifetime of at least 15 years. In this context, the attenuation at the operational wavelength(s) of the optical fibres contained in the installed cable shall not exceed values agreed between customer and

supplier. The materials in the cable shall not present a health or environmental hazard within its intended use.

There shall be no fibre splice in a delivery length unless otherwise agreed by customer and supplier.

It shall be possible to identify each individual fibre throughout the length of the cable.

3.2 Optical fibres and primary coating

A1 multimode fibres which meet the requirements of IEC 60793-2-10 or B1.1, B1.3, B6_a, and B6_b single-mode optical fibres which meet the requirements of IEC 60793-2-50 shall be used. The linear coefficient of optical fibre attenuation and attenuation point discontinuity may be affected by the cable manufacturing process. Maximum values for these optical characteristics shall be agreed between customer and supplier.

3.3 Buffer

If a tight or semi-tight (loosely applied) buffer is required, it shall consist of one or more layers of inert material. The buffer shall be easily removable. For tight buffers, the buffer and fibre primary coating shall be removable in one operation over a length of 15 mm to 25 mm, depending on customer requirements. For semi-tight buffers, the buffer shall be easily removable over a length of 0,3 m to 2,0 m.

Buffer dimensions are shown in Table 1.

Table 1 – Dimensions of buffered fibres

| <i>Buffer type</i> | <i>Nominal diameter</i> <i>mm</i> | <i>Tolerances</i> <i>mm</i> |
|--------------------------|--------------------------------------|--------------------------------|
| Semi-tight buffer | 0,3 - 1,3 | ±0,05 |
| Tight buffer | 0,3 - 1,0 | ±0,05 |

3.4 Ruggedised fibre

Further protection can be provided to tight or semi-tight secondary coated fibres by surrounding them with non-metallic strength members within a sheath of suitable material.

3.5 Slotted core

The slotted core is obtained by extruding a suitable material with a defined number of slots, providing helical or SZ (reverse-oscillating lay) configuration along the core. One or more primary coated fibres or optical elements such as ribbons or fibre bundles are located in each slot.

3.6 Tube

One or more primary coated or buffered fibres or ribbons are packaged (loosely or not) in a tube construction which may be filled. The tube may be reinforced with a composite wall.

3.7 Stranded tube

Multiple tubes, containing one or more primary coated or buffered fibres or ribbons, are stranded around a central member. For the sake of preserving cable geometry, some tubes may be "filler" or "empty" elements not containing optical fibres.

3.8 Ribbon structure

Ribbon structures shall conform to IEC 60794-3, 6.5 and 8.2.3. Fibres shall be arranged to be parallel and formed into ribbons so that the fibres remain parallel and do not cross over. Unless otherwise specified, each ribbon shall be uniquely identified with a printed legend or by uniquely colouring the reference fibre and/or by colouring the matrix material of the ribbon.

3.9 Strength and anti-buckling members

The cable shall be designed with sufficient strength members to meet installation and service conditions so that the fibres are not subjected to strain in excess of limits agreed between customer and supplier.

The strength and/or anti-buckling members may be either metallic or non-metallic and may be located in the cable core and/or under the sheath and/or in the sheath.

3.10 Ripcord

If required, a ripcord may be provided beneath the sheath.

3.11 Sheath

The cable shall have an overall protective sheath. The cable diameter shall be specified in the relevant blank detail specification (or product) specification.

3.12 Sheath marking

If required, the cable shall be marked as agreed between the customer and the supplier.

3.13 Identification

Optical fibres, secondary coatings and sub-unit sheaths shall be easily and uniquely identifiable through the use of a suitable colour code (i.e. IEC 60304) and/or an easily visible numbering scheme to be agreed between the customer and the supplier.

3.14 Examples of cable constructions

Examples of some main types of cable construction are shown in Annex A. Other configurations (e.g. multi-layer constructions) are not precluded if they meet the mechanical, environmental and transmission requirements given in this specification.

4 Tests

Compliance with relevant detail specification requirements shall be verified by carrying out tests selected from the following subclauses. It is not intended that all tests be carried out; the frequency of testing shall be agreed between the customer and the supplier.

Unless otherwise specified, all tests shall be carried out at ambient temperature. Attenuation measurements shall be conducted at the highest specified wavelength.

4.1 Dimensions

The fibre dimensions and tolerances shall be verified in accordance with test method IEC 60793-1-20, method C or IEC 60793-1-21. The diameter of the buffer and of the cable, as well as the thickness of the sheath, shall be measured in accordance with the methods of IEC 60189-1.

4.2 Mechanical requirements

Some of the following tests can be performed on a short sample length of cable which is still an integral part of a longer length. Thus it becomes possible to detect permanent changes in attenuation within the measurement uncertainty of the equipment used (see 3.8.2, Assessment of uncertainties in IEC 60794-1-2). The wavelength and maximum value of this attenuation change shall be agreed between the customer and the supplier.

4.2.1 Cable tensile performance

| | |
|---|---|
| Method: | IEC 60794-1-2-E1A and/or E1B |
| Diameter of chuck drums and transfer devices: | not smaller than the minimum bending diameter specified for the cable under load |
| Velocity of transfer device: | either 100 mm/min or 100 N/min |
| Load and duration: | 400 N or the weight of 1 km of cable, whichever is greater, and for a minimum period of 5 min |
| Length of sample: | sufficient to achieve the desired accuracy of measurement of attenuation change (typically 300 m) and shall be agreed between the customer and the supplier |
| Requirements: | for E1A there shall be no change in attenuation after the test, for E1B allowed fibre strain to be agreed between supplier and customer. There shall be no visible damage to the cable elements |

NOTE 1 Fibre strain above 60 % of the proof test of the all-glass fibre while under test load is not recommended.

NOTE 2 For certain applications specifying MICE classification of ISO/IEC 24702 and related standards, different load and duration values may be agreed between the customer and the supplier.

4.2.2 Cable crush

| | |
|--------------------------------|--|
| Method: | IEC 60794-1-2-E3 |
| Force during installation: | 500 N |
| Duration during installation: | 1 min |
| Force during operation: | ffs |
| Duration during operation: | ffs |
| Length between test locations: | 500 mm |
| Requirements: | no change in attenuation during the operational test and after the installation test. There shall be no visible damage to the cable elements |

NOTE For certain applications specifying MICE classification of ISO/IEC 24702 and related standards, different force values may be agreed between the customer and the supplier.

4.2.3 Cable impact

| | |
|-----------------------------|---|
| Method: | IEC 60794-1-2-E4 |
| Radius of striking surface: | 12,5 mm |
| Impact energy: | 1,0 J |
| Number of impacts: | at least 3, each separated by at least 500 mm |
| Requirements: | no fibre breakage |

NOTE For certain applications specifying MICE classification of ISO/IEC 24702 and related standards, impact energy values may be agreed between customer and supplier.

4.2.4 Cable bending

| | |
|----------------------------|-------------------------|
| Method: | IEC 60794-1-2-E11A |
| Mandrel diameter: | 20 times cable diameter |
| Number of turns per helix: | 6 |
| Number of cycles: | 10 |
| Requirements: | no fibre breakage |

NOTE For certain applications specifying MICE classification of ISO/IEC 24702 and related standards, different mandrel diameter values may be agreed between the customer and the supplier.

4.2.5 Cable repeated bending

| | |
|-------------------|---|
| Method: | IEC 60794-1-2-E6 |
| Bending radius: | 20 times cable diameter |
| Number of cycles: | 25 |
| Mass of weights: | 4 kg |
| Requirements: | under visual examination without magnification there shall be no damage to the sheath and to the cable elements |

4.2.6 Cable bending under tension

| | |
|-----------------|---|
| Method: | IEC 60794-1-2-E18 |
| Bending radius: | 20 times cable diameter |
| Load: | 400 N or weight of 1 km of cable, whichever is greater |
| Requirements: | no change in attenuation after the test, and there shall be no visible damage to the cable elements |

4.2.7 Cable bending at low temperature

| | |
|----------------------------|--|
| Method: | IEC 60794-1-2-E11A (see IEC 60811-1-4, Clause 8) |
| Bending radius: | 10 times cable diameter |
| Test temperature: | 0 °C, –10 °C or –15 °C depending on application and customer requirements |
| Number of turns per helix: | according to Clause 8 of IEC 60811-1-4 |
| Number of cycles: | 2 |
| Requirements: | in addition to the requirements of Clause 8 of IEC 60811-1-4, no fibre shall break during the test |

4.2.8 Cable flexing

| | |
|-------------------|-------------------------|
| Method: | IEC 60794-1-2-E8 |
| Number of cycles: | 100 |
| Pulley diameter: | 20 times cable diameter |
| Mass of weights: | 2 kg (minimum) |
| Requirements: | no fibre breakage |

NOTE For certain applications specifying MICE classification of ISO/IEC 24702 and related standards, different pulley diameter values may be agreed between the customer and the supplier.

4.2.9 Cable torsion

| | |
|--|--|
| Method: | IEC 60794-1-2-E7 |
| Number of cycles: | 10 |
| Distance between fixed and rotation clamp: | 125 times cable diameter but not more than 2,0 m |
| Tension load: | 20 N |

Requirements: no fibre breakage

NOTE For certain applications specifying MICE classification of ISO/IEC 24702 and related standards, different values for the number of cycles may be agreed between customer and supplier.

4.2.10 Cable kink

Method: IEC 60794-1-2-E10

Minimum loop diameter: 20 times cable diameter

Requirement: no kink shall occur

4.3 Environmental requirements – Temperature cycling

Method: IEC 60794-1-2-F1

Table 2 – Sample temperature cycling values

| | Low temperature T_A | High temperature T_B |
|-----------------|--------------------------|---------------------------|
| a) ^a | 0 °C | +50 °C |
| b) ^a | –5 °C | +50 °C |
| c) ^a | –20 °C | +60 °C |
| d) ^a | –40 °C | +75 °C |

^a Condition a), b) c) or d) shall be selected depending on application and customer requirements, for example condition c) is appropriate for applications to ISO/IEC 11801.

Period: t_1 = sufficient time such that the cable has reached thermal stability throughout its entire length at the specified temperature (e.g. 8 h $\leq t_1 \leq$ 24 h)

Number of cycles: 2

Length of sample: sufficient to achieve the desired accuracy of measurement of attenuation

Requirements: the wavelength and maximum increase in attenuation both at T_A and T_B and after returning to thermal stability at ambient temperature shall be agreed between the customer and the supplier

4.4 Transmission requirements

The transmission requirements shall be verified in accordance with IEC 60793-2 and shall be agreed between the customer and the supplier. Maximum cable attenuation shall comply with IEC 60794-1-1.

4.5 Fire performance

IEC/TR 62222 provides guidance and recommendations for the requirements and test methods for the fire performance of communication cables when installed in buildings. The recommendations relate to typical applications and installation practices, and an assessment of the fire hazards presented. Applicable legislation and regulation are also taken into account.

IEC/TR 62222 references several IEC fire performance test methods and also other test methods that may be required by local or National legislation and regulation. The tests to be applied, and the requirements, shall be agreed between the customer and supplier taking into

account the fire hazard presented by the end use application of the patchcord assembly in which the cable is intended to be used.


Withhold

iTeh STANDARD PREVIEW
(standards.iteh.ai)

IEC 60794-2-20:2008
<https://standards.iteh.ai/catalog/standards/sist/274828eb-8dec-414d-99bd-b396bdc6ac73/iec-60794-2-20-2008>


Annex A
(informative)

Examples of cable constructions



IEC 1992/08

Figure A.1 – Example of cross-section of a 12 fibre distribution cable



IEC 1993/08

Figure A.2 – Example of cross-section of a 36 fibre distribution cable