

INTERNATIONAL STANDARD

**Optical fibre cables –
Part 2-20: Indoor cables – Family specification for multi-fibre optical distribution
cables**

IEC 60794-2-20:2008

<https://standards.iteh.org/standards/standards/set/294828eb-8dec-414d-99bd-b396bdc6ac73/iec-60794-2-20-2008>

Withhold





THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2008 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland
Email: inmail@iec.ch
Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: www.iec.ch/online_news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: www.iec.ch/webstore/custserv

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch
Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00

INTERNATIONAL STANDARD

**Optical fibre cables –
Part 2-20: Indoor cables – Family specification for multi-fibre optical distribution
cables**

<https://standards.iteh.org/catalogue/standards/sist/274828eb-8dec-414d-99bd-b396bdc6ac73/iec-60794-2-20-2008>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE

T

ICS 33.180.01

ISBN 978-2-88910-291-4

CONTENTS

FOREWORD.....	4
1 Scope.....	6
2 Normative references	6
3 Construction.....	6
3.1 General.....	6
3.2 Optical fibres and primary coating	7
3.3 Buffer	7
3.4 Ruggedised fibre	7
3.5 Slotted core.....	7
3.6 Tube.....	7
3.7 Stranded tube.....	7
3.8 Ribbon structure.....	8
3.9 Strength and anti-buckling members	8
3.10 Ripcord	8
3.11 Sheath	8
3.12 Sheath marking	8
3.13 Identification.....	8
3.14 Examples of cable constructions	8
4 Tests.....	8
4.1 Dimensions	8
4.2 Mechanical requirements.....	9
4.2.1 Cable tensile performance.....	9
4.2.2 Cable crush.....	9
4.2.3 Cable impact.....	9
4.2.4 Cable bending.....	10
4.2.5 Cable repeated bending	10
4.2.6 Cable bending under tension	10
4.2.7 Cable bending at low temperature	10
4.2.8 Cable flexing.....	10
4.2.9 Cable torsion.....	10
4.2.10 Cable kink	11
4.3 Environmental requirements – Temperature cycling	11
4.4 Transmission requirements	11
4.5 Fire performance.....	11
Annex A (informative) Examples of cable constructions	13
Annex B (informative) Family specification for multi-fibre optical distribution cables – Blank detail specification and minimum requirements	18
Bibliography.....	24
Figure A.1 – Example of cross-section of a 12 fibre distribution cable.....	13
Figure A.2 – Example of cross-section of a 36 fibre distribution cable.....	13
Figure A.3 – Example of cross-section of a 6 fibre break-out cable	14
Figure A.4 – Example of cross-section of a 24 fibre break-out cable	14
Figure A.5 – Example of cross-section of a slotted core type indoor cable with 4 fibre ribbons	15

Figure A.6 – Example of cross-section of an SZ (reverse oscillating lay) slotted core type indoor cable with 2 fibre ribbons.....	15
Figure A.7 – Example of cross-section of an SZ (reverse oscillating lay) slotted core type indoor cable with 4 fibre bundles.....	16
Figure A.8 – Example of multi-fibre unitube cable.....	16
Figure A.9 – Example of multi-fibre cable.....	17
Table 1 – Dimensions of buffered fibres.....	7
Table 2 – Sample temperature cycling values.....	11
Table B.1 – Cable description.....	18
Table B.2 – Cable element.....	19
Table B.3 – Cable construction.....	20
Table B.4 – Installation and operating conditions.....	20
Table B.5 – Tests applicable.....	21
Table B.6 – Specifications for industrial premises installations as defined in ISO/IEC 24702.....	22

iTeh STANDARD PREVIEW
(standards.iteh.ai)

IEC 60794-2-20:2008

[https://standards.iteh.ai/catalog/standards/sist/274828eb-8dec-414d-99bd-b396bdc6ac73/iec-](https://standards.iteh.ai/catalog/standards/sist/274828eb-8dec-414d-99bd-b396bdc6ac73/iec-60794-2-20-2008)

60794-2-20-2008

Withhold

INTERNATIONAL ELECTROTECHNICAL COMMISSION

OPTICAL FIBRE CABLES –

**Part 2-20: Indoor cables –
Family specification for multi-fibre optical distribution cables**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60794-2-20 has been prepared by subcommittee 86A: Fibres and cables, of IEC technical committee 86: Fibre optics.

This second edition cancels and replaces the first edition published in 2003. It constitutes a technical revision.

The main changes from the previous edition include:

- cable crush to be measured both during and after load;
- cable torsion test length parameter correlated to cable outer diameter;
- cable description and construction blank detail specification annexes;
- MICE environment blank detail specification is addressed in Annex B.

This standard is to be used in conjunction with IEC 60794-1-1 and IEC 60794-1-2, and IEC 60794-2.

The text of this standard is based on the following documents:

CDV	Report on voting
86A/1187/CDV	86A/1221/RVC

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of IEC 60794 series, published under the general title *Optical fibre cables*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

OPTICAL FIBRE CABLES –

Part 2-20: Indoor cables – Family specification for multi-fibre optical distribution cables

1 Scope

This part of IEC 60794 is a family specification covering multi-fibre optical distribution cables for indoor use. The requirements of the sectional specification IEC 60794-2 are applicable to cables covered by this standard.

Annex B contains requirements that supersede the normal requirements in case the cables are intended to be used in installation governed by the MICE table of ISO/IEC 24702 (i.e. Industrial premises).

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

They complete the normative references already listed in the generic specification (IEC 60794-1-1, Clause 2, and IEC 60794-1-2, Clause 2).

IEC 60189-1, *Low-frequency cables and wires with PVC insulation and PVC sheath – Part 1: General test and measuring methods*

IEC 60304, *Standard colours for insulation for low-frequency cables and wires*

IEC 60793-2-10, *Optical fibres – Part 2-10: Product specifications – Sectional specification for category A1 multimode fibres*

IEC 60793-2-50, *Optical fibres – Part 2-50: Product specifications – Sectional specification for class B single-mode fibres*

IEC 60794-2, *Optical fibre cables – Part 2: Indoor cables – Sectional specification*

IEC 60811-1-4, *Common test methods for insulating and sheathing materials of electric cables – Part 1: Methods for general application – Section four: Tests at low temperature*

IEC 62222, *Fire performance of communication cables installed in buildings*

3 Construction

3.1 General

In addition to the constructional requirements in IEC 60794-2, the following considerations apply to multi-fibre indoor cables.

The cable shall be designed and manufactured for an expected operating lifetime of at least 15 years. In this context, the attenuation at the operational wavelength(s) of the optical fibres contained in the installed cable shall not exceed values agreed between customer and

supplier. The materials in the cable shall not present a health or environmental hazard within its intended use.

There shall be no fibre splice in a delivery length unless otherwise agreed by customer and supplier.

It shall be possible to identify each individual fibre throughout the length of the cable.

3.2 Optical fibres and primary coating

A1 multimode fibres which meet the requirements of IEC 60793-2-10 or B1.1, B1.3, B6_a, and B6_b single-mode optical fibres which meet the requirements of IEC 60793-2-50 shall be used. The linear coefficient of optical fibre attenuation and attenuation point discontinuity may be affected by the cable manufacturing process. Maximum values for these optical characteristics shall be agreed between customer and supplier.

3.3 Buffer

If a tight or semi-tight (loosely applied) buffer is required, it shall consist of one or more layers of inert material. The buffer shall be easily removable. For tight buffers, the buffer and fibre primary coating shall be removable in one operation over a length of 15 mm to 25 mm, depending on customer requirements. For semi-tight buffers, the buffer shall be easily removable over a length of 0,3 m to 2,0 m.

Buffer dimensions are shown in Table 1.

Table 1 – Dimensions of buffered fibres

Buffer type	Nominal diameter mm	Tolerances mm
Semi-tight buffer	0,3 - 1,3	±0,05
Tight buffer	0,3 - 1,0	±0,05

3.4 Ruggedised fibre

Further protection can be provided to tight or semi-tight secondary coated fibres by surrounding them with non-metallic strength members within a sheath of suitable material.

3.5 Slotted core

The slotted core is obtained by extruding a suitable material with a defined number of slots, providing helical or SZ (reverse-oscillating lay) configuration along the core. One or more primary coated fibres or optical elements such as ribbons or fibre bundles are located in each slot.

3.6 Tube

One or more primary coated or buffered fibres or ribbons are packaged (loosely or not) in a tube construction which may be filled. The tube may be reinforced with a composite wall.

3.7 Stranded tube

Multiple tubes, containing one or more primary coated or buffered fibres or ribbons, are stranded around a central member. For the sake of preserving cable geometry, some tubes may be "filler" or "empty" elements not containing optical fibres.

3.8 Ribbon structure

Ribbon structures shall conform to IEC 60794-3, 6.5 and 8.2.3. Fibres shall be arranged to be parallel and formed into ribbons so that the fibres remain parallel and do not cross over. Unless otherwise specified, each ribbon shall be uniquely identified with a printed legend or by uniquely colouring the reference fibre and/or by colouring the matrix material of the ribbon.

3.9 Strength and anti-buckling members

The cable shall be designed with sufficient strength members to meet installation and service conditions so that the fibres are not subjected to strain in excess of limits agreed between customer and supplier.

The strength and/or anti-buckling members may be either metallic or non-metallic and may be located in the cable core and/or under the sheath and/or in the sheath.

3.10 Ripcord

If required, a ripcord may be provided beneath the sheath.

3.11 Sheath

The cable shall have an overall protective sheath. The cable diameter shall be specified in the relevant blank detail specification (or product) specification.

3.12 Sheath marking

If required, the cable shall be marked as agreed between the customer and the supplier.

3.13 Identification

Optical fibres, secondary coatings and sub-unit sheaths shall be easily and uniquely identifiable through the use of a suitable colour code (i.e. IEC 60304) and/or an easily visible numbering scheme to be agreed between the customer and the supplier.

3.14 Examples of cable constructions

Examples of some main types of cable construction are shown in Annex A. Other configurations (e.g. multi-layer constructions) are not precluded if they meet the mechanical, environmental and transmission requirements given in this specification.

4 Tests

Compliance with relevant detail specification requirements shall be verified by carrying out tests selected from the following subclauses. It is not intended that all tests be carried out; the frequency of testing shall be agreed between the customer and the supplier.

Unless otherwise specified, all tests shall be carried out at ambient temperature. Attenuation measurements shall be conducted at the highest specified wavelength.

4.1 Dimensions

The fibre dimensions and tolerances shall be verified in accordance with test method IEC 60793-1-20, method C or IEC 60793-1-21. The diameter of the buffer and of the cable, as well as the thickness of the sheath, shall be measured in accordance with the methods of IEC 60189-1.

4.2 Mechanical requirements

Some of the following tests can be performed on a short sample length of cable which is still an integral part of a longer length. Thus it becomes possible to detect permanent changes in attenuation within the measurement uncertainty of the equipment used (see 3.8.2, Assessment of uncertainties in IEC 60794-1-2). The wavelength and maximum value of this attenuation change shall be agreed between the customer and the supplier.

4.2.1 Cable tensile performance

Method:	IEC 60794-1-2-E1A and/or E1B
Diameter of chuck drums and transfer devices:	not smaller than the minimum bending diameter specified for the cable under load
Velocity of transfer device:	either 100 mm/min or 100 N/min
Load and duration:	400 N or the weight of 1 km of cable, whichever is greater, and for a minimum period of 5 min
Length of sample:	sufficient to achieve the desired accuracy of measurement of attenuation change (typically 300 m) and shall be agreed between the customer and the supplier
Requirements:	for E1A there shall be no change in attenuation after the test, for E1B allowed fibre strain to be agreed between supplier and customer. There shall be no visible damage to the cable elements

NOTE 1 Fibre strain above 60 % of the proof test of the all-glass fibre while under test load is not recommended.

NOTE 2 For certain applications specifying MICE classification of ISO/IEC 24702 and related standards, different load and duration values may be agreed between the customer and the supplier.

4.2.2 Cable crush

Method:	IEC 60794-1-2-E3
Force during installation:	500 N
Duration during installation:	1 min
Force during operation:	ffs
Duration during operation:	ffs
Length between test locations:	500 mm
Requirements:	no change in attenuation during the operational test and after the installation test. There shall be no visible damage to the cable elements

NOTE For certain applications specifying MICE classification of ISO/IEC 24702 and related standards, different force values may be agreed between the customer and the supplier.

4.2.3 Cable impact

Method:	IEC 60794-1-2-E4
Radius of striking surface:	12,5 mm
Impact energy:	1,0 J
Number of impacts:	at least 3, each separated at least 500 mm
Requirements:	no fibre breakage

NOTE For certain applications specifying MICE classification of ISO/IEC 24702 and related standards, impact energy values may be agreed between customer and supplier.