



IEC 61158-2

Edition 4.0 2007-12

INTERNATIONAL STANDARD

Industrial communication networks – Fieldbus specifications –
Part 2: Physical layer specification and service definition

(<https://standards.iteh.ai>)

Document Preview

<https://standards.iteh.ai/cnclbg/standards/iec/2d85c882-93df-4a29-bcfa-fc59e8d67807/iec-61158-2-2007>



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2007 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembé
CH-1211 Geneva 20
Switzerland
Email: inmail@iec.ch
Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: www.iec.ch/online_news/vstpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: www.iec.ch/webstore/custserv

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch

<https://iec.ch/standardPreview>

Tel.: +41 22 919 02 11

Fax: +41 22 919 03 00



IEC 61158-2

Edition 4.0 2007-12

INTERNATIONAL STANDARD

Industrial communication networks – Fieldbus specifications –
Part 2: Physical layer specification and service definition

iTech Standard
(<https://standards.iteh.ai>)

Document Preview

IEC 61158-2:2007

<https://standards.iteh.ai/curl/g/standards/iec/3d85c882-93df-4a29-bcfa-fc59e8d67807/iec-61158-2-2007>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE

XH

ICS 25.040; 35.100; 35.240.50

ISBN 2-8318-9447-6

CONTENTS

FOREWORD	19
0 Introduction	21
0.1 General	21
0.2 Physical layer overview	21
0.3 Document overview	21
0.4 Major physical layer variations specified in this standard	22
1 Scope	25
2 Normative references	25
3 Terms and definitions	28
3.1 Common terms and definitions	28
3.2 Type 1: Terms and definitions	32
3.3 Type 2: Terms and definitions	35
3.4 Type 3: Terms and definitions	38
3.5 Type 4: Terms and definitions	41
3.6 Type 6: <i>This subclause has been removed</i>	42
3.7 Type 8: Terms and definitions	42
3.8 Type 12: Terms and definitions	45
3.9 Type 16: Terms and definitions	46
3.10 Type 18: Terms and definitions	49
4 Symbols and abbreviations	51
4.1 Symbols	51
4.2 Abbreviations	55
5 DLL – PhL interface	62
5.1 General	62
5.2 Type 1: Required services	62
5.3 Type 2: Required services	64
5.4 Type 3: Required services	67
5.5 Type 4: Required services	68
5.6 Type 6: <i>This subclause has been removed</i>	70
5.7 Type 8: Required services	70
5.8 Type 12: Required services	78
5.9 Type 16: Required services	80
5.10 Type 18: Required services	81
6 Systems management – PhL interface	83
6.1 General	83
6.2 Type 1: Systems management – PhL interface	83
6.3 Type 3: Systems management – PhL interface	85
6.4 Type 4: Systems management – PhL interface	91
6.5 Type 6: <i>This subclause has been removed</i>	91
6.6 Type 8: Systems management – PhL interface	91
6.7 Type 12: Systems management – PhL interface	96
6.8 Type 18: Systems management – PhL interface	96
7 DCE independent sublayer (DIS)	97
7.1 General	97
7.2 Type 1: DIS	97
7.3 Type 3: DIS	97

7.4	Type 6: <i>This subclause has been removed</i>	97
7.5	Type 8: DIS	98
7.6	Type 12: DIS	99
8	DTE – DCE interface and MIS-specific functions	99
8.1	General	99
8.2	Type 1: DTE – DCE interface	100
8.3	Type 3: DTE – DCE interface	110
8.4	Type 8: MIS – MDS interface	111
8.5	Type 12: DTE – DCE interface	120
9	Medium dependent sublayer (MDS)	120
9.1	General	120
9.2	Type 1: MDS: Wire and optical media	120
9.3	Type 1: MDS: Radio media	123
9.4	Type 2: MDS: Wire and optical media	123
9.5	Type 3: MDS: Wire and optical media	125
9.6	Type 4: MDS: Wire medium	125
9.7	Type 6: <i>This subclause has been removed</i>	130
9.8	Type 8: MDS: Wire and optical media	130
9.9	Type 12: MDS: Wire media	137
9.10	Type 16: MDS: Optical media	139
9.11	Type 18: MDS: Wire media	140
10	MDS — MAU interface	141
10.1	General	141
10.2	Type 1: MDS — MAU interface: Wire and optical media	141
10.3	Type 1: MDS — MAU interface: Radio signaling	143
10.4	Type 2: MDS — MAU interface: Wire and optical media	143
10.5	Type 3: MDS — MAU interface: Wire and optical media	145
10.6	Type 8: MDS — MAU interface: Wire and optical media	145
10.7	Type 18: MDS — MAU interface: Wire media	147
11	Types 1 and 7: Medium attachment unit: voltage mode, linear-bus-topology 150 Ω twisted-pair wire medium	149
11.1	General	149
11.2	Bit-rate-dependent quantities	149
11.3	Network specifications	150
11.4	MAU transmit circuit specification	152
11.5	MAU receive circuit specification	156
11.6	Jabber inhibit	158
11.7	Power distribution	158
11.8	Medium specifications	161
12	Types 1 and 3: Medium attachment unit: 31,25 kbit/s, voltage-mode with low-power option, bus- and tree-topology, 100 Ω wire medium	164
12.1	General	164
12.2	Transmitted bit rate	164
12.3	Network specifications	164
12.4	MAU transmit circuit specification	167
12.5	MAU receive circuit specification	170
12.6	Jabber inhibit	171
12.7	Power distribution	171
12.8	Medium specifications	177

12.9 Intrinsic safety.....	180
12.10 Galvanic isolators.....	181
13 Type 1: Medium attachment unit: current mode, twisted-pair wire medium.....	181
13.1 General	181
13.2 Transmitted bit rate	181
13.3 Network specifications.....	181
13.4 MAU transmit circuit specification.....	183
13.5 MAU receive circuit specification	185
13.6 Jabber inhibit	187
13.7 Power distribution.....	188
13.8 Medium specifications	189
14 Type 1: Medium attachment unit: current mode (1 A), twisted-pair wire medium.....	191
14.1 General	191
14.2 Transmitted bit rate	191
14.3 Network specifications.....	191
14.4 MAU transmit circuit specification.....	193
14.5 MAU receive circuit specification	195
14.6 Jabber inhibit	196
14.7 Power distribution.....	196
14.8 Medium specifications	198
15 Types 1 and 7: Medium attachment unit: dual-fiber optical media	199
15.1 General	199
15.2 Bit-rate-dependent quantities	199
15.3 Network specifications	200
15.4 MAU transmit circuit specifications	201
15.5 MAU receive circuit specifications	202
15.6 Jabber inhibit	203
15.7 Medium specifications	204
16 Type 1: Medium attachment unit: 31,25 kbit/s, single-fiber optical medium	206
16.1 General	206
16.2 Transmitted bit rate	206
16.3 Network specifications.....	206
16.4 MAU transmit circuit specifications	206
16.5 MAU receive circuit specifications	207
16.6 Jabber inhibit	207
16.7 Medium specifications	208
17 Type 1: Medium attachment unit: radio signaling	210
17.1 General	210
17.2 Transmit signaling rate	210
17.3 Modulation	210
17.4 Network specification	212
17.5 Antennas	216
17.6 Jabber inhibit	216
17.7 Common air interface	217
18 Type 2: Medium attachment unit: 5 Mbit/s, voltage-mode, coaxial wire medium	221
18.1 General	221
18.2 Transceiver: 5 Mbit/s, voltage-mode, coaxial wire.....	221
18.3 Transformer 5 Mbit/s, voltage-mode, coaxial wire	226

18.4	Connector 5 Mbit/s, voltage-mode, coaxial wire medium.....	227
18.5	Topology 5 Mbit/s, voltage-mode, coaxial wire medium	227
18.6	Taps 5 Mbit/s, voltage-mode, coaxial wire medium.....	229
18.7	Trunk 5 Mbit/s, voltage-mode, coaxial wire medium.....	231
19	Type 2: Medium attachment unit: 5 Mbit/s, optical medium	232
19.1	General	232
19.2	Transceiver 5 Mbit/s, optical medium.....	232
19.3	Topology 5 Mbit/s, optical medium	233
19.4	Trunk fiber 5 Mbit/s, optical medium	233
19.5	Trunk connectors 5 Mbit/s, optical medium	234
19.6	Fiber specifications 5 Mbit/s, optical medium	234
20	Type 2: Medium attachment unit: network access port (NAP)	237
20.1	General	237
20.2	Signaling	238
20.3	Transceiver	239
20.4	Connector	239
20.5	Cable	239
21	Type 3: Medium attachment unit: synchronous transmission, 31,25 kbit/s, voltage mode, wire medium	241
21.1	General	241
21.2	Transmitted bit rate	241
21.3	Network specifications.....	241
21.4	Transmit circuit specification for 31,25 kbit/s voltage-mode MAU	244
21.5	Receive circuit specification for 31,25 kbit/s voltage-mode MAU.....	247
21.6	Jabber inhibit	247
21.7	Power distribution	248
21.8	Medium specifications	250
21.9	Intrinsic safety	252
21.10	Galvanic Isolators.....	252
21.11	Coupling elements	252
21.12	Power supply.....	254
22	Type 3: Medium attachment unit: asynchronous transmission, wire medium	259
22.1	Medium attachment unit for non intrinsic safety	259
22.2	Medium attachment unit for intrinsic safety.....	264
23	Type 3: Medium attachment unit: asynchronous transmission, optical medium	276
23.1	Characteristic features of optical data transmission	276
23.2	Basic characteristics of an optical data transmission medium	277
23.3	Optical network	277
23.4	Standard optical link	278
23.5	Network structures built from a combination of standard optical links	278
23.6	Bit coding	278
23.7	Optical signal level	278
23.8	Temporal signal distortion	281
23.9	Bit error rate.....	285
23.10	Connectors for fiber optic cable	285
23.11	Redundancy in optical transmission networks.....	285
24	Type 4: Medium attachment unit: RS-485	285
24.1	General	285

24.2 Overview of the services	285
24.3 Description of the services	286
24.4 Network.....	286
24.5 Electrical specification.....	286
24.6 Time response	286
24.7 Interface to the transmission medium	286
24.8 Specification of the transmission medium	287
25 Type 4: Medium attachment unit: RS-232	288
25.1 General	288
25.2 Overview of the services	288
25.3 Description of the services	288
26 Type 6: <i>This clause has been removed</i>	288
27 Type 8: Medium attachment unit: twisted-pair wire medium	289
27.1 MAU signals	289
27.2 Transmission bit rate dependent quantities.....	289
27.3 Network.....	290
27.4 Electrical specification.....	290
27.5 Time response	290
27.6 Interface to the transmission medium	290
27.7 Specification of the transmission medium	291
28 Type 8: Medium attachment unit: optical media	294
28.1 General	294
28.2 Transmission bit rate dependent quantities.....	294
28.3 Network topology.....	294
28.4 Transmit circuit specifications	295
28.5 Receive circuit specifications.....	296
28.6 Specification of the transmission medium	297
29 Type 12: Medium attachment unit: electrical medium	301
29.1 Electrical characteristics.....	301
29.2 Medium specifications	301
29.3 Transmission method	301
30 Type 16: Medium attachment unit: optical fiber medium at 2, 4, 8 and 16 Mbit/s	303
30.1 Structure of the transmission lines.....	303
30.2 Time performance of bit transmission	303
30.3 Connection to the optical fiber	310
31 Type 18: Medium attachment unit: basic medium.....	317
31.1 General	317
31.2 Data signal encoding	317
31.3 Signal loading	317
31.4 Signal conveyance requirements	317
31.5 Media	318
31.6 Endpoint and branch trunk cable connectors	320
31.7 Recommended type 18-PhL-B MAU circuitry	320
32 Type 18: Medium attachment unit: powered medium.....	321
32.1 General	321
32.2 Data signal encoding	321
32.3 Signal loading	321
32.4 Signal conveyance requirements	321

32.5 Media	322
32.6 Endpoint and branch trunk cable connectors	325
32.7 Embedded power distribution	325
32.8 Recommended type 18-PhL-P MAU circuitry	327
Annex A (normative) Type 1: Connector specification	329
A.1 Internal connector for wire medium.....	329
A.2 External connectors for wire medium	330
Annex B (informative) Types 1 and 3: Cable specifications and trunk and spur lengths for the 31,25 kbit/s voltage-mode MAU	337
B.1 Cable description and specifications.....	337
B.2 Typical trunk and spur lengths	337
Annex C (informative) Types 1 and 7: Optical passive stars	339
C.1 Definition.....	339
C.2 Example of attenuations	339
Annex D (informative) Types 1 and 7: Star topology	340
D.1 Examples of topology	340
D.2 Optical power budget	341
D.3 Mixed with wire media	342
Annex E (informative) Type 1: Alternate fibers	344
E.1 Alternate fibers for dual-fiber mode.....	344
E.2 Alternate fibers for single-fiber mode	344
Annex F (normative) Type 2: Connector specification	345
F.1 Connector for coaxial wire medium	345
F.2 Connector for optical medium.....	345
F.3 Connector for NAP medium	346
Annex G (normative) Type 2: Repeater machine sublayers (RM, RRM) and redundant PhLs.....	348
G.1 General.....	348
G.2 Repeater machine (RM) sublayer	348
G.3 Redundant PhL	350
G.4 Ring repeater machine (RRM) sublayer	352
Annex H (informative) Type 2: Reference design examples.....	359
H.1 MAU: 5 Mbit/s, voltage mode, coaxial wire	359
H.2 Network access port (NAP)	363
Annex I (normative) Type 3: Connector specification.....	365
I.1 Connector for synchronous transmission	365
I.2 Connector for asynchronous transmission	366
I.3 Connectors for fiber optic cable	371
Annex J (normative) Type 3: Redundancy of PhL and medium.....	372
Annex K (normative) Type 3: Optical network topology	373
K.1 Signal flow in an optical network	373
Annex L (informative) Type 3: Reference design examples for asynchronous transmission, wire medium, intrinsically safe	382
L.1 Bus termination in the communication device	382
L.2 Bus termination in the connector	382
L.3 External bus termination.....	383
Annex M (normative) Type 8: Connector specification.....	385
M.1 External connectors for wire medium	385

M.2 External connectors for fiber optic medium	386
M.3 External connectors for hybrid connectors for IP65 applications	386
Annex N (normative) Type 16: Connector specification	390
Annex O (normative) Type 16: Optical network topology	391
O.1 Topology	391
O.2 Optical power budget	392
Annex P (informative) Type 16: Reference design example.....	396
P.1 Functional principles of the repeater circuit	396
P.2 Attenuation on the transmission line.....	399
Annex Q (normative) Type 18: Connector specification	400
Q.1 Overview	400
Q.2 Device connector.....	400
Q.3 Flat-cable connector.....	401
Q.4 Round cable connector.....	402
Q.5 Round cable alternate connector	403
Annex R (normative) Type 18: Media cable specifications.....	405
R.1 Type 18-PhL-B cable.....	405
R.2 Type 18-PhL-P cable.....	406
Bibliography.....	409

Figure 1 — General model of physical layer.....21

Figure 2 — Mapping between data units across the DLL – PhL interface

62

Figure 3 — Data service for asynchronous transmission

67

Figure 4 — Interactions for a data sequence of a master: identification cycle.....

72

Figure 5 — Interactions for a data sequence of a master: data cycle.....

73

Figure 6 — Interactions for a data sequence of a slave: identification cycle

74

Figure 7 — Interactions for a data sequence of a slave: data cycle

75

Figure 8 — Interactions for a check sequence of a master

76

Figure 9 — Interactions for a check sequence of a slave

77

Figure 10 — Reset, Set-value, Get-value

86

Figure 11 — Event service.....

87

Figure 12 — Interface between PhL and PNM1 in the layer model

92

Figure 13 — Reset, Set-value, Get-value PhL services

93

Figure 14 — Event PhL service.....

93

Figure 15 — Allocation of the interface number.....

94

Figure 16 — Configuration of a master.....

98

Figure 17 — Configuration of a slave with an alternative type of transmission.....

99

Figure 18 — Configuration of a bus coupler with an alternative type of transmission.....

99

Figure 19 — DTE/DCE sequencing machines

104

Figure 20 — State transitions with the ID cycle request service

113

Figure 21 — MIS-MDS interface: identification cycle request service

114

Figure 22 — MIS-MDS interface: identification cycle request service

115

Figure 23 — State transitions with the data cycle request service

115

Figure 24 — MIS-MDS interface: data cycle request service

116

Figure 25 — State transitions with the data sequence classification service.....

116

Figure 26 — Protocol machine for the message transmission service	117
Figure 27 — Protocol machine for the data sequence identification service	118
Figure 28 — Protocol machine for the message receipt service	119
Figure 29 — Protocol data unit (PhPDU)	120
Figure 30 — PhSDU encoding and decoding	121
Figure 31 — Manchester encoding rules	121
Figure 32 — Preamble and delimiters	123
Figure 33 — Manchester coded symbols	124
Figure 34 — PhPDU format, half duplex	125
Figure 35 — PhPDU format, full duplex	127
Figure 36 — Data sequence PhPDU	131
Figure 37 — Structure of the header in a data sequence PhPDU	131
Figure 38 — Check sequence PhPDU	132
Figure 39 — Structure of a headers in a check sequence PhPDU	132
Figure 40 — Structure of the status PhPDU	133
Figure 41 — Structure of the header in a status PhPDU	133
Figure 42 — Structure of the medium activity status PhPDU	134
Figure 43 — Structure of the header in a medium activity status PhPDU	134
Figure 44 — Reset PhPDU	135
Figure 45 — Configuration of a master	136
Figure 46 — Configuration of a slave	136
Figure 47 — Configuration of a bus coupler	136
Figure 48 — Protocol data unit	137
Figure 49 — PhSDU encoding and decoding	137
Figure 50 — Manchester encoding rules	137
Figure 51 — Example of an NRZI-coded signal	140
Figure 52 — Fill signal	140
Figure 53 — Jitter tolerance	147
Figure 54 — Transmit circuit test configuration	153
Figure 55 — Output waveform	153
Figure 56 — Transmitted and received bit cell jitter (zero crossing point deviation)	154
Figure 57 — Signal polarity	156
Figure 58 — Receiver sensitivity and noise rejection	157
Figure 59 — Power supply ripple and noise	160
Figure 60 — Fieldbus coupler	162
Figure 61 — Transition from receiving to transmitting	169
Figure 62 — Power supply ripple and noise	173
Figure 63 — Test circuit for single-output power supplies	174
Figure 64 — Test circuit for power distribution through an IS barrier	175
Figure 65 — Test circuit for multiple output supplies with signal coupling	176
Figure 66 — Fieldbus coupler	178
Figure 67 — Protection resistors	178
Figure 68 — Test configuration for current-mode MAU	184

Figure 69 — Transmitted and received bit cell jitter (zero crossing point deviation).....	185
Figure 70 — Noise test circuit for current-mode MAU.....	187
Figure 71 — Transmitted and received bit cell jitter (zero crossing point deviation).....	195
Figure 72 — Power supply harmonic distortion and noise	197
Figure 73 — Optical wave shape template	202
Figure 74 — Cellular radio topology and reuse of frequencies	214
Figure 75 — Radio segment between wired segments topology	215
Figure 76 — Mixed wired and radio medium fieldbus topology	216
Figure 77 — Components of 5 Mbit/s, voltage-mode, coaxial wire PhL variant	221
Figure 78 — Coaxial wire MAU block diagram.....	222
Figure 79 — Coaxial wire MAU transmitter.....	222
Figure 80 — Coaxial wire MAU receiver operation	223
Figure 81 — Coaxial wire MAU transmit mask.....	224
Figure 82 — Coaxial wire MAU receive mask.....	225
Figure 83 — Transformer symbol	226
Figure 84 — 5 Mbit/s, voltage-mode, coaxial wire topology example.....	228
Figure 85 — Coaxial wire medium topology limits	228
Figure 86 — Coaxial wire medium tap electrical characteristics	230
Figure 87 — MAU block diagram 5 Mbit/s, optical fiber medium	233
Figure 88 — NAP reference model.....	237
Figure 89 — Example of transient and permanent nodes.....	238
Figure 90 — NAP transceiver.....	239
Figure 91 — NAP cable	240
Figure 92 — Circuit diagram of the principle of measuring impedance	245
Figure 93 — Definition of CMRR	246
Figure 94 — Block circuit diagram of the principle of measuring CMRR	247
Figure 95 — Power supply ripple and noise	249
Figure 96 — Output characteristic curve of a power supply of the category EEx ib.....	257
Figure 97 — Output characteristic curve of a power supply of the category EEx ia.....	257
Figure 98 — Repeater in linear bus topology	260
Figure 99 — Repeater in tree topology.....	261
Figure 100 — Example for a connector with integrated inductance.....	262
Figure 101 — Interconnecting wiring.....	263
Figure 102 — Bus terminator	264
Figure 103 — Linear structure of an intrinsically safe segment.....	265
Figure 104 — Topology example extended by repeaters	266
Figure 105 — Bus terminator	268
Figure 106 — Waveform of the differential voltage.....	269
Figure 107 — Test set-up for the measurement of the idle level for devices with an integrated termination resistor	271
Figure 108 — Test set-up for the measurement of the idle level for devices with a connectable termination resistor	271
Figure 109 — Test set-up for measurement of the transmission levels	272
Figure 110 — Test set-up for the measurement of the receiving levels.....	272

Figure 111 — Fieldbus model for intrinsic safety	273
Figure 112 — Communication device model for intrinsic safety	273
Figure 113 — Connection to the optical network	276
Figure 114 — Principle structure of optical networking	277
Figure 115 — Definition of the standard optical link	278
Figure 116 — Signal template for the optical transmitter	283
Figure 117 — Recommended interface circuit	287
Figure 118 — MAU of an outgoing interface	289
Figure 119 — MAU of an incoming interface	289
Figure 120 — Remote bus link	290
Figure 121 — Interface to the transmission medium	290
Figure 122 — Wiring	293
Figure 123 — Terminal resistor network	293
Figure 124 — Fiber optic remote bus cable	294
Figure 125 — Optical fiber remote bus link	295
Figure 126 — Optical wave shape template optical MAU	296
Figure 127 — Optical transmission line	303
Figure 128 — Optical signal envelope	305
Figure 129 — Display of jitter (Jnoise)	306
Figure 130 — Input-output performance of a slave	308
Figure 131 — Functions of a master connection	311
Figure 132 — Valid transmitting signals during the transition from fill signal to telegram delimiters	313
Figure 133 — Valid transmitting signals during the transition from telegram delimiter to fill signal	314
Figure 134 — Functions of a slave connection	315
Figure 135 — Network with two slaves	316
Figure 136 — Minimum interconnecting wiring	317
Figure 137 — Dedicated cable topology	318
Figure 138 — T-branch topology	318
Figure 139 — Communication element isolation	320
Figure 140 — Communication element and I/O isolation	320
Figure 141 — Minimum interconnecting wiring	321
Figure 142 — Flat cable topology	322
Figure 143 — Dedicated cable topology	322
Figure 144 — T-branch topology	323
Figure 145 — Type 18-PhL-P power distribution	325
Figure 146 — Type 18-PhL-P power distribution	326
Figure 147 — Type 18-PhL-P power supply filtering and protection	327
Figure 148 — Communication element isolation	328
Figure 149 — Communication element and i/o isolation	328
Figure 150 — PhL-P power supply circuit	328
Figure A.1 — Internal fieldbus connector	329

Figure A.2 — Contact designations for the external connector for harsh industrial environments	331
Figure A.3 — External fieldbus connector keyways, keys, and bayonet pins and grooves	331
Figure A.4 — External fieldbus connector intermateability dimensions	332
Figure A.5 — External fieldbus connector contact arrangement	333
Figure A.6 — Contact designations for the external connector for typical industrial environments	334
Figure A.7 — External fixed (device) side connector for typical industrial environments: dimensions	334
Figure A.8 — External free (cable) side connector for typical industrial environments: dimensions	335
Figure A.9 — Optical connector for typical industrial environments (FC connector)	335
Figure A.10 — Optical connector for typical industrial environments (ST connector)	336
Figure C.1 — Example of an optical passive reflective star	339
Figure C.2 — Example of an optical passive transmissive star	339
Figure D.1 — Example of star topology with 31,25 kbit/s, single fiber mode, optical MAU	340
Figure D.2 — Multi-star topology with an optical MAU	341
Figure D.3 — Example of mixture between wire and optical media for a 31,25 kbit/s bit rate	343
Figure D.4 — Example of mixture between wire and optical media	343
Figure F.1 — Pin connector for short range optical medium	346
Figure F.2 — Crimp ring for short range optical medium	346
Figure G.1 — PhL repeater device reference model	348
Figure G.2 — Reference model for redundancy	351
Figure G.3 — Block diagram showing redundant coaxial medium and NAP	352
Figure G.4 — Block diagram showing ring repeaters	353
Figure G.5 — Segmentation query	354
Figure G.6 — Segmentation response	354
Figure G.7 — Main switch state machine	356
Figure G.8 — Port 1 sees network activity first	357
Figure G.9 — Port 2 sees network activity first	358
Figure H.1 — Coaxial wire MAU RxDATA detector	360
Figure H.2 — Coaxial wire MAU RxCARRIER detection	361
Figure H.3 — Redundant coaxial wire MAU transceiver	361
Figure H.4 — Single channel coaxial wire MAU transceiver	362
Figure H.5 — Coaxial wire medium tap	363
Figure H.6 — Non-isolated NAP transceiver	364
Figure H.7 — Isolated NAP transceiver	364
Figure I.1 — Schematic of the station coupler	365
Figure I.2 — Pin assignment of the male and female connectors IEC 947-5-2 (A coding)	366
Figure I.3 — Connector pinout, front view of male and back view of female respectively	367
Figure I.4 — Connector pinout, front view of female M12 connector	369
Figure I.5 — Connector pinout, front view of male M12 connector	369