IEC 61158-2

Edition 4.0 2007-12

INTERNATIONAL STANDARD

NORME INTERNATIONALE

colour inside

Withdrawn

Industrial communication networks – Fieldbus specifications – Part 2: Physical layer specification and service definition

Réseaux de communications industriels – Spécifications des bus de terrain – Partie 2: Spécification de couche physique et définition des services

iTeh Standards
(https://standards.iteh.ai)
Document Preview
IEC 61158-2:2007
https://standards.iteh.ai/catalog/standards/iec/3d83c882-93df-4a29-bcfa-fc59e8d67807/iec-61158-2-2007

IEC 61158-2:2007-12(en-fr)

THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2007 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office
3, rue de Varembé
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC
The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications
The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue
The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub
The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,…). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished
Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org
The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in 14 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary
More than 55 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc
If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

A propos de l'IEC
La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC
Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Catalogue IEC - webstore.iec.ch/catalogue
Application autonome pour consulter tous les renseignements bibliographiques sur les Normes internationales, Spécifications techniques, Rapports techniques et autres documents de l'IEC. Disponible pour PC, Mac OS, tablettes Android et iPad.

Recherche de publications IEC - www.iec.ch/searchpub
La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études,…). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished
Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

Electropedia - www.electropedia.org
Le premier dictionnaire en ligne de termes électroniques et électriques. Il contient plus de 30 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans 14 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

Glossaire IEC - std.iec.ch/glossary
Plus de 55 000 entrées terminologiques électrotechniques, en anglais et en français, extraites des articles Termes et Définitions des publications IEC parues depuis 2002. Plus certaines entrées antérieures extraites des publications des CE 37, 77, 86 et CISPR de l'IEC.

Service Clients - webstore.iec.ch/csc
Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: csc@iec.ch.

Withdrawn
(https://standardsiec.ch)

IEC 61158-2

Edition 4.0 2007-12

INTERNATIONAL STANDARD

NORME INTERNATIONALE

colour inside

Withdrawn

Industrial communication networks – Fieldbus specifications – Part 2: Physical layer specification and service definition

Réseaux de communications industriels – Spécifications des bus de terrain – Partie 2: Spécification de couche physique et définition des services

iTeh Standards
(https://standards.iteh.ai)
Document Preview
IEC 61158-2:2007
https://standards.iteh.ai/catalog/standards/iec/5d83c882-93df-4a29-bcfa-fc59e8d67807/iec-61158-2-2007

INTERNATIONAL ELECTROTECHNICAL COMMISSION

COMMISSION ELECTROTECHNIQUE INTERNATIONALE

PRICE CODE
CODE PRIX XH

ICS 25.040, 35.100, 35.240.50

ISBN 978-2-8322-1342-1

Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.

® Registered trademark of the International Electrotechnical Commission
Marque déposée de la Commission Electrotechnique Internationale

CONTENTS

FOREWORD 19
0 Introduction 21
0.1 General 21
0.2 Physical layer overview 21
0.3 Document overview 21
0.4 Major physical layer variations specified in this standard 22
1 Scope 25
2 Normative references 25
3 Terms and definitions 28
3.1 Common terms and definitions 28
3.2 Type 1: Terms and definitions 32
3.3 Type 2: Terms and definitions 35
3.4 Type 3: Terms and definitions 38
3.5 Type 4: Terms and definitions 41
3.6 Type 6: *This subclause has been removed* 42
3.7 Type 8: Terms and definitions 42
3.8 Type 12: Terms and definitions 45
3.9 Type 16: Terms and definitions 46
3.10 Type 18: Terms and definitions 49
4 Symbols and abbreviations 51
4.1 Symbols 51
4.2 Abbreviations 55
5 DLL – PhL interface 62
5.1 General 62
5.2 Type 1: Required services 62
5.3 Type 2: Required services 64
5.4 Type 3: Required services 67
5.5 Type 4: Required services 68
5.6 Type 6: *This subclause has been removed* 70
5.7 Type 8: Required services 70
5.8 Type 12: Required services 78
5.9 Type 16: Required services 80
5.10 Type 18: Required services 81
6 Systems management – PhL interface 83
6.1 General 83
6.2 Type 1: Systems management – PhL interface 83
6.3 Type 3: Systems management – PhL interface 85
6.4 Type 4: Systems management – PhL interface 91
6.5 Type 6: *This subclause has been removed* 91
6.6 Type 8: Systems management – PhL interface 91
6.7 Type 12: Systems management – PhL interface 96
6.8 Type 18: Systems management – PhL interface 96
7 DCE independent sublayer (DIS) 97
7.1 General 97
7.2 Type 1: DIS 97
7.3 Type 3: DIS 97

Withdrawn
IEC Standards
(https://standards.iteh.ai)
Document Preview
IEC 61158-2:2007
https://standards.iteh.ai/catalog/standards/sist/da3e882-93d1-4a29-bcfa-fc59e8d67807/iec-61158-2-2007

7.4 Type 6: *This subclause has been removed* 97
7.5 Type 8: DIS 98
7.6 Type 12: DIS 99
8 DTE – DCE interface and MIS-specific functions 99
8.1 General 99
8.2 Type 1: DTE – DCE interface 100
8.3 Type 3: DTE – DCE interface 110
8.4 Type 8: MIS – MDS interface 111
8.5 Type 12: DTE – DCE interface 120
9 Medium dependent sublayer (MDS) 120
9.1 General 120
9.2 Type 1: MDS: Wire and optical media 120
9.3 Type 1: MDS: Radio media 123
9.4 Type 2: MDS: Wire and optical media 123
9.5 Type 3: MDS: Wire and optical media 125
9.6 Type 4: MDS: Wire medium 125
9.7 Type 6: *This subclause has been removed* 130
9.8 Type 8: MDS: Wire and optical media 130
9.9 Type 12: MDS: Wire media 137
9.10 Type 16: MDS: Optical media 139
9.11 Type 18: MDS: Wire media 140
10 MDS – MAU interface 141
10.1 General 141
10.2 Type 1: MDS – MAU interface: Wire and optical media 141
10.3 Type 1: MDS – MAU interface: Radio signaling 143
10.4 Type 2: MDS – MAU interface: Wire and optical media 143
10.5 Type 3: MDS – MAU interface: Wire and optical media 145
10.6 Type 8: MDS – MAU interface: Wire and optical media 145
10.7 Type 18: MDS – MAU interface: Wire media 147
11 Types 1 and 7: Medium attachment unit: voltage mode, linear-bus-topology 150 Ω twisted-pair wire medium 149
11.1 General 149
11.2 Bit-rate-dependent quantities 149
11.3 Network specifications 150
11.4 MAU transmit circuit specification 152
11.5 MAU receive circuit specification 156
11.6 Jabber inhibit 158
11.7 Power distribution 158
11.8 Medium specifications 161
12 Types 1 and 3: Medium attachment unit: 31,25 kbit/s, voltage-mode with low-power option, bus- and tree-topology, 100 Ω wire medium 164
12.1 General 164
12.2 Transmitted bit rate 164
12.3 Network specifications 164
12.4 MAU transmit circuit specification 167
12.5 MAU receive circuit specification 170
12.6 Jabber inhibit 171
12.7 Power distribution 171
12.8 Medium specifications 177

Withdrawn
IECNORM.COM : Click to view the full PDF of IEC 61158-2:2007
Withdrawn
IEC Standards
(https://standards.iteh.ai)
Document Preview
https://standards.iteh.ai/catalog/standards/sist/0f882c9d-4f4d-49d4-bafa-fc59e8d67807/iec-61158-2-2007

12.9 Intrinsic safety 180
12.10 Galvanic isolators 181
13 Type 1: Medium attachment unit: current mode, twisted-pair wire medium 181
13.1 General 181
13.2 Transmitted bit rate 181
13.3 Network specifications 181
13.4 MAU transmit circuit specification 183
13.5 MAU receive circuit specification 185
13.6 Jabber inhibit 187
13.7 Power distribution 188
13.8 Medium specifications 189
14 Type 1: Medium attachment unit: current mode (1 A), twisted-pair wire medium 191
14.1 General 191
14.2 Transmitted bit rate 191
14.3 Network specifications 191
14.4 MAU transmit circuit specification 193
14.5 MAU receive circuit specification 195
14.6 Jabber inhibit 196
14.7 Power distribution 196
14.8 Medium specifications 198
15 Types 1 and 7: Medium attachment unit: dual-fiber optical media 199
15.1 General 199
15.2 Bit-rate-dependent quantities 199
15.3 Network specifications 200
15.4 MAU transmit circuit specifications 201
15.5 MAU receive circuit specifications 202
15.6 Jabber inhibit 203
15.7 Medium specifications 204
16 Type 1: Medium attachment unit: 31,25 kbit/s, single-fiber optical medium 206
16.1 General 206
16.2 Transmitted bit rate 206
16.3 Network specifications 206
16.4 MAU transmit circuit specifications 206
16.5 MAU receive circuit specifications 207
16.6 Jabber inhibit 207
16.7 Medium specifications 208
17 Type 1: Medium attachment unit: radio signaling 210
17.1 General 210
17.2 Transmit signaling rate 210
17.3 Modulation 210
17.4 Network specification 212
17.5 Antennas 216
17.6 Jabber inhibit 216
17.7 Common air interface 217
18 Type 2: Medium attachment unit: 5 Mbit/s, voltage-mode, coaxial wire medium 221
18.1 General 221
18.2 Transceiver: 5 Mbit/s, voltage-mode, coaxial wire 221
18.3 Transformer 5 Mbit/s, voltage-mode, coaxial wire 226

Withdrawn
IEC 61158-2:2007
https://standards.iteh.ai/catalog/standards/iec/ad5e882-93df-4a29-bcfa-fc59e8d67807/iec-61158-2-2007

18.4 Connector 5 Mbit/s, voltage-mode, coaxial wire medium 227
18.5 Topology 5 Mbit/s, voltage-mode, coaxial wire medium 227
18.6 Taps 5 Mbit/s, voltage-mode, coaxial wire medium 229
18.7 Trunk 5 Mbit/s, voltage-mode, coaxial wire medium 231
19 Type 2: Medium attachment unit: 5 Mbit/s, optical medium 232
19.1 General 232
19.2 Transceiver 5 Mbit/s, optical medium 232
19.3 Topology 5 Mbit/s, optical medium 233
19.4 Trunk fiber 5 Mbit/s, optical medium 233
19.5 Trunk connectors 5 Mbit/s, optical medium 234
19.6 Fiber specifications 5 Mbit/s, optical medium 234
20 Type 2: Medium attachment unit: network access port (NAP) 237
20.1 General 237
20.2 Signaling 238
20.3 Transceiver 239
20.4 Connector 239
20.5 Cable 239
21 Type 3: Medium attachment unit: synchronous transmission, 31,25 kbit/s, voltage mode, wire medium 241
21.1 General 241
21.2 Transmitted bit rate 241
21.3 Network specifications 241
21.4 Transmit circuit specification for 31,25 kbit/s voltage-mode MAU 244
21.5 Receive circuit specification for 31,25 kbit/s voltage-mode MAU 247
21.6 Jabber inhibit 247
21.7 Power distribution 248
21.8 Medium specifications 250
21.9 Intrinsic safety 252
21.10 Galvanic isolators 252
21.11 Coupling elements 252
21.12 Power supply 254
22 Type 3: Medium attachment unit: asynchronous transmission, wire medium 259
22.1 Medium attachment unit for non intrinsic safety 259
22.2 Medium attachment unit for intrinsic safety 264
23 Type 3: Medium attachment unit: asynchronous transmission, optical medium 276
23.1 Characteristic features of optical data transmission 276
23.2 Basic characteristics of an optical data transmission medium 277
23.3 Optical network 277
23.4 Standard optical link 278
23.5 Network structures built from a combination of standard optical links 278
23.6 Bit coding 278
23.7 Optical signal level 278
23.8 Temporal signal distortion 281
23.9 Bit error rate 285
23.10 Connectors for fiber optic cable 285
23.11 Redundancy in optical transmission networks 285
24 Type 4: Medium attachment unit: RS-485 285
24.1 General 285

Withdrawn
iTeh Standards
(https://standards.iteh.ai)
Document Preview
IEC 61158-2:2007
https://standards.iteh.ai/catalog/standards/iec/1d8e882-93df-4a29-bc6e-fe59e8d67807/iec-61158-2-2007

24.2 Overview of the services 285
24.3 Description of the services 286
24.4 Network 286
24.5 Electrical specification 286
24.6 Time response 286
24.7 Interface to the transmission medium 286
24.8 Specification of the transmission medium 287
25 Type 4: Medium attachment unit: RS-232 288
25.1 General 288
25.2 Overview of the services 288
25.3 Description of the services 288
26 Type 6: *This clause has been removed* 288
27 Type 8: Medium attachment unit: twisted-pair wire medium 289
27.1 MAU signals 289
27.2 Transmission bit rate dependent quantities 289
27.3 Network 290
27.4 Electrical specification 290
27.5 Time response 290
27.6 Interface to the transmission medium 290
27.7 Specification of the transmission medium 291
28 Type 8: Medium attachment unit: optical media 294
28.1 General 294
28.2 Transmission bit rate dependent quantities 294
28.3 Network topology 294
28.4 Transmit circuit specifications 295
28.5 Receive circuit specifications 296
28.6 Specification of the transmission medium 297
29 Type 12: Medium attachment unit: electrical medium 301
29.1 Electrical characteristics 301
29.2 Medium specifications 301
29.3 Transmission method 301
30 Type 16: Medium attachment unit: optical fiber medium at 2, 4, 8 and 16 Mbit/s 303
30.1 Structure of the transmission lines 303
30.2 Time performance of bit transmission 303
30.3 Connection to the optical fiber 310
31 Type 18: Medium attachment unit: basic medium 317
31.1 General 317
31.2 Data signal encoding 317
31.3 Signal loading 317
31.4 Signal conveyance requirements 317
31.5 Media 318
31.6 Endpoint and branch trunk cable connectors 320
31.7 Recommended type 18-PhL-B MAU circuitry 320
32 Type 18: Medium attachment unit: powered medium 321
32.1 General 321
32.2 Data signal encoding 321
32.3 Signal loading 321
32.4 Signal conveyance requirements 321

Withdrawn
iTeh Standards
(https://standards.iteh.ai)
Document Preview
IEC 61158-2:2007
https://standards.iteh.ai/catalog/standards/sist/...-iec-61158-2-2007

32.5 Media 322
32.6 Endpoint and branch trunk cable connectors 325
32.7 Embedded power distribution 325
32.8 Recommended type 18-PhL-P MAU circuitry 327
Annex A (normative) Type 1: Connector specification 329
A.1 Internal connector for wire medium 329
A.2 External connectors for wire medium 330
Annex B (informative) Types 1 and 3: Cable specifications and trunk and spur lengths for the 31,25 kbit/s voltage-mode MAU 337
B.1 Cable description and specifications 337
B.2 Typical trunk and spur lengths 337
Annex C (informative) Types 1 and 7: Optical passive stars 339
C.1 Definition 339
C.2 Example of attenuations 339
Annex D (informative) Types 1 and 7: Star topology 340
D.1 Examples of topology 340
D.2 Optical power budget 341
D.3 Mixed with wire media 342
Annex E (informative) Type 1: Alternate fibers 344
E.1 Alternate fibers for dual-fiber mode 344
E.2 Alternate fibers for single-fiber mode 344
Annex F (normative) Type 2: Connector specification 345
F.1 Connector for coaxial wire medium 345
F.2 Connector for optical medium 345
F.3 Connector for NAP medium 346
Annex G (normative) Type 2: Repeater machine sublayers (RM, RRM) and redundant PhLs 348
G.1 General 348
G.2 Repeater machine (RM) sublayer 348
G.3 Redundant PhL 350
G.4 Ring repeater machine (RRM) sublayer 352
Annex H (informative) Type 2: Reference design examples 359
H.1 MAU: 5 Mbit/s, voltage mode, coaxial wire 359
H.2 Network access port (NAP) 363
Annex I (normative) Type 3: Connector specification 365
I.1 Connector for synchronous transmission 365
I.2 Connector for asynchronous transmission 366
I.3 Connectors for fiber optic cable 371
Annex J (normative) Type 3: Redundancy of PhL and medium 372
Annex K (normative) Type 3: Optical network topology 373
K.1 Signal flow in an optical network 373
Annex L (informative) Type 3: Reference design examples for asynchronous transmission, wire medium, intrinsically safe 382
L.1 Bus termination in the communication device 382
L.2 Bus termination in the connector 382
L.3 External bus termination 383
Annex M (normative) Type 8: Connector specification 385
M.1 External connectors for wire medium 385

Withdrawn
IECNORM.COM : Click to view the full PDF of IEC 61158-2:2007
Withdrawn
IEC Standards
(https://standards.iteh.ai)
Document Preview
https://standards.iteh.ai/catalog/standards/iec/ad3c882-93df-4a29-bcfa-fc59e8d67807/iec-61158-2-2007

M.2 External connectors for fiber optic medium 386
M.3 External connectors for hybrid connectors for IP65 applications 386
Annex N (normative) Type 16: Connector specification 390
Annex O (normative) Type 16: Optical network topology 391
O.1 Topology 391
O.2 Optical power budget 392
Annex P (informative) Type 16: Reference design example 396
P.1 Functional principles of the repeater circuit 396
P.2 Attenuation on the transmission line 399
Annex Q (normative) Type 18: Connector specification 400
Q.1 Overview 400
Q.2 Device connector 400
Q.3 Flat-cable connector 401
Q.4 Round cable connector 402
Q.5 Round cable alternate connector 403
Annex R (normative) Type 18: Media cable specifications 405
R.1 Type 18-PhL-B cable 405
R.2 Type 18-PhL-P cable 406
Bibliography 409

Figure 1 – General model of physical layer 21
Figure 2 – Mapping between data units across the DLL – PhL interface 62
Figure 3 – Data service for asynchronous transmission 67
Figure 4 – Interactions for a data sequence of a master: identification cycle 72
Figure 5 – Interactions for a data sequence of a master: data cycle 73
Figure 6 – Interactions for a data sequence of a slave: identification cycle 74
Figure 7 – Interactions for a data sequence of a slave: data cycle 75
Figure 8 – Interactions for a check sequence of a master 76
Figure 9 – Interactions for a check sequence of a slave 77
Figure 10 – Reset, Set-value, Get-value 86
Figure 11 – Event service 87
Figure 12 – Interface between PhL and PNM1 in the layer model 92
Figure 13 – Reset, Set-value, Get-value PhL services 93
Figure 14 – Event PhL service 93
Figure 15 – Allocation of the interface number 94
Figure 16 – Configuration of a master 98
Figure 17 – Configuration of a slave with an alternative type of transmission 99
Figure 18 – Configuration of a bus coupler with an alternative type of transmission 99
Figure 19 – DTE/DCE sequencing machines 104
Figure 20 – State transitions with the ID cycle request service 113
Figure 21 – MIS-MDS interface: identification cycle request service 114
Figure 22 – MIS-MDS interface: identification cycle request service 115
Figure 23 – State transitions with the data cycle request service 115
Figure 24 – MIS-MDS interface: data cycle request service 116
Figure 25 – State transitions with the data sequence classification service 116

iTeh Standards
(https://standards.iteh.ai)
Document Preview
IEC 61158-2:2007
https://standards.iteh.ai/catalog/standards/iec/ddc8e882-93df-4a29-bcfa-fe59e8d67807/iec-61158-2-2007
Withdrawn

Figure 26 – Protocol machine for the message transmission service 117
Figure 27 – Protocol machine for the data sequence identification service 118
Figure 28 – Protocol machine for the message receipt service 119
Figure 29 – Protocol data unit (PhPDU) 120
Figure 30 – PhSDU encoding and decoding 121
Figure 31 – Manchester encoding rules 121
Figure 32 – Preamble and delimiters 123
Figure 33 – Manchester coded symbols 124
Figure 34 – PhPDU format, half duplex 125
Figure 35 – PhPDU format, full duplex 127
Figure 36 – Data sequence PhPDU 131
Figure 37 – Structure of the header in a data sequence PhPDU 131
Figure 38 – Check sequence PhPDU 132
Figure 39 – Structure of a headers in a check sequence PhPDU 132
Figure 40 – Structure of the status PhPDU 133
Figure 41 – Structure of the header in a status PhPDU 133
Figure 42 – Structure of the medium activity status PhPDU 134
Figure 43 – Structure of the header in a medium activity status PhPDU 134
Figure 44 – Reset PhPDU 135
Figure 45 – Configuration of a master 136
Figure 46 – Configuration of a slave 136
Figure 47 – Configuration of a bus coupler 136
Figure 48 – Protocol data unit 137
Figure 49 – PhSDU encoding and decoding 137
Figure 50 – Manchester encoding rules 137
Figure 51 – Example of an NRZI-coded signal 140
Figure 52 – Fill signal 140
Figure 53 – Jitter tolerance 147
Figure 54 – Transmit circuit test configuration 153
Figure 55 – Output waveform 153
Figure 56 – Transmitted and received bit cell jitter (zero crossing point deviation) 154
Figure 57 – Signal polarity 156
Figure 58 – Receiver sensitivity and noise rejection 157
Figure 59 – Power supply ripple and noise 160
Figure 60 – Fieldbus coupler 162
Figure 61 – Transition from receiving to transmitting 169
Figure 62 – Power supply ripple and noise 173
Figure 63 – Test circuit for single-output power supplies 174
Figure 64 – Test circuit for power distribution through an IS barrier 175
Figure 65 – Test circuit for multiple output supplies with signal coupling 176
Figure 66 – Fieldbus coupler 178
Figure 67 – Protection resistors 178
Figure 68 – Test configuration for current-mode MAU 184

Withdrawn
iTeh Standards
(https://standards.iteh.ai)
Document Preview
IEC 61158-2:2007
https://standards.iteh.ai/catalog/standards/sist/1da5e882-93df-4a29-bcfa-fc59e8d67807/iec-61158-2-2007

Figure 69 – Transmitted and received bit cell jitter (zero crossing point deviation) 185
Figure 70 – Noise test circuit for current-mode MAU 187
Figure 71 – Transmitted and received bit cell jitter (zero crossing point deviation) 195
Figure 72 – Power supply harmonic distortion and noise 197
Figure 73 – Optical wave shape template 202
Figure 74 – Cellular radio topology and reuse of frequencies 214
Figure 75 – Radio segment between wired segments topology 215
Figure 76 – Mixed wired and radio medium fieldbus topology 216
Figure 77 – Components of 5 Mbit/s, voltage-mode, coaxial wire PhL variant 221
Figure 78 – Coaxial wire MAU block diagram 222
Figure 79 – Coaxial wire MAU transmitter 222
Figure 80 – Coaxial wire MAU receiver operation 223
Figure 81 – Coaxial wire MAU transmit mask 224
Figure 82 – Coaxial wire MAU receive mask 225
Figure 83 – Transformer symbol 226
Figure 84 – 5 Mbit/s, voltage-mode, coaxial wire topology example 228
Figure 85 – Coaxial wire medium topology limits 228
Figure 86 – Coaxial wire medium tap electrical characteristics 230
Figure 87 – MAU block diagram 5 Mbit/s, optical fiber medium 233
Figure 88 – NAP reference model 237
Figure 89 – Example of transient and permanent nodes 238
Figure 90 – NAP transceiver 239
Figure 91 – NAP cable 240
Figure 92 – Circuit diagram of the principle of measuring impedance 245
Figure 93 – Definition of CMRR 246
Figure 94 – Block circuit diagram of the principle of measuring CMRR 247
Figure 95 – Power supply ripple and noise 249
Figure 96 – Output characteristic curve of a power supply of the category EEx ib 257
Figure 97 – Output characteristic curve of a power supply of the category EEx ia 257
Figure 98 – Repeater in linear bus topology 260
Figure 99 – Repeater in tree topology 261
Figure 100 – Example for a connector with integrated inductance 262
Figure 101 – Interconnecting wiring 263
Figure 102 – Bus terminator 264
Figure 103 – Linear structure of an intrinsically safe segment 265
Figure 104 – Topology example extended by repeaters 266
Figure 105 – Bus terminator 268
Figure 106 – Waveform of the differential voltage 269
Figure 107 – Test set-up for the measurement of the idle level for devices with an integrated termination resistor 271
Figure 108 – Test set-up for the measurement of the idle level for devices with a connectable termination resistor 271
Figure 109 – Test set-up for measurement of the transmission levels 272
Figure 110 – Test set-up for the measurement of the receiving levels 272

Withdrawn
IECNORM.COM : Click to view the full PDF of IEC 61158-2:2007
Withdrawn
IEC Standards
(https://standards.iteh.ai)
Document Preview
https://standards.iteh.ai/catalog/standards/iec/1d8e882-93df-4a29-bcfa-fc59e8d67807/iec-61158-2-2007

Figure 111 – Fieldbus model for intrinsic safety 273
Figure 112 – Communication device model for intrinsic safety 273
Figure 113 – Connection to the optical network 276
Figure 114 – Principle structure of optical networking 277
Figure 115 – Definition of the standard optical link 278
Figure 116 – Signal template for the optical transmitter 283
Figure 117 – Recommended interface circuit 287
Figure 118 – MAU of an outgoing interface 289
Figure 119 – MAU of an incoming interface 289
Figure 120 – Remote bus link 290
Figure 121 – Interface to the transmission medium 290
Figure 122 – Wiring 293
Figure 123 – Terminal resistor network 293
Figure 124 – Fiber optic remote bus cable 294
Figure 125 – Optical fiber remote bus link 295
Figure 126 – Optical wave shape template optical MAU 296
Figure 127 – Optical transmission line 303
Figure 128 – Optical signal envelope 305
Figure 129 – Display of jitter (J_{noise}) 306
Figure 130 – Input-output performance of a slave 308
Figure 131 – Functions of a master connection 311
Figure 132 – Valid transmitting signals during the transition from fill signal to telegram delimiters 313
Figure 133 – Valid transmitting signals during the transition from telegram delimiter to fill signal 314
Figure 134 – Functions of a slave connection 315
Figure 135 – Network with two slaves 316
Figure 136 – Minimum interconnecting wiring 317
Figure 137 – Dedicated cable topology 318
Figure 138 – T-branch topology 318
Figure 139 – Communication element isolation 320
Figure 140 – Communication element and I/O isolation 320
Figure 141 – Minimum interconnecting wiring 321
Figure 142 – Flat cable topology 322
Figure 143 – Dedicated cable topology 322
Figure 144 – T-branch topology 323
Figure 145 – Type 18-PhL-P power distribution 325
Figure 146 – Type 18-PhL-P power distribution 326
Figure 147 – Type 18-PhL-P power supply filtering and protection 327
Figure 148 – Communication element isolation 328
Figure 149 – Communication element and i/o isolation 328
Figure 150 – PhL-P power supply circuit 328
Figure A.1 – Internal fieldbus connector 329

Withdrawn
iTeh Standards
(https://standards.iteh.ai)
Document Preview
IEC 61158-2:2007
https://standards.iteh.ai/catalog/standards/iec/9d3e882-93df-4a29-bcfa-fe59e8d67807/iec-61158-2-2007

Figure A.2 – Contact designations for the external connector for harsh industrial environments 331
Figure A.3 – External fieldbus connector keyways, keys, and bayonet pins and grooves 331
Figure A.4 – External fieldbus connector intermateability dimensions 332
Figure A.5 – External fieldbus connector contact arrangement 333
Figure A.6 – Contact designations for the external connector for typical industrial environments 334
Figure A.7 – External fixed (device) side connector for typical industrial environments: dimensions 334
Figure A.8 – External free (cable) side connector for typical industrial environments: dimensions 335
Figure A.9 – Optical connector for typical industrial environments (FC connector) 335
Figure A.10 – Optical connector for typical industrial environments (ST connector) 336
Figure C.1 – Example of an optical passive reflective star 339
Figure C.2 – Example of an optical passive transmitive star 339
Figure D.1 – Example of star topology with 31,25 kbit/s, single fiber mode, optical MAU 340
Figure D.2 – Multi-star topology with an optical MAU 341
Figure D.3 – Example of mixture between wire and optical media for a 31,25 kbit/s bit rate 343
Figure D.4 – Example of mixture between wire and optical media 343
Figure F.1 – Pin connector for short range optical medium 346
Figure F.2 – Crimp ring for short range optical medium 346
Figure G.1 – PhL repeater device reference model 348
Figure G.2 – Reference model for redundancy 351
Figure G.3 – Block diagram showing redundant coaxial medium and NAP 352
Figure G.4 – Block diagram showing ring repeaters 353
Figure G.5 – Segmentation query 354
Figure G.6 – Segmentation response 354
Figure G.7 – Main switch state machine 356
Figure G.8 – Port 1 sees network activity first 357
Figure G.9 – Port 2 sees network activity first 358
Figure H.1 – Coaxial wire MAU RxDATA detector 360
Figure H.2 – Coaxial wire MAU RxCARRIER detection 361
Figure H.3 – Redundant coaxial wire MAU transceiver 361
Figure H.4 – Single channel coaxial wire MAU transceiver 362
Figure H.5 – Coaxial wire medium tap 363
Figure H.6 – Non-isolated NAP transceiver 364
Figure H.7 – Isolated NAP transceiver 364
Figure I.1 – Schematic of the station coupler 365
Figure I.2 – Pin assignment of the male and female connectors IEC 947-5-2 (A coding) 366
Figure I.3 – Connector pinout, front view of male and back view of female respectively 367
Figure I.4 – Connector pinout, front view of female M12 connector 369
Figure I.5 – Connector pinout, front view of male M12 connector 369
Figure I.6 – M12 Tee 370

Withdrawn
iTeh Standards
(https://standards.iteh.ai)
Document Preview
IEC 61158-2:2007
https://standards.iteh.ai/catalog/standards/sist/3d3e882-93df-4a29-bcfa-fe59e8db7807/iec-61158-2-2007