

INTERNATIONAL STANDARD

NORME INTERNATIONALE



**Cable networks for television signals, sound signals and interactive services –
Part 13: Optical systems for broadcast signal transmissions**

**Réseaux de distribution par câbles pour signaux de télévision, signaux de
radiodiffusion sonore et services interactifs –
Partie 13: Systèmes optiques pour la transmission de signaux de diffusion**





THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2010 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC online collection - oc.iec.ch

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 18 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Recherche de publications IEC - webstore.iec.ch/advsearchform

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études, ...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC online collection - oc.iec.ch

Découvrez notre puissant moteur de recherche et consultez gratuitement tous les aperçus des publications. Avec un abonnement, vous aurez toujours accès à un contenu à jour adapté à vos besoins.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire d'électrotechnologie en ligne au monde, avec plus de 22 000 articles terminologiques en anglais et en français, ainsi que les termes équivalents dans 16 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: sales@iec.ch.

INTERNATIONAL STANDARD

NORME INTERNATIONALE



**Cable networks for television signals, sound signals and interactive services –
Part 13: Optical systems for broadcast signal transmissions**

**Réseaux de distribution par câbles pour signaux de télévision, signaux de
radiodiffusion sonore et services interactifs –
Partie 13: Systèmes optiques pour la transmission de signaux de diffusion**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 33.160.01; 33.180.01

ISBN 978-2-8322-9340-9

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

CONTENTS

FOREWORD.....	5
INTRODUCTION.....	7
1 Scope.....	8
2 Normative references	8
3 Terms, definitions, symbols and abbreviations.....	9
3.1 Terms and definitions	9
3.2 Symbols	15
3.3 Abbreviations	16
4 Optical system reference model.....	17
5 Preparation of measurement	19
5.1 Environmental conditions	19
5.1.1 Standard measurement conditions.....	19
5.1.2 Temperature and humidity	19
5.1.3 Setting up the measuring setup and system under test	19
5.1.4 AGC operation.....	19
5.1.5 Impedance matching between pieces of equipment	19
5.1.6 Standard operating condition	20
5.1.7 Standard signal and measuring equipment.....	20
5.2 Accuracy of measuring equipment.....	20
5.3 Source power	20
6 Methods of measurement	20
6.1 Measuring points and items.....	20
6.1.1 General	20
6.1.2 Measuring points	21
6.1.3 Measured parameters.....	21
6.2 Optical power	22
6.2.1 General	22
6.2.2 Measuring setup	22
6.2.3 Measuring method	23
6.2.4 Precaution for measurement.....	23
6.2.5 Presentation of the results	23
6.3 Carrier level and carrier-to-noise ratio	24
6.3.1 General	24
6.3.2 Measuring setup	24
6.3.3 Measuring conditions.....	24
6.3.4 Measuring method for analogue signals (AM-VSB)	24
6.3.5 Measuring method for digitally modulated signals (64 QAM, OFDM).....	24
6.3.6 Precautions for measurement.....	24
6.3.7 Presentation of the results.....	25
6.4 Carrier-to-noise ratio defined by optical signal.....	25
6.4.1 General	25
6.4.2 Measuring setup	25
6.4.3 Measuring conditions.....	26
6.4.4 System <i>RIN</i> measuring method.....	27
6.4.5 <i>C/N</i> calculation based on <i>RIN</i> value.....	28
6.4.6 Component <i>RIN</i> calculation	28

6.5	Optical modulation index	31
6.6	Carrier-to-crosstalk ratio (CCR)	31
6.6.1	General	31
6.6.2	Equipment	31
6.6.3	General measurements	31
6.6.4	Procedure	31
6.6.5	Potential sources of error	32
6.6.6	Presentation of the results	32
7	Specification of optical system for broadcast signal transmission	33
7.1	Analogue and digital broadcast system over optical network	33
7.2	International TV systems	33
7.3	Relationship between R/N and C/N	35
7.4	Optical wavelength	36
7.5	Frequency of source signal	36
7.6	Optical system specification for broadcast signal transmission	36
7.7	C/N ratio specification for in-house and in-building wirings	37
7.8	Crosstalk due to optical fibre non-linearity	39
7.9	Single frequency interference level due to fibre non-linearity	40
7.10	Environmental conditions	40
Annex A (informative)	Actual service systems and design considerations	41
Annex B (informative)	Optical system overview	56
Annex C (informative)	Optical system degradations	60
Annex D (normative)	Measurement of parameters (R , I_{d0} , I_{eq} and G) required for R/N calculation	66
Bibliography	https://standards.iteh.ai/catalog/standards/sist/2786651d-676b-4142-bde2-424e99bbd4ea/iec-60728-13-2010	68
Figure 1	– Optical system reference model for one-fibre solution	17
Figure 2	– Optical system reference model for two-fibres solution	18
Figure 3	– Example of PON triplexer	18
Figure 4	– Performance specified points of the optical system	19
Figure 5	– Typical optical video distribution system	21
Figure 6	– Measurement of optical power using a WDM coupler	22
Figure 7	– Measurement of optical power using a wavelength filter	23
Figure 8	– Arrangement of test equipment for carrier-to-noise ratio measurement	24
Figure 9	– Measuring points in the optical cable TV network	26
Figure 10	– R/N measurement setup	26
Figure 11	– Arrangement of test equipment for measuring other services crosstalk	32
Figure 12	– Performance allocation and measuring points	33
Figure 13	– Section of C/N ratio specification (45 dB) for in-house wiring (specified for electrical signals)	38
Figure 14	– Section of C/N ratio specification for in-house wiring (specified for optical signals)	39
Figure A.1	– Example of a multi-channel service system of one million terminals	41
Figure A.2	– Example of a multi-channel service system of 2 000 terminals	42
Figure A.3	– Example of re-transmission service system of 72 terminals	43
Figure A.4	– Example of re-transmission service system of 144 terminals	43

Figure A.5 – Model No.1 of a system performance calculation	47
Figure A.6 – Model No.2 of a system performance calculation	48
Figure A.7 – Model No.3 a of system performance calculation	49
Figure A.8 – Model No.4 of a system performance calculation	50
Figure A.9 – Model No.5 of a system performance calculation	51
Figure A.10 – Model No.6 of a system performance calculation	52
Figure A.11 – Model No.7 of system performance calculation	53
Figure B.1 – Topology of optical system	56
Figure B.2 – Network composition.....	57
Figure B.3 – Example of SS system	58
Figure B.4 – Example of ADS system.....	58
Figure B.5 – Example of PON system	59
Figure C.1 – Reflection model.....	60
Figure C.2 – Degradation factors of optical transmission system.....	61
Figure C.3 – SBS generation image	61
Figure C.4 – Interference between two wavelengths	63
Figure C.5 – Simulation of SRS(OLT transmission power versus D/U)	63
Figure C.6 – Simulation of SRS (D/U in arbitrary unit versus fibre length)	64
Figure C.7 – Fibre length of the first peak of SRS D/U versus frequency.....	64
Figure C.8 – GE-PON idle pattern spectrum (IEEE 802.3ah 1000Base-PX) (62,5 MHz = 1 250 Mbps/20 bit)	65
Figure D.1 – Measurement of gain (G)	67
https://standards.iteh.ai/catalog/standards/sist/2786651d-676b-4142-bde2-424e99bbd4ea/iec-60728-13-2010	
Table 1 – Level of RF signals.....	12
Table 2 – Measuring instruments	20
Table 3 – Measuring points and measured parameters	22
Table 4 – Parameters used for the calculation of carrier-to-noise ratio (C/N).....	30
Table 5 – Minimum C/N requirements in operation	34
Table 6 – Minimum RF signal-to-noise ratio requirements in operation.....	34
Table 7 – Types of broadcast services	36
Table 8 – Type of service and minimum operational R/N values	36
Table 9 – Optical system specification	37
Table 10 – Section of C/N ratio specification for in-house/in-building wiring	38
Table 11 – Interference level due to fibre non-linearity	40
Table 12 – Environmental conditions	40
Table A.1 – Operating conditions of a multi-channel service system	42
Table A.2 – Operating conditions of re-transmission service system	43
Table A.3 – Basic system parameters for multi-channel and re-transmission service systems	45
Table A.4 – Verified optimum operation	54
Table B.1 – PON systems and main parameters	59
Table C.1 – Disturbance parameter of Raman crosstalk.....	62

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**CABLE NETWORKS FOR TELEVISION SIGNALS,
SOUND SIGNALS AND INTERACTIVE SERVICES –**

Part 13: Optical systems for broadcast signal transmissions

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60728-13 has been prepared by technical area 5: Cable networks for television signals, sound signals and interactive services, of IEC technical committee 100: Audio, video and multimedia systems and equipment.

The text of this standard is based on the following documents:

FDIS	Report on voting
100/1623/FDIS	100/1646/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The list of all the parts of the IEC 60728 series, under the general title *Cable networks for television signals, sound signals and interactive services*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

The contents of the corrigendum of August 2010 have been included in this copy.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[IEC 60728-13:2010](#)

<https://standards.iteh.ai/catalog/standards/sist/2786651d-676b-4142-bde2-424e99bbd4ea/iec-60728-13-2010>

INTRODUCTION

Standards of the IEC 60728 series deal with cable networks including equipment and associated methods of measurement for headend reception, processing and distribution of television signals, sound signals and their associated data signals and for processing, interfacing and transmitting all kinds of signals for interactive services using all applicable transmission media.

This includes

- CATV¹-networks;
- MATV-networks and SMATV-networks;
- individual receiving networks;

and all kinds of equipment, systems and installations installed in such networks.

The extent of this standardization work is from the antennas and/or special signal source inputs to the headend or other interface points to the network up to the terminal input.

The standardization of any user terminals (i.e., tuners, receivers, decoders, multimedia terminals, etc.) as well as of any coaxial, balanced and optical cables and accessories thereof is excluded.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[IEC 60728-13:2010](https://standards.iteh.ai/catalog/standards/sist/2786651d-676b-4142-bde2-424e99bbd4ea/iec-60728-13-2010)

<https://standards.iteh.ai/catalog/standards/sist/2786651d-676b-4142-bde2-424e99bbd4ea/iec-60728-13-2010>

¹ This word encompasses the HFC (Hybrid Fibre Cable) networks used nowadays to provide telecommunications services, voice, data, audio and video both broadcast and narrowcast.

CABLE NETWORKS FOR TELEVISION SIGNALS, SOUND SIGNALS AND INTERACTIVE SERVICES –

Part 13: Optical systems for broadcast signal transmissions

1 Scope

This part of IEC 60728 is applicable to optical transmission system for broadcast signal transmission that consists of a head-end equipment, optical transmission lines, in-house wirings and a system outlet. The system is primarily intended for television and sound signals using analogue and/or digital transmission technology. This standard specifies the basic system parameters and methods of measurement for optical distribution system having a system outlet in order to assess the system performance and its performance limits.

The purpose of this part of IEC 60728 is to describe the system specification of FTTH (fibre to the home) network for broadcast signal transmission. This standard is also applicable to the broadcast signal transmission using telecommunication network if it satisfies the optical portion of this standard. This standard describes RF transmission for broadcast and narrowcast (limited area distribution of broadcast) signals over FTTH, and introduces xPON system as a physical layer media. The detailed description of physical layer is out of the scope of this standard. The scope is limited to RF signal transmission over FTTH, thus, it does not include IP transport technologies, such as IP Multicast and associate protocols. Some interference descriptions between telecommunication system and broadcast system addressed in Clause 7 and Annex D should be referred to for detailed explanations. Annex A describes actual service systems with design consideration based on this standard. Annex B gives an overview of the optical transmission systems applicable for broadcast signal transmission.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60068-1:1988, *Environmental testing – Part 1: General and guidance*

IEC 60728-1:2007, *Cable networks for television signals, sound signals and interactive services – Part 1: System performance of forward paths*

IEC 60728-6:2003, *Cable networks for television signals, sound signals and interactive services – Part 6: Optical equipment*

IEC/TR 60728-6-1:2006, *Cable networks for television signals, sound signals and interactive services – Part 6-1: System guidelines for analogue optical transmission systems*

IEC 60825-1, *Safety of laser products – Part 1: Equipment classification and requirements*

IEC 60825-2, *Safety of laser products – Part 2: Safety of optical fibre communication systems (OFCS)*

IEC 60825-12, *Safety of laser products – Part 12: Safety of free space optical communication systems used for transmission of information*

IEC 61291-1:2006, *Optical amplifiers – Part 1: Generic specification*

IEC 61755-1:2005, *Fibre optic connector optical interfaces – Part 1: Optical interfaces for single mode non-dispersion shifted fibres – General and guidance*

IEC 61930:1998, *Fibre optic graphical symbology*

IEC 61931:1998, *Fibre optic – Terminology*

ITU-T Recommendation G.692, *Optical interfaces for multichannel systems with optical amplifiers*

ITU-T Recommendation G.694.2, *Spectral grids for WDM applications: CWDM wavelength grid*

3 Terms, definitions, symbols and abbreviations

3.1 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1.1

optical transmitting unit optical transmitter

transmit fibre optic terminal device accepting at its input port an electrical signal and providing at its output port an optical carrier modulated by that input signal

[IEC 61931, definition 2.9.6]

[IEC 60728-13:2010](https://standards.iteh.ai/catalog/standards/sist/2786651d-676b-4142-b1e2-424e907b14e9/iec-60728-13-2010)

[https://standards.iteh.ai/catalog/standards/sist/2786651d-676b-4142-](https://standards.iteh.ai/catalog/standards/sist/2786651d-676b-4142-b1e2-424e907b14e9/iec-60728-13-2010)

NOTE 1 For the purposes of this document, optical transmitters may have more than one input port accepting electrical RF signals.

NOTE 2 This piece of equipment amplifies frequency multiplexed electrical signals and converts these electrical signals into optical signals. The optical wavelength is a 1 500 nm band (1 550 ± 10 nm in 1 530 nm to 1 625 nm region).

3.1.2

optical receiving unit optical receiver

receive fibre optic terminal device accepting at its input port a modulated optical carrier, and providing at its output port the corresponding demodulated electrical signal (with the associated clock, if digital)

[IEC 61931, definition 2.9.7]

NOTE For the purposes of this document, optical receivers may have more than one output port providing electrical RF signals.

3.1.3

optical amplifier

optical waveguide device containing a suitably pumped, active medium which is able to amplify an optical signal

[IEC 61931, definition 2.7.75]

NOTE 1 In this document, Erbium Doped Fibre Amplifier (EDFA) is used for amplification in the 1 550 nm band.

NOTE 2 There are several methods based on wavelength to be used for amplification. The term “Erbium Doped Fibre Amplifier (EDFA)” is the synonym of optical amplifier in this document.

**3.1.4
fibre optic branching device
optical fibre coupler
splitter**

optical fibre device, possessing three or more optical ports, which shares optical power among its ports in a predetermined fashion, at the same wavelength or wavelengths, without wavelength conversion

NOTE The ports may be connected to fibres, detectors, etc.

[IEC 61931, definition 2.6.21, modified]

**3.1.5
multiplexing device
WDM device**

wavelength selective branching device (used in WDM transmission systems) in which optical signals can be transferred between two predetermined ports, depending on the wavelength of the signal

[IEC 61931, definition 2.6.51]

**3.1.6
optical modulation index**

optical modulation index of k^{th} RF carrier, m_k is defined as

$$m_k = \frac{\phi_h - \phi_l}{\phi_h + \phi_l}$$

iTeh STANDARD PREVIEW
(standards.iteh.ai)

total optical modulation index, M is defined as

<https://standards.iteh.ai/catalog/standards/sist/2786651d-676b-4142-bde2-424e99bbd4c1/iec-60728-13-2010>

$$M = \sqrt{\sum_{k=1}^K m_k^2}$$

where

- ϕ_h is the highest and
- ϕ_l is the lowest instantaneous optical power of the intensity modulated optical signal,
- K is the total number of RF carriers and
- M is the total optical modulation index.

NOTE This term is mainly used for analogue systems.

[IEC 60728-6, definition 3.1.10, modified]

**3.1.7
noise figure**

decrease of the signal-to-noise ratio (SNR), at the output of an optical detector with unitary quantum efficiency and zero excess noise, due to the propagation of a shot noise-limited signal through the optical fibre amplifier, expressed in dB

[IEC 61291-1, definition 3.2.38]

NOTE The noise figure of optical amplifiers depends on the optical input power and on the wavelength used.

3.1.8 relative intensity noise RIN

ratio of the mean square of the intensity fluctuations in the optical power of a light source to the square of the mean of the optical output power

NOTE 1 The RIN is usually expressed in dB(Hz⁻¹) resulting in negative values.

[IEC 60728-6, definition 3.1.12, modified]

NOTE 2 The value of RIN can also be calculated from the results of a carrier-to-noise measurement for the system.

3.1.9 responsivity

ratio of an optical detector's electrical output to its optical input at a given wavelength

NOTE 1 The responsivity is generally expressed in Ampere per Watt or Volt per Watt of incident radiant power.

NOTE 2 Sensitivity is sometimes used as an imprecise synonym for responsivity.

NOTE 3 The wavelength interval around the given wavelength may be specified.

[IEC 60728-6, definition 3.1.15]

3.1.10 wavelength

distance covered in a period by the wavefront of a harmonic plane wave

iTeh STANDARD PREVIEW
(standards.iteh.ai)

NOTE The wavelength λ of light in vacuum is given by

[IEC 60728-13:2010](#)

<https://standards.iteh.ai/catalog/standards/sist/2786651d-676b-4142-bde2-424e99bbd4ea/iec-60728-13-2010>

where

c is the speed of light in vacuum $c = 2,997\ 92 \times 10^8$ m/s);

f is the optical frequency

Although the wavelength in dielectric material, such as fibres, is shorter than in vacuum, only the wavelength of light in vacuum is used.

[IEC 60728-6, definition 3.1.17, modified]

3.1.11 central wavelength

the average of those wavelengths at which the amplitude of a light source reaches or last falls to half of the maximum amplitude

[IEC 60728-6, definition 3.1.26]

3.1.12 AM-VSB signal

sideband in which only the spectral components corresponding to the lower frequencies of the modulating signals are preserved, the other components being strongly attenuated

[IEV 702-06-28, modified]

NOTE This is the abbreviation for the vestigial sideband amplitude modulated signal used in the terrestrial broadcasting and CATV transmission system.

3.1.13
QAM signal
quadrature amplitude modulation
QAM

amplitude modulation by two separate signals of two sinusoidal carriers having the same amplitude and frequency but being in phase quadrature, the modulated signals being added for transmission in a single channel

[IEV 702-06-63, modified]

3.1.14
OFDM signal

orthogonal frequency division multiplexing is one of the multiplexing schemes used for the transportation of terrestrial digital broadcasting SDTV and HDTV signals

NOTE OFDM is based on the idea of frequency-division multiplexing, where each frequency channel is modulated with a simpler modulation, and the frequencies and modulation of FDM are arranged to be orthogonal with each other, which almost eliminates the interference between channels.

3.1.15
RF signal level definition

level of an RF signal is defined in Table 1; it is expressed in microvolt or in dB(μ V) or in dB(mW)

3.1.16
AM-VSB analogue signals

vision carrier signal level is the RMS value of the vision carrier at the peak of the modulation envelope (C_{rms}), expressed in dB(μ V) and measured across a 75 Ω termination or referred to 75 Ω

NOTE This will correspond, in negative modulation systems, to the carrier amplitude during synchronizing pulses and, in positive modulation systems, to that at peak white level without a chrominance signal, as shown in ITU-R Recommendation BT.470, Figure 1.

3.1.17
FM radio or FM audio carrier of a TV signals

level of an FM radio or of an FM audio carrier of a TV signal is the RMS value of the carrier expressed in dB(μ V) and measured across a 75 Ω termination or referred to 75 Ω

3.1.18
digitally modulated signals

level of a digitally modulated signal is given by the RMS power of the signal within the channel bandwidth ($S_{D,RF}$) and can be expressed in dB(mW) or in dB(μ V) referred to 75 Ω

NOTE The level of an OFDM signal is the average electrical power of the overall signal comprised of multi-carriers and is not the individual carrier level of the multi-carrier signal, as shown in Table 1.

Table 1 – Level of RF signals

Signal		Level detection	Symbol	Remarks
Analogue TV signal	AM-VSB video carrier	peak value	C_{rms}	RMS value of the carrier at the peak of the modulation envelope.
	FM audio carrier	RMS value	C_{rms}	The carrier level is a constant value.
QAM signal		RMS value	$S_{D,RF}$	The value is averaged over a sufficiently long period of time compared to period of the lowest frequency used for the modulation.
OFDM signal		RMS value		

3.1.19**carrier-to-noise ratio****C/N****signal-to-noise ratio** **$S_{D,RF}/N$**

ratios are given by

$$C/N \text{ (dB)} = C_{\text{rms}} - N_{\text{rms}} \quad (\text{for analogue signals})$$

$$S_{D,RF}/N \text{ (dB)} = S_{D,RF} - N_{\text{rms}} \quad (\text{for digital signals})$$

where N_{rms} is the RMS level of the noise in the equivalent noise bandwidth of the RF channel, expressed in dB(mW) or in dB(μ V) referred to 75 Ω

NOTE The level of the analogue modulated carrier or of the RF digitally modulated signal and the level of the noise shall be expressed in the same units, in dB(mW) or in dB(μ V) measured across a 75 Ω termination or referred to 75 Ω .

3.1.20**D/U ratio**

ratio of desired signal level, D [dB(μ V)], to undesired signal level, U [dB(μ V)]

NOTE The D/U ratio is generally used for multiple frequency interference as CSO and CTB, for single frequency interference as CCR.

3.1.21**single or multiple frequency interference**

besides the C/N and $S_{D,RF}/N$ ratios, single or multiple frequency interference to video signal is defined as the ratio of desired signal level and undesired signal level

NOTE 1 The ratio of desired signal level, D (dB(μ V)), to undesired signal level, U (dB(μ V)) is given by

$$D/U \text{ (dB)} = D - U$$

NOTE 2 The desired and the undesired signals can also be expressed both in dB(mW).

3.1.22**optical line terminal****OLT**

central office-terminal equipment that is linked with the Optical Network Unit (ONU) in customer premises

NOTE OLT usually connects with headend equipment.

3.1.23**optical network unit****ONU**

terminal equipment linked with OLT

3.1.24**video-optical network unit****V-ONU**

terminal unit that changes the optical signal of a broadcast system into an electric signal

NOTE The term V-ONU is used as the synonym of optical receiver (O/E) in this standard.