

INTERNATIONAL STANDARD

**Radio frequency and coaxial cable assemblies –
Part 2-6: Detail specification for cable assemblies for radio and TV receivers –
Frequency range 0 MHz to 3 000 MHz, IEC 61169-24 connectors**

IEC 60966-2-6:2009

<https://standards.iteh.ai/catalog/standards/sist/541b5ab3-4140-4dc6-9595-a18ff40b39fb/iec-60966-2-6-2009>



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2009 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland
Email: inmail@iec.ch
Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: www.iec.ch/online_news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: www.iec.ch/webstore/custserv

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch
Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00

INTERNATIONAL STANDARD

**Radio frequency and coaxial cable assemblies –
Part 2-6: Detail specification for cable assemblies for radio and TV receivers –
Frequency range 0 MHz to 3 000 MHz, IEC 61169-24 connectors**

<https://standards.iteh.ai/catalog/standards/sist/541b5ab3-4140-4dc6-9595-a18ff40b39fb/iec-60966-2-6-2009>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE

G

ICS 33.120.10

ISBN 978-2-88910-359-1

INTERNATIONAL ELECTROTECHNICAL COMMISSION

RADIO FREQUENCY AND COAXIAL CABLE ASSEMBLIES –**Part 2-6: Detail specification
for cable assemblies for radio and TV receivers –
Frequency range 0 MHz to 3 000 MHz, IEC 61169-24 connectors**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60966-2-6 has been prepared by IEC technical committee 46: Cables, wires, waveguides, R.F. connectors, R.F. and microwave passive components and accessories.

This third edition cancels and replaces the second edition and constitutes a technical revision.

Main changes with respect to the second edition are the updating of references as well as the requirement for screening attenuation.

The text of this standard is based on the following documents:

FDIS	Report on voting
46/305/FDIS	46/317/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This detail specification is to be read with IEC 60966-1:1999, with IEC 60966-2-1:2008 and with IEC 60966-2-2:2003.

A list of all parts of the IEC 60966 series, under the general title: *Radio frequency and coaxial cable assemblies*, can be found on the IEC website.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

[IEC 60966-2-6:2009](https://standards.iteh.ai/catalog/standards/sist/541b5ab3-4140-4dc6-9595-a18ff40b39fb/iec-60966-2-6-2009)

<https://standards.iteh.ai/catalog/standards/sist/541b5ab3-4140-4dc6-9595-a18ff40b39fb/iec-60966-2-6-2009>

INTRODUCTION

This detail specification applies to flexible coaxial cables described in IEC 60096-2. It relates to cable assemblies for radio and TV receivers, and in particular to the cable assemblies subfamily F (IEC 61169-24).

This detail specification gives subfamily requirements and severities which shall be applied.

Under qualification approval, the qualification will be conducted in accordance with 12.2 of IEC 60966-2-1 taking into account the specified variants. Only the tests whose results might depend on the variants will be repeated

Under capability approval, the qualification will be conducted on the relating CQCs as defined in 12.3 of IEC 60966-2-1 and described in the CM. Unless otherwise specified in the CM, only lot-by-lot tests from groups Ba and Eb will be conducted on delivered products, all other tests will be performed on CQCs as defined in 12.3 of IEC 60966-2-1 and described in the CM.

Reference documents

IEC 60966-1:1999, *Radio frequency and coaxial cable assemblies – Part 1: Generic specification – General requirements and test methods*

IEC 60966-2-1:2008, *Radio frequency and coaxial cable assemblies – Part 2-1: Sectional specification for flexible coaxial cable assemblies*

IEC 60966-2-2:2003, *Radio frequency and coaxial cable assemblies – Part 2-2: Blank detail specification for flexible coaxial cable assemblies*



IEC 61169-24, *Radio-frequency connectors – Part 24: Sectional specification – Radio frequency coaxial connectors with screw coupling, typically for use in 75 ohm cable distribution systems (type F)*

IEC 61196-6, *Coaxial communication cables – Sectional specification for CATV drop cables*

IEC 62153-4-3, *Metallic communication cable test methods – Part 4-3: Electromagnetic compatibility (EMC) – Surface transfer impedance – Triaxial method*

RADIO FREQUENCY AND COAXIAL CABLE ASSEMBLIES –

Part 2-6: Detail specification for cable assemblies for radio and TV receivers – Frequency range 0 MHz to 3 000 MHz, IEC 61169-24 connectors

[1] Prepared by IEC TC 46		[2] Document No. 60966-2-6 Issue: Third issue Date:		
[3] Available from: IEC 3 rue de Varembe Genève Suisse	[4] Generic specification: IEC 60966-1 Sectional specification: IEC 60966-2-1 Blank detail specification: IEC 60966-2-2			
[5] Additional references:				
Detail specification for coaxial cable assemblies for radio and TV receivers NOTE Example diagram, manufacturer to insert actual diagram				
 <p style="text-align: right; margin-right: 50px;">IEC 727/03</p>				
[6] Maximum diameter < 16,6 mm				
[7] Characteristic impedance: 75 Ω	[8] Frequency range: 0 MHz to 3 000 MHz			
[9] Weight: 40 g/m + 50 g (typically)	[10] Minimum inside radius: for static bending 25 mm for dynamic bending 75 mm			
[11] Climatic category: 40/70/21	[12] Applicable test group: Ba, Eb, Eh, Ee, Mn			
[13] <table style="width: 100%; border: none;"> <tr> <td style="width: 40%; vertical-align: top;"> Connector type: Cable type: Marking: Taper sleeves: On both ends (colour optional) </td> <td style="vertical-align: top;"> A IEC 61169-24 (F) Straight plug IEC 61196-6, IEC-75-yy or equivalent Optional </td> </tr> </table>			Connector type: Cable type: Marking: Taper sleeves: On both ends (colour optional)	A IEC 61169-24 (F) Straight plug IEC 61196-6, IEC-75-yy or equivalent Optional
Connector type: Cable type: Marking: Taper sleeves: On both ends (colour optional)	A IEC 61169-24 (F) Straight plug IEC 61196-6, IEC-75-yy or equivalent Optional			
[14] Variants	[15] Page 1 of 3 pages			

[16] Inspection values, ratings or characteristics	[17] Subclause ^a	[18] Value	[19] Remarks
Electrical			
Reflection properties	8.1	> 30 dB > 27 dB > 25 dB > 15 dB	5 MHz to 400 MHz >400 MHz to 862 MHz >862 MHz to 1 000 MHz >1 000 MHz to 3 000 MHz
Insertion loss	8.3	< 0,08 dB + 0,4 dB/m	Up to 3 000 MHz
Screening effectiveness:			
Transfer impedance Class A	IEC 62153-4-3	(<5 mΩ/m)	5 MHz to 30 MHz
Class B		UC	
Screening attenuation			
Class A	8.9 (further tests UC)	> 95 dB > 85 dB > 85 dB > 75 dB	>30 MHz to 1 000 MHz >1 GHz to 3 000 MHz >30 MHz to 1 000 MHz >1 GHz to 3 000 MHz
Class B			
Voltage proof	8.10	≥1,0 kV	50 Hz to 65 Hz peak value
Insulation resistance	8.11	≥10 ⁵ MΩ	Test voltage 500 V
Inner conductor continuity	8.12	OK	Low voltage DC
Outer conductor continuity	8.12	≤10 mΩ	After tensile test 9.1
Mechanical			
Tensile	9.1	>45 N	Interface OK Duration 1 min Test 8.12
Flexure	9.2	>500 cycles	Force 5 N 20/min Test 8.9
Flexing endurance	9.3	>20 cycles	Test 8.12 and 8.9
Cable assembly crushing	9.4	>700 N	Test 8.3
^a The relevant standard could be the generic, the sectional or both of them.			

Recommended grouping of test			Recommended severity					[27] Length of specimen
[20] Group	[21] Subclause ^a	Test	[22] Periodicity	[23] IL	[24] AQL	[25] n	[26] c	
Ba	7.2	Visual inspection	lot by lot	S3	4.0			
	7.3	Dimensional inspection	lot by lot	S3	4.0			
Eh	8.1	Reflection properties	lot by lot	II	1.0			
	8.2	Insertion loss	lot by lot	II	1.0			
Eb	8.10	Voltage proof	lot by lot	II	1.0			
	8.11	Insulation resistance	lot by lot	II	1.0			
	8.12	Inner and outer conductor continuity	lot by lot	III	1.0			
Ee	8.9	Screening attenuation Transfer impedance	1 year	I		1	0	
Mn	9.1	Tensile	3 years			3	0	On a CQC variant(e) 1 l = 300 mm
	9.2	Flexure	3 years					
	9.3	Flexing endurance	3 years					
	9.4	Cable assembly crushing	3 years					

^a The relevant standard could be the generic, the sectional or both of them.

IEC 60966-2-6:2009

<https://standards.iteh.ai/catalog/standards/sist/541b5ab3-4140-4dc6-9595-a18ff40b39fb/iec-60966-2-6-2009>

Withholdrawn

iTeh STANDARD PREVIEW
(standards.iteh.ai)

IEC 60966-2-6-2009

<https://standards.iteh.ai/catalog/standards/sist/541b5ab3-4140-4dc6-9595-a18ff40b39fb/iec-60966-2-6-2009>