

INTERNATIONAL STANDARD

NORME INTERNATIONALE



**Protection against lightning –
Part 3: Physical damage to structures and life hazard**

**Protection contre la foudre –
Partie 3: Dommages physiques sur les structures et risques humains**

STANDARD PREVIEW
(standards.iteh.ai)

IEC 62305-3:2010
<https://standards.iteh.ai/catalog/standards/sist/761a5c9b-cc0b-4d37-a995-ac286c957885/iec-62305-3-2010>





THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2010 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.
If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de la CEI ou du Comité national de la CEI du pays du demandeur.
Si vous avez des questions sur le copyright de la CEI ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de la CEI de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

Useful links:

IEC publications search - www.iec.ch/searchpub

The advanced search enables you to find IEC publications by a variety of criteria (reference number, text, technical committee,...).

It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available on-line and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary (IEV) on-line.

Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

A propos de la CEI

La Commission Electrotechnique Internationale (CEI) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications CEI

Le contenu technique des publications de la CEI est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Liens utiles:

Recherche de publications CEI - www.iec.ch/searchpub

La recherche avancée vous permet de trouver des publications CEI en utilisant différents critères (numéro de référence, texte, comité d'études,...).

Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

Just Published CEI - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications de la CEI. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire en ligne au monde de termes électroniques et électriques. Il contient plus de 30 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans les langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (VEI) en ligne.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: csc@iec.ch.



IEC 62305-3

Edition 2.0 2010-12

INTERNATIONAL STANDARD

NORME INTERNATIONALE



**Protection against lightning –
Part 3: Physical damage to structures and life hazard**

**Protection contre la foudre –
Partie 3: Dommages physiques sur les structures et risques humains**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 29.020; 91.120.40

ISBN 978-2-83220-129-9

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

CONTENTS

FOREWORD.....	7
INTRODUCTION.....	10
1 Scope.....	11
2 Normative references.....	11
3 Terms and definitions.....	12
4 Lightning protection system (LPS).....	15
4.1 Class of LPS.....	15
4.2 Design of the LPS.....	16
4.3 Continuity of steelwork in reinforced concrete structures.....	16
5 External lightning protection system.....	17
5.1 General.....	17
5.1.1 Application of an external LPS.....	17
5.1.2 Choice of external LPS.....	17
5.1.3 Use of natural components.....	17
5.2 Air-termination systems.....	18
5.2.1 General.....	18
5.2.2 Positioning.....	18
5.2.3 Air-terminations against flashes to the side of tall structures.....	19
5.2.4 Construction.....	20
5.2.5 Natural components.....	20
5.3 Down-conductor systems.....	21
5.3.1 General.....	21
5.3.2 Positioning for an isolated LPS.....	22
5.3.3 Positioning for a non-isolated LPS.....	22
5.3.4 Construction.....	23
5.3.5 Natural components.....	23
5.3.6 Test joints.....	24
5.4 Earth-termination system.....	24
5.4.1 General.....	24
5.4.2 Earthing arrangement in general conditions.....	25
5.4.3 Installation of earth electrodes.....	26
5.4.4 Natural earth electrodes.....	27
5.5 Components.....	27
5.5.1 General.....	27
5.5.2 Fixing.....	28
5.5.3 Connections.....	28
5.6 Materials and dimensions.....	28
5.6.1 Materials.....	28
5.6.2 Dimensions.....	28
6 Internal lightning protection system.....	30
6.1 General.....	30
6.2 Lightning equipotential bonding.....	31
6.2.1 General.....	31
6.2.2 Lightning equipotential bonding for metal installations.....	31
6.2.3 Lightning equipotential bonding for external conductive parts.....	32
6.2.4 Lightning equipotential bonding for internal systems.....	33

6.2.5	Lightning equipotential bonding for lines connected to the structure to be protected	33
6.3	Electrical insulation of the external LPS	34
6.3.1	General	34
6.3.2	Simplified approach	35
6.3.3	Detailed approach	35
7	Maintenance and inspection of an LPS	35
7.1	General	35
7.2	Application of inspections	36
7.3	Order of inspections	36
7.4	Maintenance	36
8	Protection measures against injury to living beings due to touch and step voltages	36
8.1	Protection measures against touch voltages	36
8.2	Protection measures against step voltages	37
Annex A (normative)	Positioning the air-termination system	38
Annex B (normative)	Minimum cross-section of the entering cable screen in order to avoid dangerous sparking	43
Annex C (informative)	Evaluation of the separation distance s	44
Annex D (normative)	Additional information for LPS in the case of structures with a risk of explosion	50
Annex E (informative)	Guidelines for the design, construction, maintenance and inspection of lightning protection systems	57
Bibliography	154
	http://standards.iteh.ai	
	IEC 62305-3:2010	
Figure 1	– Protection angle corresponding to the class of LPS	19
Figure 2	– Loop in a down-conductor	23
Figure 3	– Minimum length l_1 of each earth electrode according to the class of LPS	25
Figure A.1	– Volume protected by a vertical air-termination rod	38
Figure A.2	– Volume protected by a vertical air-termination rod	39
Figure A.3	– Volume protected by a wire air-termination system	39
Figure A.4	– Volume protected by isolated wires combined in a mesh according to the protection angle method and rolling sphere method	40
Figure A.5	– Volume protected by non-isolated wires combined in a mesh according to the mesh method and the protection angle method	41
Figure A.6	– Design of an air-termination system according to the rolling sphere method	42
Figure C.1	– Values of coefficient k_c in the case of a wire air-termination system	44
Figure C.2	– Values of coefficient k_c in the case of multiple down-conductors system	45
Figure C.3	– Values of coefficient k_c in the case of a sloped roof with air-termination on the ridge	47
Figure C.4	– Examples of calculation of the separation distance in the case of multiple down-conductors with an interconnecting ring of the down-conductors at each level	48
Figure C.5	– Values of coefficient k_c in the case of a meshed air-termination system, with a multiple down-conductors system	49
Figure E.1	– LPS design flow diagram	59
Figure E.2	– LPS design for a cantilevered part of a structure	65
Figure E.3	– Measuring the overall electrical resistance	66

Figure E.4 – Equipotential bonding in a structure with a steel reinforcement	68
Figure E.5 – Typical methods of joining reinforcing rods in concrete (where permitted).....	69
Figure E.6 – Example of clamps used as joints between reinforcing rods and conductors	70
Figure E.7 – Examples for connection points to the reinforcement in a reinforced concrete wall	71
Figure E.8 – Use of metallic facade as natural down-conductor system and connection of facade supports	75
Figure E.9 – Connection of the continuous strip windows to a metal facade covering.....	76
Figure E.10 – Internal down-conductors in industrial structures.....	79
Figure E.11 – Installation of bonding conductors in reinforced concrete structures and flexible bonds between two reinforced concrete parts	81
Figure E.12 – Protection angle method air-termination design for different heights according to Table 2	85
Figure E.13 – Isolated external LPS using two isolated air-termination masts designed according to the protection angle air-termination design method	86
Figure E.14 – Isolated external LPS using two isolated air-termination masts, interconnected by horizontal catenary wire	87
Figure E.15 – Example of design of an air-termination of a non-isolated LPS by air- termination rods.....	88
Figure E.16 – Example of design of an air-termination of a non-isolated LPS by a horizontal wire according to the protection angle air-termination design method	89
Figure E.17 – Protected volume of an air-termination rod on a sloped surface using the protection angle design method	90
Figure E.18 – Design of an LPS air-termination conductor network on a structure with complicated shape	91
Figure E.19 – Design of an LPS air-termination according to the protection angle method, mesh method and general arrangement of air-termination elements	92
Figure E.20 – Space protected by two parallel air-termination horizontal wires or two air-termination rods ($r > h_t$)	93
Figure E.21 – Three examples of design of non-isolated LPS air-termination according to the mesh method air-termination design	95
Figure E.22 – Four examples of details of an LPS on a structure with sloped tiled roofs	98
Figure E.23 – Air-termination and visually concealed conductors for buildings less than 20 m high, with sloping roofs.....	99
Figure E.24 – Construction of an LPS using natural components on the roof of the structure	101
Figure E.25 – Positioning of the external LPS on a structure made of isolating material e.g. wood or bricks with a height up to 60 m with flat roof and with roof fixtures	102
Figure E.26 – Construction of air-termination network on a roof with conductive covering where puncturing of the covering is not acceptable.....	103
Figure E.27 – Construction of external LPS on a structure of steel-reinforced concrete using the reinforcement of the outer walls as natural components.....	104
Figure E.28 – Example of an air-termination stud used on car park roofs.....	105
Figure E.29 – Air-termination rod used for protection of a metallic roof fixture with electric power installations which are not bonded to the air-termination system	106
Figure E.30 – Method of achieving electrical continuity on metallic parapet capping	107
Figure E.31 – Metallic roof fixture protected against direct lightning interception, connected to air-termination system.....	110

Figure E.32 – Examples of lightning protection of a house with a TV antenna	113
Figure E.33 – Installation of lightning protection of metallic equipment on a roof against a direct lightning flash	114
Figure E.34 – Connection of natural air-termination rod to air-termination conductor	116
Figure E.35 – Construction of the bridging between the segments of the metallic facade plates	117
Figure E.36 – Installation of external LPS on a structure of insulating material with different roof levels	120
Figure E.37 – Five examples of geometry of LPS conductors	121
Figure E.38 – Construction of an LPS using only two down-conductors and foundation earth electrodes	122
Figure E.39 – Four examples of connection of earth-termination to the LPS of structures using natural down-conductors (girders) and detail of a test joint	126
Figure E.40 – Construction of foundation earth ring for structures of different foundation design	130
Figure E.41 – Two examples of vertical electrodes in type A earthing arrangement	131
Figure E.42 – Meshed earth-termination system of a plant	135
Figure E.43 – Example of an equipotential bonding arrangement	142
Figure E.44 – Example of bonding arrangement in a structure with multiple point entries of external conductive parts using a ring electrode for interconnection of bonding bars	143
Figure E.45 – Example of bonding in the case of multiple point entries of external conductive parts and an electric power or communication line using an internal ring conductor for interconnection of the bonding bars	144
Figure E.46 – Example of bonding arrangement in a structure with multiple point entries of external conductive parts entering the structure above ground level	145
Figure E.47 – Directions for calculations of the separation distance, s , for a worst case lightning interception point at a distance l from the reference point according to 6.3	147
Table 1 – Relation between lightning protection levels (LPL) and class of LPS (see IEC 62305-1)	16
Table 2 – Maximum values of rolling sphere radius, mesh size and protection angle corresponding to the class of LPS	19
Table 3 – Minimum thickness of metal sheets or metal pipes in air-termination systems	21
Table 4 – Typical preferred values of the distance between down-conductors according to the class of LPS	22
Table 5 – LPS materials and conditions of use	27
Table 6 – Material, configuration and minimum cross-sectional area of air-termination conductors, air-termination rods, earth lead-in rods and down-conductors	29
Table 7 – Material, configuration and minimum dimensions of earth electrodes	30
Table 8 – Minimum dimensions of conductors connecting different bonding bars or connecting bonding bars to the earth-termination system	32
Table 9 – Minimum dimensions of conductors connecting internal metal installations to the bonding bar	32
Table 10 – Isolation of external LPS – Values of coefficient k_i	34
Table 11 – Isolation of external LPS – Values of coefficient k_m	34
Table 12 – Isolation of external LPS – Approximated values of coefficient k_c	35
Table B.1 – Cable length to be considered according to the condition of the screen	43
Table E.1 – Suggested fixing centres	96

Table E.2 – Maximum period between inspections of an LPS..... 149

iTeh STANDARD PREVIEW
(standards.iteh.ai)

IEC 62305-3:2010

<https://standards.iteh.ai/catalog/standards/sist/9b1a5c9b-ee6b-4d37-a995-ac286c957885/iec-62305-3-2010>

INTERNATIONAL ELECTROTECHNICAL COMMISSION

PROTECTION AGAINST LIGHTNING –**Part 3: Physical damage to structures and life hazard**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62305-3 has been prepared by IEC technical committee 81: Lightning protection.

This second edition cancels and replaces the first edition, published in 2006, and constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- 1) Minimum thicknesses of metal sheets or metal pipes given in Table 3 for air-termination systems are assumed as not able to prevent hot-spot problems.
- 2) Steel with electro-deposited copper is introduced as material suitable for LPS.
- 3) Some cross-sectional areas of LPS conductors were slightly modified.
- 4) For bonding purposes, isolating spark gaps are used for metal installations and SPD for internal systems.

- 5) Two methods – simplified and detailed – are provided for evaluation of separation distance.
- 6) Protection measures against injuries of living beings due to electric shock are considered also inside the structure.
- 7) Improved information for LPS in the case of structures with a risk of explosion are given in Annex D (normative).

This bilingual version (2012-06) corresponds to the monolingual English version, published in 2010-12.

The text of this standard is based on the following documents:

FDIS	Report on voting
81/372/FDIS	81/382/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

The French version of this standard has not been voted upon.

This publication has been drafted, as closely as possible, in accordance with the ISO/IEC Directives, Part 2.

A list of all the parts in the IEC 62305 series, under the general title *Protection against lightning*, can be found on the IEC website (standards.iteh.ai)

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

In the United States, based on the requirements of NFPA 780: Standard for the Installation of Lightning Protection Systems:2008^[1] 1 and practical experience in the use of horizontal earth electrodes, the minimum length of horizontal earth electrodes is not required to be twice that required for vertical electrodes.

In France and Portugal:

- natural components cannot substitute as lightning protection components but may be used to complete/enhance the LPS;
- aluminium solid round diameters should be increased from 8 mm to 10 mm;
- stranded conductors cannot be used as down-conductors;
- diameter of solid round conductors should be increased from 16 mm to 18 mm;
- hot dip galvanized steel solid tape thickness should be increased from 2 mm to 3,5 mm.

In Russia the use of piping carrying and tanks containing readily-combustible or explosive materials as air-termination natural components or down-conductor natural components are not allowed in any case.

In Japan the minimum values of the cross-section are reduced from:

- 16 mm² to 14 mm² for copper and 25 mm² to 22 mm² for aluminium, for bonding conductors connecting different bonding bars and conductors connecting the bars to the earth-termination system;
- 6 mm² to 5 mm² for copper, 10 mm² to 8 mm² for aluminium and 16 mm² to 14 mm² for steel, for bonding conductors connecting internal metal installations to the bonding bars.

¹ References in square brackets refer to the bibliography.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[IEC 62305-3:2010](https://standards.iteh.ai/catalog/standards/sist/9b1a5c9b-ee6b-4d37-a995-ac286c957885/iec-62305-3-2010)

<https://standards.iteh.ai/catalog/standards/sist/9b1a5c9b-ee6b-4d37-a995-ac286c957885/iec-62305-3-2010>

INTRODUCTION

This part of IEC 62305 deals with the protection, in and around a structure, against physical damage and injury to living beings due to touch and step voltages.

The main and most effective measure for protection of structures against physical damage is considered to be the lightning protection system (LPS). It usually consists of both external and internal lightning protection systems.

An external LPS is intended to

- a) intercept a lightning flash to the structure (with an air-termination system),
- b) conduct the lightning current safely towards earth (using a down-conductor system),
- c) disperse the lightning current into the earth (using an earth-termination system).

An internal LPS prevents dangerous sparking within the structure using either equipotential bonding or a separation distance (and hence electrical insulation) between the external LPS (as defined in 3.2) components and other electrically conducting elements internal to the structure.

Main protection measures against injury to living beings due to touch and step voltages are intended to:

- 1) reduce the dangerous current flowing through bodies by insulating exposed conductive parts, and/or by increasing the surface soil resistivity,
- 2) reduce the occurrence of dangerous touch and step voltages by physical restrictions and/or warning notices.

IEC 62305-3:2010

The type and location of an LPS should be carefully considered in the initial design of a new structure, thereby enabling maximum advantage to be taken of the electrically conductive parts of the structure. By doing so, design and construction of an integrated installation is made easier, the overall aesthetic aspects can be improved, and the effectiveness of the LPS can be increased at minimum cost and effort.

Access to the ground and the proper use of foundation steelwork for the purpose of forming an effective earth-termination may well be impossible once construction work on a site has commenced. Therefore, soil resistivity and the nature of the earth should be considered at the earliest possible stage of a project. This information is fundamental to the design of an earth-termination system and may influence the foundation design work for the structure.

Regular consultation between LPS designers and installers, architects and builders is essential in order to achieve the best result at minimum cost.

If lightning protection is to be added to an existing structure, every effort should be made to ensure that it conforms to the principles of this standard. The design of the type and location of an LPS should take into account the features of the existing structure.

PROTECTION AGAINST LIGHTNING –

Part 3: Physical damage to structures and life hazard

1 Scope

This part of IEC 62305 provides the requirements for protection of a structure against physical damage by means of a lightning protection system (LPS), and for protection against injury to living beings due to touch and step voltages in the vicinity of an LPS (see IEC 62305-1).

This standard is applicable to:

- a) design, installation, inspection and maintenance of an LPS for structures without limitation of their height,
- b) establishment of measures for protection against injury to living beings due to touch and step voltages.

NOTE 1 Specific requirements for an LPS in structures dangerous to their surroundings due to the risk of explosion are under consideration. Additional information is provided in Annex D for use in the interim.

NOTE 2 This part of IEC 62305 is not intended to provide protection against failures of electrical and electronic systems due to overvoltages. Specific requirements for such cases are provided in IEC 62305-4.

NOTE 3 Specific requirements for protection against lightning of wind turbines are reported in IEC 61400-24^[2].

2 Normative references

[IEC 62305-3:2010](https://standards.iteh.ai/catalog/standards/sist/9b1a5c9b-ee6b-4d37-a995-1136c770d121/iec-62305-3-2010)

[https://standards.iteh.ai/catalog/standards/sist/9b1a5c9b-ee6b-4d37-a995-](https://standards.iteh.ai/catalog/standards/sist/9b1a5c9b-ee6b-4d37-a995-1136c770d121/iec-62305-3-2010)

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60079-10-1:2008, *Explosive atmospheres – Part 10-1: Classification of areas – Explosive gas atmospheres*

IEC 60079-10-2:2009, *Explosive atmospheres – Part 10-2: Classification of areas – Combustible dust atmospheres*

IEC 60079-14:2007, *Explosive atmospheres – Part 14: Electrical installations design, selection and erection*

IEC 61557-4, *Electrical safety in low-voltage distribution systems up to 1 000 V a.c. and 1 500 V d.c. – Equipment for testing, measuring or monitoring of protective measures – Part 4: Resistance of earth connection and equipotential bonding*

IEC 61643-1, *Low-voltage surge protective devices – Part 1: Surge protective devices connected to low-voltage power distribution systems – Requirements and tests*

IEC 61643-21, *Low-voltage surge protective devices – Part 21: Surge protective devices connected to telecommunications and signalling networks – Performance requirements and testing methods*

IEC 62305-1, *Protection against lightning – Part 1: General principles*

IEC 62305-2, *Protection against lightning – Part 2: Risk management*

IEC 62305-4, *Protection against lightning – Part 4: Electrical and electronic systems within structures*

IEC 62561 (all parts)², *Lightning protection system components (LPSC)*

IEC 62561-1², *Lightning protection system components (LPSC) – Part 1: Requirements for connection components*

IEC 62561-3², *Lightning protection system components (LPSC) – Part 3: Requirements for isolating spark gaps*

ISO 3864-1, *Graphical symbols – Safety colours and safety signs – Part 1: Design principles for safety signs in workplaces and public areas*

3 Terms and definitions

For the purposes of this document, the following terms and definitions, some of which have already been cited in Part 1 but are repeated here for ease of reference, as well as those given in other parts of IEC 62305, apply.

3.1

lightning protection system

LPS

complete system used to reduce physical damage due to lightning flashes to a structure

NOTE It consists of both external and internal lightning protection systems.

3.2

external lightning protection system

part of the LPS consisting of an air-termination system, a down-conductor system and an earth-termination system

3.3

external LPS isolated from the structure to be protected

LPS with an air-termination system and down-conductor system positioned in such a way that the path of the lightning current has no contact with the structure to be protected

NOTE In an isolated LPS, dangerous sparks between the LPS and the structure are avoided.

3.4

external LPS not isolated from the structure to be protected

LPS with an air-termination system and down-conductor system positioned in such a way that the path of the lightning current can be in contact with the structure to be protected

3.5

internal lightning protection system

part of the LPS consisting of lightning equipotential bonding and/or electrical insulation of external LPS

3.6

air-termination system

part of an external LPS using metallic elements such as rods, mesh conductors or catenary wires intended to intercept lightning flashes

² In preparation.

3.7**down-conductor system**

part of an external LPS intended to conduct lightning current between the air-termination system and the earth-termination system

3.8**ring conductor**

conductor forming a loop around the structure and interconnecting the down-conductors for distribution of lightning current among them

3.9**earth-termination system**

part of an external LPS which is intended to conduct and disperse lightning current into the earth

3.10**earth electrode**

part or a group of parts of the earth-termination system which provides direct electrical contact with the earth and disperses lightning current to the earth

3.11**ring earth electrode**

earth electrode forming a closed loop around the structure below or on the surface of the earth

iTeh STANDARD PREVIEW

3.12**foundation earth electrode**

(standards.iteh.ai)

conductive part buried in the soil under a building foundation or, preferably, embedded in concrete of a building foundation, generally in form of a closed loop

<https://standards.iteh.ai/catalog/standards/sist/9b1a5c9b-ee6b-4d37-a995-ac286c957885/iec-62305-3-2010>
[IEC 60050-826:2004, 826-13-08]^[3]

3.13**conventional earth impedance**

ratio of the peak values of the earth-termination voltage and the earth-termination current which, in general, do not occur simultaneously

3.14**earth-termination voltage**

potential difference between the earth-termination system and the remote earth

3.15**natural component of LPS**

conductive component installed not specifically for lightning protection which can be used in addition to the LPS or in some cases could provide the function of one or more parts of the LPS

NOTE Examples of the use of this term include:

- natural air-termination;
- natural down-conductor;
- natural earth electrode.

3.16**connecting component**

part of an LPS which is used for the connection of conductors to each other or to metallic installations

NOTE This also includes bridging component and expansion piece.