



## Standard Practice for Selecting Bolting Lengths for Piping System Flanged Joints<sup>1</sup>

This standard is issued under the fixed designation F 704; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

*This standard has been approved for use by agencies of the Department of Defense.*

<sup>ε1</sup> NOTE—Keywords were added editorially in November 1996.

### 1. Scope

1.1 This practice covers bolt and stud bolt lengths, quantities, and thread series for pipe to pipe and pipe to valve flanged joints (Note 1) in the nominal pipe size ranges of ½-in. through 48-in. (12.7- through 1219-mm) diameter and pressure range of 125 through 2500 psi (0.8 through 17 236 kPa).

NOTE 1—This is applicable when flange of valve has the same thickness as mating flange.

1.2 The values stated in inch-pound units are to be regarded as the standard. The values given in parentheses are for information only.

1.3 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

### 2. Referenced Documents

#### 2.1 ANSI Standards:

##### B1.1 Unified Screw Threads<sup>2</sup>

B16.1 Cast Iron Pipe Flanges and Flanged Fittings (25, 125, 250, and 800 lb)<sup>2</sup>

B16.5 Steel Pipe Flanges and Flanged Fittings (150, 300, 400, 600, 900, 1500, and 2500 lb Including Reference to Valves)<sup>2</sup>

B16.24 Bronze Flanges and Flanged Fittings (150 and 300 lb)<sup>2</sup>

B18.2.1 Square and Hex Bolts and Screws<sup>2</sup>

B18.2.2 Square and Hex Nuts<sup>2</sup>

#### 2.2 Other Standard:

MSS SP-44 Steel Pipe Flanges<sup>3</sup>

### 3. Bolting Criteria

3.1 Bolt and stud bolt lengths are computed using the following (see Annex A1):

3.1.1 Includes maximum nut thickness in accordance with ANSI B18.2.2.

3.1.2 Does not include washer thickness.

3.1.3 Does not include bolt or stud bolt point height.

3.1.4 Includes allowance for up to ⅛-in. (3.2-mm) thick gaskets, except butterfly valves.

3.1.5 Includes ¼-in. (6.3-mm) raised face in addition to flange thickness listed in tables for flanges rated at 400 psi (2.8 kPa) and above.

3.1.6 Includes use of heavy hex nut and bolt design.

3.1.7 Includes plus tolerance for flange thickness in accordance with ANSI B16.5.

3.2 All bolts and stud bolts have threads in accordance with ANSI B1.1, Class 2A dimensioning and nuts Class 2B.

3.3 The material requirements for bolts, stud bolts, and nuts are obtained from the material specifications of individual system diagrams.

3.4 Alloy steel bolting 1-in. (25.4-mm) nominal diameter and smaller and all carbon steel bolting has threads of the UNC Series; alloy steel bolting above 1-in. nominal diameter has threads of the 8-UN Series.

3.5 For detailed descriptions of flange bolting assemblies, butterfly valve bolting assemblies, and tapped lug-type butterfly valve bolting assemblies, refer to Figs. 1–7.

### 4. List of Tables

4.1 The tables are arranged in the following sequence:

150-lb Steel Flanged Joints	Table 1
300-lb Steel Flanged Joints	Table 2
400-lb Steel Flanged Joints	Table 3
600-lb Steel Flanged Joints	Table 4
900-lb Steel Flanged Joints	Table 5
1500-lb Steel Flanged Joints	Table 6
2500-lb Steel Flanged Joints	Table 7
150-lb Bronze Flanged Joints	Table 8
300-lb Bronze Flanged Joints	Table 9
150-lb Steel Flat Face to 150-lb Bronze Flanged Joints	Table 10

<sup>1</sup> This practice is under the jurisdiction of ASTM Committee F-25 on Ships and Marine Technology and is the direct responsibility of Subcommittee F25.13 on Piping Systems.

Current edition approved Jan. 30, 1981. Published July 1981.

<sup>2</sup> Available from American National Standards Institute, 11 W. 42nd St., 13th Floor, New York, NY 10036.

<sup>3</sup> Available from Manufacturer's Standardization Society of the Valve and Fittings Industry, 1815 N. Fort Myer Dr., Arlington, VA 22209.

300-lb Steel Flat Face to 300-lb Bronze Flanged Joints	Table 11	Bolting Lengths for Tapped Lug-Type Butterfly Valve and 150 lb Bronze Flanges to ANSI B16.24	Table 18
125-lb Cast Iron to 150-lb Steel Flat Face Flanged Joints	Table 12		
250-lb Cast Iron to 300-lb Steel Flat Face Flanged Joints	Table 13		
800-lb Cast Iron to 600-lb Steel Flanged Joints	Table 14		
Wafer-Type Butterfly Valve and 150-lb Steel Flanges	Table 15		
Wafer-Type Butterfly Valve and 150-lb Bronze Flanges	Table 16		
Bolting Lengths for Tapped Lug-Type Butterfly Valve and 150-lb Steel Flanges to ANSI B16.5	Table 17		

5. Keywords

5.1 bolting lengths; cover bolt; flange joint(s); marine technology; ships; stud bolts

TABLE 1 Bolting Lengths for 150-lb Steel Flanged Joints to ANSI B16.5 and MSS SP-44 (see Fig. 1 and Fig. 2)

Nominal Pipe Size, in.	Bolt Diameter, in. <sup>A</sup>	Quantity per Joint	Flange Thickness, in. <sup>A</sup>	Bolt Stud Bolt Thread	Bolt Length Carbon Steel, in. <sup>A</sup>	Stud Bolt Length Carbon Steel, in. <sup>A</sup>
1/2	1/2	4	7/16	1/2-13 UNC-2A	1 3/4	2 1/4
3/4	1/2	4	1/2	1/2-13 UNC-2A	2	2 1/2
1	1/2	4	9/16	1/2-13 UNC-2A	2	2 1/2
1 1/4	1/2	4	5/8	1/2-13 UNC-2A	2 1/4	2 3/4
1 1/2	1/2	4	11/16	1/2-13 UNC-2A	2 1/4	2 3/4
2	5/8	4	3/4	5/8-11 UNC-2A	2 3/4	3 1/4
2 1/2	5/8	4	7/8	5/8-11 UNC-2A	3	3 1/2
3	5/8	4	15/16	5/8-11 UNC-2A	3	3 1/2
3 1/2	5/8	8	15/16	5/8-11 UNC-2A	3	3 1/2
4	5/8	8	15/16	5/8-11 UNC-2A	3	3 1/2
5	3/4	8	15/16	3/4-11 UNC-2A	3 1/4	3 3/4
6	3/4	8	1	3/4-10 UNC-2A	3 1/4	4
8	3/4	8	1 1/8	3/4-10 UNC-2A	3 1/2	4 1/4
10	7/8	12	1 3/16	7/8-9 UNC-2A	3 3/4	4 1/2
12	7/8	12	1 1/4	7/8-9 UNC-2A	4	4 3/4
14	1	12	1 3/8	1-8 UNC-2A	4 1/4	5 1/4
16	1	16	1 7/16	1-8 UNC-2A	4 1/2	5 1/4
18	1 1/8	16	1 9/16	1 1/8-7 UNC-2A 3/4	5 3/4	
20	1 1/8	20	1 11/16	1 1/8-7 UNC-2A	5 1/4	6 1/4
24	1 1/4	20	1 7/8	1 1/4-7 UNC-2A	5 3/4	6 3/4
26	1 1/4	24	2 1/16	1 1/4-7 UNC-2A	7 1/4	8 1/2
28	1 1/4	28	2 13/16	1 1/4-7 UNC-2A	7 1/2	8 3/4
30	1 1/4	28	2 15/16	1 1/4-7 UNC-2A	7 3/4	9
32	1 1/2	28	3 3/16	1 1/2-6 UNC-2A	8 3/4	10
34	1 1/2	32	3 1/4	1 1/2-6 UNC-2A	8 3/4	10
36	1 1/2	32	3 9/16	1 1/2-6 UNC-2A	9 1/2 10 3/4	
38	1 1/2	32	3 7/16	1 1/2-6 UNC-2A	9 1/4	10 1/2
40	1 1/2	36	3 9/16	1 1/2-6 UNC-2A	9 1/2	10 3/4
42	1 1/2	36	3 33/16	1 1/2-6 UNC-2A	10	11 1/4
44	1 1/2	40	4	1 1/2-6 UNC-2A	10 1/4	11 1/2
46	1 1/2	40	4 1/16	1 1/2-6 UNC-2A	10 1/2	11 3/4
48	1 1/2	44	4 1/4	1 1/2-6 UNC-2A	10 3/4	12 1/4

<sup>A</sup>1 in. = 25.4 mm.

TABLE 2 Bolting Lengths for 300-lb Steel Flanged Joints to ANSI B16.5 (see Fig. 1 and Fig. 2)

Nominal Pipe Size, in.	Bolt Diameter, in. <sup>A</sup>	Quantity per Joint	Flange Thickness, in. <sup>A</sup>	Bolt Stud Bolt Thread	Bolt Length Carbon Steel, in. <sup>A</sup>	Stud Bolt Length Carbon Steel, in. <sup>A</sup>
1/2	1/2	4	9/16	1/2-13 UNC-2A	2	2 1/2
3/4	5/8	4	5/8	5/8-11 UNC-2A	2 1/4	3
1	5/8	4	1 1/16	5/8-11 UNC-2A	2 1/2	3
1 1/4	5/8	4	3/4	5/8-11 UNC-2A	2 1/2	3 1/4
1 1/2	3/4	4	13/16	3/4-10 UNC-2A	3	3 1/2
2	5/8	8	7/8	5/8-11 UNC-2A	3	3 1/2
2 1/2	3/4	8	1	3/4-10 UNC-2A	3 1/4	4
3	3/4	8	1 1/8	3/4-10 UNC-2A	3 1/2	4 1/4
3 1/2	3/4	8	1 3/16	3/4-10 UNC-2A	3 3/4	4 1/4

**TABLE 2** *Continued*

Nominal Pipe Size, in.	Bolt Diameter, in. <sup>A</sup>	Quantity per Joint	Flange Thickness, in. <sup>A</sup>	Bolt Stud Bolt Thread	Bolt Length Carbon Steel, in. <sup>A</sup>	Stud Bolt Length Carbon Steel, in. <sup>A</sup>
4	3/4	8	1 1/4	3/4-10 UNC-2A	3 3/4	4 1/2
5	3/4	8	1 3/8	3/4-10 UNC-2A	4	4 3/4
6	3/4	12	1 7/16	3/4-10 UNC-2A	4 1/4	4 3/4
8	7/8	12	1 5/8	7/8-8 UNC-2A	4 3/4	5 1/2
10	1	16	1 7/8	1-8 UNC-2A	5 1/4	6 1/4
12	1 1/8	16	2	1 1/8-7 UNC-2A	5 3/4	6 3/4
14	1 1/8	20	2 1/8	1 1/8-7 UNC-2A	6	7
16	1 1/4	20	2 1/4	1 1/4-7 UNC-2A	6 1/4	7
18	1 1/4	24	2 3/8	1 1/4-7 UNC-2A	6 1/2	7 3/4
20	1 1/4	24	2 1/2	1 1/4-7 UNC-2A	7	8
24	1 1/2	24	2 3/4	1 1/2-6 UNC-2A	7 3/4	9

<sup>A</sup>1 in. = 25.4 mm.

**TABLE 3** Bolting Lengths for 400-lb Steel Flanged Joints to ANSI B16.5 (see Fig. 3 and Fig. 4)

Nominal Pipe Size, in.	Bolt Diameter, in. <sup>A</sup>	Quantity per Joint	Flange Thickness, in. <sup>A</sup>	Bolt Stud Bolt Thread	Bolt Length Alloy Steel, in. <sup>A</sup>	Stud Bolt Length Alloy Steel, in. <sup>A</sup>
1/2	B	B	B	B	B	B
3/4	B	B	B	B	B	B
1	B	B	B	B	B	B
1 1/4	B	B	B	B	B	B
1 1/2	B	B	B	B	B	B
2	B	B	B	B	B	B
2 1/2	B	B	B	B	B	B
3	B	B	B	B	B	B
3 1/2	B	B	B	B	B	B
4	7/8	8	1 3/8	7/8-9 UNC-2A	not used	5 1/2
5	7/8	8	1 1/2	7/8-9 UNC-2A	not used	5 3/4
6	7/8	12	1 5/8	7/8-9 UNC-2A	not used	6
8	1	12	1 7/8	1-8 UNC-2A	not used	6 3/4
10	1 1/8	16	2 1/8	1 1/8-8 UN-2A	not used	7 1/2
12	1 1/4	16	2 1/4	1 1/4-8 UN-2A	not used	8
14	1 1/4	20	2 3/8	1 1/4-8 UN-2A	not used	8 1/4
16	1 3/8	20	2 1/2	1 3/8-8 UN-2A	not used	8 3/4
18	1 3/8	24	2 5/8	1 3/8-8 UN-2A	not used	9
20	1 1/2	24	2 3/4	1 1/2-8 UN-2A	not used	9 1/2
24	1 3/4	24	3	1 3/4-8 UN-2A	not used	10 1/2

<sup>A</sup>1 in. = 25.4 mm.

<sup>B</sup>For dimensions of these pipe sizes, refer to Table 4.

**TABLE 4** Bolting Lengths for 600-lb Steel Flanged Joints to ANSI B16.5 (see Fig. 3 and Fig. 4)

Nominal Pipe Size, in.	Bolt Diameter, in. <sup>A</sup>	Quantity per Joint	Flange Thickness, in. <sup>A</sup>	Bolt Stud Bolt Thread	Bolt Length Alloy Steel, in. <sup>A</sup>	Stud Bolt Length Alloy Steel, in. <sup>A</sup>
1/2	1/2	4	9/16	1/2-13 UNC-2A	not used	3
3/4	5/8	4	5/8	5/8-11 UNC-2A	not used	3 1/2
1	5/8	4	1 1/16	5/8-11 UNC-2A	not used	3 1/2
1 1/4	5/8	4	1 3/16	5/8-11 UNC-2A	not used	3 3/4
1 1/2	3/4	4	7/8	3/4-10 UNC-2A	not used	4 1/4
2	5/8	8	1	5/8-11 UNC-2A	not used	4 1/4
2 1/2	3/4	8	1 1/8	3/4-10 UNC-2A	not used	4 3/4
3	3/4	8	1 1/4	3/4-10 UNC-2A	not used	5
3 1/2	7/8	8	1 3/8	7/8-9 UNC-2A	not used	5 1/2
4	7/8	8	1 1/2	7/8-9 UNC-2A	not used	5 3/4
5	1	8	1 3/4	1-8 UNC-2A	not used	6 1/2
6	1	12	1 7/8	1-8 UNC-2A	not used	6 3/4
8	1 1/8	12	2 3/16	1 1/8-8 UN-2A	not used	7 1/2
10	1 1/4	16	2 1/2	1 1/4-8 UN-2A	not used	8 1/2
12	1 1/4	20	2 5/8	1 1/4-8 UN-2A	not used	8 3/4
14	1 3/8	20	2 3/4	1 3/8-8 UN-2A	not used	9 1/4
16	1 1/2	20	3	1 1/2-8 UN-2A	not used	10
18	1 5/8	20	3 1/4	1 5/8-8 UN-2A	not used	10 3/4
20	1 5/8	24	3 1/2	1 5/8-8 UN-2A	not used	11 1/4

**TABLE 4** *Continued*

Nominal Pipe Size, in.	Bolt Diameter, in. <sup>A</sup>	Quantity per Joint	Flange Thickness, in. <sup>A</sup>	Bolt Stud Bolt Thread	Bolt Length Alloy Steel, in. <sup>A</sup>	Stud Bolt Length Alloy Steel, in. <sup>A</sup>
24	1 <sup>7</sup> / <sub>8</sub>	24	4	1 <sup>7</sup> / <sub>8</sub> -8 UN-2A	not used	13

<sup>A</sup>1 in. = 25.4 mm.

**TABLE 5** Bolting Lengths for 900-lb Steel Flanged Joints to ANSI B16.5 (see Fig. 3 and Fig. 4)

Nominal Pipe Size, in.	Bolt Diameter, in. <sup>A</sup>	Quantity per Joint	Flange Thickness, in. <sup>A</sup>	Bolt Stud Bolt Thread	Bolt Length Alloy Steel, in. <sup>A</sup>	Stud Bolt Length Alloy Steel, in. <sup>A</sup>
1/2	<i>B</i>	<i>B</i>	<i>B</i>	<i>B</i>	<i>B</i>	<i>B</i>
3/4	<i>B</i>	<i>B</i>	<i>B</i>	<i>B</i>	<i>B</i>	<i>B</i>
1	<i>B</i>	<i>B</i>	<i>B</i>	<i>B</i>	<i>B</i>	<i>B</i>
1 1/4	<i>B</i>	<i>B</i>	<i>B</i>	<i>B</i>	<i>B</i>	<i>B</i>
1 1/2	<i>B</i>	<i>B</i>	<i>B</i>	<i>B</i>	<i>B</i>	<i>B</i>
2	<i>B</i>	<i>B</i>	<i>B</i>	<i>B</i>	<i>B</i>	<i>B</i>
2 1/2	<i>B</i>	<i>B</i>	<i>B</i>	<i>B</i>	<i>B</i>	<i>B</i>
3	7/8	8	1 1/2	7/8-9 UNC-2A	not used	5 3/4
4	1 1/8	8	1 3/4	1 1/8-8 UN-2A	not used	6 3/4
5	1 1/4	8	2	1 1/4-8 UN-2A	not used	7 1/2
6	1 1/8	12	2 3/16	1 1/8-8 UN-2A	not used	7 1/2
8	1 3/8	12	2 1/2	1 3/8-8 UN-2A	not used	8 3/4
10	1 3/8	16	2 3/4	1 3/8-8 UN-2A	not used	9 1/4
12	1 3/8	20	3 1/8	1 3/8-8 UN-2A	not used	10
14	1 1/2	20	3 3/8	1 1/2-8 UN-2A	not used	10 3/4
16	1 5/8	20	3 1/2	1 5/8-8 UN-2A	not used	11 1/4
18	1 7/8	20	4	1 7/8-8 UN-2A	not used	12 3/4
20	2	20	4 1/4	2-8 UN-2A	not used	13 3/4
24	2 1/2	20	5 1/2	2 1/2-8 UN-2A	not used	17 1/4

<sup>A</sup>1 in. = 25.4 mm.

<sup>B</sup>For dimensions of these pipe sizes, refer to Table 6.

**TABLE 6** Bolting Lengths for 1500-lb Steel Flanged Joints to ANSI B16.5 (see Fig. 3 and Fig. 4)

Nominal Pipe Size, in.	Bolt Diameter, in. <sup>A</sup>	Quantity per Joint	Flange Thickness, in. <sup>A</sup>	Bolt Stud Bolt Thread	Bolt Length Alloy Steel, in. <sup>A</sup>	Stud Bolt Length Alloy Steel, in. <sup>A</sup>
1/2	3/4	4	7/8	3/4-10 UNC-2A	not used	4 1/4
3/4	3/4	4	1	3/4-10 UNC-2A	not used	4 1/2
1	7/8	4	1 1/8	7/8-9 UNC-2A	not used	5
1 1/4	7/8	4	1 1/8	7/8-9 UNC-2A	not used	5
1 1/2	1	4	1 1/4	1-8 UNC-2A	not used	5 1/2
2	7/8	8	1 1/2	7/8-9 UNC-2A	not used	5 3/4
2 1/2	1	8	1 5/8	1-8 UNC-2A	not used	6 1/4
3	1 1/8	8	1 7/8	1 1/8-8 UN-2A	not used	7
4	1 1/4	8	2 1/8	1 1/4-8 UN-2A	not used	7 3/4
5	1 1/2	8	2 7/8	1 1/2-8 UN-2A	not used	9 3/4
6	1 3/8	12	3 1/4	1 3/8-8 UN-2A	not used	10 1/4
8	1 5/8	12	3 3/8	1 5/8-8 UN-2A	not used	11 1/2
10	1 7/8	12	4 1/4	1 7/8-8 UN-2A	not used	13 1 / 4
12	2	16	4 7/8	2-8 UN-2A	not used	14 3/4
14	2 1/4	16	5 1/4	2 1/4-8 UN-2A	not used	16
16	2 1/2	16	5 3/4	2 1/2-8 UN-2A	not used	17 1/2
18	2 3/4	16	6 3/8	2 3/4-8 UN-2A	not used	19 1/2
20	3	16	7	3-8 UN-2A	not used	21 1/4
24	3 1/2	16	8	3 1/2-8 UN-2A	not used	24 1/4

<sup>A</sup>1 in. = 25.4 mm.

**TABLE 7** Bolting Lengths for 2500-lb Steel Flanged Joints to ANSI B16.5 (see Fig. 3 and Fig. 4)

Nominal Pipe Size, in.	Bolt Diameter, in. <sup>A</sup>	Quantity per Joint	Flange Thickness, in. <sup>A</sup>	Bolt Stud Bolt Thread	Bolt Length Alloy Steel, in. <sup>A</sup>	Stud Bolt Length Alloy Steel, in. <sup>A</sup>
1/2	3/4	4	1 3/16	3/4-10 UNC-2A	not used	4 3/4
3/4	3/4	4	1 1/4	3/4-10 UNC-2A	not used	5

TABLE 7 Continued

Nominal Pipe Size, in.	Bolt Diameter, in. <sup>A</sup>	Quantity per Joint	Flange Thickness, in. <sup>A</sup>	Bolt Stud Bolt Thread	Bolt Length Alloy Steel, in. <sup>A</sup>	Stud Bolt Length Alloy Steel, in. <sup>A</sup>
1	7/8	4	1 3/8	7/8-9 UNC-2A	not used	5 1/2
1 1/4	1	4	1 1/2	1-8 UNC-2A	not used	6
1 1/2	1 1/8	4	1 3/4	1 1/8-8 UN-2A	not used	6 3/4
2	1	8	2	1-8 UNC-2A	not used	7
2 1/2	1 1/8	8	2 1/4	1 1/8-8 UN-2A	not used	7 3/4
3	1 1/4	8	2 5/8	1 1/4-8 UN-2A	not used	8 3/4
4	1 1/2	8	3	1 1/2-8 UN-2A	not used	10
5	1 3/4	8	3 5/8	1 3/4-8 UN-2A	not used	11 3/4
6	2	8	4 1/4	2-8 UN-2A	not used	13 1/2
8	2	12	5	2-8 UN-2A	not used	15
10	2 1/2	12	6 1/2	2 1/2-8 UN-2A	not used	19 1/4
12	2 3/4	12	7 1/4	2 3/4-8 UN-2A	not used	21 1/4

<sup>A</sup>1 in. = 25.4 mm.

TABLE 8 Bolting Lengths for 150-lb Bronze Flanged Joints to ANSI B16.24 (see Fig. 1 and Fig. 2)

Nominal Pipe Size, in.	Bolt Diameter, in. <sup>A</sup>	Quantity per Joint	Flange Thickness, in. <sup>A</sup>	Bolt Stud Bolt Thread	Bolt Length Carbon Steel, in. <sup>A</sup>	Stud Bolt Length Carbon Steel, in. <sup>A</sup>
1/2	1/2	4	5/16	1/2-13 UNC-2A	1 1/2	2
3/4	1/2	4	11/32	1/2-13 UNC-2A	1 3/4	2 1/4
1	1/2	4	3/8	1/2-13 UNC-2A	1 3/4	2 1/4
1 1/4	1/2	4	13/32	1/2-13 UNC-2A	1 3/4	2 1/4
1 1/2	1/2	4	7/16	1/2-13 UNC-2A	1 3/4	2 1/4
2	5/8	4	1/2	5/8-11 UNC-2A	2	2 3/4
2 1/2	5/8	4	9/16	5/8-11 UNC-2A	2 1/4	2 3/4
3	5/8	4	5/8	5/8-11 UNC-2A	2 1/4	3
3 1/2	5/8	8	11/16	5/8-11 UNC-2A	2 1/2	3
4	5/8	8	11/16	5/8-11 UNC-2A	2 1/2	3
5	3/4	8	3/4	3/4-10 UNC-2A	2 3/4	3 1/2
6	3/4	8	13/16	3/4-10 UNC-2A	3	3 1/2
8	3/4	8	15/16	3/4-10 UNC-2A	3 1/4	3 3/4
10	7/8	12	1	7/8-9 UNC-2A	3 1/2	4 1/4
12	7/8	12	1 1/8	7/8-9 UNC-2A	3 1/2	4 1/4

<sup>A</sup>1 in. = 25.4 mm.

TABLE 9 Bolting Lengths for 300-lb Bronze Flanged Joints to ANSI B16.24 (see Fig. 1 and Fig. 2)

Nominal Pipe Size, in.	Bolt Diameter, in. <sup>A</sup>	Quantity per Joint	Flange Thickness, in. <sup>A</sup>	Bolt Stud Bolt Thread	Bolt Length Carbon Steel, in. <sup>A</sup>	Stud Bolt Length Carbon Steel, in. <sup>A</sup>
1/2	1/2	4	1/2	1/2-13 UNC-2A	2	2 1/2
3/4	5/8	4	17/32	5/8-11 UNC-2A	2 1/4	2 3/4
1	5/8	4	19/32	5/8-11 UNC-2A	2 1/4	3
1 1/4	5/8	4	5/8	5/8-11 UNC-2A	2 1/4	3
1 1/2	3/4	4	11/16	3/4-10 UNC-2A	2 1/2	3 1/4
2	5/8	8	3/4	5/8-11 UNC-2A	2 1/2	3 1/4
2 1/2	3/4	8	13/16	3/4-10 UNC-2A	3	3 1/2
3	3/4	8	29/32	3/4-10 UNC-2A	3	3 3/4
3 1/2	3/4	8	31/32	3/4-10 UNC-2A	3 1/4	4
4	3/4	8	1 1/16	3/4-10 UNC-2A	3 1/4	4
5	3/4	8	1 1/8	3/4-10 UNC-2A	3 1/2	4 1/4
6	3/4	12	13/16	3/4-10 UNC-2A	3 1/2	4 1/4
8	7/8	12	1 3/8	7/8-9 UNC-2A	4 1/4	5

<sup>A</sup>1 in. = 25.4 mm.

**TABLE 10 Bolting Lengths for 150-lb Steel Flat Face to Bronze Flanged Joints to ANSI B16.5 and B16.24 (see Fig. 1 and Fig. 2)**

Nominal Pipe Size, in.	Bolt Diameter, in. <sup>A</sup>	Quantity per Joint	Flange Thickness, in. <sup>A</sup>		Bolt Stud Bolt Thread	Bolt Length Carbon Steel, in. <sup>A</sup>	Stud Bolt Length Carbon Steel, in. <sup>A</sup>
			Steel	Bronze			
1/2	1/2	4	7/16	5/16	1/2-13 UNC-2A	1 3/4	2 1/4
3/4	1/2	4	1/2	11/32	1/2-13 UNC-2A	1 3/4	2 1/4
1	1/2	4	9/16	3/8	1/2-13 UNC-2A	1 3/4	2 1/4
1 1/4	1/2	4	5/8	13/32	1/2-13 UNC-2A	2	2 1/2
1 1/2	1/2	4	11/16	7/16	1/2-13 UNC-2A	2	2 1/2
2	5/8	4	3/4	1/2	5/8-11 UNC-2A	2 1/4	3
2 1/2	5/8	4	7/8	9/16	5/8-11 UNC-2A	2 1/2	3 1/4
3	5/8	4	15/16	5/8	5/8-11 UNC-2A	2 3/4	3 1/4
3 1/2	5/8	8	15/16	11/16	5/8-11 UNC-2A	2 3/4	3 1/4
4	5/8	8	15/16	1 1/16	5/8-11 UNC-2A	2 3/4	3 1/4
5	3/4	8	15/16	3/4	3/4-10 UNC-2A	3	3 3/4
6	3/4	8	1	13/16	3/4-10 UNC-2A	3	3 3/4
8	3/4	8	1 1/8	15/16	3/4-10 UNC-2A	3 1/4	4
10	7/8	12	1 3/16	1	7/8-9 UNC-2A	3 1/2	4 1/2
12	7/8	12	1 1/4	1 1/16	7/8-9 UNC-2A	3 3/4	4 1/2

<sup>A</sup>1 in. = 25.4 mm.

**TABLE 11 Bolting Lengths for 300-lb Steel Flat Face to Bronze Flanged Joints to ANSI B16.5 and B16.24 (see Fig. 1 and Fig. 2)**

Nominal Pipe Size, in.	Bolt Diameter, in. <sup>A</sup>	Quantity per Joint	Flange Thickness, in. <sup>A</sup>		Bolt Stud Bolt Thread	Bolt Length Carbon Steel, in. <sup>A</sup>	Stud Bolt Length Carbon Steel, in. <sup>A</sup>
			Steel	Bronze			
1/2	1/2	4	9/16	1/2	1/2-13 UNC-2A	2	2 1/2
3/4	5/8	4	5/8	17/32	5/8-11 UNC-2A	2 1/4	2 3/4
1	5/8	4	11/16	19/32	5/8-11 UNC-2A	2 1/4	3
1 1/4	5/8	4	3/4	5/8	5/8-11 UNC-2A	2 1/2	3
1 1/2	3/4	4	13/16	11/16	3/4-10 UNC-2A	2 3/4	3 1/2
2	5/8	8	7/8	3/4	5/8-11 UNC-2A	2 3/4	3 1/4
2 1/2	3/4	8	1	13/16	3/4-10 UNC-2A	3	3 3/4
3	3/4	8	1 1/8	29/32	3/4-10 UNC-2A	3 1/4	4
3 1/2	3/4	8	13/16	31/32	3/4-10 UNC-2A	3 1/2	4
4	3/4	8	1 1/4	1 1/16	3/4-10 UNC-2A	3 1/2	4 1/4
5	3/4	8	1 3/8	1 1/8	3/4-10 UNC-2A	3 3/4	4 1/2
6	3/4	12	1 7/16	1 3/16	3/4-10 UNC-2A	3 3/4	4 1/2
8	7/8	12	1 5/8	1 3/8	7/8-9 UNC-2A	4 1/2	5 1/4

<sup>A</sup>1 in. = 25.4 mm.

**TABLE 12 Bolting Lengths for 125-lb Cast Iron to 150-lb Steel Flat Face Flanged Joints to MSS SP-44, ANSI B16.1, and ANSI B16.5 (see Fig. 1 and Fig. 2)**

Nominal Pipe Size, in.	Bolt Diameter, in. <sup>A</sup>	Quantity per Joint	Flange Thickness, in. <sup>A</sup>		Bolt Stud Bolt Thread	Bolt Length Carbon Steel, in. <sup>A</sup>	Stud Bolt Length Carbon Steel, in. <sup>A</sup>
			Cast Iron	Steel			
1	1/2	4	7/16	9/16	1/2-13 UNC-2A	2	2 1/2
1 1/4	1/2	4	1/2	5/8	1/2-13 UNC-2A	2	2 1/2
1 1/2	1/2	4	9/16	11/16	1/2-13 UNC-2A	2 1/4	2 3/4
2	5/8	4	5/8	3/4	5/8-11 UNC-2A	2 1/2	3
2 1/2	5/8	4	11/16	7/8	5/8-11 UNC-2A	2 3/4	3 1/4
3	5/8	4	3/4	15/16	5/8-11 UNC-2A	2 3/4	3 1/2
3 1/2	5/8	8	13/16	15/16	5/8-11 UNC-2A	3	3 1/2
4 through 24	<i>B</i>	<i>B</i>	<i>B</i>	<i>B</i>	<i>B</i>	<i>B</i>	<i>B</i>
30	1 1/4	28	2 1/8	2 15/16	1 1/4-7 UNC-2A	7	8 1/4
36	1 1/2	32	2 3/8	3 9/16	1 1/2-6 UNC-2A	8 1/4	9 1/2

<sup>A</sup>1 in. = 25.4 mm.

<sup>B</sup>For dimensions of these pipe sizes, refer to Table 1.