

SLOVENSKI STANDARD SIST ISO 8459-3:2005

01-november-2005

Informatika in dokumentacija – Seznam elementov bibliografskih podatkov – 3. del: Aplikacije za iskanje informacij

Information and documentation -- Bibliographic data element directory -- Part 3: Information retrieval applications

iTeh STANDARD PREVIEW (standards.iteh.ai)

Information et documentation -- Répertoire des éléments de données bibliographiques --Partie 3: Applications à la recherche documentaire de 205-de 16-4112-bdf6-

baf2e623908e/sist-iso-8459-3-2005

Ta slovenski standard je istoveten z: ISO 8459-3:1994

ICS:

01.140.20	Informacijske vede	Information sciences
35.240.30	Uporabniške rešitve IT v informatiki, dokumentiranju in založništvu	IT applications in information, documentation and publishing

SIST ISO 8459-3:2005

en



iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST ISO 8459-3:2005</u> https://standards.iteh.ai/catalog/standards/sist/dfdfb205-de16-4112-bdf6baf2e623908e/sist-iso-8459-3-2005

INTERNATIONAL STANDARD



First edition 1994-12-15

Information and documentation — Bibliographic data element directory —

Part 3: iTeh Sinformation Petrieval applications (standards.iteh.ai)

Information et documentation — Répertoire des éléments de données bibliographiques https://standards.iten.avcatalog/standards/sist/dfdfb205-de16-4112-bdf6-Partie 3: Applicationstàjla, recherche documentaire



Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting VIEW a vote.

International Standard ISO 8459-3 was prepared by Technical Committee ISO/TC 46, Information and documentation, Subcommittee SC 4, Computer applications in information and documentation.<u>TISO 8459-3:2005</u> https://standards.iteh.ai/catalog/standards/sist/dfdfb205-de16-4112-bdf6-

ISO 8459 consists of the following parts, lunder2the3general8title3Infors mation and documentation — Bibliographic data element directory:

- Part 1: Interloan applications
- Part 2: Acquisitions applications
- Part 3: Information retrieval applications

Annex A forms an integral part of this part of ISO 8459. Annexes B and C are for information only.

© ISO 1994

Printed in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization

Case Postale 56 • CH-1211 Genève 20 • Switzerland

Introduction

Data are interchanged for the purpose of starting or supporting a process. In order to transmit information required to support a process, the various elements of data in the interchanged messages must be fully understandable to the processes concerned. This part of ISO 8459 describes, in the form of a directory, data elements used to support information retrieval processes or applications.

The data elements that may occur in an information retrieval transaction are presented in four ways:

a) A data element directory (see clause 4) with annexes containing code values and description for messages (see A.1) and date time qualifier

(see A.2); iTeh ST

D) An index (see clause 5) consisting of names, keywords and synonyms (Stafor data elements and data element values including names assigned to date/time qualifiers and messages;

c) A structured order of data elements (see clause 6) which relates https://standards.itch.ai/similar/data elements in a hierarchical fashion; baf2e62 908e/sist-iso-8459-3-200

> d) A matrix (see clause 7) showing the data elements pertaining to specific information retrieval messages.

> ISO 8459 will, when complete, comprise a comprehensive data element directory for bibliographic use. This part of ISO 8459 is primarily intended for new documentation and information retrieval systems.

iTeh STANDARD PREVIEW This page intentionally left blank (standards.iteh.ai)

<u>SIST ISO 8459-3:2005</u> https://standards.iteh.ai/catalog/standards/sist/dfdfb205-de16-4112-bdf6baf2e623908e/sist-iso-8459-3-2005

Information and documentation — Bibliographic data element directory —

Part 3:

Information retrieval applications

1 Scope iTeh STANDARD maintain registers of currently valid International Standards.

This part of ISO 8459 specifies and detailed at a distribution of the specifies at a distributic at a distribution of the distribution of the specifies at

computer or computer-to-computer). distinals o identifies dards/sist/didfb205-de16-4112-bdf6messages and their data elements which are used inst-iso-84SO/JEC 646:1991, Information technology — ISO information retrieval transactions. 7-bit coded character set for information interchange.

It is intended to support both batch and interactive information retrieval transactions. Annex B provides examples of how this part of ISO 8459 may be used.

The structuring of the data elements in support of information retrieval applications falls outside the scope of this part of ISO 8459. For sample structuring of these data elements, see ISO 8777 (commands for interactive searching), ISO 10162 (search and retrieve application service definition for open systems interconnection) and ISO 10163 (search and retrieve application protocol specification for open systems interconnection).

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this part of ISO 8459. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this part of ISO 8459 are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO ISO 2108:1992, Information and documentation — International standard book numbering (ISBN).

ISO 2709:1981, Documentation — Format for bibliographic information interchange on magnetic tape.

ISO 2788:1986, Documentation — Guidelines for the establishment and development of monolingual thesauri.

ISO 3297:1986, Documentation — International standard serial numbering (ISSN).

ISO 4217:1990, Codes for the representation of currencies and funds.

ISO 5426:1983, Extension of the Latin alphabet coded character set for bibliographic information interchange.

ISO 5427:1984, Extension of the Cyrillic alphabet coded character set for bibliographic information interchange.

ISO 5428:1984, Greek alphabet coded character set for bibliographic information interchange.

ISO 7498-3:1989, Information processing systems — Open Systems Interconnection — Basic Reference Model — Part 3: Naming and addressing.

ISO 8601:1988, Data elements and interchange formats — Information interchange — Representation of dates and times.

ISO 8777:1993, Information and documentation — Commands for interactive text searching.

ISO 9040:1990, Information technology — Open Systems Interconnection — Virtual Terminal Basic Class Service.

ISO 9041-1:1990, Information technology — Open Systems Interconnection — Virtual Terminal Basic Class Protocol — Part 1: Specification.

ISO/IEC 10027:1990, Information technology — Information Resource Dictionary System (IRDS) framework. **Teh STANDA**

ISO 10162:1993, Information and documentation **Carc3:13 search request:** A structured query which de-Open Systems Interconnection — Search and Retrieve Application Service Definition.

ISO 10163-1:1993, Information and documentation stand — Open Systems Interconnection — Search and Retrieve Application Protocol Specification — Part 1: Protocol specification.

3 Definitions

For the purposes of this part of ISO 8459, the following definitions apply.

3.1 character string: A combination of letters, digits, punctuation marks or other symbols.

3.2 data element: A basic unit of identifiable and definable data. It has a data element name represented by a tag as identifier and one or more values for expressing (a) particular fact(s).

3.3 data element directory: A listing of data elements with specifications of representative data element values, as appropriate.

3.4 data element group: A set of related data elements.

3.5 data element group name: One or more words in a natural language identifying a data element group.

3.6 data element name: One or more words in a natural language identifying a data element.

3.7 data element value: A fact expressed by codes, digits or natural language corresponding to the data element description and representation.

3.8 information retrieval: The action, methods and procedures for recovering from stored data information on a given matter or references to pertinent documents.

3.9 message: A structured combination of data elements used in an information retrieval transaction.

3.10 record: A group of data usually treated as a unit.

3.11 representation: The way in which a particular data element value is expressed using one or more number(s), letter(s) or symbol(s).

3.12 result set: The group of records, citations, items, or other information units retrieved by the use of a FIND command in the search process.

SIST ISO 8459-52005 atop/standards/sist/dfdfb205-de16-4112-bdf6standards/s

3.14 tag: An identifier allocated for use in place of a data element name or data element group name. (In this part of ISO 8459, a group of three digits.)

3.15 transaction: The creation or modification of a message required to support the retrieval of full text or secondary information request for the source document and associated payments.

4 Directory

The directory names and defines data elements and data element groups used to support information retrieval transactions. The information pertaining to each data element or data element group is presented in four separate columns, labelled tag, name, description and representation. A "tag" is used to identify a data element as well as a data element group. "Name" contains data element names and data element group names. Data element group names are printed in bold letters to differentiate them from data element names. "Description" includes a definition for each data element or data element group followed by a list of corresponding tags for data elements that comprise the group. "Representation and remarks" includes explanatory text about conventions and/or standards used to represent values applicable to a data element or a data element group as well as sample values, if applicable. To ensure that the data element names, definitions and values are maintained in a timely fashion, ISO 8459-5 will provide specific procedures to be followed in processing updates to this part of ISO 8459.

Tag	Name	Description	Representation and remarks
001	Message	Data used to identify a particular message	
	identification	Group identifier for data elements 002-010.	
002	Message name	Phrase or code identifying the function of a message.	See A.1.
003	Date	Year, month and day on which a transaction is performed.	Also used in conjunction with date/time qual- ifier (905). See A.2 for the various qualifiers that can be specified. See ISO 8601.
004	Time stamp	Time at which a message was sent or re- ceived.	Used by automated systems to indicate the precise hour, minute and second that a trans- action occurred. Used in conjunction with date/time qualifier (905). See A.2.
010	Transaction number	Code or number assigned to identify a trans- action in support of information retrieval ser- vices (i.e. invoice, claim, etc.), RD PRF	This code or number is assigned by the insti- tution or system responsible for creating the specific type of document or message (i.e. invoice, claim, etc.).
040	Session details	Data which dentify various details about a specific session.	
		Group identifier for data elements 050-110, 1120, 550, 848, 849, 900-910, 10, 1120, 550, 848, 849, 900-910, 10, 10, 10, 10, 10, 10, 10, 10, 10,	de16-4112-bdf6-
050	Transaction participant	Data which identify each party associated with a transaction and the role performed by that party.	
		Group identifier for data elements 060-078, 110, 120.	
060	Participant's	Word or code which specifies the function or	Possible functions or roles include:
	function	role performed by a party to an information retrieval session.	0 = information service provider 1 = database producer 2 = gateway 3 = user 4 = directory
076	Password	Code used by a system to authenticate the identity of an individual or automated process that has requested or is using a system function or service.	This code may be revised periodically to pre- serve its security. A password is typically supplied by the user at session initiation time but it could also be requested at any time during a session.
			Other mechanisms for user authentification are being standardized, for example, security architecture, ISO 7498-2 and new work item on authentication framework.
			This data element is used in conjunction with user's identifier (122), an institution identifier (113) and telenetwork user ID (165).

Tag	Name	Description	Representation and remarks
077	Password edition	Code or phrase used to identify the current and previous password(s)	Two editions of passwords are defined to support password revision. These are:
			0 = old password 1 = current password
078	Password type	Code or phrase used to indicate the specific services allowed to the password holder.	This data element is used by systems to support multiple levels of authentication.
			Possible values include:
			 0 = system connection 1 = database connection 2 = read access 3 = write access 4 = delete privileges 5 = output instructions
			Security level (849) is used to control access to classified information. Related to access privileges (724), which provides various details associated with type of privilege (078).
080	Session identifier	Code or number used to identify a specific period of interaction between a user and an automated system TANDARD P (standards.ite)	A session typically covers all transactions be- tween user and system from log-on to log-off. Sessions may be aborted prematurely by un- usual systems or telecommunications events to produce an artificial log-off point. Soph-
		SIST ISO 8459-3:2005	pended and resumed later or to change applications during a particular session.
081	Subsession identifier	https://standards.iteh.ai/catalog/standards/sist/dfdl Code or number used_to_identify_ia_period5of3 interaction with one specific service provided within a single session on an automated sys- tem.	
086	Reference identifier	Code or number assigned to a system to sys- tem communication.	This number is used to monitor and verify that all system interactions have been transferred and processed in the proper sequence.
087	Continue flag	Instruction that processing should continue	Possible values include:
		even though resource constraints (090, 091, 092, 725) have been exceeded.	0 = continue 1 = stop
088	Suspend flag	Indication whether processing has been sus-	Possible values include:
		pended whenever resource constraints have been exceeded (090, 091, 092, 725).	0 = processing not suspended 1 = processing suspended
090	Cost constraint	Predefined monetary value, which if exceeded will result in a specific system action.	Cost constraints are frequently used to limit the system resources that may be consumed by any one user over a given period of time.
091	Hit constraint	Maximum number of records authorized to be retrieved in any given search	
092	Session length constraint	Predefined time limit, which if exceeded will result in a predefined system action.	A system will typically terminate session after a set amount of time of system usage or in- activity.

Tag	Name	Description	Representation and remarks
093	Transmission speed	Number used to designate the rate of data transmission between two pieces of computer equipment measured in bits per second.	
094	Packet size	Number of octets in a packet.	Packet formats are based on the general structure as defined in X.25. A single X.25 interface can theoretically handle 4.095 virtual channels, packet sizes up to 2.048 octets each, and packet sequencing to 128 packets per logical channel. Since network suppliers' nodal processors are too small to handle this much traffic through a single interface, in practice the support offered over each interface is limited to the current capacity of the network's access node.
095	Resource usage type	Code or phrase used to indicate the type of system resource that has been utilized within a session or given time period.	Systems typically maintain information on the following resources in order to support planning, monitoring and controlling of these resources: 0 = CPU time
		iTeh STANDARD PRE (standards.iteh.ai	 1 = connect time 2 = records retrieved online 3 ≓ records retrieved offline 4 = number of sessions 5 = octets of disk storage 6 = number of saved profiles
]	<u>SIST ISO 8459-3:2005</u> https://standards.iteh.ai/catalog/standards/sist/dfdfb205- baf2e623908e/sist-iso-8459-3-2005	10 = number of disk accesses 11 = number of tapes
			Used in conjunction with amount of usage (097).
096	System performance	Data collected to inform management about system performance.	Typical system performance measures in- clude:
			 0 = start-up delay 1 = percentage of downtime 2 = number of system malfunctions 3 = number of telecommunication interruptions 4 = average response time
			Used in conjunction with amount of usage (097).
097	Amount of usage	Quantities which measure the values estab- lished under resource usage type (095) and system performance (096).	
098	Records returned	An integer indicating the number of database and/or diagnostic records returned.	

Tag	Name	Description	Representation and remarks
101	User types	Identification of the category, chosen for management purposes, to which a user be- longs.	Possible values are: 0 = intermediary 1 = end user 2 = government 3 = university 4 = scientific institution
102	Search type	Identification of the type of search made against a database.	Used to indicate: bibliographic, directory, nu- meric, graphic and other types of searches.
103	Database type	Identification of the type of database, both generic and specific.	Used to indicate: bibliographic, directory, nu- meric, graphic and other types of databases.
110	Institution identification	Data elements intended to identify an insti- tution participating in a session.	
		Group identifier for data elements 111-113 and 130-137.	
111	Name of institution	Word, phrase or initialism intended to identify an institution or corporation.	
112	Abbreviated name	Short form of an institution's name (111). iTeh STANDARD P	REVIEW
113	Institution identifier	Unique number or code used by an infor- mation retrieval system to identify an insti- tution.	
120	User identification	Data elements intended to identify an individ- ual using an information retrieval system, or for whom the system is used.	b205-de16-4112-bdf6- -2005
		Group identifier for data elements 121-123 and 130-137.	
121	User's name	Name of the person that initiated the infor- mation retrieval session.	
122	User's identifier	Unique number or code used by an infor- mation retrieval system to identify a person initiating a session.	
123	User's affiliation	Identification of the institution with which the user is associated.	
130	Address	Code or phrase which gives the geographic location or place associated with an individual or an institution.	This element may be used in conjunction with institution name (111) or user's name (121). For telenetwork addresses see (160).
		Group identifier for data elements 131-137.	
131	Address instruction	Word or code which indicates the address to which the search results, Selective Dissemi- nation of Information (SDI) profiles, invoices,	This data element is used in conjunction with address (130).
		etc. are to be sent if different from the ad- dress for the source of a message.	Possible values include: 0 = ship to 1 = bill to

Tag	Name	Description	Representation and remarks
132	Post office box	Box number assigned by the postal authority.	May be used in conjunction with an institution name (111) or user's name (121).
133	Street and number	Number and phrase used to identify a location within a city or rural area.	
134	City	Word or phrase used to identify a city, includ- ing suburb or postal area.	
135	Region	Word or phrase identifying an area within a country, e.g. state, province, county.	
136	Country	Word or phrase used to identify a country.	
137	Postal code	Code assigned by the postal authorities of a country which uniquely identifies an address or group of addresses.	
150	Telecom- munications carrier	Word, phrase or initialism used to identify the telecommunications carrier facilities being used to access a remote system.	It may be necessary to identify more than one carrier.
160	Telenetwork address	Unique number or code used to identify a de- vice within a communications network.	
	autress	Group identifier for data elements 161-166.	VIEW
161	Telephone number	Unique number assigned to a telephone line ai	
162	Telefacsimile _h number	SIST ISO 8459-3:2005 Telecommunications number used for sending and receiving telefacsimiles. bal2eo23908e/sist-iso-8459-3-2005	de16-4112-bdf6-
164	Electronic mail identifier	Unique number assigned to an electronic mail box or service connection.	
165	Telenetwork user identifier	Unique code assigned to a user in a com- munications network.	This data element may or may not have the same value as institution identifier (113) or user's identifier (122).
166	Host system network address	Unique number or code used to identify a host system within a communications network.	See ISO 7498-3.
200	System prompt	Character, string of characters or menu used to support and guide user interaction with an automated system.	Systems should provide user prompts to guide user interaction.
230	Command expression	Request for the performance of an operation or for the execution of a particular computer program.	A command expression typically consists of a command word (240) and a command specification (250). Certain expressions may consist
		Group identifier for data elements 232-281, 610.	of a command word only, e.g. instruction to terminate session. A command specification when present follows the command word and qualifies the computer operation invoked by the command word.
232	Search history	Listing of command expressions previously used during a session.	