

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Testing of balanced communication cabling in accordance with ISO/IEC 11801 –
Part 2-20: Patch cords and work area cords – Blank detail specification for
class D applications

IEC 61935-2-20:2008
Essais de câblages de télécommunications symétriques selon l'ISO/IEC 11801 –
Partie 2-20: Cordons de brassage et cordons de zone de travail – Spécification
particulière cadre pour les applications de classe D



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2008 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de la CEI ou du Comité national de la CEI du pays du demandeur.

Si vous avez des questions sur le copyright de la CEI ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de la CEI de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland
Email: inmail@iec.ch
Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: www.iec.ch/online_news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

[IEC 61935-2-20:2008](#)

- Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: www.iec.ch/webstore/custserv

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch
Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00

A propos de la CEI

La Commission Electrotechnique Internationale (CEI) est la première organisation mondiale qui élabore et publie des normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications CEI

Le contenu technique des publications de la CEI est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

- Catalogue des publications de la CEI: www.iec.ch/searchpub/cur_fut-f.htm

Le Catalogue en-ligne de la CEI vous permet d'effectuer des recherches en utilisant différents critères (numéro de référence, texte, comité d'études,...). Il donne aussi des informations sur les projets et les publications retirées ou remplacées.

- Just Published CEI: www.iec.ch/online_news/justpub

Restez informé sur les nouvelles publications de la CEI. Just Published détaille deux fois par mois les nouvelles publications parues. Disponible en-ligne et aussi par email.

- Electropedia: www.electropedia.org

Le premier dictionnaire en ligne au monde de termes électroniques et électriques. Il contient plus de 20 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans les langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International en ligne.

- Service Clients: www.iec.ch/webstore/custserv/custserv_entry-f.htm

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions, visitez le FAQ du Service clients ou contactez-nous:

Email: csc@iec.ch
Tél.: +41 22 919 02 11
Fax: +41 22 919 03 00



IEC 61935-2-20

Edition 1.0 2008-05

INTERNATIONAL STANDARD

NORME INTERNATIONALE

**Testing of balanced communication cabling in accordance with ISO/IEC 11801 –
Part 2-20: Patch cords and work area cords – Blank detail specification for
class D applications**

**Essais de câblages de télécommunications symétriques selon l'ISO/IEC 11801 –
Partie 2-20: Cordons de brassage et cordons de zone de travail – Spécification
particulière cadre pour les applications de classe D**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

PRICE CODE
CODE PRIX



ICS 33.120.20

ISBN 978-2-88910-589-2

CONTENTS

FOREWORD.....	3
1 Scope.....	5
2 Normative references	5
3 Guidance for preparation of detail specifications	6
4 Blank detail specification for work area cord for class D applications.....	8
Bibliography.....	11

iTeh STANDARD PREVIEW **(standards.iteh.ai)**

[IEC 61935-2-20:2008](https://standards.iteh.ai/catalog/standards/sist/dd30ef2f-61da-4d5f-9b3c-f2b1676820e2/iec-61935-2-20-2008)

<https://standards.iteh.ai/catalog/standards/sist/dd30ef2f-61da-4d5f-9b3c-f2b1676820e2/iec-61935-2-20-2008>

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**TESTING OF BALANCED COMMUNICATION
CABLING IN ACCORDANCE WITH ISO/IEC 11801 –****Part 2-20: Patch cords and work area cords –
Blank detail specification for class D applications**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61935-2-20 has been prepared by IEC technical committee 46: Cables, wires, waveguides, R.F. connectors, R.F. and microwave passive components and accessories.

This first edition cancels and replaces the ISO/IEC PAS 61935-2-20 published in 2007. It constitutes a technical revision.

This bilingual version, published in 2009-05, corresponds to the English version.

The text of this standard is based on the following documents:

FDIS	Report on voting
46/270/FDIS	46/278/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

The French version of this standard has not been voted upon.

This blank detail specification is to be used in conjunction with IEC 61156-1, IEC 61156-6, IEC 60603-7-2 and IEC 60603-7-3.

A list of all parts of the IEC 61935 series can be found, under the general title *Testing of balanced communication cabling in accordance with ISO/IEC 11801*, on the IEC website.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition; or
- amended.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[IEC 61935-2-20:2008](#)

<https://standards.iteh.ai/catalog/standards/sist/dd30ef2f-61da-4d5f-9b3c-f2b1676820e2/iec-61935-2-20-2008>

TESTING OF BALANCED COMMUNICATION CABLING IN ACCORDANCE WITH ISO/IEC 11801 –

Part 2-20: Patch cords and work area cords – Blank detail specification for class D applications

1 Scope

This blank detail specification describes work area cord for class D applications, as defined in ISO/IEC 11801 as well as in the ISO/IEC 24702.

This blank detail specification determines the layout and style for detail specifications describing cords with transmission characteristics up to 100 MHz for digital communications. Detail specifications, based on this blank detail specification, may be prepared by a national organization, a manufacturer, or a user.

Test configuration applicable to cords is detailed in the IEC 61935-2.

The designation "Category 5e" is used herein to describe an enhanced category 5 cable (see Clause 1 of IEC 61156-6).

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60603-7-2, *Connectors for electronic equipment – Part 7-2: Detail specification for 8-way, unshielded, free and fixed connectors, for data transmissions with frequencies up to 100 MHz*

IEC 60603-7-3, *Connectors for electronic equipment – Part 7-3: Detail specification for 8-way, shielded, free and fixed connectors, for data transmissions with frequencies up to 100 MHz*

IEC 60794-1-2, *Optical fibre cables – Part 1-2: Generic specification – Basic optical cable test procedures*

IEC 61156-1:2007, *Multicore and symmetrical pair/quad cables for digital communications – Part 1: Generic specification*

IEC 61156-6:2007, *Multicore and symmetrical pair/quad cables for digital communications – Part 6: Symmetrical pair/quad cables with transmission characteristics up to 1 000 MHz – Work area wiring – Sectional specification*

IEC 61935-2:2005, *Testing of balanced communication cabling in accordance with ISO/IEC 11801 – Patch cords and work area cords*

IEC 62012-1, *Multicore and symmetrical pair/quad cables for digital communications to be used in harsh environments – Part 1: Generic specifications*

ISO/IEC 11801, *Information technology – Generic cabling for customer premises*

ISO/IEC 24702, *Information technology – Generic cabling – Industrial premises*

EN 50289-1-13, *Communication cables – Specifications for test methods – Part 1-13: Electrical test methods – Coupling attenuation or screening attenuation of patch cords / coaxial cable assemblies / pre-connectorised cables*¹

3 Guidance for preparation of detail specifications

It is necessary to keep the transmission characteristics indicated in the relevant sectional specification for the referenced category number, i.e. 5e and the characteristic impedance.

The detail specification shall be written in accordance with the layout of the blank detail specification, which forms part of this standard.

NOTE 1 When a characteristic does not apply, then “na” (for not applicable) should be entered in the appropriate space.

NOTE 2 When a characteristic applies but a specific value is not considered necessary, then “ns” (for not specified) should be entered in the appropriate space. When ns is used, the appropriate requirement in the sectional specification should apply.

The numbers shown in brackets in this and the following pages correspond to the following items of required information, which should be entered in the spaces provided.

- [1] Name and address of the organization that has prepared the document.
- [2] IEC document number, issue number and date of issue.
- [3] Address of the organization from which the document is available.
- [4] Related documents.
- [5] Any other reference to the cable, national reference, trade name, etc.
- [6] A complete description of the cable which shall include
 - a) type and number of elements;
 - b) nominal impedance;
 - c) screening;
 - d) application;
 - e) category;
 - f) other distinguishing performance characteristics.

Example: 4-pair, unshielded twisted pair cable for use in work area wiring, having a nominal impedance of 100 Ω, and meeting the transmission requirements of category 5e and the coupling attenuation requirements of type III.

- [7] Details of the cable material and construction.
- [8] Special requirements for bending radius or operating temperatures.
- [9] List of cable characteristics. They are separated into electrical, transmission, mechanical and environmental characteristics.

The recommended environmental severities are derived from the MICE table requirements of ISO/IEC 24702. These recommendations were made to better reflect the cable behaviour.

It should be noted that ingress requirements using particles are not applicable to a cable.

The temperature requirements are addressed in [8]. Rapid change of temperature is irrelevant for cables.

¹ The EN 50289-1-13 will be replaced with equivalent IEC publication when available.

Electromagnetic requirements coming from the MICE table of ISO/IEC 24702 have been dealt with by using the requirements that are given for transfer impedance, screening attenuation and coupling attenuation. ESD requirements are considered non-applicable

- [10] Appropriate subclause references in the generic specification IEC 61156-1/ 61935-2/ 62012-1/ 60794-1-2 and EN 50289-1-13.
- [11] Appropriate subclause references in the sectional specification IEC 61156-6/ 61935-2/ 62012-1 and EN 50289-1-13.
- [12] Requirements applicable to this cable. The values shall meet the requirements of sectional specification IEC 61156-6 for category 5e.

For those limits that are not related to the cable category and for which a choice is proposed, they have to be chosen to meet the related MICE table requirements.


- [13] Comments – Relevant remarks.

iTeh STANDARD PREVIEW **(standards.iteh.ai)**

[IEC 61935-2-20:2008](https://standards.iteh.ai/catalog/standards/sist/dd30ef2f-61da-4d5f-9b3c-f2b1676820e2/iec-61935-2-20-2008)

<https://standards.iteh.ai/catalog/standards/sist/dd30ef2f-61da-4d5f-9b3c-f2b1676820e2/iec-61935-2-20-2008>

4 Blank detail specification for work area cord for class D applications

[1] Prepared by:	[2] Document: Issue: Date:		
[3] Available from:	[4] Sectional for the testing of cords:	IEC 61935-2	
	Blank detail specification:	IEC 61935-2-20	
[5] Additional references: ISO/IEC 11801			
[6] Cord description:			
<ul style="list-style-type: none"> a) Category b) Nominal impedance c) Connector type d) Cable e) Screening f) Housing g) MICE 			
[7] Cable assembly construction:			
 <p style="text-align: center;">IEC 61935-2-20:2008 IEC 723/08 https://standards.iteh.ai/catalog/standards/sist/dd30ef2f-61da-4d5f-9b3c-e2/iec-61935-2-20-2008</p>			
IEC 61935-2, 4.1	IEC 61156-1	IEC 61156-6	
	5.2.6	5.2.6	Sheath
	5.2.6	5.2.6	Material
	5.2.7.1	5.2.7	Nominal thickness ^a
			Colour
			Maximum overall
			Diameter
			Marking
	2.2.13	2.2.13	Packaging:
Visual inspection	IEC 61935-2, 5.1		
[8]			
Minimum bending radius for static bending:		mm	
Minimum bending radius for dynamic bending:		mm	
Temperature range for installation		°C	
Operating temperature range under static conditions: –10 °C to +60 °C (C1), –25 °C to +70 °C (C2), –40 °C to +70°C (C3) ^d			

[9] Characteristics	[10] IEC 61156-1 subclause	[11] IEC 61156-6 subclause	[12] Recommended severities/ Requirements			[13] Comments
Electrical characteristics	6.2	6.2				
DC loop resistance	6.2.1	6.2.1	Assumed to be met by design			
CS Resistance unbalance	6.2.2	6.2.2	Assumed to be met by design			
Wire map	IEC 61935-2, 5.2					
Transmission characteristics	6.3	6.3				
Propagation delay	– ^b	IEC 61935-2, 5.3	Assumed to be met by design			
Differential phase delay (skew)	– ^b	IEC 61935-2, 5.4	Assumed to be met by design			
Insertion loss		IEC 61935-2, 5.5	≤ ... dB			
Near-end crosstalk (pair to pair)	6.3.4	IEC 61935-2, 5.7	≥ ... dB			
Return loss		IEC 61935-2, 5.6	≥ ... dB			
Screening attenuation	EN 50289-1-13	EN 50289-1-13	na	≥40 dB	≥60 dB	
Transfer impedance	6.2.7	6.2.7	na	grade 2	grade 1	
Coupling attenuation	6.2.8	6.2.8	type III	type II	type I	
Mechanical and dimensional characteristics	6.4	6.4				
Tensile performance of the cord		IEC 61935-2, 6.2	≥ ...N			
Flexure		IEC 61935-2, 6.3				
Bending		IEC 61935-2, 6.4	≥ ...			
Twisting		IEC 61935-2, 6.5				
Crushing		IEC 61935-2, 6.6	700 N	1 100 N	2 200 N	d e
Dust test		IEC 61935-2, 6.7	2 cycles	10 cycles	20 cycles	
Impact test of the cable	6.4.9	6.4.9	na	10 J	20 J	d
Shock	IEC 62012-1, 3.4.4	IEC 62012-1	na	15 g / 11 ms	50 g / 11 ms	d
Bump	IEC 62012-1, 3.4.3	IEC 62012-1	na	15 g / 11 ms	50 g / 11 ms	d
Vibration	IEC 62012-1, 3.4.2	IEC 62012-1	na	10 – 500 Hz with 10 g	10 – 2 000 Hz with 20 g,	d
Water immersion	IEC 60794-1-2, méthode F10		na	1 m/ 12 h	1 m/ 12 h	j
Damp heat steady state	IEC 62012-1, 3.5.2	IEC 62012-1	na	60/90/ 10	60/90/ 56	d f g