

Edition 1.0 2009-02

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Surface mounting technology - Environmental and endurance test methods for surface mount solder joints -Part 1-5: Mechanical shear fatigue test

Technologie du montage en surface – Méthodes d'essais d'environnement et d'endurance des joints brasés montés en surface - Partie 1-5: Essai de fatigue par cisaillement mécanique





THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2009 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de la CEI ou du Comité national de la CEI du pays du demandeur. Si vous avez des questions sur le copyright de la CEI ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de la CEI de votre pays de résidence.

IEC Central Office 3, rue de Varembé CH-1211 Geneva 20 Switzerland Email: inmail@iec.ch Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

Catalogue of IEC publications: www.ieo.ch/searchpub ARD PREVIEW

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

IEC Just Published: www.iec.ch/online news/justpub
Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

• Electropedia: <u>www.electropedia.drgds.itch.ai/catalog/standards/sist/0ade255c-c3a0-4737-984b-</u> The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

Customer Service Centre: <u>www.iec.ch/webstore/custserv</u>

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: <u>csc@iec.ch</u> Tel.: +41 22 919 02 11 Fax: +41 22 919 03 00

A propos de la CEI

La Commission Electrotechnique Internationale (CEI) est la première organisation mondiale qui élabore et publie des normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications CEI

Le contenu technique des publications de la CEI est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Catalogue des publications de la CEI: www.iec.ch/searchpub/cur_fut-f.htm

Le Catalogue en-ligne de la CEI vous permet d'effectuer des recherches en utilisant différents critères (numéro de référence, texte, comité d'études,...). Il donne aussi des informations sur les projets et les publications retirées ou remplacées.

Just Published CEI: www.iec.ch/online_news/justpub

Restez informé sur les nouvelles publications de la CEI. Just Published détaille deux fois par mois les nouvelles publications parues. Disponible en-ligne et aussi par email.

Electropedia: <u>www.electropedia.org</u>

Le premier dictionnaire en ligne au monde de termes électroniques et électriques. Il contient plus de 20 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans les langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International en ligne.

Service Clients: <u>www.iec.ch/webstore/custserv/custserv_entry-f.htm</u>

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions, visitez le FAQ du Service clients ou contactez-nous:

Email: <u>csc@iec.ch</u> Tél.: +41 22 919 02 11

Fax: +41 22 919 03 00



Edition 1.0 2009-02

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Surface mountingitechnology - Environmental and endurance test methods for surface mount solder joints Tandards.iteh.ai) Part 1-5: Mechanical shear fatigue test

IEC 62137-1-5:2009

Technologie du montage en surface m Méthodes d'essais d'environnement et d'endurance des joints brases montes en surface -Partie 1-5: Essai de fatigue par cisaillement mécanique

INTERNATIONAL ELECTROTECHNICAL COMMISSION

COMMISSION ELECTROTECHNIQUE INTERNATIONALE

PRICE CODE CODE PRIX S

ICS 31.190

ISBN 978-2-88910-628-8

CONTENTS

FO	DREWORD	3
INT	TRODUCTION	5
1	Scope	6
2	Normative references	7
3	Terms and definitions	8
4	Test equipment and materials	
	4.1 Test equipment for mechanical shear fatigue testing	8
	4.2 Test substrate	8
	4.3 Solder alloy	9
	4.4 Solder paste	9
	4.5 Reflow soldering equipment	9
5	Mounting	9
6	Test conditions	10
	6.1 Pre-treatment	10
	6.2 Test procedures	10
7	6.3 Judging criteria	10
/ 0	Items to be included in the test report	۱۱ ۸۸
8	items to be given in the product specification	
Anı	Inex A (normative) Mechanical shear fatigue test equipment	
Anı	inex B (normative) Mechanical shear fatigue test procedure	15
Ani	inex C (informative) Evaluation of mechanical properties of a single solder joint by	17
Rih	24e39f1b8d595/jec-62137-1-5-2009	
	Shography	
Fig	gure 1 – Image drawing on evaluation area of joint strength	6
Fig	gure 2 – Schematic illustrations of thermomechanical and mechanical fatigue for	
sol	Ider joints	7
Fig	gure 3 – A typical temperature profile taken by reflow soldering equipment	10
Fig	gure A.1 – Sample structures of shear fatigue jig	13
Fig	gure B.1 – Example of set-up for electrical resistance measuring	16
Fig	gure C.1 – Schematic illustration of the single solder joint for mechanical fatigue	
tes	sting	18
Fig	gure C.2 – Schematic illustration of fixing jig for soldering of the single solder joint	18
Fig	gure C.3 – Schematic illustration of the shear fatigue jig	19
Fig	gure C.4 – Relationship between reaction forces and the number of cycles during a	1
Tati	igue test	
⊦ig	gure C.5 – Relationship between the displacement range and fatigue life	20

INTERNATIONAL ELECTROTECHNICAL COMMISSION

SURFACE MOUNTING TECHNOLOGY – ENVIRONMENTAL AND ENDURANCE TEST METHODS FOR SURFACE MOUNT SOLDER JOINTS –

Part 1-5: Mechanical shear fatigue test

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible <u>6</u> in their <u>5</u> national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter. 4e39flb8d595/iec-62137-1-5-2009
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62137-1-5 has been prepared by IEC technical committee 91: Electronics assembly technology.

The text of this standard is based on the following documents:

FDIS	Report on voting
91/826/FDIS	91/841/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 62137 series, under the general title *Surface mounting technology – Environmental and endurance test methods for surface mount solder joints*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>IEC 62137-1-5:2009</u> https://standards.iteh.ai/catalog/standards/sist/0ade255c-c3a0-4737-984b-4e39f1b8d595/iec-62137-1-5-2009

INTRODUCTION

The mechanical properties of lead-free solder joints between leads and lands on a printed wiring board are not the same with tin-lead-containing solder joints, due to their solder compositions. Thus, it becomes important to test the mechanical properties of solder joints of different alloys.

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>IEC 62137-1-5:2009</u> https://standards.iteh.ai/catalog/standards/sist/0ade255c-c3a0-4737-984b-4e39f1b8d595/iec-62137-1-5-2009

SURFACE MOUNTING TECHNOLOGY – ENVIRONMENTAL AND ENDURANCE TEST METHODS FOR SURFACE MOUNT SOLDER JOINTS –

Part 1-5: Mechanical shear fatigue test

1 Scope

The test method described in this part of IEC 62137 applies to area array packages, such as BGA. This test method is designed to evaluate the fatigue life of the solder joints between component leads and lands on a substrate as shown in Figure 1. A temperature cyclic approach is generally used to evaluate the reliability of solder joints. Another method is to mechanically cycle the solder joints to shorten the testing time rather than to produce the strains by changing temperatures. The methodology is the imposition of shear deformation on the solder joints by mechanical displacement instead of relative displacement generated by CTE (coefficient of thermal expansion) mismatch, as shown in Figure 2. In place of the temperature cycle test, the mechanical shear fatigue predicts the reliability of the solder joints. In this test method, the evaluation requires first to mount the surface mount component on the solder joints until fracture of the solder joints occurs. The properties of the solder joints (for example solder alloy, substrate, mounted device or design, etc.) are evaluated to assist in improving the strength of the solder joints.

NOTE This test, however, does not measure the strength of the electronic components. The test method to evaluate the robustness of the joint to a board is described in IEC 60068-2-21.



Figure 1 – Image drawing on evaluation area of joint strength







Key

 Δd Relative displacement

Δ*T* Temperature range Teh STANDARD PREVIEW

α Coefficient of thermal expansiostandards.iteh.ai)

Figure 2 – Schematic illustrations of thermomechanical and mechanical fatigue for solder joints

https://standards.iteh.ai/catalog/standards/sist/0ade255c-c3a0-4737-984b-

4e39f1b8d595/iec-62137-1-5-2009

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60068-1, Environmental testing – Part 1: General and guidance

IEC 61188-5 (all parts), Printed boards and printed board assemblies – Design and use

IEC 60194, Printed board design, manufacture and assembly – Terms and definitions

IEC 61190-1-2:2007, Attachment materials for electronic assembly – Part 1-2: Requirements for soldering pastes for high-quality interconnects in electronics assembly

IEC 61190-1-3, Attachment materials for electronic assembly – Part 1-3: Requirements for electronic grade solder alloys and fluxed and non-fluxed solid solders for electronic soldering applications

IEC 61249-2-7:2002, Materials for printed boards and other interconnecting structures – Part 2-7: Reinforced base materials clad and unclad – Epoxide woven E-glass laminated sheet of defined flammability (vertical burning test), copper-clad

IEC 61760-1, Surface mounting technology – Part 1: Standard method for the specification of surface mounting components (SMDs)

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60068-1, in IEC 60194, as well as the following apply.

3.1

mechanical shear fatigue life

number of cycles to attain the joint fracture between surface mount component terminals mounted on the printed board and the copper land of the substrate after application of cyclic mechanical shear deformation

3.2

ramp rate

moving velocities of the fixing jig attached to the actuator of the mechanical testing machine

3.3

displacement range

distance between the maximum and the minimum test position caused by pushing and pulling the actuator back, which means relative displacement in shear direction between the surface mount component and the substrate

3.4

maximum and minimum forces

reaction forces at the maximum and minimum test positions caused by shear deformation of the solder joint at each cycle

(standards.iteh.ai)

4 Test equipment and materials

IEC 62137-1-5:2009

4.1 Test equipments for a mechanical she ar fatigue (testing-c3a0-4737-984b-

4e39f1b8d595/iec-62137-1-5-2009

The equipment for mechanical shear testing consists of a tension-compression testing machine, sample fixing jigs, a resistance-measuring instrument and a recorder. The specifications shall be in compliance with those of the mechanical test equipment prescribed in Annex A.

4.2 Test substrate

Unless otherwise stated in the relevant product specifications, the test substrate shall satisfy the following conditions.

- a) Material: Epoxide woven glass fabric copper-clad laminated sheet, general purpose grade (IEC 61249-2-7:2002), with foil bonded to one side and a nominal thickness of the sheet, including the metal foil, of 1,6 mm with a tolerance of ±0,20 mm. The copper foil shall have a thickness of 0,035 mm ± 0,010 mm.
- b) Size: The size of the substrate depends on the size and shape of a surface mount device soldered on the substrate. The substrate shall be able to be fastened to the mechanical shear fatigue test equipment.
- c) Land geometry: The shape and size of a land shall comply with IEC 61188-5 (all parts) or the pad geometry recommended by the respective component supplier.
- d) Surface protection: The solderable areas of the substrate (lands) shall be protected against oxidization by suitable means, for example by an organic surface protection layer (OSP), or other finishes. This protective layer shall not have an adverse effect on the solderability of the lands under the soldering conditions of the reflow soldering equipment.

4.3 Solder alloy

Unless otherwise specified, the solder alloy shall consist of a ternary composition of Sn, Ag and Cu with 3,0 wt. % to 4,0 wt. % Ag and 0,5 wt. % to 1,0 wt. % Cu with Sn for balancing, for example Sn96,5Ag3,0Cu0,5. The solder alloy shall be in accordance with IEC 61190-1-3.

4.4 Solder paste

Unless otherwise stated in the relevant product specifications, solder paste should be chosen from IEC 61190-1-2. However, the solder to be used shall be the one that is specified in 4.3 above.

4.5 Reflow soldering equipment

Unless otherwise stated in the relevant product specifications, reflow-soldering equipment should be the one that can realize the temperature profile as shown in Figure 3.

5 Mounting

Unless otherwise stated in the relevant product specifications, the surface mount component shall be mounted on the substrate in the following sequence.

The following steps shall be taken.

- a) Apply the solder paste specified in 4.4 to the lands of a test substrate as specified in 4.2, using a stainless steel mask that has openings of the same size, shape and configuration as the lands as specified in item c) of 4.2 with a thickness of 100 μ m to 150 μ m.
- b) Mount the test specimen on the test substrate with the printed solder paste.
- c) Perform soldering using the reflow soldering equipment specified in 4.5 and the solder paste specified in 4.4 with the following conditions. Typical temperature profile of reflow soldering is given in Figure 3 and as proposed in IEC 61760-1. The temperature shall be measured at the land.



Continous line: typical process (terminal temperature) Dotted line: process limits. Bottom process limit (terminal temperature). Upper process limit (top surface temperature)

IEC 1176/07

Figure 3 – A typical temperature profile taken by reflow soldering equipment

<u>IEC 62137-1-5:2009</u>

6 Test conditions://standards.iteh.ai/catalog/standards/sist/0ade255c-c3a0-4737-984b-4e39f1b8d595/jec-62137-1-5-2009

6.1 Pre-treatment

Unless otherwise stated in the relevant product specifications, leave the specimen under standard atmospheric conditions (specified in IEC 60068-1) for 4 h or more.

6.2 Test procedures

Unless otherwise stated in the relevant product specifications, the following procedures should be followed. The detail of the mechanical shear fatigue test procedures is prescribed in Annex B.

- a) Fix the test sample to the fixing jig.
- b) Ramp rate, allowable displacement range and test temperature shall be set.
- c) Continue the mechanical shear fatigue tests at each level in the selected displacement range until the maximum force decreases to a certain value or the electrical resistancemeasuring instrument can detect electric continuity interruption. Make a record of the number of cycles at fatigue life.
- d) Make analytical observations of the fractured parts, as needed, verify the fracture mode and record it.

6.3 Judging criteria

When the maximum force decreases to a certain value, for example a 20 % drop from the initial value, or a momentary interruption detector detects that electrical continuity interruption has occurred in the specimen, it shall be judged as fatigue life.

The result obtained by the methods described in Annex A and Annex B shows the average measures for all the joints of the component mounted on the test specimen, including the

influences of the component and substrate with respect to fatigue life. Annex C describes the test procedure for evaluating the mechanical shear fatigue life of a single solder joint which is effective for eliminating the effects of the component and substrate on the fatigue life.

7 Items to be included in the test report

When a test report is required, agreement shall be made between the reporting party and the recipient on the selection of reporting items from the following:

- a) test date;
- b) location of the test organization;
- c) name of the electronic component, type, size, body dimensions and lead pitch;
- d) base materials of lead on electronic components; and with or without plating, and materials of plating;
- e) materials of the test substrate, dimensions and layer structure;
- f) measurements of the land on the substrate and materials for the surface treatment;
- g) type of solder and type of solder paste;
- h) temperature profile of reflow soldering and soldering ambience (for the case of a nitrogen ambient atmosphere, oxygen concentration should apply);
- i) model of the tensile and compression machine;
- j) details of the substrate bending jig (drawing is preferable);
- k) specifications of the electrical resistance-measuring instrument;
- I) specifications of the recorder;
- m) displacement rate;
- IEC 62137-1-5:2009
- n) displacement range/and the number of cycles to fracture initiation; -984b-
- o) fracture mode (photos, etc.). 4e39f1b8d595/iec-62137-1-5-2009

8 Items to be given in the product specification

The following items shall be included:

- a) test substrate (4.2);
- b) solder alloy (4.3);
- c) solder paste (4.4);
- d) reflow soldering equipment (4.5);
- e) mounting (Clause 5);
- f) pre-treatment (6.1);
- g) test procedures (6.2).