

Edition 3.1 2011-07

INTERNATIONAL STANDARD





THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2011 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de la CEI ou du Comité national de la CEI du pays du demandeur.

Si vous avez des questions sur le copyright de la CEI ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de la CEI de votre pays de résidence.

IFC Central Office 3, rue de Varembé CH-1211 Geneva 20 Switzerland Email: inmail@iec.ch

Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

Catalogue of IEC publications: www.iec.ch/searshpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

IEC Just Published: www.iec.ch/online news/justpub/

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

■ Customer Service Centre: www.iec.ch/webstore/custserv
If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us

Email: csc@iec.ch Tel.: +41 22 919 02 11 Fax: +41 22 919 03 00

A propos de la CEI

La Commission Electrotechnique Internationale (CEI) est la première organisation mondiale qui élabore et publie des normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications CEI

Le contenu technique des publications de la CEI est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

■ Catalogue des publications de la CEI: www.iec.ch/searchpub/cur_fut-f.htm

Le Catalogue en-ligne de la CEI vous permet d'effectuer des recherches en utilisant différents critères (numéro de référence, texte, comité d'études,...). Il donne aussi des informations sur les projets et les publications retirées ou remplacées.

Just Published CEI: www.iec.ch/online news/justpub

Restez informé sur les nouvelles publications de la CEI. Just Published détaille deux fois par mois les nouvelles publications parues. Disponible en-ligne et aussi par email.

Electropedia: www.electropedia.org

Le premier dictionnaire en ligne au monde de termes électroniques et électriques. Il contient plus de 20 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans les langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International en ligne.

Service Clients: <u>www.iec.ch/webstore/custserv/custserv_entry-f.htm</u>

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions, visitez le FAQ du Service clients ou contactez-nous:

Email: csc@iec.ch Tél.: +41 22 919 02 11 Fax: +41 22 919 03 00



Edition 3.1 2011-07

INTERNATIONAL STANDARD



INTERNATIONAL ELECTROTECHNICAL COMMISSION

COMMISSION ELECTROTECHNIQUE INTERNATIONALE

ICS 29.140.10 ISBN 978-2-88912-608-8

CONTENTS

FO	REWORD	4
INT	RODUCTION	6
1	General	7
	1.1 Scope	7
	1.2 Normative references	7
2	Terms and definitions	8
	2.1 Materials	8
	2.2 Means of fixing	8
3	General requirements	12
4	General conditions for tests	12
5		13
		13
	5.2 Standard rated currents	14
6	Classification	14
7	Marking	15
8	Dimensions	17
9	Protection against electric shock	18
10	Terminals	
11	Provision for earthing	21
12	Provision for earthing	23
13	Switched lampholders	27
14	Moisture resistance, insulation resistance and electrical strength	
15	Mechanical strength	30
P16	Screws, current-carrying parts and connections	
17	Creepage distances and clearances	
18	General resistance to heat	
19	Resistance to heat, fire and tracking	
20	Resistance to excessive residual stresses (season cracking) and to rusting	
Anı	nex A (normative) Season cracking/corrosion test	63
	liography	
Fig	ure 1 – Loading device (see 15.1)	44
_	ure 2 – Bending apparatus (see 15.4)	
_	ure 3 – Gauge for holes for backplate lampholders screws (see 12.11)	
·	ure 4 – Clarification of some of the definitions in Clause 2	
_		
_	ure 5 – Test cap B15d (see 18.3)	
_	ure 6 – Test cap B22d (see 18.3)	
_	ure 7 – Testing device (see 9.1)	
	ure 8 – Dimensions for shade support devices (see 8.1)	
Fig	ure 9 – Dimensions for protective shields for B22d lampholders (see 9.1)	52

Figure 10 – Test cap B15d (see 14.3)	53
Figure 11 – Test cap B22d (see 14.3)	54
Figure 12 – Typical apparatus for the heating test (see 18.5)	55
Figure 13 – Nipple thread for lampholders – Basic profile and design profile for the nut and for the screw	57
Figure 14 – Gauges for metric ISO thread for nipples	60
Figure 15 – Impact-test apparatus	61
Figure 16 – Mounting support	61
Figure 17 – Ball-pressure test apparatus	62
Figure 18 – Pressure apparatus	62
Table 1 – Dimensions of threaded entries and set screws	18
Table 2 – Minimum dimensions of pillar type terminals	
Table 4 – Pull and torque values	
Table 5 – Heights of fall	
Table 7 – Torque values	
Table 8 – Minimum distances for a.c. (50/60 Hz) sinusoidal voltages – Impulse	04
withstand category II	35
Table 9 – Heating cabinet temperature	36
Table 10 – Heating cabinet temperature	37
Table 11 – Test temperature and test lamp data	39
Table A.1 – Ph adjustment	63
s://standards.itehi/at.ing/stanlard/iec/07/1faea-18a9-4ad3-9b1f-10829bfba005/iec-611	

INTERNATIONAL ELECTROTECHNICAL COMMISSION

BAYONET LAMPHOLDERS

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall affach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This consolidated version of IEC 611843 consists of the third edition (2008) [documents 34B/1385/FDIS and 34B/1401/RVD, its amendment 1 (2011) [documents 34B/1587/FDIS and 34B/1599/RVD] and its corrigendum of February 2009. It bears the edition number 3.1.

The technical content is therefore identical to the base edition and its amendment and has been prepared for user convenience. A vertical line in the margin shows where the base publication has been modified by amendment 1. Additions and deletions are displayed in red, with deletions being struck through.

International Standard IEC 61184 has been prepared by subcommittee 34B: Lamp caps and holders, of IEC technical committee 34: Lamps and related equipment.

In this edition, information to lampholders intended to be used in applications where they are accessible in normal use (class II as well as class I luminaires) are introduced. Additionally, in Table 11, lamp data where lamps no longer exist has been removed and requirements for shade holder rings have been amended to include shade rings according to IEC 60399 into testing.

In this standard, the following print types are used:

- requirements proper: in roman type;
- test specifications: in italic type;
- notes: in small roman type.

The committee has decided that the contents of the base publication and its amendments will remain unchanged until the stability date indicated or the JEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- · reconfirmed,
- · withdrawn,
- · replaced by a revised edition, or
- amended.

IMPORTANT – The "colour inside" logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this publication using a colour printer.

ttps://standards.itch.ii/alay.g/standard.iie/07/11faea-18a9-4ad3-9h1f-10829hfba005/iec-61184-200

INTRODUCTION

This standard covers safety requirements for bayonet lampholders and includes references to IEC 60061 for the control of interchangeability and safety of the cap and holder fit.

NOTE Safety requirements ensure that electrical equipment constructed in accordance with these requirements does not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which it was intended.

The thermal characteristics of lampholders are specified by the rated operating temperature (symbol T), which is the highest temperature for which the lampholder is designed. The temperature rating and the resistance to heat specified in this standard are based on two different principles, as presently found in IEC 60238 for Edison screw lampholders and in other national standards for bayonet lampholders. After experience, it may be possible to rationalize the systems in future editions of this standard.

iTex Standards
(https://standards.iteh.ai)
Decureer Preview

(https://standards.iteh.ai)
(https://standards.iteh.a

BAYONET LAMPHOLDERS

1 General

1.1 Scope

This International Standard applies to bayonet lampholders B15d and B22d for connection of lamps and semi-luminaires to a supply voltage of 250 V.

This standard also covers lampholders which are integral with a luminaire or intended to be built into appliances. It covers the requirements for the lampholder only.

For all other requirements, such as protection against electric shock in the area of the terminals, the requirements of the relevant appliance standard shall be observed and tested after building into the appropriate equipment, when that equipment is tested according to its own standard. Lampholders for use by luminaire manufacturers only are not for retail sale.

NOTE Where lampholders are used in luminaires, their maximum operating temperatures are specified in IEC 60598-1.

B15d denotes the cap/holder fit as defined by IEC 60061-1, sheet 7004-11 and IEC 60061-2, sheet 7005-16 with the corresponding gauges.

B22d denotes the cap/holder fit as defined by IEC 60061-1, sheet 7004-10 and IEC 60061-2, sheet 7005-10 with the corresponding gauges.

1.2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60061 (all parts), Lamp caps and holders together with gauges for the control of interchangeability and safety

IEC 60061-1, Lamp caps and holders together with gauges for the control of interchangeability and safety – Part 1: Lamp caps

IEC 60061-2, Lamp caps and holders together with gauges for the control of interchangeability and safety – Part 2: Lampholders

IEC 60061-3, Lamp caps and holders together with gauges for the control of interchangeability and safety – Part 3: Gauges

IEC 60064, Tungsten filament lamps for domestic and similar general lighting purposes – Performance requirements

IEC 60068-2-75:1997, Environmental testing - Part 2-75: Tests - Test Eh: Hammer tests

IEC 60112:2003, Method for the determination of the proof and the comparative tracking indices of solid insulating materials

IEC 60227 (all parts), Polyvinyl chloride insulated cables of rated voltages up to and including 450/750 V

IEC 60245 (all parts), Rubber insulated cables – Rated voltages up to and including 450/750 V

IEC 60399, Barrel thread for lampholders with shade holder ring

IEC 60417, Graphical symbols for use on equipment

IEC 60432 (all parts), Incandescent lamps – Safety specifications

IEC 60529:1989, Degrees of protection provided by enclosures (IP Code)

IEC 60598-1, Luminaires – Part 1: General requirements and tests

IEC 60664-1:2007, Insulation coordination for equipment within low-voltage systems – Part 1: Principles, requirements and tests

IEC 60695-2-11:2000, Fire hazard testing – Part 2-11: Glowing/hot-wire based test methods – Glow-wire flammability test method for end-products

IEC 60695-11-5:2004, Fire hazard testing – Part 11-5: Test flames – Needle-flame test method – Apparatus, confirmatory test arrangement and guidance

ISO 4046-4:2002, Paper, board, pulps and related terms – Vocabulary – Part 4: Paper and board grades and converted products

2 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

NOTE For clarification of some definitions, see also Figure 4.

2.1 Materials

2.1.1

plastic lampholder

lampholder, the exterior of which is made wholly of plastic material

NOTE The exterior is any part of the lampholder which, when wired and fully assembled and fitted with the testing device shown in Figure 7, can be touched directly by the standard test finger of IEC 60529.

2.1.2

ceramic lampholder

lampholder, the exterior of which is made wholly of ceramic material (see note to 2.1.1)

2.1.3

metal lampholder

lampholder, the exterior of which is made wholly or partly of metal (see note to 2.1.1)

2.2 Means of fixing

2.2.1

cord grip lampholder

lampholder incorporating a method of retaining a flexible cord by which it may be suspended (see Figure 4a)

2.2.2

threaded entry lampholder

lampholder incorporating a threaded component at the point of entry of the supply wires permitting the lampholder to be mounted on a mating threaded support (formerly called nipple lampholder) (see Figure 4b)

2.2.3

backplate lampholder

lampholder so designed as to be suitable for mounting, by means of an associated or integral backplate, directly on to a supporting surface or appropriate box (see Figure 4c)

2.3

terminal/contact assembly

part or assembly of parts which provides a means of connection between the termination of a supply conductor and the contact-making surfaces of the corresponding lamp cap as well as resilient means to maintain contact pressure

- a) rising type, where the terminal is allowed to rise parallel with the lamp axis on insertion of a lamp cap;
- b) non-rising type, where the terminal is not allowed to rise on insertion of a lamp cap

NOTE The terminal and the barrel may be a unique element.

2.4

union ring

cylindrical component which joins together separate external parts of the lampholder

2.5

shade ring

cylindrical component having an internal thread or other means to engage a corresponding support on the outer shell and intended to carry or retain a shade

2.6

skirt (plastic lampholders only)

component similar to a shade ring but having a longer cylindrical form to extend to the full length of the lampholder body

2.6.1

protective shield (plastic lampholders only)

component similar to a skirt but having a flared open end to protect the user from accidental contact with the lamp cap (see Figure 9)

2.7

dome

part of a cord grip lampholder or threaded entry lampholder which shields the connecting terminals

2.8

barrel

part of a lampholder which serves for mechanical connection of the lamp cap with the lampholder

2.9

lampholder for building-in

lampholder designed to be built into a luminaire, an additional enclosure or the like

2.9.1

unenclosed lampholder

lampholder for building-in so designed that it requires additional means, for example enclosures, to meet the requirements of this standard with regard to protection against electric shock

2.9.2

enclosed lampholder

lampholder for building-in so designed that, on its own, it fulfils the requirements of this standard with regard to protection against electric shock and, if appropriate, IP classification

2.10

independent lampholder

lampholder so designed that it can be mounted separately from a luminaire and at the same time provide all the necessary protection according to its classification and marking

2.11

switched lampholder

lampholder provided with an integral switch to control the supply to the lamp

2.12

basic insulation

insulation applied to live parts to provide basic protection against electric shock

NOTE Basic insulation does not necessarily include insulation used exclusively for functional purposes.

2.13

supplementary insulation

independent insulation applied in addition to basic insulation in order to provide protection against electric shock in the event of a failure of basic insulation

2.14

double insulation

insulation comprising both basic insulation and supplementary insulation 9bfba005/iec-61184-2008

2.15

reinforced insulation

single insulation system applied to live parts which provides a degree of protection against electric shock equivalent to double insulation under the conditions specified

NOTE The term "insulation system" does not imply that the insulation must be one homogeneous piece. It may comprise several layers which cannot be tested singly as supplementary or basic insulation.

2.16

live part

conductive part which may cause an electric shock in normal use

The neutral conductor is, however, regarded as a live part.

The test to determine whether or not a conductive part is a live part which may cause an electric shock is given in Annex A of IEC 60598-1.

2.17

type test

test or series of tests made on a type test specimen for the purpose of checking compliance of the design of a given product with the requirements of the relevant standard

2.18

type test sample

sample consisting of one or more similar specimens submitted by the manufacturer or responsible vendor for the purpose of a type test

2.19

semi-luminaire

unit similar to a self-ballasted lamp but designed to utilize a replaceable light source and/or starting device

2.20

rated operating temperature

highest temperature for which the lampholder is designed

2.21

rated pulse voltage

highest peak of pulse voltages that the holder is able to withstand

2.22

impulse withstand category

numeral defining a transient overvoltage condition

NOTE Impulse withstand categories I, II, III and IV are used.

a) Purpose of classification of impulse withstand categories

Impulse withstand categories are to distinguish different degrees of availability of equipment with regard to required expectations on continuity of service and on an acceptable risk of failure.

By selection of impulse withstand levels of equipment, insulation co-ordination can be achieved in the whole installation reducing the risk of failure to an acceptable level providing a basis for overvoltage control.

A higher characteristic numeral of an impulse withstand category indicates a higher specific impulse withstand of the equipment and offers a wider choice of methods for overvoltage control.

The concept of impulse withstand categories is used for equipment energized directly from the mains. 2018 4-2008

b) Description of impulse withstand categories

Equipment of impulse with stand category I is equipment which is intended to be connected to the fixed electrical installations of buildings. Protective means are taken outside the equipment - either in the fixed installation or between the fixed installation and the equipment - to limit transient overvoltages to the specific level.

Equipment of impulse withstand category II is equipment to be connected to the fixed electrical installations of buildings.

Equipment of impulse withstand category III is equipment which is part of the fixed electrical installations and other equipment where a higher degree of availability is expected.

Equipment of impulse withstand category IV is for use at or in the proximity of the origin of the electrical installations of buildings upstream of the main distribution board.

2.23

primary circuit

circuit which is directly connected to the AC mains supply

It includes, for example, the means for connection to the AC mains supply, the primary windings of transformers, motors and other loading devices.

2.24

secondary circuit

circuit which has no direct connection to a primary circuit and derives its power from a transformer, converter or equivalent isolation device, or from a battery

Exception: autotransformers. Although having direct connection to a primary circuit, the tapped part of them is also deemed to be a secondary circuit in the above sense.

NOTE Mains transients in such a circuit are attenuated by the corresponding primary windings. Also inductive ballasts reduce the mains transient voltage height. Therefore, components located after a primary circuit or after an inductive ballast can be suited for an impulse withstand category of one step lower, i.e. for impulse withstand category II.

2.25

enclosed reinforced insulated lampholder

lampholder for building-in, so designed that on its own it fulfils the requirements for double or reinforced insulated parts in class II applications

2.26

partly reinforced insulated lampholder

lampholder for building-in, so designed that some parts of the lampholder require additional means to fulfil the requirements with regard to double or reinforced insulation

NOTE In some cases, the dimensions might be achieved only after mounting into the luminaire.

3 General requirements

Lampholders shall be so designed and constructed that in normal use they function reliably and cause no danger to persons or surroundings.

In general, compliance is checked by carrying out all the relevant tests specified.

Independent lampholders, not specifically intended for building-in, shall comply with the requirements of the following sections and subclauses of IEC 60598-1 where the subject-matter of these headings is not dealt with in the present standard.

Section 2 – Classification
Section 3 – Marking

Section 4 – Construction (as appropriate)

Section 8 – Protection against electric shock

Section 9 - Resistance to dust, solid objects and moisture

Section 10 – Insulation resistance and electric strength (for class II)

Subclauses 12.4 and 12.5 - Thermal tests

4 General conditions for tests

4.1 Tests according to this standard are type tests.

NOTE The requirements and tolerances permitted by this standard are related to testing of a type test sample submitted for that purpose. Compliance of the type test sample does not ensure compliance of the whole production of a manufacturer with this safety standard. In addition to type testing, conformity of production is the responsibility of the manufacturer and may include routine tests and quality control.

For further information see IEC 60061-4, sheet 7007-13.

4.2 Unless otherwise specified, the samples are tested as delivered and installed as in normal use without lamps, at an ambient temperature of 20 °C \pm 5 °C.