

# INTERNATIONAL STANDARD

## NORME INTERNATIONALE

Fibre optic interconnecting devices and passive components performance standard –

Part 111-9: Sealed closures for category S – Subterranean

Dispositifs d'interconnexion et composants passifs à fibres optiques norme de qualité de fonctionnement –

Partie 111-9: Boîtiers scellés pour catégorie S – Souterrain



## THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2009 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de la CEI ou du Comité national de la CEI du pays du demandeur.

Si vous avez des questions sur le copyright de la CEI ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de la CEI de votre pays de résidence.

IEC Central Office  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland  
Email: [inmail@iec.ch](mailto:inmail@iec.ch)  
Web: [www.iec.ch](http://www.iec.ch)

### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

### About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: [www.iec.ch/searchpub](http://www.iec.ch/searchpub)

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: [www.iec.ch/online\\_news/justpub](http://www.iec.ch/online_news/justpub)

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

[IEC 61753-111-9:2009](mailto:IEC.61753-111-9:2009)

- Electropedia: [www.electropedia.org](http://www.electropedia.org)

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: [www.iec.ch/webstore/custserv](http://www.iec.ch/webstore/custserv)

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: [csc@iec.ch](mailto:csc@iec.ch)

Tel.: +41 22 919 02 11

Fax: +41 22 919 03 00

### A propos de la CEI

La Commission Electrotechnique Internationale (CEI) est la première organisation mondiale qui élabore et publie des normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

### A propos des publications CEI

Le contenu technique des publications de la CEI est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

- Catalogue des publications de la CEI: [www.iec.ch/searchpub/cur\\_fut-f.htm](http://www.iec.ch/searchpub/cur_fut-f.htm)

Le Catalogue en-ligne de la CEI vous permet d'effectuer des recherches en utilisant différents critères (numéro de référence, texte, comité d'études,...). Il donne aussi des informations sur les projets et les publications retirées ou remplacées.

- Just Published CEI: [www.iec.ch/online\\_news/justpub](http://www.iec.ch/online_news/justpub)

Restez informé sur les nouvelles publications de la CEI. Just Published détaille deux fois par mois les nouvelles publications parues. Disponible en-ligne et aussi par email.

- Electropedia: [www.electropedia.org](http://www.electropedia.org)

Le premier dictionnaire en ligne au monde de termes électroniques et électriques. Il contient plus de 20 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans les langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International en ligne.

- Service Clients: [www.iec.ch/webstore/custserv/custserv\\_entry-f.htm](http://www.iec.ch/webstore/custserv/custserv_entry-f.htm)

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions, visitez le FAQ du Service clients ou contactez-nous:

Email: [csc@iec.ch](mailto:csc@iec.ch)

Tél.: +41 22 919 02 11

Fax: +41 22 919 03 00



IEC 61753-111-9

Edition 1.0 2009-11

# INTERNATIONAL STANDARD

# NORME INTERNATIONALE

**Fibre optic interconnecting devices and passive components performance standard –**

**Part 111-9: Sealed closures for category S – Subterranean**

**Dispositifs d'interconnexion et composants passifs à fibres optiques norme de qualité de fonctionnement –**

**Partie 111-9: Boîtiers scellés pour catégorie S – Souterrain**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

COMMISSION  
ELECTROTECHNIQUE  
INTERNATIONALE

PRICE CODE  
CODE PRIX

T

ICS 33.180.20

ISBN 978-2-88910-561-8

## CONTENTS

FOREWORD.....	3
INTRODUCTION.....	5
1 Scope.....	6
2 Normative references.....	6
3 Terms, definitions and abbreviations.....	8
4 General requirements.....	8
4.1 Storage, transportation and packaging.....	8
4.2 Marking and identification.....	8
4.3 Materials.....	8
4.4 Closure overpressure safety.....	9
4.5 Test report.....	9
5 Test.....	9
5.1 General.....	9
5.2 Test specimen preparation.....	9
5.3 Test and measurement methods.....	10
5.4 Installation or intervention.....	10
5.5 Pass/fail criteria.....	10
6 Performance requirements.....	11
6.1 Sample size.....	11
6.2 Sealing, optical and appearance performance criteria.....	11
6.3 Mechanical sealing performance requirements.....	12
6.4 Environmental sealing performance requirements.....	14
6.5 Mechanical optical performance requirements.....	15
6.6 Environmental optical performance requirements.....	17
Annex A (normative) Sample definition.....	18
Annex B (normative) Sample size.....	20
Annex C (normative) Intervention and reconfiguration/resplicing.....	22
Bibliography.....	24
Figure A.1 – Track joint configuration sample.....	18
Figure A.2 – Distribution joint configuration sample.....	19
Table 1 – Tightness, optical and appearance performance criteria.....	11
Table 2 – Mechanical sealing performance requirements.....	12
Table 3 – Environmental sealing performance requirements.....	14
Table 4 – Mechanical optical performance requirements.....	15
Table 5 – Environmental optical performance requirements.....	17
Table A.1 – Fibre type for testing.....	18
Table B.1 – Sample size.....	20

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

**FIBRE OPTIC INTERCONNECTING DEVICES  
AND PASSIVE COMPONENTS  
PERFORMANCE STANDARD –**

**Part 111-9: Sealed closures for category S –  
Subterranean**

## FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61753-111-9 has been prepared by subcommittee 86B: Fibre optic interconnecting devices and passive components, of IEC technical committee 86: Fibre optics.

The text of this standard is based on the following documents:

FDIS	Report on voting
86B/2906/FDIS	86B/2936/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of IEC 61753 series, published under the general title *Fibre optic interconnecting devices and passive components – Performance standard*, can be found on the IEC website.

Future standards in this series will carry the new general title as cited above. Titles of existing standards in this series will be updated at the time of the next edition.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

## **iTeh STANDARD PREVIEW (standards.iteh.ai)**

[IEC 61753-111-9:2009](#)

<https://standards.iteh.ai/catalog/standards/sist/2d4e541e-2665-43e9-8f56-06c046e35021/iec-61753-111-9-2009>

## INTRODUCTION

Performance standards for closures define the requirements for standard optical performance under a set of specified conditions. This part of IEC 61753 contains a series or a set of tests and measurements with clearly stated conditions, severities and pass/fail criteria. The set of tests are intended to be a basis to prove the product's ability to satisfy the requirements of a specific application, market sector or user group.

A product that has been shown to meet all the requirements of this performance standard may be declared as complying with this performance standard. Products having the same classification from one manufacturer that satisfy this performance standard will operate within the boundaries set by the performance standard. There is no guarantee that products from different manufacturers, having the same classification and which conform to the same performance standard, will provide an equivalent level of performance when they are used together.

Conformance with IEC environmental policy according to IEC Guide 109 and concerning the need to reduce the impact on the natural environment of fibre optic closures during all phases of their life – from acquiring materials to manufacturing, distribution, use, and end-of-life treatment (i.e. re-use, recycling (recovery and disposal)) are not part of this standard, but will be covered in the generic specification.

Conformance to a performance standard demonstrates that a product has passed a design verification test. It is not a guarantee of lifetime assured performance or reliability. Reliability testing must be the subject of a separate test schedule, where the tests and severities selected are such that they are truly representative of the requirements of this reliability test programme. Consistency of manufacture should be maintained using a recognised Quality Assurance programme whilst the reliability of product should be evaluated using the procedures recommended in IEC 62005 series.

[IEC 61753-111-9:2009](#)

[https://standards.iteh.ai/catalog/standards/sist/2d4e541e-2665-43e9-8f56-](https://standards.iteh.ai/catalog/standards/sist/2d4e541e-2665-43e9-8f56-08c64cc55021/iec-61753-111-9-2009)

Tests and measurements are selected from the IEC 61300 series.

# FIBRE OPTIC INTERCONNECTING DEVICES AND PASSIVE COMPONENTS PERFORMANCE STANDARD –

## Part 111-9: Sealed closures for category S – Subterranean

### 1 Scope

This part of IEC 61753 contains the minimum test and measurement requirements and severities which a sealed fibre optic closure must satisfy in order to be categorised as meeting the IEC standard for category S – subterranean, as defined in Annex A of IEC 61753-1. Free breathing closures are not covered in this standard.

### 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60068-2-10, *Environmental testing – Part 2-10: Tests – Test J and guidance: Mould growth*

IEC 60721-3-2, *Classification of environmental conditions – Part 3: Classification of groups of environmental parameters and their severities – Section 2: Transportation*

IEC 60793-2-50:2008, *Optical fibres – Part 2-50 : Product specifications – Sectional specification for class B single-mode fibres*

IEC 61300-1, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 1: General and guidance*

IEC 61300-2-1, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-1: Tests – Vibration (sinusoidal)*

IEC 61300-2-4, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-4: Tests – Fibre/cable retention*

IEC 61300-2-5, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-5: Tests – Torsion (only available in English)*

IEC 61300-2-9, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-9: Tests – Shock*

IEC 61300-2-10, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-10: Tests – Crush resistance<sup>1</sup>*

---

<sup>1</sup> This publication was withdrawn in 2002. A project is currently under consideration.



IEC 61300-2-11, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-11: Tests – Axial compression*<sup>2</sup>

IEC 61300-2-12:2009, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-12: Tests – Impact*

IEC 61300-2-22, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-22: Tests – Change of temperature*

IEC 61300-2-23, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-23: Tests – Sealing for non-pressurized closures of fibre optic devices*

IEC 61300-2-26, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-26: Tests – Salt mist*

IEC 61300-2-33, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-33: Tests – Assembly and disassembly of fibre optic closures*

IEC 61300-2-34, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-34: Tests – Resistance to solvents and contaminating fluids of interconnecting components and closures* (only available in English)

IEC 61300-2-37, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-37: Tests – Cable bending for fibre optic closures*

IEC 61300-2-38:2006, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-38: Tests – Sealing for pressurized fibre optic closures*

IEC 61300-3-1, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-1: Examinations and measurements – Visual examination*

IEC 61300-3-3:2009, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-3: Examinations and measurements – Active monitoring of changes in attenuation and return loss* (only available in English)

IEC 61300-3-28, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-28: Examinations and measurements – Transient loss*

IEC 61753-1:2007, *Fibre optic interconnecting devices and passive components performance standard – Part 1: General and guidance for performance standards*

IEC 61753-111-7, *Fibre optic interconnecting devices and passive components – Performance standard – Part 111-7: Sealed closures for category A – Aerial*

IEC 62134-1, *Fibre optic interconnecting devices and passive components – Fibre optic closures – Part 1: Generic specification*

ISO 1998 (all parts), *Petroleum industry – Terminology*

---

<sup>2</sup> This publication was withdrawn in 2002. A project is currently under consideration.

ISO 4892-3:2006, *Plastics – Methods of exposure to laboratory light sources – Part 3:Fluorescent UV lamps*

### 3 Terms, definitions and abbreviations

For the purposes of this document, the terms, definitions and abbreviations given in IEC 61753-111-7 apply.

## 4 General requirements

### 4.1 Storage, transportation and packaging

The classes of environmental conditions and their severities to which closures may be exposed during transportation are defined in IEC 60721-3-2. Normal transportation time is considered to be 30 days or less.

The product, in its original packaging, shall be suitable for normal public or commercial transportation and storage in weather protected non-temperature controlled storage environments.

### 4.2 Marking and identification

Marking of the closure and its package shall be according to IEC 62134-1.

Product marking and identification shall survive the storage and transportation.

Each test sample should contain the following information at a minimum:

- manufacturer's identification mark or logo;
- product designation, model or type,
- one of the following: lot number, batch number, date (at least month and year) of production or serial number;
- expiry date (at least year) if the product contains components with a limited shelf life.

### 4.3 Materials

For all applied materials, a Material Safety Data Sheet shall be made available upon request.

The materials of the closure and fibre management system shall be compatible with the other materials or solvents that can come into contact with it, for example cable filling compounds and degreasing agents.

All materials that can come in contact with personnel shall meet appropriate health and safety regulations.

The effect of UV light on all polymeric materials that are directly exposed to the environment, shall not adversely affect the product's performance. UV test shall be according to ISO 4892-3 Mode 1 lamp type 2. The effect of UV light shall be determined by measuring a suitable property (e.g. tensile strength) both before and after exposure of the material slabs.

Polymeric materials shall not support mould growth causing mechanical degradation of the materials. Mould growth shall be tested according to IEC 60068-2-10. The effect of mould growth shall be determined by measuring a suitable property (e.g. tensile strength) both before and after exposure of the material slabs.

Metallic elements shall be corrosion resistant. Dissimilar metals should not be used in contact with each other unless they are suitably finished to prevent electrolytic corrosion.

Materials which are not specified or which are not specifically described are left to the discretion of the manufacturer.

#### 4.4 Closure overpressure safety

Special attention should be taken when opening sealed closures that are carrying an overpressure. Overpressure can build up in sealed closures due to temperature differentials, atmospheric pressure changes over a period of time, flash testing of the seals after installation or incorrect installation techniques. Care should be taken when opening a sealed closure. Provisions shall be made that overpressure is exhausted when opening the closure prior to complete removal of the cover.

#### 4.5 Test report

Conformance to a performance standard shall be supported by a test report. The test report shall clearly demonstrate that the tests were carried out in accordance with the requirements of the performance standard and provide full details of the tests together with a pass/fail declaration. An analysis of the cause of the failure shall be undertaken and any corrective actions taken shall be described.

If design changes are made, a risk assessment should be carried out to determine whether full or partial requalification should be done.

### 5 Test

#### 5.1 General

The mechanical and environmental performance of a closure is vital to the optical cabling system. The purpose of testing is to demonstrate that the closure can survive under defined environmental conditions, without irreversible or reversible failures and perform according to the requirements.

The performance test procedure of a closure shall:

- evaluate the product for 3 basic acceptance criteria: sealing, mechanical integrity and optical transmission requirements;
- simulate the effects of exposure to the environment in which it will be installed;
- simulate installation and intervention conditions.

Optical performance testing is accomplished by subjecting the test specimen to a number of mechanical and environmental conditions and measuring any optical performance deviations at prescribed intervals during and after completion of each test.

#### 5.2 Test specimen preparation

Sealing performance test samples shall be provided with an air pressure test access valve. The length of the cables extending the closure shall be at least 1 m. The free ends of the cables shall be sealed. Each applicable cable type with minimum and maximum cable dimensions shall be represented in the test program. When applicable, open closure ports shall be sealed with a cap.

Optical test samples shall be constructed in such a way that they will cover all allowed functions as specified by the manufacturer, being "track joint" configuration or "track joint and distribution joint" configuration. This shall be realised by building optical circuits for each fibre separation level (typical SC, SE, or ME splicing and uncut fibre storage). The type of fibre for

the optical test samples and the test sample preparation are single mode fibres as described in Annex A.

### 5.3 Test and measurement methods

All tests and measurements have been selected from the IEC 61300 series.

Unless otherwise stated in the individual test details, all attenuation measurements shall be performed at  $1\,310\text{ nm} \pm 25\text{ nm}$ ,  $1\,550\text{ nm} \pm 25\text{ nm}$  and  $1\,625\text{ nm} \pm 25\text{ nm}$  for the environmental optical tests, and at  $1\,550\text{ nm} \pm 25\text{ nm}$  and  $1\,625\text{ nm} \pm 25\text{ nm}$  for the mechanical optical tests.

All optical losses indicated are referenced to the initial attenuation at the start of the test.

No deviation from the specified test method is allowed.

Effects that are due to the properties of the optical components themselves are not to be taken into account for the evaluation of the closure system.

Closures under test shall be mounted and connected in accordance with the manufacturer's guidelines.

Unless otherwise specified, tests should be carried out under standard atmospheric conditions according to IEC 61300-1.

### 5.4 Installation or intervention

The minimum and maximum temperatures at which a closure may be installed (installation conditions) or re-entered (intervention) are not necessarily equal to the maximum temperature excursion of the environment in which it will reside, once installed. Accessing fibres and the fibre management system inside the closure is typically done in a more controlled environment. Closures and the fibre management system should be installable in the temperature range between  $-5\text{ °C}$  and  $+45\text{ °C}$  for subterranean applications (category S). Closure handling alone should be possible at temperatures between  $-15\text{ °C}$  and  $+45\text{ °C}$ .

Typically the following operations are carried out during an intervention:

- handling of closure;
- opening closure;
- getting access to fibres and splices (e.g. hinging, pivoting, sliding, removal of splice trays, or other organiser components);
- breaking a splice, re-routing fibres and connecting to another fibre end;
- cutting one or more uncut fibres, re-routing and connecting to another fibre end;
- disconnecting a connector and mating with another connector (when applicable);
- adding organiser elements/components and connecting the fibres;
- closing and sealing the closure.

### 5.5 Pass/fail criteria

A product will have met the requirements of this standard provided no failures occur in any test.

In the event of a failure occurring on a sealing performance test sample, the test shall be re-run using a sample size double that of the original.

Due to the complexity of the optical test samples, consecutive testing on the same optical sample is allowed. In case of a failure during the consecutive testing, a new sample shall be prepared and the failed test shall be re-done.

## 6 Performance requirements

### 6.1 Sample size

A detailed description of the sample size can be found in Annex B.

### 6.2 Sealing, optical and appearance performance criteria

**Table 1 – Tightness, optical and appearance performance criteria**

No.	Test	Requirement	Details	
1	Sealing for pressurised closures of fibre optic devices – sealing performance after test	No emission of air bubbles indicating a leak	Method: Test temperature: Test pressure: Immersion depth: Duration: Pre-conditioning procedure:	IEC 61300-2-38, Method A 23 °C ± 3 °C Internal overpressure 40 kPa ± 2 kPa (Note 1) Just below the surface of the water 15 min Sample should be conditioned to room temperature for at least 2 h
2	Sealing for pressurised closures of fibre optic devices - pressure loss during test	Difference in pressure before and after test shall be less than 2 kPa. Measurements taken at same atmospheric conditions	Method: Test temperature: Test pressure: Pressure detector: Pre-conditioning procedure:	IEC 61300-2-38, Method B As specified by individual test Internal overpressure 40 kPa ± 2 kPa at test temperature (Note 1) Minimum resolution 0,1 kPa Sample should be conditioned to specified temperature at test pressure for at least 4 h
3	Visual examination	No defects which would affect functionality of the closure	Method: Examination:	IEC 61300-3-1 Product shall be checked with the naked eye
4	Active monitoring of change in attenuation and return loss (Note 2)	<u>Excursion losses:</u> $\delta IL \leq 0,2$ dB at 1 310 nm and 1 550 nm per incoming fibre during test.  $\delta IL \leq 0,5$ dB at 1 625 nm per incoming fibre during test.  <u>Residual losses:</u> $\delta IL \leq 0,1$ dB at 1 310 nm, 1 550 nm and 1 625 nm per incoming fibre after test.	Method: Wavelengths:  Source stability: Detector linearity: Measurements required: Sampling Rate:	IEC 61300-3-3, Method 1 1 310 nm ± 25 nm 1 550 nm ± 25 nm 1 625 nm ± 25 nm Within ± 0,05 dB over the measuring period Within ± 0,05 dB over the dynamic range to be measured Before, during and after the test Every 10 min
5	Transient loss (Note 2)	<u>Transient losses:</u> $\delta IL \leq 0,5$ dB at 1 550 nm per active circuit during test.  $\delta IL \leq 1$ dB at 1 625 nm per active circuit during test.	Method: Wavelengths:  Source stability:	IEC 61300-3-28 1 550 nm ± 25 nm 1 625 nm ± 25 nm Within ± 0,05 dB over the measuring period

No.	Test	Requirement	Details	
		<u>Residual losses:</u> $\delta IL \leq 0,1$ dB at 1 550 nm and 1 625 nm per active circuit after test.	Detector linearity:  Measurements required:  active circuit:	Within $\pm 0,05$ dB over the dynamic range to be measured  Before, during and after the test  10 incoming fibres in series
NOTE 1 For products used in pressurised networks, all testing should be carried out at $98,0$ kPa $\pm$ $9,8$ kPa over-pressure instead of $40$ kPa over-pressure.				
NOTE 2 All optical losses indicated are referenced to the initial attenuation at the start of the test.				

### 6.3 Mechanical sealing performance requirements

Table 2 – Mechanical sealing performance requirements

No.	Test	Requirement	Details	
6	Vibration (sinusoidal)	Sealing performance (test 1) Visual examination (test 3)	Method: Frequency range: Amplitude /acceleration force: Cross-over frequency: Number of sweeps No. of axes: Test temperature: Test pressure:  Pre-conditioning procedure:	IEC 61300-2-1  5 Hz – 500 Hz at 1 octave/min  3 mm or $10 \text{ m/s}^2$ ( $\sim 1 g_n$ ) maximum  9 Hz  10 sweeps (5-500-5)  3 mutually perpendicular  $+23 \text{ }^\circ\text{C} \pm 3 \text{ }^\circ\text{C}$  Internal overpressure $40 \text{ kPa} \pm 2 \text{ kPa}$  Sample should be conditioned at room temperature for at least 2 h
7	Cable retention	Sealing performance (test 1) Pressure loss (test 2) Visual examination (test 3)	Method: Test temperatures: Load:  Duration: Test pressure:  Pre-conditioning procedure:	IEC 61300-2-4  $-15 \text{ }^\circ\text{C} \pm 2 \text{ }^\circ\text{C}$ and $+45 \text{ }^\circ\text{C} \pm 2 \text{ }^\circ\text{C}$  $\varnothing_{\text{Cable}} \text{ (mm)}/45 \times 1\,000 \text{ N}$  or $1\,000 \text{ N}$ maximum  1 h per cable  Internal overpressure $40 \text{ kPa} \pm 2 \text{ kPa}$ at test temperature  Sample should be conditioned at the specified temperature for at least 4 h
8	Axial compression of central strength member	Visual examination (test 2) No movement of central strength member by more than 5 mm	Method: Test temperature: Load: Duration: Pre-conditioning procedure:	IEC 61300-2-11  $+23 \text{ }^\circ\text{C} \pm 3 \text{ }^\circ\text{C}$  450 N on central strength member  30 min per strength member  Sample should be conditioned at room temperature for at least 2 h
9	Cable bending	Sealing performance (test 1) Pressure loss (test 2) Visual examination	Method: Test temperatures: Force:	IEC 61300-2-37  $-15 \text{ }^\circ\text{C} \pm 2 \text{ }^\circ\text{C}$ and $+45 \text{ }^\circ\text{C} \pm 2 \text{ }^\circ\text{C}$  $30^\circ$ or maximum 500 N

No.	Test	Requirement	Details	
		(test 3)	Force application: Number of cycles: Test pressure: Pre-conditioning procedure:	400 mm from end of seal (Note) 5 cycles per cable Internal overpressure 40 kPa ± 2 kPa at test temperature Sample should be conditioned at the specified temperature for at least 4 h
10	Torsion/Twist	Sealing performance (test 1) Pressure loss (test 2) Visual examination (test 3)	Method: Test temperatures: Torque: Force application: Number of cycles: Test pressure: Pre-conditioning procedure:	IEC 61300-2-5 -15 °C ± 2 °C and +45 °C ± 2 °C 90° or maximum 50 Nm 400 mm from end of seal (Note) 5 cycles per cable Internal overpressure 40 kPa ± 2 kPa at test temperature Sample should be conditioned at the specified temperature for at least 4 h
11	Impact (free fall)	Sealing performance (test 1)	Method: Test temperatures: Severity: Number of drops: Test pressure: Pre-conditioning procedure:	IEC 61300-2-12, Method A -15 °C ± 2 °C and +45 °C ± 2 °C Drop height 75 cm 1 Internal overpressure 0 kPa at room temperature Sample should be conditioned at the specified temperature for at least 4 h
12	Impact	Sealing performance (test 1) Pressure loss (test 2) Visual examination (test 3)	Method: Test temperatures: Impact tool: Drop height: Impact locations: Number of impacts: Test pressure: Pre-conditioning procedure:	IEC 61300-2-12, Method B -15 °C ± 2 °C and +45 °C ± 2 °C Steel ball of 1 kg 2 m 0°, 90°, 180° and 270° 1 per location Internal overpressure 40 kPa ± 2 kPa at test temperature Sample should be conditioned at the specified temperature for at least 4 h
13	Crush resistance	Sealing performance (test 1) Pressure loss (test 2) Visual examination (test 3)	Method: Test temperatures: Load: Application area: Locations: Duration: Test pressure: Pre-conditioning procedure:	IEC 61300-2-10 -15 °C ± 2 °C and +45 °C ± 2 °C 1 000 N 25 cm <sup>2</sup> Centre of closure at 0° and 90° around longitudinal axis of closure 10 min Internal overpressure 40 kPa ± 2 kPa at test temperature Sample should be conditioned at the specified temperature for at least 4 h
14	Assembly and disassembly of closures	Sealing performance (test 1) Visual examination (test 3)	Method: Test temperature:	IEC 61300-2-33 +23 °C ± 3 °C