

INTERNATIONAL STANDARD

NORME INTERNATIONALE



Fibre optic interconnecting devices and passive components performance standard –

Part 086-2: Non-connectorized single-mode bidirectional 1 490 / 1 550 nm downstream and 1 310 nm upstream WWDM devices for category C – Controlled environment

<https://standards.iteh.ai/catalog/standards/sist/c03c1983-677e-465a-8578-918847e6c908/iec-61753-086-2-2009>

Norme de qualité de fonctionnement des dispositifs d'interconnexion et composants passifs à fibres optiques –

Partie 086-2: Dispositifs WWDM unimodaux non connectorisés bidirectionnels 1 490 / 1 550 nm en voie descendante et 1 310 nm en voie montante pour la catégorie C – Environnement contrôlé



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2009 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in 15 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

More than 60 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Catalogue IEC - webstore.iec.ch/catalogue

Application autonome pour consulter tous les renseignements bibliographiques sur les Normes internationales, Spécifications techniques, Rapports techniques et autres documents de l'IEC. Disponible pour PC, Mac OS, tablettes Android et iPad.

Recherche de publications IEC - www.iec.ch/searchpub

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études,...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire en ligne de termes électroniques et électriques. Il contient plus de 30 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans 15 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

Glossaire IEC - std.iec.ch/glossary

Plus de 60 000 entrées terminologiques électrotechniques, en anglais et en français, extraites des articles Termes et Définitions des publications IEC parues depuis 2002. Plus certaines entrées antérieures extraites des publications des CE 37, 77, 86 et CISPR de l'IEC.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: csc@iec.ch.

INTERNATIONAL STANDARD

NORME INTERNATIONALE



**Fibre optic interconnecting devices and passive components performance standard –
Part 086-2: Non-connectorized single-mode bidirectional 1 490 / 1 550 nm downstream and 1 310 nm upstream WDM devices for category C – Controlled environment**

<https://standards.iteh.ai/catalog/standards/sist/c03c1983-677e-465a-8578-918847e6c908/iec-61753-086-2-2009>

**Norme de qualité de fonctionnement des dispositifs d'interconnexion et composants passifs à fibres optiques –
Partie 086-2: Dispositifs WDM unimodaux non connectorisés bidirectionnels 1 490 / 1 550 nm en voie descendante et 1 310 nm en voie montante pour la catégorie C – Environnement contrôlé**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 33.180.10

ISBN 978-2-8322-3068-8

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

CONTENTS

FOREWORD	3
1 Scope	5
2 Normative references	5
3 Test	6
4 Test report	6
5 Performance requirements	7
5.1 Reference components	7
5.2 Dimensions	7
5.3 Sample size	7
5.4 Test details and requirements	7
Annex A (normative) Sample size	12
Annex B (informative) General information for 1 490 / 1 550 nm downstream and 1 310 nm upstream PON WWDM devices	13
Bibliography	14
Figure B.1 – Example of 1 490 / 1 550 nm downstream and 1 310 nm upstream WWDM at central office and customer side – Separate video detection inside the ONU	13
Figure B.2 – Example of 1 490 / 1 550 nm downstream and 1 310 nm upstream WWDM at central office side – Integrated video detection inside the ONU	13
Table 1 – Test details and requirements	7
Table A.1 – Sample size	12

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**FIBRE OPTIC INTERCONNECTING DEVICES AND
PASSIVE COMPONENTS PERFORMANCE STANDARD –****Part 086-2: Non-connectorized single-mode
bidirectional 1 490 / 1 550 nm downstream and 1 310 nm
upstream WWDM devices for category C –
Controlled environment**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61753-086-2 has been prepared by subcommittee 86B: Fibre optic interconnecting devices and passive components, of IEC technical committee 86: Fibre optics.

This bilingual version (2015-12) corresponds to the monolingual English version, published in 2009-09.

The text of this standard is based on the following documents:

FDIS	Report on voting
86B/2892/FDIS	86B/2922/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

The French version of this standard has not been voted upon.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of IEC 61753 series, under the general title *Fibre optic interconnecting devices and passive components performance standard*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[IEC 61753-086-2:2009](#)

<https://standards.iteh.ai/catalog/standards/sist/c03c1983-677e-465a-8578-918847e6c908/iec-61753-086-2-2009>

FIBRE OPTIC INTERCONNECTING DEVICES AND PASSIVE COMPONENTS PERFORMANCE STANDARD –

Part 086-2: Non-connectorized single-mode bidirectional 1 490 / 1 550 nm downstream and 1 310 nm upstream WWDM devices for category C – Controlled environment

1 Scope

This part of IEC 61753 contains the minimum initial performance, test and measurement requirements and severities which a fibre optic pigtailed 1 490 / 1 550 nm downstream and 1 310 nm upstream wide wavelength division multiplexing (WWDM) passive optical network (PON) device must satisfy in order to be categorized as meeting the requirements of category C (controlled environments), as defined in Annex A of IEC 61753-1.

Annex B of this standard provides information concerning the function of the 1 490 / 1 550 nm downstream and 1 310 nm upstream WWDM.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

<https://standards.iteh.ai/catalog/standards/sist/c03c1983-677e-465a-8578-918847c6c908/iec-61753-086-2-2009>

IEC 60793-2-50, *Optical fibres – Part 2-50: Product specifications – Sectional specification for class B single-mode fibres*

IEC 61300 (all parts), *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures*

IEC 61300-2-1, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-1: Tests – Vibration (sinusoidal)*

IEC 61300-2-4, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-4: Tests – Fibre/cable retention*

IEC 61300-2-9, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-9: Tests – Shock*

IEC 61300-2-14, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-14: Tests – Optical power handling and damage threshold characterization*

IEC 61300-2-17, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-17: Tests – Cold*

IEC 61300-2-18, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-18: Tests – Dry heat – High temperature endurance*

IEC 61300-2-19, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-19: Tests – Damp heat (steady state)*

IEC 61300-2-22, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-22: Tests – Change of temperature*

IEC 61300-2-42, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-42: Tests – Static side load for connectors*

IEC 61300-2-44, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-44: Tests – Flexing of the strain relief of fibre optic devices*

IEC 61300-3-2, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-2: Examinations and measurements – Polarization dependence of attenuation in a single-mode fibre optic device*

IEC 61300-3-6, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-6: Examinations and measurements – Return loss*

IEC 61300-3-7, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-7: Wavelength dependence of attenuation and return loss*

IEC 61300-3-20, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-20: Examinations and measurements – Directivity of fibre optic branching devices*

IEC 61300-3-29, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-29: Examinations and measurements – Measurement techniques for characterizing the amplitude of the spectral transfer function of DWDM components*

iTeh STANDARD PREVIEW

(standard.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/c03c1983-677e-465a-8578-1d04700296/iec-61753-086-2-2009>

IEC 61753-1, *Fibre optic interconnecting devices and passive components performance standard – Part 1: General and guidance for performance standard*

3 Test

Unless otherwise specified, all test methods are in accordance with the relevant part of IEC 61300 series.

Each test defines the number of samples to be evaluated. The samples used for each test are intended to be previously unstressed new samples but may also be selected from previously used samples if desired. The samples shall be terminated onto single-mode fibres as per IEC 60793-2-50, Type B 1.1, in either coated fibres (primary and secondary) or reinforced cable format. All measurements shall be carried out at normal room conditions, unless otherwise stated.

All tests shall be carried out over the optical wavelength bands of 1 260 nm to 1 360 nm, 1 480 nm to 1 500 nm, and 1 550 nm to 1 560 nm, unless otherwise specified.

NOTE 1 310 nm, 1 490 nm and 1 550 nm are the peak or centre wavelengths, stated for the bands 1 260 nm to 1 360 nm, 1 480 nm to 1 500 nm and 1 550 nm to 1 560 nm.

4 Test report

Fully documented test reports and supporting evidence shall be prepared and be available for inspection as evidence that the tests have been carried out and complied with.

5 Performance requirements

5.1 Reference components

The testing for these components does not require the use of reference components.

5.2 Dimensions

Dimensions shall comply with either an appropriate IEC interface standard or with those given in appropriate manufacturers drawings, where the IEC interface standard does not exist or cannot be used.

5.3 Sample size

Sample sizes for the tests are defined in Annex A of this standard.

5.4 Test details and requirements

Table 1 – Test details and requirements

No.	Test	Requirement	Details	
1	Attenuation IEC 61300-3-7	$\leq 0,8$ dB Attenuation shall be met over the operating wavelength ranges	Launch patchcord length: Source type: Launch conditions: Other requirements:	≥ 2 m Unpolarised The wavelength of the source shall be longer than cut-off wavelength of the fibre Test results shall be obtained under measurement uncertainty of $\pm 0,1$ dB
2	Total channel isolation IEC 61300-3-7; IEC 61300-3-29	≥ 18 dB between wavelength ranges 1 480 nm to 1 500 nm and 1 550 nm to 1 560 nm; ≥ 30 dB between wavelength ranges 1 260 nm to 1 360 nm and 1 550 nm to 1 560 nm	Launch patchcord length: Source type: Launch conditions: Other requirements:	≥ 2 m Unpolarised The wavelength of the source shall be longer than cut-off wavelength of the fibre Test results shall be obtained under measurement uncertainty of ± 1 dB
3	Directivity IEC 61300-3-20	≥ 50 dB Grade U Directivity shall be met over the specified wavelength ranges	Source: Other requirements:	Laser diode (LD) Test results shall be obtained under measurement uncertainty of ± 1 dB All ports not under test shall be terminated to avoid unwanted reflections contributing to the measurement The directivity shall be measured between any pair of input or output ports

Table 1 (continued)

No.	Test	Requirement	Details	
4	Return loss IEC 61300-3-6	≥ 50 dB Grade U Return loss shall be met over the specified wavelength ranges	Source: Other requirements:	LD Test results shall be obtained under measurement uncertainty of ± 1 dB All ports not under test shall be terminated to avoid unwanted reflections contributing to the measurement
5	Polarisation dependent loss (PDL) IEC 61300-3-2	≤ 0,2 dB Polarisation dependent loss shall be met over the specified wavelength ranges	Launch patchcord length: Source type: Other requirements:	≥ 2 m LD Test results shall be obtained under measurement uncertainty of ± 0,05 dB
6	Optical power handling and damage threshold characterization IEC 61300-2-14	≥ 300 mW (sum of power at the three wavelength ranges at the same time) During and on completion of the test the attenuation limits of test No. 1 shall be met After the test the isolation limits of test No. 2 shall be met During and on completion of the test the return loss limits of test No. 4 shall be met	Source type Max. power to be applied at wavelength range 1 550 nm to 1 560 nm: Max. power to be applied at wavelength ranges 1 480 nm to 1 500 nm and 1 260 nm to 1 360 nm: Power increments: Test duration: Other requirements:	LD 300 mW (+ ~25 dBm) 10 mW (+ 10 dBm) 3 dB 0,5 h at each power level Test results shall be obtained under attenuation measurement uncertainty of ± 0,1 dB Test results shall be obtained under return loss measurement uncertainty of ± 1 dB
7	Cold IEC 61300-2-17	During and on completion of the test the attenuation limits of test No. 1 shall be met After the test the isolation limits of test No. 2 shall be met During and on completion of the test the return loss limits of test No. 4 shall be met	Temperature: Duration of the exposure: Maximum sampling interval during the test: Measurements required:	- 10 °C ± 2 °C 96 h 1 h Attenuation shall be measured before, during and after the test Return loss shall be measured before, during and after the test

Table 1 (continued)

No.	Test	Requirement	Details	
8	Dry heat – High temperature endurance IEC 61300-2-18	During and on completion of the test the attenuation limits of test No. 1 shall be met After the test the isolation limits of test No. 2 shall be met During and on completion of the test the return loss limits of test No. 4 shall be met	Temperature: Duration of the exposure: Maximum sampling interval during the test: Measurements required:	+ 60 °C ± 2 °C 96 h 1 h Attenuation shall be measured before, during and after the test Return loss shall be measured before, during and after the test
9	Change of temperature IEC 61300-2-22	During and on completion of the test the attenuation limits of test No. 1 shall be met After the test the isolation limits of test No. 2 shall be met During and on completion of the test the return loss limits of test No. 4 shall be met	High temperature: Low temperature: Number of cycles: Rate of temperature change: Duration at extreme temperatures: Maximum sampling interval during the test: Measurements required:	+ 60 °C ± 2 °C - 10 °C ± 2 °C 5 1 °C/min 1 h 0,5 h Attenuation shall be measured before, during and after the test Return loss shall be measured before, during and after the test
10	Damp heat (steady state) IEC 61300-2-19	During and on completion of the test the attenuation limits of test No. 1 shall be met After the test the isolation limits of test No. 2 shall be met During and on completion of the test the return loss limits of test No. 4 shall be met	Temperature: Humidity: Duration of the exposure: Maximum sampling interval during the test: Measurements required:	+ 40 °C ± 2 °C 93 % RH ± 2 % RH 96 h 1 h Attenuation shall be measured before, during and after the test Return loss shall be measured before, during and after the test

Table 1 (continued)

No.	Test	Requirement	Details	
11	Vibration IEC 61300-2-1	After the test the attenuation limits of test No. 1 shall be met After the test the isolation limits of test No. 2 shall be met After the test the return loss limits of test No. 4 shall be met	Frequency range: Constant vibration amplitude: Number of cycles: (10 Hz – 55 Hz -10 Hz): Frequency change: Number of axes: Duration per axis: Measurements required:	10 Hz – 55 Hz 0,75 mm 15 1 octave/min 3 orthogonal 0,5 h Attenuation shall be measured before and after the test Return loss shall be measured before and after the test
12	Shock IEC 61300-2-9	After the test the attenuation limits of test No. 1 shall be met After the test the isolation limits of test No. 2 shall be met After the test the return loss limits of test No. 4 shall be met	Acceleration force: Number of axes: Duration shock: Pulse: Number of shocks: Measurements required:	500 G 3 main axes, perpendicular on each other 1 ms Half sine 2 per axis (one in each direction) Attenuation shall be measured before, after each axis and after the test Return loss shall be measured before and after the test