

SLOVENSKI STANDARD SIST EN 2205:2009

01-maj-2009

Aeronavtika - Jeklo FE-PL1502 (25CrMo4) - 900 MPa =< Rm =< 1100 MPa - Palice - De =< 40 mm

Ў-ŒÁ}åÁÜæĕ{-æ@¢ÁÄÄÚœæ@ÁØÒËÚŠFÍ€GÁÇGÍÔ¦T[IDÆÁJ€EÁTÚæÁmÁÜ{ÁmÁFÁF€EÁTÚæÁË Ùœa)*^}ÁÄÄÖ^ÁmÁ\€Á\{<mark>iTeh STANDARD PREVIEW</mark>

https://standards.iteh.ai/catalog/standards/sist/ab01f59a-0d91-440b-a219-

Ta slovenski standard je istoveten z: EN 2205-2009

ICS:

49.025.10 Jekla Steels

SIST EN 2205:2009 en

SIST EN 2205:2009

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 2205:2009

https://standards.iteh.ai/catalog/standards/sist/ab01f59a-0d91-440b-a219-c7aa73e24aac/sist-en-2205-2009

EUROPEAN STANDARD

EN 2205

NORME EUROPÉENNE

EUROPÄISCHE NORM

March 2009

ICS 49.025.10

English Version

Aerospace series - Steel FE-PL1502 (25CrMo4) - 900 MPa ≤ Rm ≤ 1 100 MPa - Bars - De ≤ 40 mm

Série aérospatiale - Acier FE-PL1502 (25CrMo4) - 900 MPa ≤ Rm ≤ 1 100 MPa - Barres - De ≤ 40 mm

Luft- und Raumfahrt - Stahl FE-PL1502 (25CrMo4) - 900 MPa \leq Rm \leq 1 100 MPa - Stangen - De \leq 40 mm

This European Standard was approved by CEN on 16 August 2008.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Iteland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

SIST EN 2205:2009

https://standards.iteh.ai/catalog/standards/sist/ab01f59a-0d91-440b-a219-c7aa73e24aac/sist-en-2205-2009



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

Foreword

This document (EN 2205:2009) has been prepared by the Aerospace and Defence Industries Association of Europe - Standardization (ASD-STAN).

After enquiries and votes carried out in accordance with the rules of this Association, this Standard has received the approval of the National Associations and the Official Services of the member countries of ASD, prior to its presentation to CEN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by September 2009, and conflicting national standards shall be withdrawn at the latest by September 2009.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom, NDARD PREVIEW

(standards.iteh.ai)

SIST EN 2205:2009 https://standards.iteh.ai/catalog/standards/sist/ab01f59a-0d91-440b-a219-c7aa73e24aac/sist-en-2205-2009

Introduction

This standard is part of the series of EN metallic material standards for aerospace applications. The general organization of this series is described in EN 4258.

This standard has been prepared in accordance with EN 4500-5.

1 Scope

This standard specifies the requirements relating to:

Steel FE-PL1502 (25CrMo4) 900 MPa \leq R_m \leq 1 100 MPa Bars $D_{\rm e} \leq$ 40 mm

for aerospace applications.

iTeh STANDARD PREVIEW

2 Normative references (standards.iteh.ai)

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies is for hundated references, the latest edition of the referenced document (including any amendments) applies standards/sist/ab01f59a-0d91-440b-a219-c7aa73e24aac/sist-en-2205-2009

EN ISO 642, Steel — Hardenability test by end quenching (Jominy test).

EN 2034, Round steel bars drawn and/or descaled — Dimensions — Tolerance h 11 — Aerospace series. 1)

EN 4258, Aerospace series — Metallic materials — General organization of standardization — Links between types of EN standards and their use.

EN 4500-5, Aerospace series — Metallic materials — Rules for drafting and presentation of material standards — Part 5: Specific rules for steels. 2)

EN 4700-2, Aerospace series — Steel and heat resisting alloys — Wrought products — Technical specification — Part 2: Bar and section. ²⁾

EN 9133, Aerospace series — Quality management systems - Qualification procedure for aerospace standard parts.

¹⁾ Published as an ASD Standard at the date of publication of this standard.

²⁾ Published as an ASD Prestandard at the date of publication of this standard.

1	Material designation						Steel FE	-PL1502 (2	5CrMo4)			
2	Chemical	Element		С	Si	Mn	Р	S	Cr	Мо	Ni	Fe
	composition %	min.		0,22	0,10	0,50	_	-	0,90	0,15	-	Base
		max.		0,29	0,35	0,80	0,020	0,015	1,20	0,25	0,30	Dase
3	Method of melting			ting Air melted								
4.1	.1 Form							Bars				
4.2	2 Method of production							-				
4.3	Limit dimension(s) mm		<i>D</i> _e ≤ 40									
5	Technical specification			EN 4700-2								

6.1	Delivery condition	Annealed	Hardened and tempered		
	Heat treatment	-	830 °C ≤ θ≤ 880 °C / OQ or WQ + Temper θ≥ 520 °C		
6.2	Delivery condition code	Α	U		
7	Use condition	Hardened and tempered	Hardened and tempered		
	Heat treatment	Delivery condition + 830 °C ≤ θ ≤ 880 °C / OQ or WQ + θ ≥ 520 °C	Delivery condition		

iTeh STANDARD Characteristics F.W.

8.1	Те	est sample(s)			(standards.itsee EN 4700-2.						
8.2	3.2 Test piece(s)				See EN 4700-2.						
8.3	Нє	eat treatment		htt	ps://standards.itch.aj/catalog/stand c7aa73e24aac/s	ards/sist/ab.0159a.0d91-440b-a/ ist-en-2205-2009	Reference ^a See line 29 D = 16 mm				
9	9 Dimensions concerned mm			mm	-						
10	Th ea	ickness of cladding ch face	on	%	-						
11	Di	rection of test piece	:			_					
12		Temperature θ		°C							
13		Proof stress	R _{p0,2}	MPa*	-	≥ 700	≥ 750				
14	Т	Strength	R _m	MPa*	-	- 900 ≤ R _m ≤ 1 100					
15		Elongation	Α	%	-	≥ 12	≥ 12				
16		Reduction of area	Z	%	-	-	-				
17	17 Hardness			•	≤ 212 HB	269 ≤ HB ≤ 331					
18	18 Shear strength R _c MPa*			MPa*	-						
19	19 Bending k -			_	-						
20	Impact strength K\		KV	J	- ≥40		≥ 40				
21		Temperature	θ	°C	-						
22		Time h		h	-						
23	Stress σ_a MPa			MPa	-						
24	Elongation a		%	-							
25	Rupture stress σ_R MPa*			MPa*	-						
26	Elongation at rupture –										
27	No	otes (see line 98)				a					

29	9 Reference heat treatment		Hardened and tempered + (870 \pm 10) °C / OQ + (545 \pm 5) °C						00 (L)	
31	Hardenability (Jominy test)				EN IS	O 642				
			Distance (mm) 1,5 5 9 15 25 40							
		7	HRC ≥	44	40	34	27	21	_	
			HRC ≤	52	51	48	41	35	31	
95			STANDA! (standard SIST EN 2 s.iteh.ai/catalog/standa c7aa73e24aac/sis	ls.iteh. 205:2009 rds/sist/ab01f	.ai) 59a-0d91-4	40b-a219-				
	Dimensional inspection –		See EN 4700-2.							
			EN 2034							
97	Designation	7			-					
			* 1 MPa = 1 N/mm ² .							
98	Notes	-	a Optional test.							
99	Typical use	_	General purpose steel	; weldable.						

100	-	Product qualification	-	See EN 9133.				
				Qualification programme to be agreed between manufacturer and purchaser.				
100			iП					
		htt		(standards.iteh.ai) SIST EN 2205:2009 tandards.iteh.ai/catalog/standards/sist/ab01f59a-0d91-440b-a219-				