

Edition 1.0 2010-05

# TECHNICAL REPORT





#### THIS PUBLICATION IS COPYRIGHT PROTECTED

#### Copyright © 2010 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.


If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de la CEI ou du Comité national de la CEI du pays du demandeur.

Si vous avez des questions sur le copyright de la CEI ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de la CEI de votre pays de résidence.

IFC Central Office 3, rue de Varembé CH-1211 Geneva 20 Switzerland

Email: inmail@iec.ch Web: www.iec.ch



The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

■ Catalogue of IEC publications: <u>www.iec.ch/searchpub</u>

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

■ IEC Just Published: <a href="https://www.iec.ch/online\_news/justpub">www.iec.ch/online\_news/justpub</a>
Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

■ Customer Service Centre: <a href="https://www.ieo.ch/webstore/custserv">https://www.ieo.ch/webstore/custserv</a>
If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact os:


Email: csc@iec.ch

Tel.: +41 22 919 02 11 Fax: +41 22 919 03 00



Edition 1.0 2010-05

# TECHNICAL REPORT



Selection of optical fibre cable specifications relative to mechanical, ingress, climatic or electromagnetic characteristics – Guidance



INTERNATIONAL ELECTROTECHNICAL COMMISSION

PRICE CODE

R

ICS 33.180.10

ISBN 978-2-88910-941-8

### CONTENTS

1 Sc	Scope					
2 No	Normative references					
3 Ac	Acronyms					
4 MI	MICE attributes and severities					
4.	4.1 General					
4.2		anical				
	4.2.1	Shock/bump				
	4.2.2	Vibration	7			
	4.2.3	Tensile force	7			
	4.2.4	Crush				
	4.2.5	Impact	<del>1</del>			
	4.2.6					
4.3	/ - \ \					
	4.3.1					
	4.3.2	Particulate ingress				
4.4	4.3.3	Water immersion				
4.4	4.4.1	tic				
	4.4.1	Ambient temperature				
	4.4.3	Rate of change of temperature				
	4.4.4	Humidity				
	4.4.5	Solar radiation.				
	4.4.6	Liquid pollution	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,			
	4.4.7	Gaseous pollution				
4.	5 Electr	omagnetic	10			
Annex	A (inform	pative) Details of MICE classification	11			
Annex	B (inform	native) IEC cable standards	13			
Annex	C (inform	pative) Fibre specifications and tests	15			
	raphy					
Table	1 – Resis	tance to solar radiation	8			
		l pollution				
		ous pollution resistance				
		ous pollution resistance				
		·				
		ails of MICE classification (Mechanical)				
		ails of MICE classification (Ingress)				
	^ ~ I)∧ <del>t</del>	ails of MICE classification (Chemical)	11			

#### INTERNATIONAL ELECTROTECHNICAL COMMISSION

## SELECTION OF OPTICAL FIBRE CABLE SPECIFICATIONS RELATIVE TO MECHANICAL, INGRESS, CLIMATIC OR ELECTROMAGNETIC CHARACTERISTICS – GUIDANCE

#### **FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter veterred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and 2010 members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
  - 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
  - 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. However, a technical committee may propose the publication of a technical report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

IEC 62362 which is a technical report, has been prepared by subcommittee 86A: Fibres and cables, of IEC technical committee 86: Fibre optics.

The text of this technical report is based on the following documents:

Enquiry draft	Report on voting	
86A/1297/DTR	86A/1302/RVC	

Full information on the voting for the approval of this technical report can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- · replaced by a revised edition, or
- · amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

iTex Synda (as (https://stanaxyd.iteh.ai)

Dycurren Preview

https://standards.iteh.aix/sylvstanaxyds/sext.sase8f-ac37-4579-8855-f86662318002/ice-tr-62362-2010

#### INTRODUCTION

Optical fibre cable specification standards are defined in the IEC 60794 series, which are listed in Annex B. They are organized in a hierarchy similar to the IECQ system. They differ from the IECQ system in that they are all performance standards. Optical fibre cable standards mainly cover the attributes and tests that protect the fibre from the environment, including installation, and the fibre attributes that may be affected by cabling. The attributes of the fibres within the cable are defined by reference to optical fibre specification standards of the IEC 60793 series, which are listed in Annex C. A complete and up-to-date listing of standards in the IEC 60793 and IEC 60794 series is available on website of the IEC: http://www.iec.ch.

The different levels of hierarchy are: general, sectional, family, and product. The primary distinction between these is the level of detail. Typically more options or wider ranges are present at the higher level. At a given level, the distinctions are with respect to application or cable construction. The references section of this document gives a more complete mapping. Parts of the family specification include blank detail specifications for various attributes that do not have normative requirements.

At the sectional specification level, two main categories are indoor and outdoor cables. Typically the outdoor cables have tougher tests than the indoor cables. At the product specification level, there are series of standards intended to support ISO/IEC 11801 for premises cabling, using both indoor and outdoor varieties.

This guidance will not attempt to reproduce the requirements of all the different specifications. For each of the MICE attributes, it will discuss the situation and mention the key options.



## SELECTION OF OPTICAL FIBRE CABLE SPECIFICATIONS RELATIVE TO MECHANICAL, INGRESS, CLIMATIC OR ELECTROMAGNETIC CHARACTERISTICS – GUIDANCE

#### 1 Scope

The purpose of this guidance is to provide information on the specification of optical fibre cables with respect to the mechanical, ingress, climatic or electromagnetic characteristics (MICE) as classified within ISO/IEC 24702.

In this classification system each letter of the four initials of the acronym are subscripted with a value of from one to three to indicate different severities. The current attributes and severities are found in Annex A.

#### 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60794-1-2, Optical fibre cables – Part 1-2: Generic spesification – Basic optical cable test procedures

IEC 60794-2 (all parts), Optical fibre cables - Part 2: Indoor optical fibre cables

IEC 60794-3 (all parts), Optical fibre cables - Part 3: Outdoor cables

ISO/IEC 24702, Information technology - Generic cabling - Industrial premises 2/1904-1906 (2362-2010)

ISO/IEC 11801, Information technology - Generic cabling for customer premises

#### 3 Acronyms

MICE Mechanical, ingress, climatic and chemical, electromagnetic

#### 4 MICE attributes and severities

#### 4.1 General

The MICE classification system has three levels of severity:

- the first level of severity (M<sub>1</sub>I<sub>1</sub>C<sub>1</sub>E<sub>1</sub>) describes a typical environment such as that assumed within ISO/IEC 11801; (i.e. office premises etc.);
- the second level of severity (M<sub>2</sub>I<sub>2</sub>C<sub>2</sub>E<sub>2</sub>) describes a worst-case light industrial environment;
- the third level of severity (M₃I₃C₃E₃) describes a worst-case industrial environment.

See Annex A for a more detailed description of the MICE severity levels.

#### 4.2 Mechanical

#### 4.2.1 Shock/bump

Shock and bump are not specified for optical fibre cables. They are inherently robust in this respect. A more important attribute is bending.

#### 4.2.2 Vibration

Vibration in the industrial premises (as opposed to wind induced vibration on aerially deployed cables) is not specified for optical fibre cables. They are inherently robust in this respect.

#### 4.2.3 Tensile force

For outdoor premises cables specified in IEC 60794-3 series, manufacturers specify a rated tensile force. The requirement is that the fibre shall not exceed a percentage of the proof test strain (to be agreed between customer and supplier) when the cable is tested at the rated load.

For indoor cables, the different family specifications of IEC 60794-2 series have different requirements on the tensile load.

#### 4.2.4 Crush

For optical fibre cables, the crushing force is applied in a plate to plate test.

For indoor cables, crush is specified at 500 N. For outdoor cables, different levels are specified depending on whether the cable is armoured or not. For unarmoured cable, values of between 1 500 N and 3 000 N may be specified. For armoured cable, values between 2 200 N and 10 000 N may be specified.

#### **4.2.5** Impact

For indoor cables a value of 1 J with a 12,5 mm radius is specified. For un-armoured outdoor cables, a value of either 10 J with a 300 mm radius or 3 J with a 10 mm radius is specified.

#### 4.2.6 Bending, flexing and torsion

All the family specifications have requirements on these attributes.

For bending, there are multiple tests such as bending under tension, repeated bending and simple bending. The bending diameter is typically 20 times the cable diameter.

For torsion, the test length, load, and number of turns varies depending on the family specification. For indoor cables, the length is from 250 mm to 1 000 mm, loaded at 20 N with 20 cycles applied.

#### 4.3 Ingress

#### 4.3.1 Basic consideration

Optical fibre cables come in a variety of constructions. Some examples are slotted core, loose tube, tight buffered. The slotted core and loose tube can be filled or unfilled. These different constructions have different ingress characteristics.

#### 4.3.2 Particulate ingress

Particulate ingress is not specified for optical fibre cables. They are inherently robust in this respect.

#### 4.3.3 Water immersion

On cables for which water immersion is specified, the test is different from that found in Annex A. The requirement is that a pressure equivalent to 1 m of water is applied at or near one end of a short (<3m) cable. After 24 h, the requirement is: No water found at the other end.

It is expected that cables passing this test would pass both  $I_2$  and  $I_3$  severities.

#### 4.4 Climatic

#### 4.4.1 General

Terminations such as cable closures are generally considered separately from the cables and are covered by IEC SC 86B.

NOTE The values that appear in Tables 1 to 3b below indicate levels of resistance to climatic phenomena. Values of 1 – 3 correspond to the relevant level of severity in the MICE classification system. A value of 0 indicates no effective resistance to the climatic phenomena described.

#### 4.4.2 Ambient temperature

The different specifications allow different ranges of values to be specified by the customer, depending on the climate in which the cable will be installed. For the detailed specifications for premises cabling, -20 °C to +60 °C are specified. Other ranges and combinations from -45 °C to +70 °C are also found as options in the family specifications.

#### 4.4.3 Rate of change of temperature

This is not specified. All the cables that pass the other requirements will, however, have the capability of 3 °C/min.

#### 4.4.4 Humidity

https: For further study.

#### 4.4.5 Solar radiation

Polyvinyl chloride

Resistance to solar radiation in the industrial premises environment is not specified. Resistance to solar radiation is a property of the sheath material. The severities associated with some common generic materials are indicated in Table 1.

A specific grade of the generic material may have a different performance to that identified in the Table 1.

Material	Natural	Stabilized	With ~2,5 % of active carbon black content
Medium-density polyethylene	0	3	3
Track-resistant medium-density polyethylene	0	3	3
High-density polyethylene	0	3	3
Thermoplastic (co)polyester elastomer	0	3	3

Table 1 - Resistance to solar radiation