

INTERNATIONAL STANDARD

NORME INTERNATIONALE

BASIC SAFETY PUBLICATION

PUBLICATION FONDAMENTALE DE SÉCURITÉ

Fire hazard testing –

**Part 1-11: Guidance for assessing the fire hazard of electrotechnical products –
Fire hazard assessment**

Essais relatifs aux risques du feu –

**Partie 1-11: Lignes directrices pour l'évaluation des risques du feu des produits
électrotechniques – Evaluation des risques du feu**



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2010 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de la CEI ou du Comité national de la CEI du pays du demandeur.

Si vous avez des questions sur le copyright de la CEI ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de la CEI de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland
Email: inmail@iec.ch
Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: www.iec.ch/online_news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: www.iec.ch/webstore/custserv

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch
Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00

A propos de la CEI

La Commission Electrotechnique internationale (CEI) est la première organisation mondiale qui élabore et publie des normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications CEI

Le contenu technique des publications de la CEI est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

- Catalogue des publications de la CEI: www.iec.ch/searchpub/cur_fut-f.htm

Le Catalogue en-ligne de la CEI vous permet d'effectuer des recherches en utilisant différents critères (numéro de référence, texte, comité d'études,...). Il donne aussi des informations sur les projets et les publications retirées ou remplacées.

- Just Published CEI: www.iec.ch/online_news/justpub

Restez informé sur les nouvelles publications de la CEI. Just Published détaille deux fois par mois les nouvelles publications parues. Disponible en-ligne et aussi par email.

- Electropedia: www.electropedia.org

Le premier dictionnaire en ligne au monde de termes électroniques et électriques. Il contient plus de 20 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans les langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International en ligne.

- Service Clients: www.iec.ch/webstore/custserv/custserv_entry-f.htm

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions, visitez le FAQ du Service clients ou contactez-nous:

Email: csc@iec.ch
Tél.: +41 22 919 02 11
Fax: +41 22 919 03 00

INTERNATIONAL STANDARD

NORME INTERNATIONALE

BASIC SAFETY PUBLICATION

PUBLICATION FONDAMENTALE DE SÉCURITÉ

**Fire hazard testing –
Part 1-11: Guidance for assessing the fire hazard of electrotechnical products –
Fire hazard assessment**

**Essais relatifs aux risques du feu –
Partie 1-11: Lignes directrices pour l'évaluation des risques du feu des produits
électrotechniques – Evaluation des risques du feu**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

PRICE CODE
CODE PRIX



ICS 13.220.40; 29.020

ISBN 978-2-88912-027-7

CONTENTS

FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	7
2 Normative references.....	7
3 Terms and definitions.....	8
4 Elements of fire hazard assessment.....	14
4.1 Ignition sources.....	14
4.2 Fire hazard.....	14
4.3 Fire risk.....	14
4.4 Fire hazard assessment.....	14
5 Fire hazard tests.....	15
6 The fire hazard assessment process.....	15
6.1 General.....	15
6.2 Definition of the product range and the circumstances of use.....	16
6.3 Identification and analysis of fire scenarios.....	16
6.3.1 General.....	16
6.3.2 Qualitative description of the fire scenario.....	17
6.3.3 Quantitative analysis of the fire scenario.....	18
6.3.4 Simple hypothetical fire scenarios.....	19
6.4 Selection of criteria for acceptable fire scenario outcomes.....	19
6.5 Performance requirements.....	20
6.6 Interpretation of test results.....	20
6.7 Consequential testing.....	20
7 Scope and limitations of the fire hazard assessment.....	20
8 Fire test requirements and specifications.....	21
Annex A (informative) Calculation of acceptable toxic yield values for an electrical insulation material, based on a simple hypothetical fire scenario.....	26
Annex B (informative) Use of rigid plastic conduit – A fire hazard assessment.....	31
Bibliography.....	43
Figure B.1 – Schematic of conduit installation.....	38
Figure B.2 – Corridor upper layer temperature (concrete wall).....	38
Figure B.3 – Corridor upper layer temperature (gypsum wall board).....	39
Figure B.4 – Flux measured at the conduit 2 m away (concrete wall).....	39
Figure B.5 – Flux measured at the conduit 2 m away (gypsum wall).....	40
Figure B.6 – Comparative mass loss rates of furniture and conduit (concrete wall).....	40
Figure B.7 – Comparative mass loss rates of furniture and conduit (gypsum wall board).....	41
Figure B.8 – Relative increase of toxicity due to exposed conduit (concrete wall).....	41
Figure B.9 – Relative increase of toxicity due to exposed conduit (gypsum wall board).....	42
Table A.1 – Irritant F values and calculated X values for the defined fire scenario.....	27
Table A.2 – Asphyxiant X values calculated for the defined fire scenario.....	28
Table A.3 – Incapacitation times for hydrogen cyanide.....	29

Table A.4 – Multiplication factors for carbon dioxide 30
Table B.1 – Summary of fire scenario information 33
Table B.2 – Time of occurrence of highly-hazardous conditions in building corridors..... 36

Withhold

iTeh STANDARD PREVIEW
(standards.iteh.ai)

IEC 60695-1-11:2010
<https://standards.iteh.ai/catalog/standards/sist/94279db3-2f9c-435d-b86f-185e745ce288/iec-60695-1-11-2010>

INTERNATIONAL ELECTROTECHNICAL COMMISSION

FIRE HAZARD TESTING –

Part 1-11: Guidance for assessing the fire hazard of electrotechnical products – Fire hazard assessment

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60695-1-11 has been prepared by IEC technical committee 89: Fire hazard testing.

This first edition of this standard, together with IEC 60695-1-10, cancels and replaces the third edition of IEC 60695-1-1 published in 1999, and corrigenda 1 and 2 (2000). It also constitutes a technical revision.

It has the status of a basic safety publication in accordance with IEC Guide 104 and ISO/IEC Guide 51.

This standard is to be used in conjunction with IEC 60695-1-10.

The text of this standard is based on the following documents:

FDIS	Report on voting
89/991A/FDIS	89/1005/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all the parts in the IEC 60695 series, under the general title *Fire hazard testing*, can be found on the IEC website.

Part 1 consists of the following parts:

- Part 1-10: *Guidance for assessing the fire hazard of electrotechnical products – General guidelines*
- Part 1-11: *Guidance for assessing the fire hazard of electrotechnical products – Fire hazard assessment*
- Part 1-20: *Guidance for assessing the fire hazard of electrotechnical products – Ignitability – General guidance*
- Part 1-21: *Guidance for assessing the fire hazard of electrotechnical products – Ignitability – Summary and relevance of test methods*
- Part 1-30: *Guidance for assessing the fire hazard of electrotechnical products – Preselection testing process – General guidelines*
- Part 1-40: *Guidance for assessing the fire hazard of electrotechnical products – Insulating liquids*

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

INTRODUCTION

In the design of any electrotechnical product the risk of fire and the potential hazards associated with fire need to be considered. In this respect, the objective of component, circuit and equipment design as well as the choice of materials is to reduce to acceptable levels the potential risks of fire even in the event of foreseeable abnormal use, malfunction or failure. This standard, together with its companion, IEC 60695-1-10, provides guidance on how this is to be accomplished.

The primary aims are to prevent ignition caused by an electrically energised component part and, in the event of ignition, to confine any resulting fire within the bounds of the enclosure of the electrotechnical product.

Secondary aims include the minimisation of any flame spread beyond the product's enclosure and the minimisation of harmful effects of fire effluents including heat, smoke, and toxic or corrosive combustion products.

Fires involving electrotechnical products can also be initiated from external non-electrical sources. Considerations of this nature are dealt with in the overall fire hazard assessment.

Fire hazard assessment is used to identify the kinds of fire events (fire scenarios) which will be associated with the product, to establish how the measurable fire properties of the product are related to the outcome of those events, and to establish test methods and performance requirements for those properties which will either result in a tolerable fire outcome or eliminate the event altogether.

Annex A demonstrates a relatively simple fire hazard assessment process as applied to the toxic hazard from a burning material.

Annex B demonstrates a more complex fire hazard assessment process as applied to an electrotechnical product: rigid plastic conduit.

Attention is drawn to the principles in IEC Guide 104, and to the role of committees with horizontal safety functions and group safety functions.

FIRE HAZARD TESTING –

Part 1-11: Guidance for assessing the fire hazard of electrotechnical products – Fire hazard assessment

1 Scope

This part of IEC 60695-1 provides guidance for assessing the fire hazard of electrotechnical products and for the resulting development of fire hazard testing as related directly to harm to people, animals or property. For the purposes of this standard, product means complete electrotechnical equipments, their parts (including components) and electrical insulating materials.

It outlines a hazard-based process to identify appropriate fire test methods and performance criteria for products. The principles of the methodology are to identify fire events (fire scenarios) which will be associated with the product, to establish how the measurable fire properties of the product are related to the possible occurrence and outcome of those events, and to establish test methods and performance requirements for those properties which will either result in a tolerable fire outcome or eliminate the event altogether.

This standard is intended as guidance to IEC committees, and should be used with respect to their individual applications. The actual implementation of this standard remains the responsibility of each product committee, according to the minimum acceptable fire safety in its application field and taking into account the feedback from experience.

This basic safety publication is intended for use by technical committees in the preparation of standards in accordance with the principles laid down in IEC Guide 104 and ISO/IEC Guide 51.

One of the responsibilities of a technical committee is, wherever applicable, to make use of basic safety publications in the preparation of its publications. The requirements, test methods or test conditions of this basic safety publication will not apply unless specifically referred to or included in the relevant publications.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60695-1-10:2009, *Fire hazard testing – Part 1-10: Guidance for assessing the fire hazard of electrotechnical products – General guidelines*

IEC 60695-1-21:2008, *Fire hazard testing – Part 1-21: Guidance for assessing the fire hazard of electrotechnical products – Ignitability – Summary and relevance of test methods*

IEC/TS 60695-5-2:2002, *Fire hazard testing – Part 5-2: Corrosion damage effects of fire effluents – Summary and relevance of test methods*

IEC/TS 60695-6-2:2005, *Fire hazard testing – Part 6-2: Smoke obscuration – Summary and relevance of test methods*

IEC/TR 60695-7-2:2002, *Fire hazard testing – Part 7-2: Toxicity of fire effluent – Summary and relevance of test methods*

IEC/TR 60695-8-2:2008, *Fire hazard testing – Part 8-2: Heat release – Summary and relevance of test methods*

IEC/TS 60695-9-2:2005, *Fire hazard testing – Part 9-2: Surface spread of flame – Summary and relevance of test methods*

IEC Guide 104:1997, *The preparation of safety publications and the use of basic safety publications and group safety publications*

ISO/IEC Guide 51:1999, *Safety aspects – Guidelines for their inclusion in standards*

ISO/IEC 13943:2008, *Fire safety – Vocabulary*

ISO/TR 13387:1999 (all parts), *Fire safety engineering*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO/IEC 13943, some of which are reproduced below for the use' convenience, as well as the followings apply.

3.1 asphyxiant

toxicant that causes hypoxia, which can result in central nervous system depression or cardiovascular effects

NOTE Loss of consciousness and ultimately death may occur.

[ISO/IEC 13943, definition 4.17]

3.2 available safe escape time ASET

time available for escape for an individual occupant, the calculated time interval between the time of ignition (3.27) and the time at which conditions become such that the occupant is estimated to be incapacitated, i.e. unable to take effective action to escape (3.8) to a safe refuge or place of safety

NOTE 1 The time of ignition can be known, e.g. in the case of a fire model or a fire test, or it may be assumed, e.g. it may be based upon an estimate working back from the time of detection. The basis on which the time of ignition is determined is always stated.

NOTE 2 This definition equates incapacitation with failure to escape. Other criteria for ASET are possible. If an alternate criterion is selected, it is necessary that it be stated.

NOTE 3 Each occupant can have a different value of ASET, depending on that occupant's personal characteristics.

[ISO/IEC 13943, definition 4.20]

3.3 built environment building or other structure

EXAMPLES off-shore platforms, civil engineering works such as tunnels, bridges and mines; and means of transportation such as motor vehicles and marine vessels.

NOTE ISO 6707-1 contains a number of terms and definitions for concepts related to the built environment.

[ISO/IEC 13943, definition 4.26]

3.4 combustion

exothermic reaction of a substance with an oxidizing agent

NOTE Combustion generally emits fire effluent accompanied by flames and/or glowing.

[ISO/IEC 13943, definition 4.46]

3.5 combustion product product of combustion

solid, liquid and gaseous material resulting from combustion (3.4)

NOTE Combustion products can include fire effluent, ash, char, clinker and/or soot.

[ISO/IEC 13943, definition 4.48]

3.6 effective heat of combustion

heat released (3.25) from a burning test specimen in a given time interval divided by the mass lost from the test specimen in the same time period

NOTE 1 It is the same as the net heat of combustion if all the test specimen is converted to volatile combustion (3.4) products and if all the combustion products (3.5) are fully oxidized.

NOTE 2 The typical units are $\text{kJ}\cdot\text{g}^{-1}$.

[ISO/IEC 13943, definition 4.74]

3.7 environment

conditions and surroundings that may influence the behaviour of an item or persons when exposed to fire (3.13)

[ISO/IEC 13943, definition 4.80]

3.8 escape

effective action taken to reach a safe refuge or place of safety

[ISO/IEC 13943, definition 4.82]

3.9 exposure dose

measure of the maximum amount of a toxic gas or fire effluent (3.14) which is available for inhalation, calculated by integration of the area under a concentration-time curve

NOTE 1 For fire effluent, typical units are grams times minutes per cubic metre ($\text{g}\cdot\text{min}\cdot\text{m}^{-3}$).

NOTE 2 For a toxic gas, typical units are microlitres times minutes per litre ($\mu\text{L}\cdot\text{min}\cdot\text{L}^{-1}$) (at $T = 298\text{ K}$ and $P = 1\text{ atm}$).

[ISO/IEC 13943, definition 4.89]

3.10 extinction area of smoke

product of the volume occupied by smoke (3.35) and the extinction coefficient of the smoke

NOTE It is a measure of the amount of smoke, and the typical units are square metres (m^2).

[ISO/IEC 13943, definition 4.92]

3.11

fire

(general) process of combustion (3.4) characterized by the emission of heat and fire effluent (3.14) and usually accompanied by smoke (3.35), flame or glowing or a combination thereof

NOTE In the English language, the term "fire" is used to designate three concepts, two of which, fire (3.12) and fire (3.13), relate to specific types of self-supporting combustion with different meanings and two of them are designated using two different terms in both French and German.

[ISO/IEC 13943, definition 4.96]

3.12

fire

(controlled) self-supporting combustion (3.4) that has been deliberately arranged to provide useful effects and is limited in its extent in time and space

[ISO/IEC 13943, definition 4.97]

3.13

fire

(uncontrolled) self-supporting combustion (3.4) that has not been deliberately arranged to provide useful effects and is not limited in its extent in time and space

[ISO/IEC 13943, definition 4.98]

3.14

fire effluent

totality of gases and aerosols, including suspended particles, created by combustion (3.4) or pyrolysis in a fire (3.11)

[ISO/IEC 13943, definition 4.105]

3.15

fire growth

stage of fire (3.11) development during which the heat release rate (3.26) and the temperature of the fire are increasing

[ISO/IEC 13943, definition 4.111]

3.16

fire hazard

physical object or condition with a potential for an undesirable consequence from fire (3.13)

[ISO/IEC 13943, definition 4.112]

3.17

fire risk

probability of a fire (3.13) combined with a quantified measure of its consequence

NOTE It is often calculated as the product of probability and consequence.

[ISO/IEC 13943, definition 4.124]

3.18

fire safety engineering

application of engineering methods based on scientific principles to the development or assessment of designs in the built environment (3.3) through the analysis of specific fire scenarios (3.19) or through the quantification of risk for a group of fire scenarios

[ISO/IEC 13943, definition 4.126]

3.19

fire scenario

qualitative description of the course of a fire (3.13) with respect to time, identifying key events that characterise the studied fire and differentiate it from other possible fires

NOTE It typically defines the ignition (3.28) and fire growth (3.15) processes, the fully developed fire stage, the fire decay stage, and the environment (3.7) and systems that will impact on the course of the fire.

[ISO/IEC 13943, definition 4.129]

3.20

fire test

test that measures behaviour of a fire (3.11) or exposes an item to the effects of a fire (3.12)

NOTE The results of a fire test can be used to quantify fire severity or determine the fire resistance or reaction to fire (3.34) of the test specimen.

[ISO/IEC 13943, definition 4.132]

3.21

flame front

boundary of flaming combustion at the surface of a material or propagating through a gaseous mixture

[ISO/IEC 13943, definition 4.136]

3.22

flame spread

propagation of a flame front (3.21)

[ISO/IEC 13943, definition 4.142]

3.23

flashover

(stage of fire) transition to a state of total surface involvement in a fire (3.13) of combustible materials within an enclosure

[ISO/IEC 13943, definition 4.156]

3.24

fractional effective dose

FED

ratio of the exposure dose (3.9) for an asphyxiant (3.1) to that exposure dose of the asphyxiant expected to produce a specified effect on an exposed subject of average susceptibility

NOTE 1 As a concept, fractional effective dose may refer to any effect, including incapacitation, lethality or other endpoints.

NOTE 2 When not used with reference to a specific asphyxiant, the term *FED* represents the summation of *FED* values for all asphyxiants in a combustion atmosphere.

NOTE 3 The *FED* is dimensionless.

[ISO/IEC 13943, definition 4.160]

3.25

heat release

thermal energy produced by combustion (3.4)

NOTE The typical units are joules (J).

[ISO/IEC 13943, definition 4.176]

3.26

heat release rate

burning rate (deprecated)

rate of burning (deprecated)

rate of thermal energy production generated by combustion (3.4)

NOTE The typical units are watts (W).

[ISO/IEC 13943, definition 4.177]

3.27

ignition

sustained ignition (deprecated)
(general) initiation of combustion (3.4)

[ISO/IEC 13943, definition 4.187]

3.28

ignition

sustained ignition (deprecated)
(flaming combustion) initiation of sustained flame

[ISO/IEC 13943, definition 4.188]

3.29

incapacitation

state of physical inability to accomplish a specific task

NOTE An example of a specific task is to accomplish escape from a fire.

[ISO/IEC 13943, definition 4.194]

3.30

irritant, noun

(sensory/upper respiratory) gas or aerosol that stimulates nerve receptors in the eyes, nose, mouth, throat and respiratory tract, causing varying degrees of discomfort and pain with the initiation of numerous physiological defence responses

NOTE Physiological defence responses include reflex eye closure, tear production, coughing, and bronchoconstriction.

[ISO/IEC 13943, definition 4.203]

3.31

mass loss rate

test specimen mass loss per unit time under specified conditions

NOTE The typical units are grams per second ($\text{g}\cdot\text{s}^{-1}$).

[ISO/IEC 13943, definition 4.224]

3.32

obscuration by smoke

reduction in the intensity of light due to its passage through smoke (3.35)

NOTE 1 In practice, obscuration by smoke is usually measured as the transmittance which is normally expressed as a percentage.

NOTE 2 Obscuration by smoke causes a reduction in visibility.

[ISO/IEC 13943, definition 4.242]

3.33

qualitative fire test

fire test which is either:

- a) a pass/fail test; or
- b) a test which categorizes the behaviour of the test specimen by determining its position in a rank order of performance

**3.34
quantitative fire test**

fire test which takes into account the circumstances of product use in which the test conditions are based on, or are relatable to, the circumstances of use of the test specimen, and which measures a parameter or parameters, expressed in well defined terms and using rational scientific units, which can be used in the quantitative assessment of fire risk

**3.35
radiant heat flux**

power per unit area emitted, transferred or received in the form of heat radiation

NOTE The typical units are kilowatts per square metre ($\text{kW}\cdot\text{m}^{-2}$).

[ISO/IEC 13943, definition 4.269]

**3.36
reaction to fire**

response of a test specimen when it is exposed to fire (3.12) under specified conditions in a fire test (3.20)

NOTE Fire resistance is regarded as a special case and is not normally considered as a reaction to fire property.

[ISO/IEC 13943, definition 4.272]

**3.37
smoke**

visible part of fire effluent (3.14)

[ISO/IEC 13943, definition 4.293]

**3.38
specific extinction area of smoke**

extinction area of smoke (3.10) produced by a test specimen in a given time period divided by the mass lost from the test specimen in the same time period

NOTE The typical units are square metres per gram ($\text{m}^2\cdot\text{g}^{-1}$).

[ISO/IEC 13943, definition 4.301]

**3.39
toxic
poisonous**

NOTE A poisonous substance produces adverse effects upon a living organism, e.g. irritation, narcosis or death.

[ISO/IEC 13943, definition 4.335]

**3.40
toxic potency**

measure of the amount of toxicant (3.39) required to elicit a specific toxic (3.37) effect

NOTE A small value of toxic potency corresponds to a high toxicity (3.40) and vice versa.

[ISO/IEC 13943, definition 4.338]

**3.41
toxicant
toxin**

toxic substance (3.37)

[ISO/IEC 13943, definition 4.340]