



IEC 61158-4-2

Edition 1.0 2007-12

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Industrial communication networks – Fieldbus specifications –
Part 4-2: Data-link layer protocol specification – Type 2 elements

Réseaux de communication industriels – Spécifications des bus de terrain –
Partie 4-2: Spécification du protocole de la couche liaison de données –
Éléments de Type 2

<https://standards.iteh.ai/standard/iec-61158-4-2-2007>



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2007 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office
3, rue de Varembé
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/jupublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in 14 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

More than 55 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Catalogue IEC - webstore.iec.ch/catalogue

Application autonome pour consulter tous les renseignements bibliographiques sur les Normes internationales, Spécifications techniques, Rapports techniques et autres documents de l'IEC. Disponible pour PC, Mac OS, tablettes Android et iPad.

Recherche de publications IEC - www.iec.ch/searchpub

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études,...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/jupublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire en ligne de termes électroniques et électriques. Il contient plus de 30 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans 14 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

Glossaire IEC - std.iec.ch/glossary

Plus de 55 000 entrées terminologiques électrotechniques, en anglais et en français, extraites des articles Termes et Définitions des publications IEC parues depuis 2002. Plus certaines entrées antérieures extraites des publications des CE 37, 77, 86 et CISPR de l'IEC.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: csc@iec.ch.



IEC 61158-4-2

Edition 1.0 2007-12

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Industrial communication networks – Fieldbus specifications –
Part 4-2: Data-link layer protocol specification – Type 2 elements

Réseaux de communication industriels – Spécifications des bus de terrain –
Partie 4-2: Spécification du protocole de la couche liaison de données –
Éléments de Type 2

<https://standards.iteh.ai/catalog/standards/sc/44b2364-e464-4326-ac4b-f66f0b29b25c/iec-61158-4-2-2007>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

PRICE CODE
CODE PRIX
XH

ICS 25.040.40; 35.100.20

ISBN 978-2-8322-1697-2

Warning! Make sure that you obtained this publication from an authorized distributor.

Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.

CONTENTS

| | |
|--|----|
| FOREWORD..... | 7 |
| INTRODUCTION..... | 9 |
| 1 Scope | 10 |
| 1.1 General | 10 |
| 1.2 Specifications | 10 |
| 1.3 Procedures..... | 10 |
| 1.4 Applicability..... | 11 |
| 1.5 Conformance..... | 11 |
| 2 Normative references | 11 |
| 3 Terms, definitions, symbols and abbreviations..... | 12 |
| 3.1 Reference model terms and definitions..... | 12 |
| 3.2 Service convention terms and definitions..... | 14 |
| 3.3 Common terms and definitions | 15 |
| 3.4 Additional Type 2 definitions | 16 |
| 3.5 Type 2 symbols and abbreviations | 23 |
| 4 Overview of the DL-protocol..... | 24 |
| 4.1 General | 24 |
| 4.2 Services provided by the DL | 26 |
| 4.3 Structure and definition of DL addresses..... | 27 |
| 4.4 Services assumed from the PhL | 29 |
| 4.5 Functional classes..... | 31 |
| 5 General structure and encoding of PhIDUs and DLPDUs and related elements of procedure..... | 32 |
| 5.1 Overview..... | 32 |
| 5.2 Media access procedure | 32 |
| 5.3 DLPDU structure and encoding | 35 |
| 5.4 Lpacket components | 39 |
| 5.5 DLPDU procedures | 41 |
| 5.6 Summary of DLL support services and objects | 42 |
| 6 Specific DLPDU structure, encoding and procedures | 44 |
| 6.1 Modeling language | 44 |
| 6.2 DLS user services | 46 |
| 6.3 Generic tag Lpacket..... | 52 |
| 6.4 Moderator Lpacket..... | 53 |
| 6.5 Time distribution Lpacket | 54 |
| 6.6 UCMM Lpacket..... | 57 |
| 6.7 Keeper UCMM Lpacket | 57 |
| 6.8 TUI Lpacket | 58 |
| 6.9 Link parameters Lpacket and tMinus Lpacket | 59 |
| 6.10 I'm-alive Lpacket | 60 |
| 6.11 Ping Lpackets..... | 62 |
| 6.12 WAMI Lpacket | 64 |
| 6.13 Debug Lpacket | 64 |
| 6.14 IP Lpacket | 65 |
| 6.15 Ethernet Lpacket | 65 |
| 7 Objects for station management..... | 65 |

| | | |
|--|---|-----|
| 7.1 | General | 65 |
| 7.2 | ControlNet object..... | 66 |
| 7.3 | Keeper object | 76 |
| 7.4 | Scheduling object | 98 |
| 7.5 | TCP/IP Interface object..... | 109 |
| 7.6 | Ethernet link object..... | 118 |
| 7.7 | DeviceNet object | 124 |
| 7.8 | Connection configuration object (CCO) | 132 |
| 8 | Other DLE elements of procedure | 152 |
| 8.1 | Network attachment monitor (NAM)..... | 152 |
| 8.2 | Calculating link parameters..... | 159 |
| 9 | Detailed specification of DL components | 167 |
| 9.1 | General | 167 |
| 9.2 | Access control machine (ACM) | 167 |
| 9.3 | TxLLC | 184 |
| 9.4 | RxLLC | 188 |
| 9.5 | Transmit machine (TxM) | 191 |
| 9.6 | Receive machine (RxM)..... | 194 |
| 9.7 | Serializer..... | 200 |
| 9.8 | Deserializer | 201 |
| 9.9 | DLL management | 202 |
| Annex A (normative) | Indicators and switches | 205 |
| A.1 | Purpose | 205 |
| A.2 | Indicators | 205 |
| A.3 | Switches | 216 |
| Bibliography | 218 | |
| INDEX | 219 | |
| Figure 1 – Relationships of DLSAPs, DLSAP-addresses and group DL-addresses | 15 | |
| Figure 2 – Data-link layer internal architecture | 25 | |
| Figure 3 – Basic structure of a MAC ID address | 27 | |
| Figure 4 – Basic structure of a generic tag address | 27 | |
| Figure 5 – Basic structure of a fixed tag address | 28 | |
| Figure 6 – M_symbols and Manchester encoding at 5 MHz (informative) | 29 | |
| Figure 7 – NUT structure | 33 | |
| Figure 8 – Media access during scheduled time | 33 | |
| Figure 9 – Media access during unscheduled time | 34 | |
| Figure 10 – DLPDU format | 35 | |
| Figure 11 – Aborting a DLPDU during transmission | 39 | |
| Figure 12 – Lpacket format | 39 | |
| Figure 13 – Generic tag Lpacket format | 40 | |
| Figure 14 – Fixed tag Lpacket format | 41 | |
| Figure 15 – Goodness parameter of TimeDist_Lpacket | 55 | |
| Figure 16 – Example I'm alive processing algorithm | 62 | |
| Figure 17 – Keeper CRC algorithm | 82 | |
| Figure 18 – Keeper object power-up state diagram | 94 | |

| | |
|--|-----|
| Figure 19 – Keeper object operating state diagram | 95 |
| Figure 20 – Synchronized network change processing | 98 |
| Figure 21 – State transition diagram for TCP/IP Interface object | 118 |
| Figure 22 – Connection configuration object edit flowchart..... | 152 |
| Figure 23 – NAM state machine | 153 |
| Figure A.1 – Non redundant network status indicator labeling | 209 |
| Figure A.2 – Redundant network status indicator labeling | 210 |
| Table 1 – Data-link layer components..... | 24 |
| Table 2 – MAC ID addresses allocation | 27 |
| Table 3 – Fixed tag service definitions..... | 28 |
| Table 4 – Data encoding rules..... | 29 |
| Table 5 – M Data symbols..... | 30 |
| Table 6 – Truth table for ph_status_indication | 31 |
| Table 7 – FCS length, polynomials and constants..... | 37 |
| Table 8 – DLL support services and objects | 43 |
| Table 9 – Elementary data types | 46 |
| Table 10 – DLL events | 51 |
| Table 11 – Time distribution priority | 56 |
| Table 12 – Format of the TUI Lpacket | 58 |
| Table 13 – ControlNet object class attributes..... | 67 |
| Table 14 – ControlNet object instance attributes | 67 |
| Table 15 – TUI status flag bits..... | 71 |
| Table 16 – Channel state bits..... | 72 |
| Table 17 – ControlNet object common services | 74 |
| Table 18 – ControlNet object class specific services | 75 |
| Table 19 – Keeper object revision history | 77 |
| Table 20 – Keeper object class attributes | 77 |
| Table 21 – Keeper object instance attributes | 77 |
| Table 22 – Keeper operating state definitions | 80 |
| Table 23 – Port status flag bit definitions | 80 |
| Table 24 – TUI status flag bits..... | 81 |
| Table 25 – Keeper attributes | 84 |
| Table 26 – Memory requirements (in octets) for the Keeper attributes | 84 |
| Table 27 – Keeper object common services..... | 85 |
| Table 28 – Keeper object class specific services | 86 |
| Table 29 – Service error codes | 87 |
| Table 30 – Wire order format of the TUI Lpacket..... | 91 |
| Table 31 – Service error codes | 92 |
| Table 32 – Keeper object operating states..... | 92 |
| Table 33 – Keeper object state event matrix | 96 |
| Table 34 – Scheduling object class attributes | 99 |
| Table 35 – Scheduling object instance attributes | 100 |

| | |
|--|-----|
| Table 36 – Scheduling object common services | 100 |
| Table 37 – Status error descriptions for Create | 101 |
| Table 38 – Status error descriptions for Delete and Kick_Timer | 102 |
| Table 39 – Scheduling object class specific services | 102 |
| Table 40 – Status error descriptions for Read | 104 |
| Table 41 – Status error descriptions for Conditional_Write | 105 |
| Table 42 – Status error descriptions for Forced_Write | 105 |
| Table 43 – Status error descriptions for Change_Start | 106 |
| Table 44 – Status error descriptions for Break_Connections | 106 |
| Table 45 – Status error descriptions for Change_Complete | 107 |
| Table 46 – Status error descriptions for Restart_Connections | 108 |
| Table 47 – TCP/IP Interface object class attributes | 109 |
| Table 48 – TCP/IP Interface object instance attributes | 110 |
| Table 49 – Status bits | 112 |
| Table 50 – Configuration capability bits | 112 |
| Table 51 – Configuration control bits | 113 |
| Table 52 – Example path | 113 |
| Table 53 – Interface configuration components | 114 |
| Table 54 – Alloc control values | 115 |
| Table 55 – TCP/IP Interface object common services | 116 |
| Table 56 – Get_Attribute_All reply format | 117 |
| Table 57 – Ethernet link object revision history | 118 |
| Table 58 – Ethernet link object class attributes | 119 |
| Table 59 – Ethernet link object instance attributes | 119 |
| Table 60 – Interface flags bits | 121 |
| Table 61 – Control bits | 123 |
| Table 62 – Ethernet Link object common services | 123 |
| Table 63 – Ethernet Link object class specific services | 124 |
| Table 64 – DeviceNet object revision history | 124 |
| Table 65 – DeviceNet object class attributes | 125 |
| Table 66 – DeviceNet object instance attributes | 125 |
| Table 67 – Bit rate attribute values | 127 |
| Table 68 – BOI attribute values | 128 |
| Table 69 – Diagnostic counters bit description | 129 |
| Table 70 – DeviceNet object common services | 130 |
| Table 71 – Reset service parameter | 130 |
| Table 72 – Reset service parameter values | 131 |
| Table 73 – DeviceNet object class specific services | 131 |
| Table 74 – Connection configuration object revision history | 132 |
| Table 75 – Connection configuration object class attributes | 132 |
| Table 76 – Format number values | 134 |
| Table 77 – Connection configuration object instance attributes | 135 |
| Table 78 – Originator connection status values | 137 |

| | |
|--|-----|
| Table 79 – Target connection status values | 138 |
| Table 80 – Connection flags | 138 |
| Table 81 – I/O mapping formats | 140 |
| Table 82 – Connection configuration object common services | 141 |
| Table 83 – Get_Attribute_All error codes | 141 |
| Table 84 – Get_Attribute_All response | 142 |
| Table 85 – Set_Attribute_All error codes | 143 |
| Table 86 – Set_Attribute_All request | 144 |
| Table 87 – Create request parameters | 145 |
| Table 88 – Create error codes | 146 |
| Table 89 – Delete error codes | 146 |
| Table 90 – Restore error codes | 146 |
| Table 91 – Connection configuration object class specific services | 147 |
| Table 92 – Kick_Timer error codes | 147 |
| Table 93 – Open_Connection error codes | 148 |
| Table 94 – Close_Connection error codes | 148 |
| Table 95 – Stop_Connection error codes | 148 |
| Table 96 – Change_Start error codes | 149 |
| Table 97 – Get_Status service parameter | 149 |
| Table 98 – Get_Status service response | 149 |
| Table 99 – Get_Status service error codes | 150 |
| Table 100 – Change_Complete service parameter | 150 |
| Table 101 – Change_Complete service error codes | 150 |
| Table 102 – Audit_Changes service parameter | 151 |
| Table 103 – Audit_Changes service error codes | 151 |
| Table 104 – NAM states | 153 |
| Table 105 – Default link parameters | 154 |
| Table 106 – PHL timing characteristics | 160 |
| Table A.1 – Module status indicator | 206 |
| Table A.2 – Network status indicators | 207 |
| Table A.3 – Network status indicator | 211 |
| Table A.4 – Network status indicator | 213 |
| Table A.5 – Combined module/network status indicator | 214 |
| Table A.6 – I/O status indicator | 215 |
| Table A.7 – Bit rate switch encoding | 217 |

INTERNATIONAL ELECTROTECHNICAL COMMISSION

INDUSTRIAL COMMUNICATION NETWORKS –
FIELDBUS SPECIFICATIONS –**Part 4-2: Data-link layer protocol specification – Type 2 elements**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.

NOTE Use of some of the associated protocol types is restricted by their intellectual-property-right holders. In all cases, the commitment to limited release of intellectual-property-rights made by the holders of those rights permits a particular data-link layer protocol type to be used with physical layer and application layer protocols in Type combinations as specified explicitly in the IEC 61784 series. Use of the various protocol types in other combinations may require permission from their respective intellectual-property-right holders.

IEC draws attention to the fact that it is claimed that compliance with this standard may involve the use of patents as follows, where the [xx] notation indicates the holder of the patent right:

Type 2 and possibly other types:

| | | |
|--------------|------|--|
| US 5,400,331 | [RA] | Communication network interface with screeners for incoming messages |
| US 5,471,461 | [RA] | Digital communication network with a moderator station election process |
| US 5,491,531 | [RA] | Media access controller with a shared class message delivery capability |
| US 5,493,571 | [RA] | Apparatus and method for digital communications with improved delimiter detection |
| US 5,537,549 | [RA] | Communication network with time coordinated station activity by time slot and periodic interval number |
| US 5,553,095 | [RA] | Method and apparatus for exchanging different classes of data during different time intervals |

IEC takes no position concerning the evidence, validity and scope of these patent rights.

The holders of these patent rights have assured IEC that they are willing to negotiate licences under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statement of the holders of these patent rights are registered with IEC. Information may be obtained from

[RA]: Rockwell Automation, Inc.
1201 S. Second Street
Milwaukee, WI 53204
USA
Attention: Intellectual Property Dept.

Attention is drawn to the possibility that some of the elements of this standard may be the subject of patent rights other than those identified above. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61158-4-2 has been prepared by subcommittee 65C: Industrial networks, of IEC technical committee 65: Industrial-process measurement, control and automation.

This bilingual version (2014-07) corresponds to the English version, published in 2007-12.

This first edition and its companion parts of the IEC 61158-4 subseries cancel and replace IEC 61158-4:2003. This edition of this part constitutes a minor revision. This part and its companion Type 2 parts also cancel and replace IEC PAS 62413, published in 2005.

This edition of IEC 61158-4 includes the following significant changes from the previous edition:

- deletion of the former Type 6 fieldbus, and the placeholder for a Type 5 fieldbus data link layer, for lack of market relevance;
- addition of new types of fieldbuses,
- division of this part into multiple parts numbered -4-1, -4-2, ..., -4-19.

The text of this standard is based on the following documents:

| FDIS | Report on voting |
|--------------|------------------|
| 65C/474/FDIS | 65C/485/RVD |

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

The French version of this standard has not been voted upon.

This publication has been drafted in accordance with ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under <http://webstore.iec.ch> in the data related to the specific publication. At this date, the publication will be:

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

NOTE The revision of this standard will be synchronized with the other parts of the IEC 61158 series.

The list of all the parts of the IEC 61158 series, under the general title *Industrial communication networks – Fieldbus specifications*, can be found on the IEC web site.

INTRODUCTION

This part of IEC 61158 is one of a series produced to facilitate the interconnection of automation system components. It is related to other standards in the set as defined by the “three-layer” fieldbus reference model described in IEC/TR 61158-1.

The data-link protocol provides the data-link service by making use of the services available from the physical layer. The primary aim of this standard is to provide a set of rules for communication expressed in terms of the procedures to be carried out by peer data-link entities (DLEs) at the time of communication. These rules for communication are intended to provide a sound basis for development in order to serve a variety of purposes:

- a) as a guide for implementors and designers;
- b) for use in the testing and procurement of equipment;
- c) as part of an agreement for the admittance of systems into the open systems environment;
- d) as a refinement to the understanding of time-critical communications within OSI.

This standard is concerned, in particular, with the communication and interworking of sensors, effectors and other automation devices. By using this standard together with other standards positioned within the OSI or fieldbus reference models, otherwise incompatible systems may work together in any combination.

<https://standards.iteh.ai/stadl/standards/iec/4462364-e464-4326-ac4b-f66f0b29b25c/iec-61158-4-2-2007>

INDUSTRIAL COMMUNICATION NETWORKS – FIELDBUS SPECIFICATIONS –

Part 4-2: Data-link layer protocol specification – Type 2 elements

1 Scope

1.1 General

The data-link layer provides basic time-critical messaging communications between devices in an automation environment.

This protocol provides communication opportunities to all participating data-link entities, sequentially and in a cyclic synchronous manner. Foreground scheduled access is available for time-critical activities together with background unscheduled access for less critical activities.

Deterministic and synchronized transfers can be provided at cyclic intervals up to 1 ms and device separations of 25 km. This performance is adjustable dynamically and on-line by re-configuring the parameters of the local link whilst normal operation continues. By similar means, DL connections and new devices may be added or removed during normal operation.

This protocol provides means to maintain clock synchronization across an extended link with a precision better than 10 µs.

This protocol optimizes each access opportunity by concatenating multiple DLSDUs and associated DLPCI into a single DLPDU, thereby improving data transfer efficiency for data-link entities that actively source multiple streams of data.

The maximum system size is an unlimited number of links of 99 nodes, each with 255 DLSAP-addresses. Each link has a maximum of 2^{24} related peer and publisher DLCEPs.

1.2 Specifications

This standard specifies

- procedures for the timely transfer of data and control information from one data-link user entity to a peer user entity, and among the data-link entities forming the distributed data-link service provider;
- the structure of the fieldbus DLPDUs used for the transfer of data and control information by the protocol of this standard, and their representation as physical interface data units.

1.3 Procedures

The procedures are defined in terms of

- the interactions between peer DL-entities (DLEs) through the exchange of fieldbus DLPDUs;
- the interactions between a DL-service (DLS) provider and a DLS-user in the same system through the exchange of DLS primitives;
- the interactions between a DLS-provider and a Ph-service provider in the same system through the exchange of Ph-service primitives.

1.4 Applicability

These procedures are applicable to instances of communication between systems which support time-critical communications services within the data-link layer of the OSI or fieldbus reference models, and which require the ability to interconnect in an open systems interconnection environment.

Profiles provide a simple multi-attribute means of summarizing an implementation's capabilities, and thus its applicability to various time-critical communications needs.

1.5 Conformance

This standard also specifies conformance requirements for systems implementing these procedures. This standard does not contain tests to demonstrate compliance with such requirements.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61131-3, *Programmable controllers – Part 3: Programming languages*

IEC 61158-2 (Ed.4.0), *Industrial communication networks – Fieldbus specifications – Part 2: Physical layer specification and service definition*

IEC 61158-3-2, *Industrial communication networks – Fieldbus specifications – Part 3-2: Data-link layer service definition – Type 2 elements*

IEC 61158-5-2, *Industrial communication networks – Fieldbus specifications – Part 5-2: Application layer service definition – Type 2 elements*

IEC 61158-6-2, *Industrial communication networks – Fieldbus specifications – Part 6-2: Application layer protocol specification – Type 2 elements*

IEC 61784-3-2, *Industrial communication networks – Profiles – Part 3-2: Functional safety fieldbuses – Additional specifications for CPF 2*

IEC 62026-3¹, *Low-voltage switchgear and controlgear – Controller-device interfaces (CDIs) – Part 3: DeviceNet*

ISO/IEC 3309, *Information technology – Telecommunications and information exchange between systems – High-level data link control (HDLC) procedures – Frame structure*

ISO/IEC 7498-1, *Information technology – Open Systems Interconnection – Basic Reference Model: The Basic Model*

ISO/IEC 7498-3, *Information technology – Open Systems Interconnection – Basic Reference Model: Naming and addressing*

ISO/IEC 8802-3, *Information technology – Telecommunications and information exchange between systems – Local and metropolitan area networks – Specific requirements – Part 3:*

¹ To be published.

Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications

ISO/IEC 10731, Information technology – Open Systems Interconnection – Basic Reference Model – Conventions for the definition of OSI services

ISO 11898:1993², Road vehicles – Interchange of digital information – Controller area network (CAN) for high-speed communication

3 Terms, definitions, symbols and abbreviations

For the purposes of this document, the following terms, definitions, symbols and abbreviations apply.

3.1 Reference model terms and definitions

This standard is based in part on the concepts developed in ISO/IEC 7498-1 and ISO/IEC 7498-3, and makes use of the following terms defined therein.

| | | |
|---------------|---|------------------|
| 3.1.1 | called-DL-address | [ISO/IEC 7498-3] |
| 3.1.2 | calling-DL-address | [ISO/IEC 7498-3] |
| 3.1.3 | centralized multi-end-point-connection | [ISO/IEC 7498-1] |
| 3.1.4 | correspondent (N)-entities correspondent DL-entities (N=2) correspondent Ph-entities (N=1) | [ISO/IEC 7498-1] |
| 3.1.5 | demultiplexing | [ISO/IEC 7498-1] |
| 3.1.6 | DL-address | [ISO/IEC 7498-3] |
| 3.1.7 | DL-address-mapping | [ISO/IEC 7498-1] |
| 3.1.8 | DL-connection | [ISO/IEC 7498-1] |
| 3.1.9 | DL-connection-end-point | [ISO/IEC 7498-1] |
| 3.1.10 | DL-connection-end-point-identifier | [ISO/IEC 7498-1] |
| 3.1.11 | DL-connection-mode transmission | [ISO/IEC 7498-1] |
| 3.1.12 | DL-connectionless-mode transmission | [ISO/IEC 7498-1] |
| 3.1.13 | DL-data-sink | [ISO/IEC 7498-1] |
| 3.1.14 | DL-data-source | [ISO/IEC 7498-1] |
| 3.1.15 | DL-duplex-transmission | [ISO/IEC 7498-1] |
| 3.1.16 | DL-facility | [ISO/IEC 7498-1] |
| 3.1.17 | DL-local-view | [ISO/IEC 7498-3] |
| 3.1.18 | DL-name | [ISO/IEC 7498-3] |
| 3.1.19 | DL-protocol | [ISO/IEC 7498-1] |

² A newer edition of this standard has been published, but only the cited edition applies.