

# INTERNATIONAL STANDARD

**Industrial communication networks – Fieldbus specifications –  
Part 4-17: Data-link layer protocol specification – Type 17 elements**

(<https://standards.iteh.ai>)

Document Preview

[IEC 61158-4-17:2007](https://standards.iteh.ai/catalog/standards/iec/8764d6a8-7f80-4030-9f15-acacbe1b0395/iec-61158-4-17-2007)

<https://standards.iteh.ai/catalog/standards/iec/8764d6a8-7f80-4030-9f15-acacbe1b0395/iec-61158-4-17-2007>





## THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2007 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland  
Email: [inmail@iec.ch](mailto:inmail@iec.ch)  
Web: [www.iec.ch](http://www.iec.ch)

### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

### About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: [www.iec.ch/searchpub](http://www.iec.ch/searchpub)

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: [www.iec.ch/online\\_news/justpub](http://www.iec.ch/online_news/justpub)

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: [www.electropedia.org](http://www.electropedia.org)

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: [www.iec.ch/webstore/custserv](http://www.iec.ch/webstore/custserv)

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: [csc@iec.ch](mailto:csc@iec.ch)

Tel: +41 22 919 02 11  
Fax: +41 22 919 03 00

[IEC 61158-4-17:2007](http://www.iec.ch/online_news/justpub)

[https://www.iec.ch/online\\_news/justpub](https://www.iec.ch/online_news/justpub)



IEC 61158-4-17

Edition 1.0 2007-12

# INTERNATIONAL STANDARD

---

**Industrial communication networks – Fieldbus specifications –  
Part 4-17: Data-link layer protocol specification – Type 17 elements**

(<https://standards.iteh.ai>)  
Document Preview

[IEC 61158-4-17:2007](https://standards.iteh.ai/catalog/standards/iec/8764d6a8-7f80-4030-9f15-acacbe1b0395/iec-61158-4-17-2007)

<https://standards.iteh.ai/catalog/standards/iec/8764d6a8-7f80-4030-9f15-acacbe1b0395/iec-61158-4-17-2007>

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

PRICE CODE



---

ICS 35.100.20; 25.040.40

ISBN 2-8318-9440-9

## CONTENTS

FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	7
1.1 General.....	7
1.2 Specifications.....	7
1.3 Procedures.....	7
1.4 Applicability.....	7
1.5 Conformance.....	8
2 Normative reference.....	8
3 Definitions.....	8
3.1 Terms and definitions.....	8
3.2 Abbreviations and symbols.....	11
3.3 Conventions.....	11
4 Overview of the DL-protocol.....	12
4.1 General.....	12
4.2 Characteristics of the protocol.....	12
4.3 Data-link layer architecture.....	12
4.4 Services provided by the DLL.....	14
4.5 Network sharing with other protocols.....	15
5 DLPDU-parameter structure and encoding.....	15
5.1 Overview.....	15
5.2 DLPDU common header format.....	16
5.3 DLPDU body format.....	17
6 Local parameters and resources.....	21
6.1 General.....	21
6.2 Parameters and resources related to network structure.....	22
6.3 Parameters and resources to support real-time data transfer.....	23
6.4 Parameters and resources to support the scheduling function.....	24
6.5 Parameters and resources to support the security function.....	25
7 DL-service elements of procedure.....	26
7.1 Unacknowledged unitdata transfer service (UUS).....	26
7.2 Acknowledged unitdata transfer service (AUS).....	26
7.3 Acknowledged sequence of unitdata transfer service (ASS).....	26
7.4 Multipoint unitdata transfer service (MUS).....	27
7.5 Multipoint sequence of unitdata transfer service (MSS).....	27
8 DL-support protocol.....	28
8.1 Transmission scheduling.....	28
8.2 Redundancy.....	29
8.3 DLPDU authentication.....	31
Bibliography.....	32
Table 1 – Conventions used for protocol procedure definitions.....	12
Table 2 – Referenced standards for the layers.....	13
Table 3 – Bit positions.....	16
Table 4 – Common header format.....	17

Table 5 – DLPDU types .....	17
Table 6 – Service subtype and PDU type of DLPDUs .....	18
Table 7 – UUS_DT_PDU .....	18
Table 8 – AUS_DT_PDU .....	19
Table 9 – AUS_RSP_PDU .....	19
Table 10 – ASS_DT_PDU .....	20
Table 11 – ASS_ENQ_PDU .....	20
Table 12 – ASS_RSP_PDU .....	20
Table 13 – MUS_DT_PDU .....	21
Table 14 – MSS_DT_PDU .....	21
Table 15 – Parameters and resources for the network structure .....	22
Table 16 – Ranges of parameters for the network structure .....	23
Table 17 – Parameters and resources real-time data transfer .....	23
Table 18 – Ranges of parameters for real-time data transfer .....	23
Table 19 – Parameters and resources for scheduling function .....	24
Table 20 – Ranges of parameters for scheduling .....	25
Table 21 – Parameters and resources for security function .....	25
Table 22 – Ranges of parameters for security function .....	25
Table 23 – UUS procedure .....	26
Table 24 – AUS procedure .....	26
Table 25 – ASS procedure .....	27
Table 26 – MUS procedure .....	27
Table 27 – MSS procedure .....	28

[IEC 61158-4-17:2007](https://standards.iteh.ai/catalog/standards/iec/8764d6a8-7f80-4030-9f15-acacbe1b0395/iec-61158-4-17-2007)

<https://standards.iteh.ai/catalog/standards/iec/8764d6a8-7f80-4030-9f15-acacbe1b0395/iec-61158-4-17-2007>

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

---

**INDUSTRIAL COMMUNICATION NETWORKS –  
 FIELDBUS SPECIFICATIONS –**
**Part 4-17: Data-link layer protocol specification – Type 17 elements**

## FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.

**NOTE** Use of some of the associated protocol types is restricted by their intellectual-property-right holders. In all cases, the commitment to limited release of intellectual-property-rights made by the holders of those rights permits a particular data-link layer protocol type to be used with physical layer and application layer protocols in Type combinations as specified explicitly in the IEC 61784 series. Use of the various protocol types in other combinations may require permission from their respective intellectual-property-right holders.

IEC draws attention to the fact that it is claimed that compliance with this standard may involve the use of patents as follows, where the [xx] notation indicates the holder of the patent right:

Type 17 and possibly other Types:

PCT Application No. PCT/JP2004/011537	[YEC]	Communication control method
PCT Application No. PCT/JP2004/011538	[YEC]	Communication control method

IEC takes no position concerning the evidence, validity and scope of these patent rights.

The holders of these patent rights have assured IEC that they are willing to negotiate licences under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statement of the holders of these patent rights are registered with IEC. Information may be obtained from:

[YEC]: Yokogawa Electric Corporation  
 2-9-32 Nakacho, Musashino-shi, 180-8750 Tokyo,  
 180-8750 Tokyo,  
 Japan  
 Attention: Intellectual Property & Standardization Center

Attention is drawn to the possibility that some of the elements of this standard may be the subject of patent rights other than those identified above. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61158-4-17 has been prepared by subcommittee 65C: Industrial networks, of IEC technical committee 65: Industrial-process measurement, control and automation.

This first edition and its companion parts of the IEC 61158-4 subseries cancel and replace IEC 61158-4:2003. This edition of this part constitutes a technical addition. This part and its Type 17 companion parts also cancel and replace IEC/PAS 62405, published in 2005.

This edition of IEC 61158-4 includes the following significant changes from the previous edition:

- a) deletion of the former Type 6 fieldbus, and the placeholder for a Type 5 fieldbus data link layer, for lack of market relevance;
- b) addition of new types of fieldbuses;
- c) division of this part into multiple parts numbered -4-1, -4-2, ..., -4-19.

The text of this standard is based on the following documents:

FDIS	Report on voting
65C/474/FDIS	65C/485/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under <http://webstore.iec.ch> in the data related to the specific publication. At this date, the publication will be:

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

NOTE The revision of this standard will be synchronized with the other parts of the IEC 61158 series.

The list of all the parts of the IEC 61158 series, under the general title *Industrial communication networks – Fieldbus specifications*, can be found on the IEC web site.

## INTRODUCTION

This part of IEC 61158 is one of a series produced to facilitate the interconnection of automation system components. It is related to other standards in the set as defined by the “three-layer” fieldbus reference model described in IEC/TR 61158-1.

The data-link protocol provides the data-link service by making use of the services available from the physical layer. The primary aim of this standard is to provide a set of rules for communication expressed in terms of the procedures to be carried out by peer data-link entities (DLEs) at the time of communication. These rules for communication are intended to provide a sound basis for development in order to serve a variety of purposes:

- a) as a guide for implementors and designers;
- b) for use in the testing and procurement of equipment;
- c) as part of an agreement for the admittance of systems into the open systems environment;
- d) as a refinement to the understanding of time-critical communications within OSI.

This standard is concerned, in particular, with the communication and interworking of sensors, effectors and other automation devices. By using this standard together with other standards positioned within the OSI or fieldbus reference models, otherwise incompatible systems may work together in any combination.

**iTeh Standards**  
**(<https://standards.iteh.ai>)**  
**Document Preview**

[IEC 61158-4-17:2007](https://standards.iteh.ai/catalog/standards/iec/8764d6a8-7f80-4030-9f15-acacbe1b0395/iec-61158-4-17-2007)

<https://standards.iteh.ai/catalog/standards/iec/8764d6a8-7f80-4030-9f15-acacbe1b0395/iec-61158-4-17-2007>

## INDUSTRIAL COMMUNICATION NETWORKS – FIELDBUS SPECIFICATIONS –

### Part 4-17: Data-link layer protocol specification – Type 17 elements

#### 1 Scope

##### 1.1 General

The data-link layer provides basic time-critical messaging communications between devices in an automation environment.

This protocol provides communication opportunities to all participating data-link entities

- a) in a cyclic asynchronous manner, sequentially to each of those data-link entities, and
- b) in a synchronous manner, either cyclically or acyclically, according to a pre-established schedule.

The specified protocol also provides means of changing the set of participating data-link entities and of modifying the set of scheduled communications opportunities. When the set of scheduled communications opportunities is null, the distribution of communication opportunities to the participating data-link entities is completely asynchronous.

Thus this protocol can be characterized as one which provides access asynchronously but with a synchronous overlay.

##### 1.2 Specifications

This standard specifies

- a) procedures for the timely transfer of data and control information from one data-link user entity to a peer user entity, and among the data-link entities forming the distributed data-link service provider;
- b) the structure of the fieldbus DLPDUs used for the transfer of data and control information by the protocol of this standard, and their representation as physical interface data units.

##### 1.3 Procedures

The procedures are defined in terms of

- a) the interactions between peer DL-entities (DLEs) through the exchange of fieldbus DLPDUs;
- b) the interactions between a DL-service (DLS) provider and a DLS-user in the same system through the exchange of DLS primitives;
- c) the interactions between a DLS-provider and a Ph-service provider in the same system through the exchange of Ph-service primitives.

##### 1.4 Applicability

These procedures are applicable to instances of communication between systems which support time-critical communications services within the data-link layer of the OSI or fieldbus reference models, and which require the ability to interconnect in an open systems interconnection environment.

Profiles provide a simple multi-attribute means of summarizing an implementation's capabilities, and thus its applicability to various time-critical communications needs.

## 1.5 Conformance

This standard also specifies conformance requirements for systems implementing these procedures. This standard does not contain tests to demonstrate compliance with such requirements.

## 2 Normative reference

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For all other undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61158-3-17, *Industrial communication networks – Fieldbus specifications – Part 3-17: Data-link layer service definition – Type 17 elements*

ISO/IEC 7498 (all parts), *Information technology – Open Systems Interconnection – Basic Reference Model*

ISO/IEC 8802-3, *Information technology – Telecommunications and information exchange between systems – Local and metropolitan area networks - Specific requirements – Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications*

ISO/IEC 10731, *Information technology – Open Systems Interconnection – Basic Reference Model – Conventions for the definition of OSI services*

IEEE Std 802.3ab, *Information technology – Telecommunications and information exchange between systems - Local and metropolitan area networks – Specific requirements – Supplement to Carrier Sense Multiple Access with Collision Detection (CSMA/CD) access method and physical layer specifications – Physical layer parameters and specifications for 1000 Mb/s operation over 4-pair of category 5 balanced copper cabling, type 1000BASE-T*

<https://standards.iteh.ai/IEC/61158-4-17:2007>

<https://www.rfc-editor.org/rfc/rfc1100> Internet Engineering Task Force (IETF), *Request for Comments (RFC): 1100*

RFC 768	<i>User Datagram Protocol</i> (available at < <a href="http://www.ietf.org/rfc/rfc0768.txt">http://www.ietf.org/rfc/rfc0768.txt</a> >)
RFC 791	<i>Internet Protocol</i> (available at < <a href="http://www.ietf.org/rfc/rfc0791.txt">http://www.ietf.org/rfc/rfc0791.txt</a> >)
RFC 792	<i>Internet Control Message Protocol</i> (available at < <a href="http://www.ietf.org/rfc/rfc0792.txt">http://www.ietf.org/rfc/rfc0792.txt</a> >)
RFC 826	<i>Ethernet Address Resolution Protocol</i> (available at < <a href="http://www.ietf.org/rfc/rfc0826.txt">http://www.ietf.org/rfc/rfc0826.txt</a> >)
RFC 894	A standard for the Transmission of IP Datagrams over Ethernet Networks (available at < <a href="http://www.ietf.org/rfc/rfc0894.txt">http://www.ietf.org/rfc/rfc0894.txt</a> >)
RFC 1112	<i>Host Extensions for IP Multicasting</i> (available at < <a href="http://www.ietf.org/rfc/rfc1112.txt">http://www.ietf.org/rfc/rfc1112.txt</a> >)
RFC 2236	<i>Internet Group Management Protocol Version 2</i> (available at < <a href="http://www.ietf.org/rfc/rfc2236.txt">http://www.ietf.org/rfc/rfc2236.txt</a> >)

## 3 Definitions

For the purposes of this document, the following terms and definitions apply.

### 3.1 Terms and definitions

#### 3.1.1 ISO/IEC 10731 terms

- a) (N)-connection
- b) (N)-entity
- c) (N)-layer

- d) (N)-service
- e) (N)-service-access-point
- f) confirm (primitive)
- g) deliver (primitive)
- h) indication (primitive)
- i) request (primitive)
- j) response (primitive)

### 3.1.2 Other terms and definitions

#### 3.1.2.1

##### **bridge**

intermediate equipment that connects two or more segments using a Data Link layer relay function

#### 3.1.2.2

##### **domain**

part of the RTE network consisting of one or two subnetwork(s)

NOTE Two subnetworks are required to compose a dual-redundant RTE network, and each end node in the domain is connected to both of the subnetworks.

#### 3.1.2.3

##### **domain master**

station which performs diagnosis of routes to all other domains, distribution of network time to nodes inside the domain, acquisition of absolute time from the network time master and notification of status of the domain

#### 3.1.2.4

##### **domain number**

numeric identifier which indicates a domain

[IEC 61158-4-17:2007](https://standards.iteh.ai/catalog/standards/iec/8764d6a8-7f80-4030-9f15-acacbe1b0395/iec-61158-4-17-2007)

<https://standards.iteh.ai/catalog/standards/iec/8764d6a8-7f80-4030-9f15-acacbe1b0395/iec-61158-4-17-2007>

#### 3.1.2.5

##### **external bridge**

bridge to which neither internal bridges nor RTE stations are connected directly

#### 3.1.2.6

##### **interface port**

physical connection point of an end node, which has an independent DL-address

#### 3.1.2.7

##### **internal bridge**

bridge to which no routers, external bridges or nodes non-compliant with this specification are connected directly

#### 3.1.2.8

##### **junction bridge**

bridge to which at least one router, external bridge or node non-compliant with this specification, and to which at least one internal bridge or RTE station is connected

#### 3.1.2.9

##### **link**

physical communication channel between two nodes

#### 3.1.2.10

##### **network time master**

station which distributes network time to domain masters