

TECHNICAL SPECIFICATION



**Design of earth electrode stations for high-voltage direct current (HVDC) links –
General guidelines**

(<https://standards.iteh.ai>)
Document Preview

IEC/TS 62344:2013

<https://standards.iteh.ai> / <https://standards.iteh.ai/standards/iec/62344-67dc-4472-a29b-2e135fe2159f/iec-ts-62344-2013>

WITHDRAWN





THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2013 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.
If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

Useful links:

IEC publications search - www.iec.ch/searchpub

The advanced search enables you to find IEC publications by a variety of criteria (reference number, text, technical committee,...).

It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available on-line and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary (IEV) on-line.

Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

IEC TS 62344:2013

<https://standards.iteh.ai/en/standards/iec/62344-2013>

TECHNICAL SPECIFICATION



**Design of earth electrode stations for high-voltage direct current (HVDC) links –
General guidelines**

<https://standards.iteh.ai>
Document Preview

IEC/TS 62344:2013

<https://standards.iteh.ai/standards/iec/62344/62344-2013>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE **XC**

ICS 29.240.99

ISBN 978-2-83220-575-4

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	7
INTRODUCTION.....	9
1 Scope.....	10
2 Normative references.....	10
3 Terms and definitions.....	10
3.22 current-releasing density.....	13
4 System conditions.....	14
4.1 General principles.....	14
4.2 System parameters related to earth electrode design.....	14
4.2.1 Amplitude and duration of the current.....	14
4.2.2 Polarity.....	14
4.2.3 Designed lifespan.....	15
4.2.4 Common earth electrodes.....	15
5 Design of land electrode stations.....	15
5.1 Main technical parameters.....	15
5.1.1 General principles.....	15
5.1.2 Temperature rise.....	16
5.1.3 Earthing resistance.....	16
5.1.4 Step voltage.....	17
5.1.5 Touch voltage.....	17
5.1.6 Current density.....	17
5.1.7 Field intensity in fish ponds.....	18
5.2 Electrode site selection and parameter measurement.....	18
5.2.1 General principles.....	18
5.2.2 Data collection survey.....	18
5.2.3 Distance from converter station (substation).....	18
5.2.4 Environment conditions.....	19
5.2.5 Terrain and landform.....	19
5.2.6 Measurement of soil parameters.....	19
5.2.7 Geological exploration.....	19
5.2.8 Topographical map.....	19
5.2.9 Values selected during design.....	19
5.3 Earth electrode and associated components.....	20
5.3.1 General principles for material selection.....	20
5.3.2 Selection of feeding rods and characteristics.....	20
5.3.3 Chemical and physical properties of petroleum coke.....	21
5.3.4 Current-guiding system.....	21
5.3.5 Bus.....	22
5.3.6 Electrode line monitoring device.....	22
5.4 Electrode arrangement.....	22
5.4.1 General principles.....	22
5.4.2 Filling coke.....	22
5.4.3 Selection of earth electrode shape.....	22
5.4.4 Earth electrode corridor (right of way).....	23
5.4.5 Distance between sub-electrodes in the arrangement.....	23
5.4.6 Burial depth of the earth electrodes.....	23

5.4.7	Segmentation of earth electrodes	24
5.5	Minimum size of earth electrode	24
5.5.1	General principles	24
5.5.2	Total earth electrode length	24
5.5.3	Side length of coke section	24
5.5.4	Diameter of feeding rods	25
5.6	Current guiding system	26
5.6.1	General principles	26
5.6.2	Placement of the current-guiding wire	26
5.6.3	Connection of current-guiding wire	26
5.6.4	Selection of current-guiding wire cross-section	27
5.6.5	Insulation of the current-guiding wire	27
5.6.6	Disconnecting switch	27
5.6.7	Connection of the feeding cable	27
5.6.8	Connection of jumper cables	28
5.6.9	Selection of cable structure	28
5.6.10	Selection of cable cross-section	28
5.6.11	Selection of cable insulation	28
5.6.12	Cable welding position	29
5.6.13	Welding	29
5.6.14	Mechanical protection for cable	29
5.7	Auxiliary facilities	29
5.7.1	Online monitoring	29
5.7.2	Soil treatment	29
5.7.3	Exhaust equipment	30
5.7.4	Fence	30
5.7.5	Marker	30
6	Design of sea electrode station and shore electrode station	30
6.1	Main technical parameters	30
6.1.1	Temperature rise	30
6.1.2	Earthing resistance	30
6.1.3	Step voltage	31
6.1.4	Touch voltage	32
6.1.5	Voltage gradient in water	32
6.1.6	Current density	32
6.2	Electrode site selection and parameter measurement	32
6.2.1	General principles	32
6.2.2	Data collection survey	32
6.2.3	Distance from converter station (substation)	32
6.2.4	Environment conditions	33
6.2.5	Measurement of soil parameters	33
6.3	Earth electrode and associated components	33
6.3.1	General principles for material selection	33
6.3.2	Common feeding rods and characteristics	33
6.3.3	Chemical properties of petroleum coke	34
6.3.4	Current-guiding system	34
6.3.5	Bus	34
6.3.6	Electrode line monitoring device	34
6.4	Electrode arrangement	34

6.4.1	General principles	34
6.4.2	Filling coke	34
6.4.3	Selection of earth electrode shape	34
6.4.4	Segmentation of earth electrodes	35
6.5	Current-guiding system	35
6.5.1	Placement of the current-guiding wire	35
6.5.2	Connection of current-guiding system	35
6.5.3	Selection of cable cross-section	36
6.5.4	Insulation of the current-guiding system	36
6.5.5	Selection of cable structure	36
6.5.6	Mechanical protection for cable	36
6.6	Auxiliary facilities	36
7	Impact on surrounding facilities and mitigation measures	37
7.1	Impact on insulated metallic structures and mitigation measures	37
7.1.1	General principles	37
7.1.2	Relevant limits	37
7.1.3	Mitigation measures	37
7.2	Impact on bare metallic structures	37
7.2.1	General principles	37
7.2.2	Relevant limits	37
7.2.3	Mitigation measures	37
7.3	Impact on the power system (power transformer, grounding network, and surrounding towers)	38
7.3.1	General principles	38
7.3.2	Relevant limits	38
7.3.3	Mitigation measures	38
7.4	Impact on electrified railway	38
7.5	Other facilities (such as greenhouses and water pipes)	39
Annex A (informative)	Basic concepts of earth electrodes	40
Annex B (informative)	Soil parameter measurement method	52
Annex C (informative)	Electrode line design	60
Annex D (informative)	Assessment of measurement method	63
Annex E (informative)	Earth electrode electrical parameter calculation method	67
Annex F (informative)	Thermal time constant	78
Annex G (informative)	Schematic diagram of online monitoring system	80
Annex H (informative)	Calculation method for corrosion of nearby metal structures caused by earth electrodes	81
Annex I (informative)	Calculation method for d.c. current flowing through a.c. transformer neutral near earth electrodes	83
Annex J (informative)	Chemical aspects	86
Annex K (informative)	Simple introduction of shore electrodes	87
Bibliography	89
Figure 1	– Electrode cross-section	22
Figure 2	– Vertical arrangement	23
Figure 3	– Placement of the current-guiding wire	26
Figure 4	– Feeding cable	28

Figure 5 – Resistivity layers with sea or shore electrodes	31
Figure 6 – Sea electrode	34
Figure 7 – Sea bottom electrode with titanium nets	35
Figure 8 – Titanium net	36
Figure 9 – Impact of earth electrodes on a.c. systems (transformer, grounding network, tower)	38
Figure A.1 – HVDC power transmission system structure	40
Figure A.2 – Schematic diagram of the structure of a monopolar earth (sea water) return system	41
Figure A.3 – Schematic diagram of the structure of monopolar metallic return system	41
Figure A.4 – Schematic diagram of the structure of bipolar neutral grounded at both ends	42
Figure A.5 – Schematic diagram of the structure of bipolar neutral grounded at one end	42
Figure A.6 – Schematic diagram of the structure of bipolar neutral line	43
Figure A.7 – Schematic diagram of touch voltage and step voltage	44
Figure A.8 – Schematic diagram of single circular earth electrode	45
Figure A.9 – Axial distribution of step voltage of single circular earth electrode	45
Figure A.10 – 3-D distribution of step voltage of single circular earth electrode	46
Figure A.11 – Schematic diagram of double circular earth electrode	46
Figure A.12 – Axial distribution of step voltage of double circular earth electrode	46
Figure A.13 – 3-D distribution of step voltage of double circular earth electrode	47
Figure A.14 – Schematic diagram of triple circular earth electrode	47
Figure A.15 – Axial distribution of step voltage of triple circular earth electrode	47
Figure A.16 – 3-D distribution of step voltage of triple circular earth electrode	48
Figure B.1 – Equivalent circuit of Wenner method	54
Figure B.2 – Equivalent circuit of Schlumberger method	54
Figure B.3 – Equivalent circuit of dipole-dipole method	55
Figure E.1 – π shape equivalent circuit of an individual earth electrode unit	67
Figure E.2 – Ohm's Law applied to cylinder conductor	68
Figure E.3 – Continuity of axial component of the electric field in the soil and in the conductor	68
Figure E.4 – Spatial division of the earth electrode	68
Figure E.5 – Network for solving axis current	69
Figure E.6 – Horizontally layered soil	71
Figure E.7 – Geometrical structure of a tetrahedron unit	72
Figure E.8 – Structure of a double-circle d.c. earth electrode	76
Figure E.9 – Ground potential and step voltage distribution of a double-circle earth electrode	77
Figure F.1 – Earth electrode temperature rise characteristics	78
Figure G.1 – Schematic diagram of earth electrode online monitoring system	80
Figure H.1 – Calculation of current flowing through a metal pipe	82
Figure I.1 – Schematic diagram of ground resistance network and underground voltage source	83
Figure I.2 – Circuit model for the analysis of d.c. distribution of a.c. systems	85
Figure K.1 – Top view of shore electrode, beach type	87

Figure K.2 – Shore electrode, pond type 87

Table 1 – Composition of iron-silicon alloy electrode..... 21

Table 2 – Chemical composition of the coke after calcination..... 21

Table 3 – Physical properties of petroleum coke used for earth electrodes 21

Table 4 – Electric corrosion characteristics of different materials 26

Table B.1 – Soil (rock) resistivity..... 52

Table B.2 – Soil thermal capacity..... 53

Table B.3 – Soil thermal conductivity 53

Table B.4 – Number of measurement points with different pole distances 56

Table E.1 – Model of soil with two layers 77

Witholdam

iTech Standards
(<https://standards.iteh.ai>)
Document Preview

TS 62344:2013

<https://standards.iteh.ai/standards/iec/62344-2013>

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**DESIGN OF EARTH ELECTRODE STATIONS
FOR HIGH-VOLTAGE DIRECT CURRENT (HVDC) LINKS –
GENERAL GUIDELINES**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. In exceptional circumstances, a technical committee may propose the publication of a technical specification when

- the required support cannot be obtained for the publication of an International Standard, despite repeated efforts, or
- the subject is still under technical development or where, for any other reason, there is the future but no immediate possibility of an agreement on an International Standard.

Technical specifications are subject to review within three years of publication to decide whether they can be transformed into International Standards.

IEC 62344, which is a technical specification, has been prepared by IEC technical committee 115: High-voltage direct current (HVDC) transmission for d.c. voltages above 100 kV.

This technical specification cancels and replaces IEC/PAS 62344 published in 2007. This first edition constitutes a technical revision.

The text of this technical specification is based on the following documents:

Enquiry draft	Report on voting
115/53/DTS	115/64/RVC

Full information on the voting for the approval of this technical specification can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- transformed into an International Standard,
- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

<https://standards.iteh.ai/> TS 62344:2013

<https://standards.iteh.ai/en/standards/iec/60368f45-67dc-4472-a29b-2e135fe2159f/iec-ts-62344-2013>

INTRODUCTION

The high-voltage d.c. earth electrode is an important part of the d.c. power transmission system. It takes on the task of guiding the current into the earth under the monopolar metallic return operation mode, and the unbalanced current under the bipolar operation mode. Further, it secures and provides the reference potential of valve neutral point under the bipolar/ monopolar operation mode, to protect the safe operation of valves.

D.C. earth electrodes include land electrodes, sea electrodes, and shore electrodes. Today, there are around tens of d.c. electrodes in the world. Their influence on the nearby and far away environment is produced when there is d.c. current continuously leaking into the earth through d.c. earth electrodes.

Their influence on the surrounding environment includes:

- a) influence on humans, mainly due to step voltage, touch voltage and transferred voltage;
- b) influence on the electrode itself, mainly reflected by earth temperature rise and corrosion on the electrode;
- c) influence on nearby ponds and organisms in the sea;
- d) influence on the a.c. power system, mainly reflected by the d.c. voltage excursion of transformer neutral point;
- e) influence on buried metallic objects, mainly revealed by the corrosion on buried metallic pipelines, a.c. grounding grids, tower foundations for power transmission lines and armoured cables, etc.

For years, a great deal of experience has been accumulated in the research and design work in many countries, and relevant native standards or enterprise standards have been developed. The aim of this Technical Specification is to develop the design guide for d.c. earth electrodes, on the site selection, material selection, shape, buried depth, adoption of equipment and connection styles, etc. It could be referred to by the specialized employees in different countries, to ensure the safe operation of earth electrode under different modes, control the influence on the environment nearby and the environment far away to the acceptable level, and to reasonably decrease engineering costs.

To ensure this Technical Specification is more scientific, precise and practical, IEC/PAS 62344:2007 is referred to, and some research results obtained in recent years are adopted.

DESIGN OF EARTH ELECTRODE STATIONS FOR HIGH-VOLTAGE DIRECT CURRENT (HVDC) LINKS – GENERAL GUIDELINES

1 Scope

This Technical Specification applies to the design of earth electrode stations for high-voltage direct current (HVDC) links. It is intended to provide necessary guidelines, limits, and precautions to be followed during the design of earth electrodes to ensure safety of personnel and earth electrodes and prevent any significant impact they may exert on d.c. power transmission systems and the surrounding environment.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC/TS 60479-1, *Effects of current on human beings and livestock – Part 1: General aspects*

IEC/TS 61201, *Use of conventional touch voltage limits – Application guide*

IEC 61936-1, *Power installations exceeding 1 kV a.c. – Part 1: Common rules*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

earth electrode

ground electrode (US)

structure with a conductor or a group of conductors embedded in the soil or immersed in sea water, directly or surrounded with a specific conductive medium

EXAMPLE Coke, providing an electric connection to the earth, for transmission of d.c. current from a d.c. system.

[SOURCE: IEC 60050-195:1998, 195-02-01]

3.2

land electrode

earth electrode buried in the ground more than 1 km away from the coastline

3.3 shore electrode

3.3.1

beach electrode

electrode located on the beach inside the waterline (usually less than 1 km away from the waterline), and the active part of the electrode makes contact with the soil or with underground water, but not directly with seawater or pond electrodes

3.3.2**pond electrode**

electrode usually placed outside but within 100 m of the waterline, having electrodes directly in contact with sea water, within a small area which is usually protected against waves and possible ice damage by a breakwater

3.4**sea electrode**

electrode located away from the shoreline at a distance deeper than 100 m into the sea

3.5**electrode station**

whole system which guides current from electrode line to the earth or sea water, usually including, in addition to the electrode itself, the feeding cable, towers, switchgear and necessary auxiliary equipment

3.6**common earth electrode**

earth electrode system, which is composed of a single earth electrode or multiple earth electrodes in parallel, shared by multiple converter stations

Note 1 to entry: It mainly consists of earth electrodes and intertie lines between sub-earth electrodes in different electrode sites.

3.7**electrode site**

site where the earth electrode is located

3.8**electrode line**

overhead line or underground cable used to connect the neutral bus in a converter station to the earth electrode station.

3.9**feeding rod**

earthing conductor buried underground or in the sea for guiding earthing current into the surrounding medium (soil or sea water)

Note 1 to entry: They are the most important devices in an earth electrode station.

3.10**feeding cable**

cable used to guide current from current-guiding wire to feeding rods

3.11**current-guiding wire**

main branch used to conduct current from electrode line (or bus) to feeding cables

3.12**current guiding system**

system used to guide the current from electrode line to feeding rods

Note 1 to entry: It consists of current-guiding wire(s), disconnecting switches, feeding cables and connections.

3.13**jumper cable**

cable used to connect two feeding rods placed at some distance from each other

EXAMPLE At two sides of a channel.

3.14

earth return operation mode

operation mode in the HVDC power transmission system, using d.c. lines and earth (or sea water) as the current loop

3.15

earth return system

series of devices designed and built specifically for earth return operation mode

Note 1 to entry: It mainly consists of the electrode line, earth electrode, current guiding system, and other auxiliary facilities.

3.16

rated current under monopolar mode

current of a converter station at rated power in monopolar (operation) mode

3.17

maximum overload current

maximum current for which the associated d.c. system(s) is designed for monopolar operation for longer than several minutes

3.18

maximum transient overcurrent

average maximum current flowing through the earth electrode for a few seconds when a system disturbance occurs

3.19

unbalanced current

difference of current between two poles during operation of a bipolar d.c. system

Note 1 to entry: For symmetrical bipolar operation mode, the unbalance current flowing can be controlled automatically by the control system within about 1 % of the rated current.

Note 2 to entry: For asymmetrical bipolar operation mode, the current flowing through the earth electrode is the difference in currents between the two poles.

3.20

cathode

electrode capable of emitting negative charge carriers to and/or receiving positive charge carriers from the medium of lower conductivity

Note 1 to entry: The direction of electric current is from the medium of lower conductivity, through the cathode, to the external circuit.

Note 2 to entry: In some cases (e.g. electrochemical cells), the term "cathode" is applied to one or another electrode, depending on the electric operating condition of the device. In other cases (e.g. electronic tubes and semiconductor devices), the term "cathode" is assigned to a specific electrode.

[SOURCE: IEC 60050-151:2001, 151-13-03]

3.21

anode

electrode capable of emitting positive charge carriers to and/or receiving negative charge carriers from the medium of lower conductivity

Note 1 to entry: The direction of electric current is from the external circuit, through the anode, to the medium of lower conductivity.

Note 2 to entry: In some cases (e.g. electrochemical cells), the term "anode" is applied to one or another electrode, depending on the electric operating condition of the device. In other cases (e.g. electronic tubes and semiconductor devices), the term "anode" is assigned to a specific electrode.

[SOURCE: IEC 60050-151:2001, 151-13-02]