

Edition 1.0 2007-12

INTERNATIONAL STANDARD





THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2007 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office 3, rue de Varembé CH-1211 Geneva 20 Switzerland Email: inmail@iec.ch

About the IEC

Web: www.iec.ch

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

■ Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications,

■ IEC Just Published: www.iec.ch/online news/justpub

Stay up to date on all new IEC publications. Just Published details wice a month all new publications released. Available on-line and also by email.

■ Electropedia: <u>www.electropedia.org</u>

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

■ Customer Service Centre: www.iec.ch/webstore/custserv
If you wish to give us your feedback on this publication of need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch Tel.: +41 22 919 02 11

Fax: +41 22 919 03 00



Edition 1.0 2007-12

INTERNATIONAL STANDARD

Industrial communication networks - Fieldbus specifications - Part 6-5: Application layer protocol specification - Type 5 elements



INTERNATIONAL ELECTROTECHNICAL COMMISSION

PRICE CODE

XE

ICS 35.100.70; 25.040.40

ISBN 2-8318-9477-8

CONTENTS

FO	REWORD	
IN	FRODUCTION	9
1	Scope	10
	1.1 General	1
	1.2 Specifications	1
	1.3 Conformance	1
2	Normative references	1
3	Terms, definitions, symbols, abbreviations and conventions	1
	3.1 Terms and definitions from other ISO/IEC standards	1
		1:
		1
		1
	3.5 Conventions used in state machines	1
4	Protocol	19
	4.1 Overview	1
	4.1 Overview	1
	4.3 Transfer syntax	1
	4.4 FAL protocol state machine structure	7
	4.5 SMK state machine	7
	4.7 FAL service protocol machine (FSPM)	
	4.8 Application relationship protocol machines (ARPMs)	
Rih	liography	
sta	idal ds. itch. at 1/1 tanda 18/1 / /6/0 1853c-6514-46/6-9562-3c190a/3dd09/1ec-	61158-6
Eio.	ure 1 – State transition diagram for SMK	7
	ure 2 – State transition diagram of client / server ARPM	
	ure 3 – State transition diagram of the publisher / subscriber ARPM	
Fig	ure 4 – State transition diagram of DMPM	11
	ble 1 – Conventions used for state machines	
Та	ble 2 – Data types	2
Та	ble 3 – Data types	2
Та	ole 4 – APDU header format	2
Та	ble 5 – FDA address use	2
Та	ble 6 – FDA address header field APDUs sent by a client VCR endpoint	2
Та	ble 7 – FDA address header field APDUs sent by a server VCR endpoint	2
	ble 8 – FDA address header field APDUs sent by a publisher VCR endpoint	
	ble 9 – FDA address header field APDUs sent by a report source VCR endpoint	
	ble 10 – APDU trailer fields	
	ble 11 – Request APDU parameters	
	ble 12 – SMK FDA address values	
Та	ble 13 – SMK FDA address values	3

Table 14 – Request APDU parameters	31
Table 15 – SMK FDA address values for SM identify	32
Table 16 – SMK FDA address values for SMK set assignment info request APDUs	32
Table 17 – SMK clear address request APDU parameters	33
Table 18 – SMK FDA address values for SMK set assignment info request APDUs	33
Table 19 – SMK set assignment info request APDU parameters	34
Table 20 – SMK set assignment info response APDU parameters	35
Table 21 – SMK FDA address values for SMK device clear assignment Info APDUs	36
Table 22 – SMK clear assignment info request APDU parameters	36
Table 23 – SMK FDA address values for SMK device annunciation request APDUs	36
Table 24 – SMK device annunciation request APDU parameters	37
Table 25 – Initiate request APDU parameters	40
Table 26 – Initiate response APDU parameters	40
Table 27 – Abort request APDU parameters	
Table 28 – Get response APDU parameters	
Table 29 – Identify response APDU parameters	41
Table 30 – Get OD request APDU parameters	41
Table 31 – Get OD response APDU parameters	42
Table 32 – Initiate put OD request APDU parameters	42
Table 33 – Put OD request APDU parameters	42
Table 34 – Generic initiate download sequence request APDU parameters	43
Table 35 – Generic download segment request APPU parameters	44
Table 36 – Generic terminate down oad sequence request APDU parameters	44
Table 37 – Response APDU parameters	44
Table 38 - Initiate download sequence request APDU parameters99973.dd.999999999	58.455-
Table 39 - Download segment request APDU parameters	45
Table 40 – Download segment response APDU parameters	
Table 41 – Terminate download sequence request APDU parameters	46
Table 42 - Initiate upload sequence request APDU parameters	46
Table 43 – Upload segment request APDU parameters	47
Table 44 – Upload segment response APDU parameters	47
Table 45 – Terminate upload sequence request APDU parameters	47
Table 46 – Request domain download request APDU parameters	48
Table 47 – Request domain upload request APDU parameters	48
Table 48 – Create program invocation request APDU parameters	49
Table 49 – Create program invocation response APDU parameters	49
Table 50 – Delete program invocation request APDU parameters	49
Table 51 – Start request APDU parameters	50
Table 52 – Stop request APDU parameters	50
Table 53 – Resume request APDU parameters	50
Table 54 – Reset request APDU parameters	51
Table 55 – Kill request APDU parameters	51
Table 56 – Read request APDU parameters	51

Table 57 – Read response APDU parameters	52
Table 58 – Read with subindex request APDU parameters	52
Table 59 – Read with subindex response APDU parameters	52
Table 60 – Write request APDU parameters	. 52
Table 61 – Write with subindex request APDU parameters	53
Table 62 – Define variable list request APDU parameters	. 53
Table 63 – Define variable list response APDU parameters	. 53
Table 64 – Delete variable list request APDU parameters	. 54
Table 65 – Information report request APDU parameters	
Table 66 – Information report with subindex request APDU parameters	
Table 67 – Information report on change request APDU parameters	. 55
Table 68 – Information report on change with subindex request APDU parameters	. 55
Table 69 – Event notification request APDU parameters	55
Table 70 – Alter event condition monitoring request APDU parameters	
Table 71 – Acknowledge event notification request APDU parameters	. 56
Table 72 – LAN redundancy diagnostic message request APDU parameters	57
Table 73 – LAN redundancy get information response APDU parameters	
Table 74 – LAN redundancy get statistics request APDU parameters	
Table 75 – Object description header	
Table 76 – Null object	63
Table 77 – Structure of the list of object descriptions	
Table 78 – Structure of a load region in the S-OD.	65
Table 79 – Structure of a function invocation in the DP-OD	
Table 80 - Structure of an event in the S-QD	
Table 81 - Structure of a data type in the ST-OD.514-4675-9567-36190873dd09/icc-6115	675-200
Table 82 – Structure of a data type structure description in the ST-OD	68
Table 83 – Structure of a simple variable in the S-OD	68
Table 84 – Structure of an array in the S-OD	69
Table 85 - Structure of a record in the S-OD	
Table 86 - Structure of a variable list in the DV-OD	71
Table 87 – Common error parameters	72
Table 88 – PI error parameters	72
Table 89 – OD error parameters	72
Table 90 – Error class and error code values	73
Table 91 – SMKPM service primitives	76
Table 92 – SMKPM states	77
Table 93 – SMKPM state table – initialization	
Table 94 – SMKPM state table – receive transitions	
Table 95 – SMKPM state table – internal events	
Table 96 – HseRepeatTimerExpires ()	84
Table 97 – RcvNewNetworkAddress (interface, address)	84
Table 98 – RcvMsg ()	84
Table 99 – SntpSyncLost ()	84

Table	e 100 – AddressToClear (sm_svc)	85
Table	e 101 – AssignmentInfo_Set ()	85
Table	e 102 – ConfigurationSessionActive ()	85
Table	e 103 – DeviceRedundancyState ()	85
Table	e 104 – Devld_Match (sm_svc)	86
Table	e 105 – DuplicateQueryIdMatch (sm_svc)	86
Table	e 106 – DuplicatePdTagDetected ()	86
Table	e 107 - FdaAddressType (sm_svc)	86
	e 108 – IsValid (sm_svc)	
Table	e 109 – NetworkAddressChange (interface, address)	87
Table	e 110 – NumberOfAssignedAddresses ()	87
Table		87
Table	e 112 – PdTag_Match (sm_svc)	87
Table	e 113 – PdTagDeviceIndex_Check (sm_svc)	
Table	e 114 – Query_Match (sm_svc)	88
Table	2 115 – QueryTyne (sm. syc)	88
Table	e 116 – SmCacheEntry (sm. svc)	88
Table	e 117 – Clear_Address (interface_to_clear)	89
	e 118 – Clear_DuplicatePdTagFlag ()	
		89
Table	e 119 – Get_AddlCode () e 120 – New_Address (interface, address)	89
Table	e 121 – Restart_HseRepeatTimer ()	90
	e 122 – Restore_Defaults ()	
	e 123 – Send_SM_CommonErrorRsp (sm_service_type, svc_spec_params)	
	e 124 - Send_SM_RegRspMessage (sm_svc)	
	e 125 – Set_Assignment_Data (sm_svc)	
	e 126 – Set_QuplicatePdTagFlag ()	
	e 127 – SvcType (sm_svc)	
	e 128 – Additional code used by error class and code	
	e 129 – Additional code parameter IDs	
	e 130 – Primitives issued by FSPM to ARPM	
	e 131 – Primitives issued by ARPM to FSPM	
	e 132 – Parameters used with primitives exchanged between FSPM and ARPM	
	e 133 – Client / Server ARPM states	
	e 134 – Client / server ARPM state table – sender transitions	
Table	e 135 – Client / server ARPM state table – receiver transitions	99
Table	e 136 – Primitives issued by FSPM to ARPM	101
	2 137 – Primitives issued by ARPM to FSPM	
	e 138 – Parameters used with primitives exchanged between FSPM and ARPM	
	e 139 – Publisher / subscriber ARPM states	
	e 140 – MulticastARPM state table – sender transitions	
	e 141 – MulticastARPM state table – receiver transitions	
	e 142 – BuildFAL-ErrPDU()	

Table 143 – BuildFAL-ReqRspPDU()	106
Table 144 – GetArepId()	106
Table 145 – ConfigurationArCheckOK()	106
Table 146 – FAL_Pdu_BufferSize()	106
Table 147 – FAL_Pdu_Confirmed()	106
Table 148 – FAL_Pdu_DuplicateMsg ()	106
Table 149 – FAL_Pdu_GetVcrld()	107
Table 150 - FAL_Pdu_InactivityCloseTime()	107
Table 151 – FAL_Pdu_TransmitDelayTime()	
Table 152 – FAL_Pdu_SvcType()	107
Table 153 – FAL Pdu RemoteAddress()	107
Table 154 – FAL Pdu TrailerFields()	107
Table 455 FAL Ddy Convice Charific Devemptors ()	100
Table 156 – FAL_Pdu_Valid()	108
Table 156 – FAL_Pdu_ServiceSpecificParameters() Table 156 – FAL_Pdu_Valid() Table 157 – MaxOutstandingReached() Table 158 – StartInactivityCloseTimer() Table 159 – Primitives issued by ARPM to DMPM	108
Table 158 – StartInactivityCloseTimer()	108
Table 160 – Primitives issued by DMPM to ARPM	109
Table 161 - Parameters used with primitives exchanged between ARPM and DMPM	
Table 162 - Primitives exchanged between the socket model and DMPM	109
Table 163 – Parameters of DMPM/socket model primitives	110
Table 164 – DMPM state descriptions	110
Table 165 – DMPM state table – sender transitions	
Table 166 - DMPM state table - receiver transitions 7007	112
Table 167 - Connection Oriented	1.5.1125-200
Table 168 – GetBufferedData	112
Table 169 – GetConnectionId	
Table 170 – LoadBuffer	113
Table 171 - RemainingBufferSizeCheck	113
Table 172 - StartTransmitDelayTimer	113

INTERNATIONAL ELECTROTECHNICAL COMMISSION

INDUSTRIAL COMMUNICATION NETWORKS – FIELDBUS SPECIFICATIONS –

Part 6-5: Application layer protocol specification - Type 5 elements

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in contormity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

NOTE Use of some of the associated protocol types is restricted by their intellectual-property-right holders. In all cases, the commitment to limited release of intellectual-property-rights made by the holders of those rights permits a particular data-link layer protocol type to be used with physical layer and application layer protocols in Type combinations as specified explicitly in the IEC 61784 series. Use of the various protocol types in other combinations may require permission from their respective intellectual-property-right holders.

International standard IEC 61158-6-5 has been prepared by subcommittee 65C: Industrial networks, of IEC technical committee 65: Industrial-process measurement, control and automation.

This first edition and its companion parts of the IEC 61158-6 subseries cancel and replace IEC 61158-6:2003. This edition of this part constitutes an editorial revision.

This edition of IEC 61158-6 includes the following significant changes from the previous edition:

a) deletion of the former Type 6 fieldbus for lack of market relevance;

- b) addition of new types of fieldbuses;
- c) partition of part 6 of the third edition into multiple parts numbered -6-2, -6-3, ...

The text of this standard is based on the following documents:

FDIS	Report on voting
65C/476/FDIS	65C/487/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under http://webstore.iec.ch in the data related to the specific publication. At this date, the publication will be:

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- · amended.

NOTE The revision of this standard will be synchronized with the other parts of the IEC 61158 series.

The list of all the parts of the IEC 61158 series, under the general title Industrial communication networks – Fieldbus specifications, can be found on the IEC web site.



INTRODUCTION

This part of IEC 61158 is one of a series produced to facilitate the interconnection of automation system components. It is related to other standards in the set as defined by the "three-layer" fieldbus reference model described in IEC/TR 61158-1.

The application protocol provides the application service by making use of the services available from the data-link or other immediately lower layer. The primary aim of this standard is to provide a set of rules for communication expressed in terms of the procedures to be carried out by peer application entities (AEs) at the time of communication. These rules for communication are intended to provide a sound basis for development in order to serve a variety of purposes:

- · as a guide for implementors and designers;
- for use in the testing and procurement of equipment;
- as part of an agreement for the admittance of systems into the open systems environment;
- as a refinement to the understanding of time-critical communications within OSI.

This standard is concerned, in particular, with the communication and interworking of sensors, effectors and other automation devices. By using this standard together with other standards positioned within the OSI or fieldbus reference models, otherwise incompatible systems may work together in any combination.

(https://standaxa.iteh.ai)

Deuxer Peview

https://standards.iteh.aiv/v.tandaxds/xe/0x3853c-6514-467b-9562-3c190a73dd09/iec-61158-6-5-2007

INDUSTRIAL COMMUNICATION NETWORKS – FIELDBUS SPECIFICATIONS –

Part 6-5: Application layer protocol specification – Type 5 elements

1 Scope

1.1 General

The fieldbus Application Layer (FAL) provides user programs with a means to access the fieldbus communication environment. In this respect, the FAL can be wewed as a "window between corresponding application programs."

This standard provides common elements for basic time-critical and non-time-critical messaging communications between application programs in an automation environment and material specific to Type 5 fieldbus. The term "time-critical" is used to represent the presence of a time-window, within which one or more specified actions are required to be completed with some defined level of certainty. Failure to complete specified actions within the time window risks failure of the applications requesting the actions, with attendant risk to equipment, plant and possibly human life.

This standard defines in an abstract way the externally visible behavior provided by the Type 5 fieldbus Application Layer in terms of

- a) the abstract syntax defining the application layer protocol data units conveyed between communicating application entities,
- b) the transfer syntax defining the application layer protocol data units conveyed between communicating application entities,
- c) the application context state machine defining the application service behavior visible between communicating application entities; and
- d) the application relationship state machines defining the communication behavior visible between communicating application entities; and.

The purpose of this standard is to define the protocol provided to

- 1) define the wire-representation of the service primitives defined in IEC 61158-5-5, and
- 2) define the externally visible behavior associated with their transfer.

This standard specifies the protocol of the Type 5 IEC fieldbus Application Layer, in conformance with the OSI Basic Reference Model (ISO/IEC 7498) and the OSI Application Layer Structure (ISO/IEC 9545).

FAL services and protocols are provided by FAL application-entities (AE) contained within the application processes. The FAL AE is composed of a set of object-oriented Application Service Elements (ASEs) and a Layer Management Entity (LME) that manages the AE. The ASEs provide communication services that operate on a set of related application process object (APO) classes. One of the FAL ASEs is a management ASE that provides a common set of services for the management of the instances of FAL classes.

Although these services specify, from the perspective of applications, how request and responses are issued and delivered, they do not include a specification of what the requesting and responding applications are to do with them. That is, the behavioral aspects of the applications are not specified; only a definition of what requests and responses they can send/receive is specified. This permits greater flexibility to the FAL users in standardizing such object behavior. In addition to these services, some supporting services are also defined in this standard to provide access to the FAL to control certain aspects of its operation.

1.2 Specifications

The principal objective of this standard is to specify the syntax and behavior of the application layer protocol that conveys the application layer services defined in IEC 61158-5-5.

A secondary objective is to provide migration paths from previously-existing industrial communications protocols. It is this latter objective which gives rise to the diversity of protocols standardized in IEC 61158-6.

1.3 Conformance

This standard-6 does not specify individual implementations or products, nor does it constrain the implementations of application layer entities within industrial automation systems. Conformance is achieved through implementation of this application layer protocol specification.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61158-3-1, Industrial communication networks - Fieldbus specifications - Part 3-1: Datalink layer service definition - Type 1 elements

IEC 61158-4-1, Industrial communication networks - Fieldbus specifications - Part 4-1: Datalink layer protocol specification - Type 1 elements

IEC 61158-5-5, Industrial communication networks – Fieldbus specifications – Part 5-5: Application layer service definition – Type 5 elements

ISO/IEC 9545, Information technology - Open Systems Interconnection - Application Layer structure

ISO/IEC 7498-1, Information technology – Open Systems Interconnection – Basic Reference Model — Part 1: The Basic Model

ISO/IEC 8824, Information technology – Open Systems Interconnection – Specification of Abstract Syntax Notation One (ASN.1)

ISO/IEC 8825, Information technology – ASN.1 encoding rules: Specification of Basic Encoding Rules (BER), Canonical Encoding Rules (CER) and Distinguished Encoding Rules (DER)

3 Terms, definitions, symbols, abbreviations and conventions

For the purposes of this document, the following definitions apply.

3.1 Terms and definitions from other ISO/IEC standards

3.1.1 Terms and definitions from ISO/IEC 7498-1

- a) abstract syntax
- b) application entity
- c) application process
- d) application protocol data unit
- e) application service element

- f) application entity invocation
- g) application process invocation
- h) application transaction
- i) presentation context
- j) real open system
- k) transfer syntax

3.1.2 Terms and definitions from ISO/IEC 9545

- a) application-association
- b) application-context
- c) application context name
- d) application-entity-invocation
- e) application-entity-type
- f) application-process-invocation
- g) application-process-type
- h) application-service-element
- i) application control service element

3.1.3 Terms and definitions from ISO/IEC 8824

- a) object identifier
- b) type
- c) value
- d) simple type
- e) structured type
- f) component type
- g) tag
- h) Boolean type
- i) true
- j) false
- k) integer type
- I) bitstring type <
- m) octetstring type
- n) null type
- o) sequence type
- p) sequence of type
- q) choice type
- r) tagged type
- s) any type
- t) module
- u) production

3.1.4 Terms and definitions from ISO/IEC 8825

- a) encoding (of a data value)
- b) data value
- c) identifier octets (the singular form is used in this standard)
- d) length octet(s) (both singular and plural forms are used in this standard)
- e) contents octets

3.2 IEC/TR 61158-1 terms

The following IEC/TR 61158-1 terms apply.

3.2.1 application

function or data structure for which data is consumed or produced

3.2.2 application layer interoperability

capability of application entities to perform coordinated and cooperative operations using the services of the FAL