


Edition 1.0 2007-12

INTERNATIONAL STANDARD





THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2007 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office 3, rue de Varembé CH-1211 Geneva 20 Switzerland

Email: inmail@iec.ch Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Rease make sure that you have the latest edition, a corrigenda or an amendment might have been published.

■ Catalogue of IEC publications: <u>www.iec.ch/searchpub</u>

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

■ IEC Just Published: www.iec.ch/online news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

■ Electropedia: <u>www.electropedia.org</u>

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

Customer Service Centre: www.ies.ch/webstore/custserv

If you wish to give us your feedback on this publication of need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch

Tel.: +41 22 919 02 11 Fax: +41 22 919 03 00



Edition 1.0 2007-12

INTERNATIONAL STANDARD

Industrial communication networks - Fieldbus specifications - Part 6-9: Application layer protocol specification - Type 9 elements



INTERNATIONAL ELECTROTECHNICAL COMMISSION

PRICE CODE



CONTENTS

2 3	Scope 1.1 General 1.2 Specifications 1.3 Conformance Normative references Terms, definitions, symbols, abbreviations and conventions	
2	1.2 Specifications 1.3 Conformance Normative references Terms, definitions, symbols, abbreviations and conventions	
2	1.3 Conformance	
2	Normative references Terms, definitions, symbols, abbreviations and conventions	
3	Terms, definitions, symbols, abbreviations and conventions	
	Terms, definitions, symbols, abbreviations and conventions	
	3.1 Terms and definitions from other ISO/IEC standards	
	3.2 IEC/TR 01130-1 tellis	
	3.3 Abbreviations and symbols	
		<i>.</i>
	3.5 Conventions used in state machines	
4	Abstract syntax	
	4.1 FAL-AR PDU abstract syntax	
	4.2. Abstract syntax of DDI Pody	
	4.2 Abstract syntax of PD0B0dy 4.3 Type definitions for ASEs	
	4.4 Abstract syntax of data types	
5	Transfer syntax	
	5.1.1 General	
	5.1.2 Coding rules	
	5.1.2 County rules	
6	5.1.3 Structure of the identification information	
,	AP-Context state machines. 7.1 VCR PM structure.	· · · · · · · · · · · · · · · · · · ·
	7.2 VCR PM state machine	
	FAL service protocol machine (FSPM)	
	8.1 General	
	8.2 FSRM state tables	
	8.3 Functions used by FSPM	
	8.4 Parameters of FSPM/ARPM primitives	
9	Application relationship protocol machines (ARPMs)	
	9.1 AREP mapping to data-link layer	
	9.2 Application relationship protocol machines (ARPMs)	
	9.3 AREP state machine primitive definitions	
	9.4 AREP state machine functions	
10	DLL mapping protocol machine (DMPM)	
	10.1 DMPM States	
	10.2 DMPM state table	
	10.3 Primitives exchanged between data-link layer and DMPM	
	10.4 Functions used by DMPM	
	iography	
ווטוים		

Figure 3 – Coding with identification	30
Figure 4 – Coding without identification	30
Figure 5 – Representation of the value true	30
Figure 6 – Representation of the value false	31
Figure 7 – Coding of data of data type Integer16	31
Figure 8 – Coding of data of data type Unsigned16	32
Figure 9 – Coding of data of data type Floating Point	32
Figure 10 – Coding of data of data type Visible String	33
Figure 11 – Coding of data of data type Octet String	33
Figure 12 – Coding of data of type Date	34
Figure 13 – Coding of data of data type Time-of-day	35
Figure 14 – Coding of data of data type Time-difference	35
Figure 15 – Coding of data of data type Bit String	36
Figure 16 – Coding of data of data type Time-value	36
Figure 17 – Coding of data of user data definitions with identifier	37
Figure 18 – Coding of data of user data definitions without identifier	•
Figure 19 – Coding of ID info for a SEQUENCE	37
Figure 20 – Relationships among protecol magnines and adjacent layers	39
Figure 21 – Relationships among protocol machines and adjacent layers	
Figure 22 – VCR state machine	
Figure 23 – State transition diagram of FSPM	53
Figure 24 – State transition diagram of the QUU ARPM	67
Figure 25 – State transition diagram of QUB ARPM	69
Figure 26 – State fransition diagram of the BNU ARPM	78
Figure 27 – State transition diagram of DMPM	d024/iec-61.158- 86 9-2
Table 1 – Conventions used for state machines	
Table 2 - Coding for Date type	
Table 3 – AR-VCR state machine transactions	
Table 4 – Primitives is sued by FAL-User to VCR PM	51
Table 5 – Primitives issued by VCR PM to FAL-User	
Table 6 – Primitives issued by VCR PM to FSPM	
Table 7 – Primitives issued by FSPM to VCR PM	53
Table 8 – FSPM state table – sender transactions	54
Table 9 – FSPM state table – receiver transactions	
Table 10 – Function SelectArep()	56
Table 11 – Parameters used with primitives exchanged between FSPM and	ARPM56
Table 12 – QUU ARPM states	66
Table 13 – QUU ARPM state table – sender transactions	67
Table 14 – QUU ARPM state table – receiver transactions	68
Table 15 – QUB ARPM states	69
Table 16 – QUB ARPM state table – sender transactions	70
Table 17 – QUB ARPM state table – receiver transactions	71

Table 18 - BNU ARPM states	//
Table 19 – BNU ARPM state table – sender transactions	78
Table 20 – BNU ARPM state table – receiver transactions	80
Table 21 – Primitives issued from ARPM to DMPM	83
Table 22 – Primitives issued by DMPM to ARPM	83
Table 23 – Parameters used with primitives exchanged between ARPM and DMPM	84
Table 24 – Function GetArepId()	85
Table 25 – Function BuildFAS-PDU	85
Table 26 – Function FAS_Pdu_Type	85
Table 27 – Function AbortIdentifier	85
Table 28 – Function AbortReason	85
Table 29 – Function AbortDetail	86
Table 30 – DMPM state descriptions	86
Table 31 – DMPM state table – sender transactions	87
Table 32 – DMPM state table – receiver transactions	89
Table 33 – Primitives exchanged between data-link layer and DMPM	95
Table 34 – Function PickArep	97
Table 35 – Function FindAREP	98
Table 36 – Function LocateQubArep	98
Table 37 – Function SetIdentifier()	98

100 11 8-6-9:2007

https://standards.iteh.ai/____tandards/hc/1_8b3af7-c6c8-4048-b80c-2d8b7d7ed024/iec-61158-6-9-2007

INTERNATIONAL ELECTROTECHNICAL COMMISSION

INDUSTRIAL COMMUNICATION NETWORKS – FIELDBUS SPECIFICATIONS –

Part 6-9: Application layer protocol specification – Type 9 elements

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees, any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC sharl not be held responsible for identifying any or all such patent rights.

NOTE Use of some of the associated protocol types is restricted by their intellectual-property-right holders. In all cases, the commitment to limited release of intellectual-property-rights made by the holders of those rights permits a particular data-link layer protocol type to be used with physical layer and application layer protocols in Type combinations as specified explicitly in the IEC 61784 series. Use of the various protocol types in other combinations may require permission from their respective intellectual-property-right holders.

International Standard IEC 61158-6-9 has been prepared by subcommittee 65C: Industrial networks, of IEC technical committee 65: Industrial-process measurement, control and automation.

This first edition and its companion parts of the IEC 61158-6 subseries cancel and replace IEC 61158-6:2003. This edition of this part constitutes an editorial revision.

This edition of IEC 61158-6 includes the following significant changes from the previous edition:

a) deletion of the former Type 6 fieldbus for lack of market relevance;

- b) addition of new types of fieldbuses;
- c) partition of part 6 of the third edition into multiple parts numbered -6-2, -6-3, ...

The text of this standard is based on the following documents:

FDIS	Report on voting
65C/476/FDIS	65C/487/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under http://webstore.iec.ch in the data related to the specific publication. At this date, the publication will be:

- reconfirmed;
- · withdrawn;
- · replaced by a revised edition, or
- · amended.

NOTE The revision of this standard will be synchronized with the other parts of the IEC 61158 series.

The list of all the parts of the IEC 61158 series, under the general title Industrial communication networks – Fieldbus specifications, can be found on the IEC web site.



INTRODUCTION

This part of IEC 61158 is one of a series produced to facilitate the interconnection of automation system components. It is related to other standards in the set as defined by the "three-layer" fieldbus reference model described in IEC/TR 61158-1.

The application protocol provides the application service by making use of the services available from the data-link or other immediately lower layer. The primary aim of this standard is to provide a set of rules for communication expressed in terms of the procedures to be carried out by peer application entities (AEs) at the time of communication. These rules for communication are intended to provide a sound basis for development in order to serve a variety of purposes:

- as a guide for implementors and designers;
- for use in the testing and procurement of equipment;
- as part of an agreement for the admittance of systems into the open systems environment;
- as a refinement to the understanding of time-critical communications within QSI.

This standard is concerned, in particular, with the communication and interworking of sensors, effectors and other automation devices. By using this standard together with other standards positioned within the OSI or fieldbus reference models, otherwise incompatible systems may work together in any combination.

iTex Syn (a cos (https://standardx.iteh.ai)

Dycurem Preview

https://standards.iteh.ai

tandads/vy/13/05af7-c6c8-4048-b80c-2d8b7d7ed024/iec-61158-6-9-2007

INDUSTRIAL COMMUNICATION NETWORKS – FIELDBUS SPECIFICATIONS –

Part 6-9: Application layer protocol specification – Type 9 elements

1 Scope

1.1 General

The fieldbus Application Layer (FAL) provides user programs with a means to access the fieldbus communication environment. In this respect, the FAL can be viewed as a "window between corresponding application programs."

This standard provides common elements for basic time-critical and non-time-critical messaging communications between application programs in an automation environment and material specific to type 9 fieldbus. The term "time-critical" is used to represent the presence of a time-window, within which one or more specified actions are required to be completed with some defined level of certainty. Failure to complete specified actions within the time window risks failure of the applications requesting the actions, with attendant risk to equipment, plant and possibly human life.

This standard defines in an abstract way the externally visible behavior provided by the Type 9 fieldbus Application Layer in terms of

- a) the abstract syntax defining the application layer protocol data units conveyed between communicating application entities,
- b) the transfer syntax defining the application layer protocol data units conveyed between communicating application entities.
- c) the application context state machine defining the application service behavior visible between communicating application entities; and
- d) the application relationship state machines defining the communication behavior visible between communicating application entities; and.

The purpose of this standard is to define the protocol provided to

- 1) define the wire representation of the service primitives defined in IEC 61158-5-5, and
- 2) define the externally visible behavior associated with their transfer.

This standard specify the protocol of the Type 9 IEC fieldbus application layer, in conformance with the OSI Basic Reference Model (ISO/IEC 7498) and the OSI Application Layer Structure (ISO/IEC 9545).

1.2 Specifications

The principal objective of this standard is to specify the syntax and behavior of the application layer protocol that conveys the application layer services defined in IEC 61158-5-9.

A secondary objective is to provide migration paths from previously-existing industrial communications protocols. It is this latter objective which gives rise to the diversity of protocols standardized in IEC 61158-6.

1.3 Conformance

This standard does not specify individual implementations or products, nor does it constrain the implementations of application layer entities within industrial automation systems.

Conformance is achieved through implementation of this application layer protocol specification.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60559, Binary floating-point arithmetic for microprocessor systems

IEC 61158-3-1, Industrial communication networks – Fieldbus specifications – Rart 3-1: Datalink layer service definition – Type 1 elements

IEC 61158-4-1, Industrial communication networks – Fieldbus specifications – Part 4-7: Data-link layer protocol specification – Type 1 elements

IEC 61158-5-5, Industrial communication networks – Fieldbus specifications – Part 5-5: Application layer service definition – Type 5 elements

IEC 61158-5-9, Industrial communication networks — Fieldbus specifications — Part 5-9: Application layer service definition — Type 9 elements

ISO/IEC 7498-1, Information technology — Open Systems Interconnection — Basic Reference Model — Part 1: The Basic Model

ISO/IEC 8824, Information technology — Open Systems Interconnection — Specification of Abstract Syntax Notation One (ASN.1)

ISO/IEC 8825, Information technology – ASN.1 encoding rules: Specification of Basic Encoding Rules (BER), Canonical Encoding Rules (CER) and Distinguished Encoding Rules (DER)

ISO/IEC 9545, Information technology – Open Systems Interconnection – Application Layer structure

ISO/IEC 10731, Information technology – Open Systems Interconnection – Basic Reference Model – Conventions for the definition of OSI services

3 Terms, definitions, symbols, abbreviations and conventions

For the purposes of this document, the following definitions apply.

3.1 Terms and definitions from other ISO/IEC standards

3.1.1 Terms and definitions from ISO/IEC 7498-1

- a) abstract syntax
- b) application entity
- c) application process
- d) application protocol data unit
- e) application service element
- f) application entity invocation
- g) application process invocation

- h) application transaction
- i) presentation context
- j) real open system
- k) transfer syntax

3.1.2 Terms and definitions from ISO/IEC 9545

- a) application-association
- b) application-context
- c) application context name
- d) application-entity-invocation
- e) application-entity-type
- f) application-process-invocation
- g) application-process-type
- h) application-service-element
- i) application control service element

3.1.3 Terms and definitions from ISO/IEC 8824

- a) object identifier
- b) type
- c) value
- d) simple type
- e) structured type
- f) component type
- g) tag
- h) Boolean type
- i) true
- j) false
- k) integer type
- I) bitstring type
- m) octetstring type
- n) null type
- o) sequence type
- p) sequence of type
- q) choice type
- r) tagged type
- s) any type
- t) module
- u) production

3.1.4 Terms and definitions from ISO/IEC 8825

- a) encoding (of a data value)
- b) data value
- c) identifier octets (the singular form is used in this standard)
- d) length octet(s) (both singular and plural forms are used in this standard)
- e) contents octets

3.2 IEC/TR 61158-1 terms

The following IEC/TR 61158-1 terms apply.

3.2.1 application

function or data structure for which data is consumed or produced

3.2.2 application layer interoperability

capability of application entities to perform coordinated and cooperative operations using the services of the FAL

3.2.3 application object

object class that manages and provides the run time exchange of messages across the network and within the network device

NOTE: Multiple types of application object classes may be defined

3.2.4 application process

part of a distributed application on a network, which is located on one device and unambiguously addressed

3.2.5 application process identifier

distinguishes multiple application processes used in a device

3.2.6 application process object

component of an application process that is identifiable and accessible through an FAL application relationship. Application process object definitions are composed of a set of values for the attributes of their class (see the definition for Application Process Object Class Definition). Application process object definitions may be accessed remotely using the services of the FAL Object Management ASE. FAL Object Management services can be used to load or update object definitions, to read object definitions, and to dynamically create and delete application objects and their corresponding definitions

3.2.7 application process object class

a class of application process objects defined in terms of the set of their network-accessible attributes and services

3.2.8 application relationship

cooperative association between two or more application-entity-invocations for the purpose of exchange of information and coordination of their joint operation. This relationship is activated either by the exchange of application-protocol-data-units or as a result of preconfiguration activities

3.2.9 application relationship application service element

application-service element that provides the exclusive means for establishing and terminating all application relationships

3.2.10 application relationship endpoint

context and behavior of an application relationship as seen and maintained by one of the application processes involved in the application relationship. Each application process involved in the application relationship maintains its own application relationship endpoint

3.2.11 attribute

description of an externally visible characteristic or feature of an object. The attributes of an object contain information about variable portions of an object. Typically, they provide status information or govern the operation of an object. Attributes may also affect the behaviour of an object. Attributes are divided into class attributes and instance attributes

3.2.12 behaviour

indication of how the object responds to particular events. Its description includes the relationship between attribute values and services

3.2.13 class

a set of objects, all of which represent the same kind of system component. A class is a generalisation of the object; a template for defining variables and methods. All objects in a class are identical in form and behaviour, but usually contain different data in their attributes

3.2.14 class attributes

an attribute that is shared by all objects within the same class

3.2.15 class code

a unique identifier assigned to each object class

3.2.16 class specific service

a service defined by a particular object class to perform a required function which is not performed by a common service. A class specific object is unique to the object class which defines it

3.2.17 client

- (a) an object which uses the services of another (server) object to perform a task
- (b) an initiator of a message to which a server reacts, such as the role of an AR endpoint in which it issues confirmed service request APDUs to a single AR endpoint acting as a server

3.2.18 conveyance path

unidirectional flow of APDUs across an application relationship

3.2.19 cyclic

term used to describe events which repeat in a regular and repetitive manner 024/jec-61158-6-9-2007

3.2.20 dedicated AR

AR used directly by the FAL User. On Dedicated ARs, only the FAL Header and the user data are transferred

3.2.21 device

a physical hardware connection to the link. A device may contain more than one node

3.2.22 device profile

a collection of device dependent information and functionality providing consistency between similar devices of the same device type

3.2.23 dynamic AR

AR that requires the use of the AR establishment procedures to place it into an established state

3.2.24 endpoint

one of the communicating entities involved in a connection