

# INTERNATIONAL STANDARD

## NORME INTERNATIONALE



**Arc welding equipment –  
Part 6: Limited duty equipment**

**Matériel de soudage à l'arc –  
Partie 6: Matériel à service limité**

60974-6-2010

<https://standards.iech.org/standards/sst/6/7152aa-cd08-4604-a9df-1c793a77070a/iec-60974-6-2010>



**THIS PUBLICATION IS COPYRIGHT PROTECTED**  
**Copyright © 2010 IEC, Geneva, Switzerland**

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de la CEI ou du Comité national de la CEI du pays du demandeur.

Si vous avez des questions sur le copyright de la CEI ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de la CEI de votre pays de résidence.

IEC Central Office  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland  
Email: [inmail@iec.ch](mailto:inmail@iec.ch)  
Web: [www.iec.ch](http://www.iec.ch)

### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

### About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: [www.iec.ch/searchpub](http://www.iec.ch/searchpub)

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: [www.iec.ch/online\\_news/justpub](http://www.iec.ch/online_news/justpub)

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: [www.electropedia.org](http://www.electropedia.org)

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: [www.iec.ch/webstore/custserv](http://www.iec.ch/webstore/custserv)

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: [csc@iec.ch](mailto:csc@iec.ch)

Tel.: +41 22 919 02 11

Fax: +41 22 919 03 00

### A propos de la CEI

La Commission Electrotechnique Internationale (CEI) est la première organisation mondiale qui élabore et publie des normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

### A propos des publications CEI

Le contenu technique des publications de la CEI est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

- Catalogue des publications de la CEI: [www.iec.ch/searchpub/cur\\_fut-f.htm](http://www.iec.ch/searchpub/cur_fut-f.htm)

Le Catalogue en-ligne de la CEI vous permet d'effectuer des recherches en utilisant différents critères (numéro de référence, texte, comité d'études,...). Il donne aussi des informations sur les projets et les publications retirées ou remplacées.

- Just Published CEI: [www.iec.ch/online\\_news/justpub](http://www.iec.ch/online_news/justpub)

Restez informé sur les nouvelles publications de la CEI. Just Published détaille deux fois par mois les nouvelles publications parues. Disponible en-ligne et aussi par email.

- Electropedia: [www.electropedia.org](http://www.electropedia.org)

Le premier dictionnaire en ligne au monde de termes électroniques et électriques. Il contient plus de 20 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans les langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International en ligne.

- Service Clients: [www.iec.ch/webstore/custserv/custserv\\_entry-f.htm](http://www.iec.ch/webstore/custserv/custserv_entry-f.htm)

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions, visitez le FAQ du Service clients ou contactez-nous:

Email: [csc@iec.ch](mailto:csc@iec.ch)

Tél.: +41 22 919 02 11

Fax: +41 22 919 03 00

# INTERNATIONAL STANDARD

# NORME INTERNATIONALE



**Arc welding equipment –  
Part 6: Limited duty equipment**

**Matériel de soudage à l'arc –  
Partie 6: Matériel à service limité**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

COMMISSION  
ELECTROTECHNIQUE  
INTERNATIONALE

PRICE CODE  
CODE PRIX

W

ICS 25.160.30

ISBN 978-2-88912-265-3

## CONTENTS

FOREWORD.....	6
1 Scope.....	8
2 Normative references.....	8
3 Terms and definitions.....	9
4 Environmental conditions.....	10
5 Tests.....	10
5.1 Test conditions .....	10
5.2 Measuring instruments.....	10
5.3 Conformity of components.....	10
5.4 Type tests .....	10
5.5 Routine tests .....	11
6 Protection against electric shock .....	11
6.1 Insulation .....	11
6.1.1 General.....	11
6.1.2 Clearances.....	11
6.1.3 Creepage distances.....	11
6.1.4 Insulation resistance.....	12
6.1.5 Dielectric strength.....	12
6.2 Protection against electric shock in normal service (direct contact).....	12
6.2.1 Protection provided by the enclosure.....	12
6.2.2 Capacitors.....	12
6.2.3 Automatic discharge of input capacitors.....	13
6.3 Protection against electric shock in case of a fault condition (indirect contact).....	13
6.3.1 Protective provisions .....	13
6.3.2 Isolation of the supply circuit and the welding circuit.....	13
6.3.3 Insulation between windings of the supply circuit and the welding circuit.....	13
6.3.4 Internal conductors and connections .....	13
6.3.5 Additional requirements for plasma cutting systems .....	13
6.3.6 Movable coils and cores.....	13
6.3.7 Touch current in fault condition.....	13
7 Thermal requirements .....	15
7.1 Devices for thermal protection and thermal control .....	15
7.2 Heating test.....	15
7.2.1 Test conditions .....	15
7.2.2 Tolerances of the test parameters.....	15
7.2.3 Rated maximum welding current .....	15
7.2.4 Calculation .....	16
7.3 Temperature measurement .....	16
7.3.1 Measurement condition.....	16
7.3.2 Surface temperature sensor .....	16
7.3.3 Resistance .....	16
7.3.4 Embedded temperature sensor .....	16
7.3.5 Determination of the ambient air temperature.....	16
7.3.6 Recording of temperatures .....	16
7.4 Limits of temperature.....	16

7.4.1	Windings, commutators and slip-rings .....	16
7.4.2	External surfaces .....	17
7.4.3	Other components .....	17
7.5	Loading test .....	17
7.6	Commutators and slip-rings .....	17
8	Thermal control device .....	18
8.1	Construction .....	18
8.2	Location .....	18
8.3	Operation .....	18
8.4	Resetting .....	18
8.5	Operating capacity .....	18
8.6	Indication .....	18
9	Thermal protection .....	19
9.1	Construction .....	19
9.2	Location .....	19
9.3	Operation .....	19
10	Abnormal operation .....	19
10.1	General requirements .....	19
10.2	Stalled fan test .....	20
10.3	Short circuit test .....	20
10.4	Overload test .....	20
11	Connection to the input supply network .....	20
11.1	Input supply .....	20
11.1.1	Supply voltage .....	20
11.1.2	Supply current .....	20
11.1.3	Engine driven welding power source .....	20
11.2	Multi supply voltage .....	21
11.3	Means of connection to the supply circuit .....	21
11.4	Supply circuit terminals .....	21
11.5	Cable anchorage .....	21
11.6	Inlet openings .....	21
11.7	Supply circuit on/off switching device .....	21
11.8	Supply cables .....	21
11.9	Supply coupling device (attachment plug) .....	21
12	Output .....	22
12.1	Rated no-load voltage .....	22
12.1.1	Rated no-load voltage for arc welding power source .....	22
12.1.2	Rated no-load voltage for plasma cutting power source .....	22
12.1.3	Additional requirements .....	23
12.1.4	Measuring circuit .....	23
12.2	Type test values of the conventional load voltage .....	25
12.2.1	Manual metal arc welding with covered electrodes .....	25
12.2.2	Tungsten inert gas .....	25
12.2.3	Metal inert/active gas and flux cored arc welding .....	25
12.2.4	Plasma cutting .....	25
12.2.5	Additional requirements .....	25
12.3	Mechanical switching devices used to adjust output .....	25
12.4	Welding circuit connections .....	25

12.4.1	Protection against unintentional contact .....	25
12.4.2	Location of coupling devices .....	25
12.4.3	Outlet openings.....	25
12.4.4	Marking.....	25
12.4.5	Connections for plasma cutting torches .....	25
12.5	Power supply to external devices.....	25
12.6	Auxiliary power output .....	26
12.7	Welding cables .....	26
13	Control circuits.....	26
14	Hazard reducing device.....	26
15	Mechanical provisions.....	27
15.1	General requirements.....	27
15.2	Enclosure.....	27
15.2.1	Enclosure materials.....	27
15.2.2	Enclosure strength .....	27
15.3	Handling means.....	27
15.4	Drop withstand.....	27
15.5	Tilting stability .....	27
16	Auxiliaries.....	27
16.1	General.....	27
16.2	Wire feeder .....	27
16.2.1	General.....	27
16.2.2	Test conditions .....	27
16.2.3	Thermal requirements.....	27
16.2.4	Protection against unintentional contact .....	27
16.3	Torch.....	28
16.3.1	General.....	28
16.3.2	Test conditions .....	28
16.3.3	Thermal requirements.....	28
16.4	Electrode holder.....	28
16.5	Pressure regulator.....	28
17	Rating plate .....	28
17.1	General requirements.....	28
17.2	Description.....	28
17.3	Contents .....	29
17.4	Tolerances .....	31
18	Adjustment of the output .....	31
19	Instructions and markings.....	31
19.1	Instructions .....	31
19.1.1	General.....	31
19.1.2	Instruction manual.....	32
19.1.3	Safety instructions.....	32
19.2	Markings .....	33
Annex A (informative)	Test probes .....	34
Annex B (informative)	Examples of rating plates .....	35
Annex C (informative)	Symbols-only precautionary label.....	36
Bibliography.....		37

Figure 1 – Measurement of touch current in fault condition .....	14
Figure 2 – Measuring network for weighted touch current .....	14
Figure 3 – Measurement of r.m.s values .....	24
Figure 4 – Measurement of peak values.....	24
Figure 5 – Principle of the rating plate .....	29
Figure A.1 – Test probe 12 of IEC 61032 .....	34
Figure A.2 – Test probe 13 of IEC 61032 .....	34
Figure B.1 – Rating plate.....	35
Figure C.1 – Example of precautionary label for engine driven manual metal arc welding power sourceBibliography .....	36
Table 1 – Temperature limits according to the class of insulation.....	17
Table 2 – Summary of rated no-load voltages.....	23
Table 3 – Hazard reducing device requirements for plasma cutting power source.....	26

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/60974-6-2010>

<https://standards.iteh.ai/catalog/standards/sist/60974-6-2010>

60974-6-2010



# INTERNATIONAL ELECTROTECHNICAL COMMISSION

## ARC WELDING EQUIPMENT –

### Part 6: Limited duty equipment

#### FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60974-6 has been prepared by IEC technical committee 26: Electric welding.

This second edition cancels and replaces the first edition published in 2003. It constitutes a technical revision.

The main significant technical changes with respect to the previous edition are the following:

- extension of the scope;
- amendment of the title;
- touch current at fault condition (see 6.3.7);
- new definition of thermal requirements based two independent devices, one for thermal protection and one for thermal control (see 7.1);
- new definition for thermal performances at 20 °C (see 7.2);
- thermal safety requirements are based on operating temperature for normal condition and maximum temperature in overload condition (see 7.4);



- addition of abnormal operation test for thermal control device (see 10.4);
- new requirement for auxiliaries (see Clause 16);
- new rating plate definition (see Clause 17);
- introduction of new mandatory warning symbols (see 12.1.117.3, Box 17b) and 19.2);
- induced changes due to publication of IEC 60974-1:2005.

The text of this standard is based on the following documents:

FDIS	Report on voting
26/429/FDIS	26/437/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

This standard is to be used in conjunction with IEC 60974-1:2005.

In this standard, the following print types are used:

- *conformity statements: in italic type.*

A list of all the parts in the IEC 60974 series, published under the general title *Arc welding equipment*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

**IMPORTANT – The “colour inside” logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this publication using a colour printer.**

## ARC WELDING EQUIPMENT –

### Part 6: Limited duty equipment

#### 1 Scope

This part of IEC 60974 specifies safety and performance requirements applicable to limited duty arc welding and cutting power sources, and auxiliaries designed for use by laymen. Electrically powered equipment is intended to be connected to the single phase public low-voltage supply system. Engine driven power sources can not exceed output power of 7,5 kVA.

NOTE 1 This equipment is typically used by non-professionals in residential areas.

This part of IEC 60974 is not applicable to arc welding and cutting power sources that require for operation:

- arc striking and stabilizing devices;
- liquid cooling systems;
- gas consoles;
- three-phase input supply;

and which are intended for industrial and professional use only.

This part of IEC 60974 is not applicable to arc welding and cutting power sources and ancillary equipment used in:

- mechanically guided applications;
- submerged arc welding process;
- plasma gouging process;
- plasma welding process;

that are covered by other parts of IEC 60974.

NOTE 2 Power sources, wire feeders, torches and electrode holders designed for industrial and professional use are respectively covered by IEC 60974-1, IEC 60974-5, IEC 60974-7 and IEC 60974-11.

NOTE 3 This part of IEC 60974 does not specify electromagnetic compatibility (EMC) requirements that are given in IEC 60974-10.

#### 2 Normative references

The following normative documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60529, *Degrees of protection provided by enclosures (IP Code)*

IEC 60974-1:2005, *Arc welding equipment – Part 1: Welding power sources*

IEC 60974-5, *Arc welding equipment – Part 5: Wire feeders*

IEC 60974-7, *Arc welding equipment – Part 7: Torches*

IEC 60974-10, *Arc welding equipment – Part 10: Electromagnetic compatibility (EMC) requirements*

IEC 60974-11, *Arc welding equipment – Part 11: Electrode holders*

IEC 61032:1997, *Protection of persons and equipment by enclosure – Probes for verification*

ISO 2503, *Gas welding equipment – Pressure regulators and pressure regulators with flow-metering devices for gas cylinders used in welding, cutting and allied processes up to 300 bar (30 MPa)*

### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60974-1, as well as the following apply:

#### 3.1

##### **touch current**

electric current passing through a human body or through an animal body when it touches one or more accessible parts of an installation or equipment

[IEC 60050-195, Amendment 1:2001, 195-05-21]

#### 3.2

##### **limited duty welding power source**

power source intended for use by a layman

#### 3.3

##### **layman**

operator who does not weld in the performance of his profession and has little or no formal instruction in arc welding

#### 3.4

##### **effective supply current**

##### **$I_{1\text{eff}}$**

value of the effective input current, calculated from the rated maximum supply current ( $I_{1\text{max}}$  in A), the supply current at no-load ( $I_0$  in A) and the rated maximum welding time in intermittent mode ( $\sum t_{\text{ON}}$  in s) at the rated maximum welding current during an uninterrupted time of one hour by the formula:

$$I_{1\text{eff}} = \sqrt{I_{1\text{max}}^2 \times \frac{\sum t_{\text{ON}}}{3600} + I_0^2 \times \left(1 - \frac{\sum t_{\text{ON}}}{3600}\right)}$$

#### 3.5

##### **ON time**

##### **$t_{\text{ON}}$**

period of welding operation as allowed by the thermal control device of the welding power source

#### 3.6

##### **OFF time**

##### **$t_{\text{OFF}}$**

period of non-welding operation as imposed by the thermal control device of the welding power source

### 3.7 rated welding time in 1 h

$$\sum t_{ON}$$

summation of the ON times ( $t_{ON}$ ) at the rated maximum welding current in a 60 min period following the first OFF time ( $t_{OFF}$ )

### 3.8 rated continuous welding time

$$t_{ON(max)}$$

ON time ( $t_{ON}$ ) at the rated maximum welding current before the first OFF time ( $t_{OFF}$ )

## 4 Environmental conditions

Welding power sources and auxiliaries shall be capable of operating when the following environmental conditions prevail:

- a) range of ambient air temperature:  
during operation:  $-10\text{ °C}$  to  $+40\text{ °C}$ ;
- b) relative humidity of the air:  
up to 50 % at  $40\text{ °C}$ ;  
up to 90 % at  $20\text{ °C}$ ;
- c) ambient air, free from abnormal amounts of dust, acids, corrosive gases or substances etc. other than those generated by the welding process;
- d) altitude above sea level up to 1 000 m;
- e) base of the welding power source inclined up to  $10^\circ$ .

Welding power sources and auxiliaries shall withstand storage and transport at an ambient air temperature of  $-20\text{ °C}$  to  $+55\text{ °C}$  without any damage to function and performance.

Welding power source and auxiliaries shall be capable of delivering the rated continuous welding time and the rated welding time in 1 hour at an ambient temperature of  $20\text{ °C}$ .

## 5 Tests

### 5.1 Test conditions

The thermal tests shall be carried out at an ambient temperature of  $20\text{ °C}$ , see tolerances in 7.2.2 e).

Other tests shall be carried out at an ambient air temperature between  $10\text{ °C}$  and  $40\text{ °C}$ .

### 5.2 Measuring instruments

See 5.2 of IEC 60974-1.

### 5.3 Conformity of components

See 5.3 of IEC 60974-1.

### 5.4 Type tests

Unless otherwise specified, the tests in this standard are type tests.

The welding power source shall be tested with any ancillary equipment fitted that could affect the test results.

All type tests shall be carried out on the same welding power source except where it is specified that a test may be carried out on another welding power source.

As a condition of conformity the type tests given below shall be carried out in the following sequence with no drying time between f),g) and h):

- a) general visual inspection, see 3.7 of IEC 60974-1:2005;
- b) insulation resistance, see 6.1.4 (preliminary check);
- c) enclosure, see 15.2;
- d) handling means, see 15.3;
- e) drop withstand, see 15.4;
- f) protection provided by the enclosure, see 6.2.1;
- g) insulation resistance, see 6.1.4;
- h) dielectric strength, see 6.1.5;
- i) visual inspection, see 3.7 of IEC 60974-1:2005.

The other tests included in this standard and not listed in 5.4 shall be carried out in any convenient sequence.

## 5.5 Routine tests

All routine tests shall be carried out on each welding power source. The following sequence is recommended:

- a) visual inspection, see 3.7 of IEC 60974-1:2005;
- b) continuity of the protective circuit, see 10.4.2 of IEC 60974-1:2005;
- c) dielectric strength, see 6.1.5;
- d) no-load voltage
  - 1) rated no-load voltage, see 12.1; or
  - 2) for plasma cutting power source, rated reduced no-load voltage, see 13.2 of IEC 60974-1:2005;
- e) test to ensure rated minimum and maximum output values in accordance with 15.4 b) and 15.4 c) of IEC 60974-1:2005. The manufacturer may select conventional load, short circuit load or other test conditions;

NOTE In short circuit and other test condition, the output values may differ from conventional load values.

## 6 Protection against electric shock

### 6.1 Insulation

#### 6.1.1 General

See 6.1.1 of IEC 60974-1:2005.

#### 6.1.2 Clearances

See 6.1.2 of IEC 60974-1:2005.

#### 6.1.3 Creepage distances

See 6.1.3 of IEC 60974-1:2005.

#### **6.1.4 Insulation resistance**

See 6.1.4 of IEC 60974-1:2005.

#### **6.1.5 Dielectric strength**

See 6.1.5 of IEC 60974-1:2005.

### **6.2 Protection against electric shock in normal service (direct contact)**

#### **6.2.1 Protection provided by the enclosure**

##### **6.2.1.1 General**

Welding power sources shall have a minimum degree of protection of IP21S using IEC 60529 test procedures and conditions.

Remote controls for welding power sources shall have a minimum degree of protection of IP2X using IEC 60529 test procedures and conditions.

##### **6.2.1.2 Protection against ingress of water**

Adequate drainage shall be provided by the enclosure. Retained water shall not interfere with the correct operation of the equipment or impair safety.

*Conformity shall be checked as follows:*

*A welding power source shall be subjected to the appropriate water test without being energized. Immediately after the test, the welding power source shall be moved to a safe environment and subjected to the insulation resistance and dielectric strength tests.*

*Adequate drainage of the enclosure shall be checked by visual inspection.*

##### **6.2.1.3 Side and top enclosure openings**

The enclosure shall be such that a 50 mm long test pin cannot be inserted from all sides except the underside to touch:

- a) live parts of the input circuit or
- b) in the case of Class II welding power sources, any metal part which is separated from live parts of the input circuit by basic insulation.

*Conformity shall be checked with test probe 12 of IEC 61032:1997 (see Figure A.1).*

##### **6.2.1.4 Bottom enclosure openings**

The enclosure shall be such that a 15 mm long test pin cannot be inserted from the underside to touch:

- a) live parts of the input circuit and
- b) in the case of Class II welding power sources, any metal part which is separated from live parts of the input circuit by basic insulation.

*Conformity shall be checked with test probe 13 of IEC 61032:1997 (see Figure A.2).*

#### **6.2.2 Capacitors**

See 6.2.2 of IEC 60974-1:2005.

### 6.2.3 Automatic discharge of input capacitors

See 6.2.3 of IEC 60974-1:2005.

## 6.3 Protection against electric shock in case of a fault condition (indirect contact)

### 6.3.1 Protective provisions

See 6.3.1 of IEC 60974-1:2005.

### 6.3.2 Isolation of the supply circuit and the welding circuit

See 6.3.2 of IEC 60974-1:2005.

### 6.3.3 Insulation between windings of the supply circuit and the welding circuit

See 6.3.3 of IEC 60974-1:2005.

### 6.3.4 Internal conductors and connections

See 6.3.4 of IEC 60974-1:2005.

### 6.3.5 Additional requirements for plasma cutting systems

See 6.3.5 of IEC 60974-1:2005.

### 6.3.6 Movable coils and cores

See 6.3.6 of IEC 60974-1:2005.

### 6.3.7 Touch current in fault condition

The weighted touch current shall not exceed 7 mA peak in the case of external protective conductor failure or disconnection.

*Conformity shall be checked using the measuring circuit as shown in Figure 1 and Figure 2 under the following conditions:*

- a) *the welding power source is:*
  - *isolated from the ground plane;*
  - *supplied by the highest rated supply voltage;*
  - *not connected to the protective earth except through measurement components;*
- b) *the output circuit is in the no-load condition;*
- c) *interference suppression capacitors shall not be disconnected.*

NOTE Caution! A qualified person should perform this test. The protective conductor is disabled for this test.