TECHNICAL REPORT



First edition 1994-12-15

Information technology — Telecommunications and information exchange between systems — Local and metropolitan area networks — Specific requirements — (standards.iteh.ai) Part 1:

Overviewr of 2 Jocal Area Network Standards https://standards.iteh.ai/catalog/standards/sist/406727c1-ce4f-4695-9b29-41d2aef6657e/iso-iec-tr-8802-1-1994

> Technologies de l'information — Télécommunications et échange d'information entre systèmes — Réseaux locaux et métropolitains — Exigences spécifiques —

Partie 1: Vue d'ensemble sur les normes de réseaux locaux



Reference number ISO/IEC TR 8802-1:1994(E)

ISO/IEC TR 8802-1:1994(E)

Contents

Page

1. Scope	
2. Normative References	2
3. Abbreviations	
4. Local Area Network Technologies	
4.1. Introduction	
4.2. The LAN Technologies	4
4.2.1. CSMA/CD	4
4.2.2. Token-passing Bus	4
4.2.3. Token-passing Ring	
4.2.4. Distributed Queue Dual Bus	5
4.2.5. Slotted Ring	5
4.2.6. Fibre Distributed Data Interface	ANDARD PREVIEW
4.3. Cabling Aspects (Sta	andards.iteh.ai)
5. Data Link Layer	6
5.1. Introduction	<u>ISO/IEC TR 8802-1:1994</u> 6
https://standards.iteh.ai 5.2. Provision and Support of the Data Link Lav	/catalog/standards/sist/406727c1-ce4f-4695-9b29- yet/Service
6. Medium Access Control Sublayer	
6.1. Introduction	6
6.2. Provision and Support of the MAC Service	6
6.2.1. Connectionless-mode Service	6
6.2.2. Acknowledged Connectionless-mode	Service
6.3. 48-Bit MAC Address Format	7
6.4. Standard Group MAC Addresses	7
7. Logical Link Control Sublayer	
7.1. Provision and Support of the LLC Services	
7.1.1. LLC Type 1 Connectionless-mode Op	peration8
7.1.2. LLC Type 2 Connection-mode Operat	tion8
7.1.3. LLC Type 3 Acknowledged Connection	onless-mode Operation
7.2. Logical Link Control Addresses	8

© ISO/IEC 1994 All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office • Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

© ISO/IEC

ISO/IEC TR 8802-1:1994(E)

8. Internetworking	9
8.1. Transparent Bridging	9
8.2. Source Routing	9
8.3. Source Routing Transparent Architecture	9
9. System Load Protocol	9
10. The Use of PICS Proforma	
11. Management	
Annex A The Numbering Scheme for LAN/MAN	International Standards11

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/IEC TR 8802-1:1994 https://standards.iteh.ai/catalog/standards/sist/406727c1-ce4f-4695-9b29-41d2aet6657e/iso-iec-tr-8802-1-1994

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

The main task of technical committees is to prepare International Standards, but in exceptional circumstances a technical committee may propose the publication of a Technical Report of one of the following types:

- -- type 1, when the required support cannot be obtained for the publication of an International Standard, despite repeated efforts;
- type 2, when the subject is still under technical development or where for any other reason there is the future but not immediate possibility of an agreement on an International Standard; standa
- type 3, when a technical committee has collected data of a different kind from that which is normally published as an International Standard ("state of the art", for example). https://standards.iteh.ai/catalog/standards/sist/406727c1-ce4f-4695-9b29-41d2aef6657e/iso-iec-tr-8802-1-1994

Technical Reports of types 1 and 2 are subject to review within three years of publication, to decide whether they can be transformed into International Standards. Technical Reports of type 3 do not necessarily have to be reviewed until the data they provide are considered to be no longer valid or useful.

ISO/IEC TR 8802-1, which is a Technical Report of type 3, was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 6, *Telecommunications and information exchange between systems*.

ISO/IEC 8802 consists of the following parts, under the general title Information technology — Telecommunications and information exchange between systems — Local and metropolitan area networks — Specific requirements:

- Part 1: Overview of Local Area Network Standards [Technical Report]
- Part 2: Logical link control
- Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications
- Part 4: Token-passing bus access method and physical layer specifications
- Part 5: Token ring access method and physical layer specifications
- Part 6: Distributed Queue Dual Bus (DQDB) access method and physical layer specifications
- Part 7: Slotted ring access method and physical layer specification

Introduction

This technical report introduces the set of International Standards produced to facilitate the interconnection of information processing systems connected to Local Area Networks (LAN). The LAN is a shared-medium peer-to-peer communications network that broadcasts information for all end systems to receive. As a consequence it does not inherently provide privacy. The LAN enables end system communication directly using a common physical medium on a point-to-point basis without the involvement of any intermediate system.

This technical report provides a source of reference to all International Standards that relate to local area networks; specifically the ISO/IEC 8802 technologies and FDDI.

(standards.iteh.ai)

ISO/IEC TR 8802-1:1994 https://standards.iteh.ai/catalog/standards/sist/406727c1-ce4f-4695-9b29-41d2aef6657e/iso-iec-tr-8802-1-1994

and the spatial sectors.

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/IEC TR 8802-1:1994 https://standards.iteh.ai/catalog/standards/sist/406727c1-ce4f-4695-9b29-41d2aef6657e/iso-iec-tr-8802-1-1994 Information technology — Telecommunications and information exchange between systems — Local and metropolitan area networks — Specific requirements —

Part 1:

Overview of Local Area Network Standards

iTeh STANDARD PREVIEW

(standards.iteh.ai)

1. Scope

ISO/IEC TR 8802-1:1994

This technical report provides an introduction to the set of International Standards which describe local area networks, specifically those which make use of the 48-bit address format.

In addition the MAC Service definition will be central to the operation of these technologies both as service providers and service users.

The scope of this Technical Report is therefore limited to those International Standards which describe processes and procedures resident in the Data Link and Physical Layers of the OSI Basic Reference Model and can be said to relate to local area networks.

This technical report does not itself describe new Service or Protocol definitions. Its intent is to set the context for local area networks which include both the International Standards describing FDDI and the technologies described by the set of ISO/IEC 8802 International Standards.

2. References

NOTE - It was agreed in October 1993 to revise the existing numbering scheme of LAN/MAN International Standards within ISO/IEC JTC1 to provide alignment with the numbering scheme used by IEEE for their LAN/MAN Standards. The process of introducing the new scheme for new International Standards and the renumbering of existing International Standards is on-going. Annex A describes the new numbering scheme in detail and indicates how its implementation will proceed.

ISO 7498 : 1984, Information processing systems - Open Systems Interconnection - Basic Reference Model.

ISO 7498-3: 1989, Information processing systems - Open Systems Interconnection - Part 3: Naming and addressing.

ISO/IEC 8802-2 : 1994, Information technology - Telecommunications and information exchange between end systems - Local and metropolitan area networks - Specific requirements - Part 2: Logical link control.

ISO/IEC 8802-2/AM 5 : 1991, Information technology - Telecommunications and information exchange between systems - Local and metropolitan area network - Guidelines for bridged LAN source routeing operation by end systems.

ISO/IEC 8802-3: 1993, Information processing systems - Local and metropolitan area networks - Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specification.

ISO/IEC 8802-4 : 1990, Information processing systems - Local and metropolitan area networks - Part 4: Token-passing bus access method and physical layer specification.

ISO/IEC 8802-5 : $-^{1}$, Information processing systems - Local and metropolitan area networks - Part 5: Token ring access method and physical layer specification.

ISO/IEC 8802-6: 1993, Information processing systems - Local and metropolitan area networks - Part 6 Distributed queue dual bus (DQDB) access method and physical layer specification

https://standards.iteh.ai/catalog/standards/sist/406727c1-ce4f-4695-9b29-ISO 8802-7 : 1991, Information technology - Local and metropolitan area networks₄ Part 7: Slotted ring access method and physical layer specification.

ISO 9314-1 : 1989, Information processing systems - Fibre-Distributed Data Interface (FDDI) - Token ring physical layer protocol (PHY).

ISO 9314-2 : 1989, Information processing systems - Fibre-Distributed Data Interface (FDDI) - Token ring medium access control (MAC).

ISO/IEC 9314-3: 1990, Information processing systems - Fibre-Distributed Data Interface (FDDI) - Physical layer medium dependent (PMD).

ISO/IEC CD 9314-6 : 1994, Information Processing system - Fibre-Distributed Data Interface (FDDI) - Station management (SMT).

ISO/IEC 15802-1 : $-^{1}$, Information technology - Telecommunications and information exchange between systems - Local and metropolitan area network - Common specifications - Medium access control service definition. (Formerly published as ISO/IEC 10039)

ISO/IEC 10038 : 1993, Information technology - Telecommunications and information exchange between systems - Local and metropolitan area network - MAC Bridging. (In the future to be published as ISO/IEC 15802-3)

ISO/IEC 15802-4 : 1994, Information technology - Telecommunications and information exchange between systems - Local and metropolitan area network - Common specifications - LAN system load protocol.

ISO/IEC 10742 : 1994, Information technology - Telecommunications and information exchange between systems - Elements of management information related to OSI Data Link layer standards.

ISO/IEC TR 11802-1 : 1994, Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Technical reports and guidelines - The structure and coding of logical link control addresses in Local Area Networks. (Formerly published as ISO/IEC TR10178)

ISO/IEC TR 11802-2 : 1994, Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Technical reports and guidelines - Standard Group MAC Addresses. (Formerly published as ISO/IEC TR 10735)

ISO/IEC 8886 : 1992 | ITU-T Recommendation X.212, Information technology - Telecommunications and information exchange between end systems - Data Link service definition for Open Systems Interconnection.

ISO/IEC 11575 : 1994, Information technology - Telecommunications and information exchange between end systems - Provision and support of the OSI Data Link service.

ISO/IEC 10165-4 : 1992, Information technology - Open systems interconnection - Status of management information - Part 4 : Guidelines for the definition of management objects.

ISO/IEC TR 9577 : 1993, Information Technology - Telecommunications and information exchange between systems - Protocol identification in the network layer.

ISO/IEC 11801 : ___1, Information technology - Generic cabling for customer premises cabling.

3. Abbreviations and ards.iteh.ai)

The following abbreviations are used in this Technical Report.

https://stan	dards.iteh.ai/catalog/standards/sist/406727c1-ce4f-4695-9b2
CSMA/CD	Carrier Sense Multiple Access with Collision Detection
DLS	Data Link Service
DQDB	Distributed Queue Dual Bus
DSAP	Destination Service Access Point
FDDI	Fibre Distributed Data Interface
LAN	Local Area Network
LLC	Logical Link Control
MAC	Media Access Control
MAN	Metropolitan Area Network
PHY	Physical Layer
PICS	Protocol Implementation Conformance Statement
PMD	Physical Layer Medium Dependent
SMT	Station Management
SNAP	Sub-network Access Protocol
SSAP	Source Service Access Point

4. Local Area Network Technologies

4.1. Introduction

The local area network technologies considered in this Technical Report are shown in Table 1.

1) To be published.

and the second		
LAN Technology	Data Transmission Rate	International Standard
CSMA/CD	1Mbit/s / 10Mbit/s	ISO/IEC 8802-3
Token-passing Bus	5Mbit/s / 10Mbit/s	ISO/IEC 8802-4
Token-passing Ring	4Mbit/s / 16Mbit/s	ISO/IEC 8802-5
DQDB	no upper limit defined	ISO/IEC 8802-6
Slotted Ring	10Mbit/s	ISO/IEC 8802-7
FDDI	100Mbit/s	ISO/IEC 9314 -1 -2 -3 (-6)

Table 1 - Local area network technologies and their related International Standards

These International Standards are organised along the architectural lines of the OSI Basic Reference model, and in the case of the 8802 LANs into the medium-dependent aspects of the Physical Layer (PHY) and the formats and protocols used by the particular media access control sublayer (MAC).

Figure 1 shows the relationship and dependencies of the various technologies within this overall architecture. This family of International Standards deals with the physical and data link layers as defined by the Open Systems Interconnection Reference Model. It comprises a set of medium access technologies and associated physical media, each appropriate for particular applications or system objectives.



Figure 1 - Relationship of family of International Standards for Local Area Networks

4.2. The LAN Technologies

LANs cover a wide variety of Physical Layer International Standards, physical media, and methods of media access control. The following is a brief synopsis for each of the LAN technologies identified in Table 1, however the reader is referred to the International Standard documents (see Clause 2) for the precise detail for each of the LAN technologies.

4.2.1. CSMA/CD

This form of LAN technology, Carrier Sense Multiple Access with Collision Detection, controls access to the medium by means by which two or more stations share a common transmission medium. To transmit, a station waits (defers) for a quiet period on the medium (that is, no other station is transmitting) and then sends the intended message in bit-serial form. If, after initiating a transmission, the message collides with that of another station, then each transmitting station intentionally sends a few additional bytes to ensure propagation of the collision throughout the system. The station then remains silent for a random amount of time (backoff) before attempting to transmit again. The CSMA/CD LAN technology is defined for use on 50 ohm coaxial cable (10BASE5 and 10BASE2), on unshielded twisted pair (10BASE-T), and on fibre optic cable (FOIRL and 10BASE-F).

4.2.2. Token-passing Bus

This form of LAN technology controls access to the medium through the use of a bus transmitted token which allows the holder to transmit information onto the bus. The token bus LAN technology is defined for use on broadband coaxial cable, on baseband coaxial cable, and on fibre optic cable.

4.2.3. Token-passing Ring

In a token-passing ring, stations are serially connected to form a logical ring over which data and control information is transmitted and received.

Access to this ring is controlled by a signalling sequence referred to as the "token" which circulates around the ring from station to station.

A station desiring to transmit waits until it receives a token. The station changes the token to a start-ofmessage, transmits its message and, upon completion of the message, releases a new token for use by other stations on the ring.

Token ring is defined for operation on shielded and unshielded twisted pair medium at data rates of 4 and 16 Mbps. In addition, token ring may operate using fibre optic cable.

4.2.4. Distributed Queue Dual Bus

DQDB is defined to have the capability to work over the local area and to interoperate with the other local area network technologies. In particular DQDB has the capability to use the 48-bit MAC address format and for that reason it is included in this Overview.

However, DQDB is more often encountered in the Metropolitan Area and it introduces the concept of the Metropolitan Area Network (MAN) where the development of a high speed technology to support connectionless data services is required. Because of the differing environments in which the DQDB MAN will be utilised, a variety of Physical Layer protocols are required. Physical Layer protocols which make use of existing underlying transmission standards have been defined. However it is intended that all Physical Layer specifications (PHY) will be based upon a common framework. 41d2ae1665/e160-1ec-tr-8802-1-1994

4.2.5. Slotted Ring

This form of LAN technology controls access to the medium through an entity known as a repeater. The repeater entity encodes and decodes mini packets during the process of transmission and receipt between the end station and the medium. The logical topology of the LAN is a ring which may be implemented as a physical star. The medium is defined as unscreened twisted pair; two pairs being used to carry a single signal with a link between end stations limited to 100m in length. A single subnet may support up to 254 end stations with a ring circumference of 4 km.

4.2.6. Fibre Distributed Data Interface

The Physical Medium Dependent (PMD) provides the digital baseband channel for point to point communication between nodes on the FDDI network. It provides all services necessary to transport a suitably coded digital bit stream. The specific definition and characterisation may be found in ISO/IEC 9314-3.

The Physical Layer Protocol (PHY) provides the connection between the PMD and the Data Link Layer (the MAC). It provides clock synchronisation with the upstream data stream and provides the encoding and decoding of symbols, and the delineation of symbol boundaries as required for the transmission of information to or from higher layers. The specific definitions and characterisations may be found in ISO 9314-1.

4.3. Cabling Aspects

For the implementation of the LAN applications mentioned in Table 1, an application independent solution has been developed in ISO/IEC 11801. The document provides for the generic cabling of customer premises, supporting all major applications. The specific definitions and characterisations may be found in this document.