



SLOVENSKI STANDARD

SIST EN 2817:2010

01-januar-2010

5 YfcUj H_U!>Y_c: 9!DA % \$&fL) 7fB]7 i % !) L! DfYHJ Ybc g HJ]bc YY_hcXc!
bUf Ybc j hcd]i]b i f Ybc ! DU]W nUc VXY Uj c ! UU]8 ®&\$\$'a a !Fa - %\$+\$'ADU

DEA[•] æ&^Á|^á• ÁEÜc^|ÁØÉÚT FÍ EGÁYÍ ÓÍ| þ ad^ FÍ EÍ DÆA[} • { æ| ^Á|^&d[å^Á^{ ^|cå
EÅU[| cí } Á^æ^å Áø åÁ|^&q; åæç } Á^æ^å ÁEÓæ ÁF | Á æ@ q; æ* ÁEæ{ | ÁØÁnGEEÁ { ÁEÜ{ Á
FÉI €AT Uæ

RESTAURANT REVIEW (standard Irish.ai)

SIST EN 2817-2010
https://standards.bipb.ca/en/standards/sist/c5cc4acc-282b-4383-800f-
{ AEEA{ ÁFEE{ Uæ

Ta slovenski standard je istoveten z: EN 2817:2009

ICS:

49.025.10 Jekla

Steels

SIST EN 2817:2010

en,de

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

SIST EN 2817:2010

<https://standards.iteh.ai/catalog/standards/sist/e5c8c4ee-282b-4485-80a6-8c3e8e73c596/sist-en-2817-2010>

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

EN 2817

November 2009

ICS 49.025.10

English Version

**Aerospace series - Steel FE-PM1802 (X5CrNiCu15-5) -
 Consumable electrode remelted - Solution treated and
 precipitation treated - Bar for machining - a or D ≤ 200 mm - Rm
 ≥ 1 070 MPa**

Série aérospatiale - Acier FE-PM1802 (X5CrNiCu15-5) -
 Refondu à l'électrode consommable - Mis en solution et
 vieilli - Barres pour usinage - a ou D ≤ 200 mm - Rm ≥ 1
 070 MPa

Luft- und Raumfahrt - Stahl FE-PM1802 (X5CrNiCu15-5) -
 Mit selbstverzehrender Elektrode umgeschmolzen -
 Lösungsgeglüht und ausgelagert - Stangen zur spanenden
 Bearbeitung - a oder D ≤ 200 mm - Rm ≥ 1 070 MPa

This European Standard was approved by CEN on 8 August 2009.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
 COMITÉ EUROPÉEN DE NORMALISATION
 EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

Foreword

This document (EN 2817:2009) has been prepared by the Aerospace and Defence Industries Association of Europe - Standardization (ASD-STAN).

After enquiries and votes carried out in accordance with the rules of this Association, this Standard has received the approval of the National Associations and the Official Services of the member countries of ASD, prior to its presentation to CEN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by May 2010, and conflicting national standards shall be withdrawn at the latest by May 2010.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

**Get STANDARD PREVIEW
(standards.iteh.ai)**

SIST EN 2817:2010

<https://standards.iteh.ai/catalog/standards/sist/e5c8c4ee-282b-4485-80a6-8c3e8e73c596/sist-en-2817-2010>

Introduction

This European Standard is part of the series of EN metallic material standards for aerospace applications. The general organization of this series is described in EN 4258.

This standard has been prepared in accordance with EN 4500-5.

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 2817:2010

<https://standards.iteh.ai/catalog/standards/sist/e5c8c4ee-282b-4485-80a6-8c3e8e73c596/sist-en-2817-2010>

1 Scope

This European Standard specifies the requirements relating to:

Steel FE-PM1802 (X5CrNiCu15-5)
 Consumable electrode remelted
 Solution treated and precipitation treated
 Bar for machining
 a or $D \leq 200$ mm
 $R_m \geq 1\,070$ MPa

for aerospace applications.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 2043, *Aerospace series — Metallic materials — General requirements for semi-finished product qualification (excluding forgings and castings)*¹⁾

The STANDARD PREVIEW

EN 4258, *Aerospace series — Metallic materials — General organization of standardization — Links between types of EN standards and their use*

EN 4436, *Aerospace series — Steel — Test methods — Determination of δ ferrite content*¹⁾
<https://standards.teh.ai/catalog/standards/sist/e5c8c4ee-282b-4485-80a6-863e8e73-596/sist/en-2817-2010>

EN 4500-5, *Aerospace series — Metallic materials — Rules for drafting and presentation of material standards — Part 5: Specific rules for steels*¹⁾

EN 4700-002, *Aerospace series — Steel and heat resisting alloys — Wrought products — Technical specification — Part 002: Bar and section*¹⁾

1) Published as ASD-STAN Prestandard at the date of publication of this standard.

1	Material designation			Steel FE-PM1802 (X5CrNiCu15-5)													
2	Chemical composition %	Element		C	Si	Mn	P	S	Cr	Mo	Ni	Cu	Nb + Ta	Fe			
		min.		—	—	—	—	—	14,0	—	3,5	2,5	5 × C	Base			
		max.		0,07	1,00	1,00	0,030	0,015	15,5	0,50	5,5	4,5	0,45				
3	Method of melting			Consumable electrode remelted													
4.1	Form			Bar													
4.2	Method of production			—													
4.3	Limit dimension(s)		mm	a or D ≤ 200													
5	Technical specification			EN 4700-2													

6.1	Delivery condition			Solution treated			Solution treated and precipitation treated						
	Heat treatment			1 025 °C ≤ θ ≤ 1 055 °C / t ≥ 30 min / AC or OQ + cool to θ ≤ 30 °C			1 025 °C ≤ θ ≤ 1 055 °C / t ≥ 30 min / AC or OQ + cool to θ ≤ 30 °C + 535 °C ≤ θ ≤ 565 °C / t ≥ 4 h / AC						
6.2	Delivery condition code			W			U						
7	Use condition			Solution treated and precipitation treated			Delivery condition						
	Heat treatment			Delivery condition + 535 °C ≤ θ ≤ 565 °C / t ≥ 4 h / AC			—						

iTeh STANDARD PREVIEW

Characteristics

(standards.iteh.ai)

8.1	Test sample(s)			See EN 4700-2.																		
8.2	Test piece(s)			See EN 4700-2.																		
8.3	Heat treatment			Solution treated			Use condition															
9	Dimensions concerned		mm	a or D ≤ 200		a or D ≤ 75		75 < a or D ≤ 200														
10	Thickness of cladding on each face		%	—		—		—														
11	Direction of test piece			—		L		L		T												
12	Temperature	θ	°C	—		Ambient		Ambient		Ambient												
13	Proof stress	R _{p0,2}	MPa	—		≥ 1 000		≥ 1 000		≥ 1 000												
14	T	Strength	R _m	MPa	—		≥ 1 070		≥ 1 070		≥ 1 070											
15		Elongation	A	%	—		≥ 11		≥ 10		≥ 7											
16	Z	Reduction of area	%	—		≥ 45		≥ 40		≥ 27												
17	Hardness			≤ 363 HB			331 ≤ HB ≤ 401			331 ≤ HB ≤ 401			331 ≤ HB ≤ 401									
18	Shear strength		R _c	MPa	—		—		—		—											
19	Bending		k	—	—		—		—		—											
20	Impact strength		KV	J	—		≥ 80; Notch direction T + ≥ 35, at - 30 °C		≥ 80; Notch direction T + ≥ 35, at - 30 °C		≥ 55; Notch direction L + ≥ 25, at - 30 °C											
21	C	Temperature	θ	°C	—																	
22		Time		h	—																	
23		Stress	σ _a	MPa	—																	
24		Elongation		a	%	—																
25		Rupture stress		σ _R	MPa	—																
26		Elongation at rupture		A	%	—																
27	Notes (see line 98)				—																	

EN 2817:2009 (E)

30	Microstructure	-	EN 4436		
		2	One per cast		
		3	Corresponding to ingot top		
		7	The δ ferrite content shall not exceed 2 %		
34	Grain size	-	See EN 4700-2.		
		7	$G \geq 5$		
44	External defects	-	See EN 4700-2.		
		1	Visual		
50	Cleanliness/inclusion content (micro-cleanliness)	-	See EN 4700-2.		
		7	Category 4		
51	Macrostructure	-	See EN 4700-2.		
		7	Class	Condition	Severity
			1	Freckles	A
			2	White spots	A
			3	Radial segregation	A
		4	Ring pattern		B
61	Internal defects	-	See EN 4700-2.		
		6	a or $D \leq 100$ mm may be tested either on the product or at an earlier stage of manufacturing.		
		7	Class 3		
			(standards.iteh.ai)		
			<p style="text-align: center;">SIST EN 2817:2010 https://standards.iteh.ai/catalog/standards/sist/e5c8c4ee-282b-4485-80a6-8c3e8e73c596/sist-en-2817-2010</p>		
95	Marking inspection	-	See EN 4700-2.		
96	Dimensional inspection	-	See EN 4700-2.		
98	Notes	-	-		
99	Typical use	-	-		