

**SLOVENSKI STANDARD
SIST EN 3047:2001****01-januar-2001**

Aerospace series - Bearings, airframe rolling - Rigid single row ball bearings in corrosion resisting steel - Diameter series 0 and 2 - Reduced clearance category - Dimensions and loads

Aerospace series - Bearings, airframe rolling - Rigid single row ball bearings in corrosion resisting steel - Diameter series 0 and 2 - Reduced clearance category - Dimensions and loads

Luft- und Raumfahrt - Flugwerkklager - Einreihige Rillenkugellager aus korrosionsbeständigem Stahl - Durchmesserreihen 0 und 2 - Reduzierte Lagerluft - Maße und Belastungen

[SIST EN 3047:2001](https://standards.iteh.ai/catalog/standards/sist/1232a7b8-5dae-4b5b-b56f-106681c9e10e)

Série aérospatiale - Roulements pour structures d'aéronefs - Roulements en acier résistant à la corrosion, rigides, à une rangée de billes - Séries de diamètres 0 et 2 - Catégorie à jeux réduits - Dimensions et charges

Ta slovenski standard je istoveten z: EN 3047:1993

ICS:

49.035

Sestavni deli za letalsko in vesoljsko gradnjo

Components for aerospace construction

SIST EN 3047:2001**en**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 3047:2001

<https://standards.iteh.ai/catalog/standards/sist/1232a7b8-5dae-4b5b-b56f-103c6a02c871/sist-en-3047-2001>

EUROPEAN STANDARD

EN 3047

NORME EUROPÉENNE

EUROPÄISCHE NORM

November 1993

UDC 629.7.02:621.822.74.004.1:669.14.018.89

Descriptors: Aircraft industry, airframe bearings, ball bearings, corrosion resisting steel, dimensions, static loads

English version

**Aerospace series - Bearings, airframe rolling -
Rigid single row ball bearings in corrosion resisting
steel - Diameter series 0 and 2 - Reduced
clearance category - Dimensions and loads**

Série aérospatiale - Roulements pour structures
d'aéronefs - Roulements en acier résistant à la
corrosion, rigides, à une rangée de billes -
Séries de diamètres 0 et 2 - Catégorie à jeux
réduits - Dimensions et charges

Luft- und Raumfahrt - Flugwerklager -
Einreihige Rillenkugellager aus
korrosionsbeständigem Stahl - Durchmesserreihen
0 und 2 - Reduzierte Lagerluft - Maße und
Belastungen

SIST EN 3047:2001

<https://standards.iteh.ai/catalog/standards/sist/1232a7b8-5dae-4b5b-b56f-103c6a02c871/sist-en-3047-2001>

This European Standard was approved by CEN on 1993-11-15. CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CEN member.

The European Standards exist in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Central Secretariat has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.

CEN

European Committee for Standardization
Comité Européen de Normalisation
Europäisches Komitee für Normung

Central Secretariat: rue de Stassart, 36 B-1050 Brussels

Foreword

This European Standard has been prepared by the European Association of Aerospace Manufacturers (AECMA).

After inquiries and votes carried out in accordance with the rules of this Association, this Standard has successively received the approval of the National Associations and the Official Services of the member countries of AECMA, prior to its presentation to CEN.

This standard was submitted for Formal Vote, and the result was positive.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by May 1994, and conflicting national standards shall be withdrawn at the latest by May 1994.

According to the CEN/CENELEC Internal Regulations, the following countries are bound to implement this European Standard: Austria, Belgium, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland, United Kingdom.

ITeH STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 3047:2001

<https://standards.iteh.ai/catalog/standards/sist/1232a7b8-5dae-4b5b-b56f-10-000002a871-1/sist-en-3047-2001>

STANDARD PREVIEW
SIST EN 3047:2001
INTERNATIONAL STANDARDIZATION ORGANIZATION
ANALOGUE

.....T010
INQUIRY FOR TECHNICAL INFORMATION

1 Scope

This standard specifies the characteristics of rigid single row ball bearings in corrosion resisting steel of diameter series 0 and 2¹⁾ designed to withstand only slow rotations and oscillations under load.

They are intended for use between fixed and moving parts of the aircraft structure and their control mechanisms, in particular the mounting of more than one bearing on the same shaft axis, which may require reduced clearances and runouts (axial and radial).

The airframe rolling bearings defined in this standard are used from - 54 °C to + 150 °C.

However, being lubricated with the following greases :

- very high pressure grease, ester type (code A), operational range - 73 °C to + 121 °C or
- very high pressure grease, synthetic hydrocarbons, general purpose (code B), operational range - 54 °C to + 177 °C (see EN 3280),

their field of application when lubricated with code A grease is limited to + 121 °C.

2 Normative references

This European Standard incorporates by dated or undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this European Standard only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referred to applies.

ISO 15	Rolling bearings - Radial bearings - Boundary dimensions - General plan
ISO 1132	Rolling bearings - Tolerances - Definitions
EN 2030	Steel FE-PM43 - Hardened and tempered - Bars $D \leq 150$ mm - Aerospace series 2)
EN 2226	Steel FE-PM43 - Hardened and tempered - Hand and die forgings $D_e \leq 150$ mm - Aerospace series 2)
EN 3280	Aerospace series - Bearings, airframe rolling, rigid or self-aligning - Technical specification

(standards.iteh.ai)

3 Definition

For the purposes of this standard the following definition applies:

Bearing, full complement of balls (without cage), with filling slot.

4 Symbols

The definitions of tolerances and clearances are given in ISO 1132.

Δ_{dmp}	=	single plane mean bore diameter deviation
Δ_{Dmp}	=	single plane mean outside diameter deviation
Δ_{ds}	=	deviation of a single bore diameter
Δ_{Ds}	=	deviation of a single outside diameter
G_a	=	axial internal clearance
G_r	=	radial internal clearance
S_{ia}	=	assembled bearing inner ring face runout with raceway
S_{ea}	=	assembled bearing outer ring face runout with raceway
K_{ia}	=	radial runout of assembled bearing inner ring
K_{ea}	=	radial runout of assembled bearing outer ring
$F_a \text{ max.}$	=	permissible static axial load
C_s	=	permissible static radial load.

1) See ISO 15.

2) Published as AECMA Standard at the date of publication of this standard.

5 Required characteristics

5.1 Dimensions - Tolerances - Clearances - Loads - Mass

Configuration : see figure 1 ; the bearings are fitted with either seals or shields.

Values : see table 1.

5.2 Surface roughness

Raceways and rolling elements : $R_a = 0,2 \mu\text{m}$

Bore, side faces and cylindrical outer surface : $R_a = 0,8 \mu\text{m}$.

5.3 Materials


Inner ring : EN 2030 or EN 2226, ≥ 58 HRC

Outer ring : EN 2030 or EN 2226, ≥ 58 HRC

Balls : EN 2030, ≥ 58 HRC

Shields : Corrosion resisting material

Seals : Polytetrafluoroethylene (PTFE) or polytetrafluoroethylene (PTFE) reinforced with fibreglass.



NOTE 1 - The installation of seals and shields is at the manufacturer's option.

NOTE 2 - The seal shall not extend beyond « C ».

Figure 1

Table 1

Dimensions in millimetres

d		B	C	D	d1	Tolerances μm				r	Mass kg/1000 parts \approx			
Code	Nominal	0 -0,12	0 -0,12		min.	Δ_{dmp}	Δ_{Dmp}	Δ_{ds}	Δ_{Ds}					
05	5	7	5	16	7,6	0 -8	0 -8	+2 -10	+2 -10	0,3 to 0,8	4			
06	6	8	6	19	8,6		0 -9		+2 -10		+2 -11	9		
08	8	9	7	22	10,6							26	12,6	12
10	10	10	8	28	14,7									21
12	12			11	9			32				17,7	+3 -11	+3 -14
15	15	12	10	35	20,2		0 -11	+3 -14	32					
17	17	14	12	42	23,5				+3 -13		+4 -17	42		
20	20			47	28,6		72							
25	25	15	13	55	34,1	0 -10	0 -13	85	0,3 to 1	123				


iTeh STANDARD PREVIEW
(standards.itech.ai)

d Code	Internal clearances μm		Runout tolerances max. μm				Starting torque in mN.m ¹⁾		Permissible static loads ²⁾ kN	
	Axial max. G_a	Radial G_r	Axial		Radial		Code P	Code E	Axial F_a max.	Radial C_s
			S_{ia}	S_{ea}	K_{ia}	K_{ea}				
05	80	2 to 9	15	20	6	8	2	4	3,1	6,8
06							2,5	5	4,2	9,2
08							3	6,5	5,4	11,8
10							4	7,5	7,7	17
12	100	3 to 11	20	20	7	10	5	8,5	8,9	19,5
15							6	10	10,6	23,3
17							8	12	12,2	26,9
20							10,5	15	18,7	41,2
25	120	5 to 13	20	20	8	10	13,5	18	21,2	46,6
30							19	25	28,5	62,6

1) Definition, see EN 3280.
2) Axial and radial loads may be applied simultaneously.
For ultimate static loads, see EN 3280.

6 Designation

EXAMPLE :



NOTE : If necessary, the code I9005 shall be placed between the description block and the identity block.

7 Marking

In addition to the manufacturer's own marking, each bearing shall be marked, on one side face only, using the identity block, see 6.

Marking position and method are at the manufacturer's option.

ITeH STANDARD PREVIEW
(standards.iteh.ai)

8 Technical specification

See EN 3280.

SIST EN 3047:2001

<https://standards.iteh.ai/catalog/standards/sist/1232a7b8-5dae-4b5b-b56f-103c6a02c871/sist-en-3047-2001>