



Designation: C 1433M – 00a
METRIC

Standard Specification for Precast Reinforced Concrete Box Sections for Culverts, Storm Drains, and Sewers [Metric]¹

This standard is issued under the fixed designation C 1433M; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This specification covers single-cell precast reinforced concrete box sections intended to be used for the construction of culverts and for the conveyance of storm water industrial wastes and sewage.

1.2 This specification is the companion to inch-pound Specification C 1433.

NOTE 1—This specification is primarily a manufacturing and purchasing specification. However, standard designs are included and the criteria used to develop these designs are given in Appendix X1. The successful performance of this product depends upon the proper selection of the box section, bedding, backfill, and care that the installation conforms to the construction specifications. The purchaser of the precast reinforced concrete box sections specified herein is cautioned that he must properly correlate the loading conditions and the field requirements with the box section specified and provide for inspection at the construction site.

2. Referenced Documents

ASTM Standards:

- A 82 Specification for Steel Wire, Plain, for Concrete Reinforcement²
- A 185 Specification for Steel Welded Wire Fabric, Plain, for Concrete Reinforcement²
- A 496 Specification for Steel Wire, Deformed, for Concrete Reinforcement²
- A 497 Specification for Steel Welded Wire Fabric, Deformed, for Concrete Reinforcement²
- A 615/A 615M Specification for Deformed and Plain Billet-Steel Bars for Concrete Reinforcement²

¹ This specification is under the jurisdiction of ASTM Committee C13 on Concrete Pipe and is the direct responsibility of Subcommittee C13.07 on Acceptance Specifications and Precast Concrete Box Sections.

Current edition approved Oct. 10, 2000. Published November 2000. Originally published as C 1433M-99. Last previous edition C 1433M-00.

² *Annual Book of ASTM Standards*, Vol 01.04.

- C 31/C 31M Practice for Making and Curing Concrete Test Specimens in the Field³
- C 33 Specification for Concrete Aggregates³
- C 39 Test Method for Compressive Strength of Cylindrical Concrete Specimens³
- C 150 Specification for Portland Cement⁴
- C 309 Specification for Liquid Membrane-Forming Compounds for Curing Concrete³
- C 497M Test Methods for Concrete Pipe, Manhole Sections, or Tile [Metric]⁵
- C 595 Specification for Blended Hydraulic Cements⁴
- C 618 Specification for Coal Fly Ash and Raw or Calcined Natural Pozzolan for Use as a Mineral Admixture in Portland Cement Concrete³
- C 822 Terminology Relating to Concrete Pipe and Related Products⁵
- 2.2 *AASHTO Standards:*⁶
 - Specifications for Highway Bridges, 1997 Edition

3. Terminology

3.1 *Definitions*—For definitions of terms relating to concrete pipe, see Terminology C 822.

4. Types

4.1 Precast reinforced concrete box sections manufactured in accordance with this specification shall be one of two types identified in Tables 1 and 2, and shall be designated by type, span, rise, and design earth cover.

³ *Annual Book of ASTM Standards*, Vol 04.02.

⁴ *Annual Book of ASTM Standards*, Vol 04.01.

⁵ *Annual Book of ASTM Standards*, Vol 04.05.

⁶ Available from American Association of State Highway and Transportation Officials (AASHTO).

TABLE 1 Design Requirements for Precast Concrete Box Sections Under Earth Dead and HS20 Live Load Conditions

NOTE 1—Design earth covers and reinforcement areas are based on the weight of a column of earth over the width of the box section as defined in Appendix X1.

NOTE 2—Concrete design strength 35 MPa.

NOTE 3—The design earth cover indicated is the height of fill above the top of the box section. Design requirements are based on the material and soil properties, loading data, and typical section as included in Appendix X1. For alternative or special designs, see 7.2.

NOTE 4—Design steel area in millimetres per linear metre of box section at those locations which are indicated on the typical section included in Appendix X1.

NOTE 5—The top section designation, for example, 900 by 600 by 100 mm indicates (interior horizontal span in millimetres) by (interior vertical rise in millimetres) by (wall and slab thickness in millimetres).

NOTE 6—In accordance with the acceptance criteria in 7.2, the manufacturer may interpolate the steel area requirements for fill heights between noted increments or may submit independent designs.

900 by 600 by 100 mm									
Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M," mm
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}	
0<0.6 ^A	360	830	470	210	400	360	360	300	460
0.6<0.9	320	570	570	210					460
0.9-1.5	210	250	250	210					460
3.0	210	210	210	210					460
4.6	210	280	300	210					460
6.1	230	360	380	210					460
7.6	300	470	470	210					460
9.1	360	550	550	210					460

^A Top slab 175 mm, bottom slab 150 mm.

900 by 900 by 100 mm									
Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M," mm
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}	
0<0.6 ^A	360	870	490	210	420	360	360	300	460
0.6<0.9	230	660	660	210					460
0.9-1.5	210	300	300	210					460
3.0	210	230	230	210					460
4.6	210	320	320	210					460
6.1	210	400	420	210					460
7.6	210	490	510	210					460
9.1	250	590	610	210					460

^A Top slab 175 mm, bottom slab 150 mm.

1200 by 600 by 125 mm									
Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M," mm
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}	
0<0.6 ^A	380	890	470	250	440	380	380	300	460
0.6<0.9	510	610	530	250					460
0.9-1.5	260	300	300	250					460
3.0	250	250	250	250					460
4.6	320	340	340	250					460
6.1	400	440	440	250					460
7.6	510	550	550	250					460
9.1	590	660	660	250					460

^A Top slab 200 mm, bottom slab 150 mm.

1200 by 900 by 125 mm									
Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M," mm
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}	
0<0.6 ^A	380	970	530	250	490	380	380	300	460
0.6<0.9	420	740	660	250					460
0.9-1.5	250	360	360	250					460
3.0	250	300	300	250					460

4.6	250	400	400	250	460
6.1	300	510	530	250	460
7.6	380	640	640	250	460
9.1	440	760	760	250	460

^A Top slab 200 mm, bottom slab 150 mm.

1200 by 1200 by 125 mm									
Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M," mm
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}	
0<0.6 ^A	380	1020	570	250	510	380	380	300	460
0.6<0.9	340	800	720	250					460
0.9-1.5	250	380	380	250					460
3.0	250	320	320	250					460
4.6	250	420	440	250					460
6.1	250	550	550	250					460
7.6	320	660	680	250					460
9.1	360	800	800	250					460

^A Top slab 200 mm, bottom slab 150 mm.

1500 by 900 by 150 mm									
Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M," mm
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}	
0<0.6 ^A	410	990	510	300	470	410	410	360	460
0.6<0.9	550	760	590	300					460
0.9-1.5	300	400	400	300					460
3.0	300	340	340	300					460
4.6	360	470	470	300					460
6.1	440	590	610	300					460
7.6	550	740	740	300					460
9.1	680	890	890	300					460

^A Top slab 200 mm, bottom slab 175 mm.

1500 by 1200 by 150 mm									
Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M," mm
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}	
0<0.6 ^A	400	1060	570	300	510	410	410	360	460
0.6<0.9	470	870	700	300					460
0.9-1.5	300	440	440	300					460
3.0	300	360	380	300					460
4.6	300	510	530	300					460
6.1	380	660	680	300					460
7.6	470	800	830	300					460
9.1	550	970	970	300					460

^A Top slab 200 mm, bottom slab 175 mm.

1500 by 1500 by 150 mm									
Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M," mm
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}	
0<0.6 ^A	410	1100	610	300	510	410	410	360	460
0.6<0.9	400	910	740	300					460
0.9-1.5	300	470	470	300					460
3.0	300	380	400	300					460
4.6	300	530	550	300					460
6.1	320	680	700	300					460
7.6	400	850	870	300					460
9.1	490	990	1020	300					460

^A Top slab 200 mm, bottom slab 175 mm.

1800 by 900 by 175 mm									
Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M," mm
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}	
0<0.6 ^A	530	1020	490	360	440	410	400	360	460
0.6<0.9	640	800	550	360					460
0.9-1.5	360	420	360	360					460
3.0	360	380	380	360					460
4.6	490	530	530	360					460

6.1	610	680	680	360	460
7.6	760	830	850	360	460
9.1	910	990	990	360	740

^A Top slab 200 mm.

1800 by 1200 by 175 mm

Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M _i ," mm
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}	
0<0.6 ^A	420	1100	550	360	470	410	410	360	
0.6<0.9	550	890	660	360					460
0.9-1.5	360	490	440	360					460
3.0	360	420	440	360					460
4.6	400	590	590	360					460
6.1	530	760	760	360					460
7.6	640	930	950	360					460
9.1	760	1100	1120	360					460

^A Top slab 200 mm.

1800 by 1500 by 175 mm

Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M _i ," mm
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}	
0<0.6 ^A	410	1160	610	360	510	410	410	360	
0.6<0.9	490	950	720	360					460
0.9-1.5	360	510	470	360					460
3.0	360	440	490	360					460
4.6	360	610	660	360					460
6.1	440	800	830	360					460
7.6	550	970	1020	360					460
9.1	660	1190	1230	360					460

^A Top slab 200 mm.

1800 by 1800 by 175 mm

Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M _i ," mm
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}	
0<0.6 ^A	410	1210	660	360	530	410	410	360	
0.6<0.9	440	1020	760	360					460
0.9-1.5	360	530	490	360					460
3.0	360	470	510	360					460
4.6	360	660	680	360					460
6.1	400	830	870	360					460
7.6	490	1020	1040	360					460
9.1	590	1230	1290	360					460

^A Top slab 200 mm.

2100 by 1200 by 200 mm

Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M _i ," mm
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}	
0<0.6	590	1120	510	400	440	410	410	400	
0.6<0.9	640	910	610	400					460
0.9-1.5	410	510	410	400					460
3.0	410	470	490	400					460
4.6	530	660	680	400					460
6.1	680	850	850	400					460
7.6	830	1040	1040	400					460
9.1	990	1230	1250	400					790

2100 by 1500 by 200 mm

Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M _i ," mm
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}	
0<0.6	530	1190	590	400	470	410	410	400	
0.6<0.9	570	990	700	400					460
0.9-1.5	400	550	470	400					460
3.0	400	510	530	400					460
4.6	470	700	720	400					460
6.1	590	910	930	400					460
7.6	720	1100	1140	400					460
9.1	870	1350	1400	400					460

2100 by 1800 by 200 mm

Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M _i ," mm
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}	
0<0.6	470	1230	640	410	490	410	410	400	
0.6<0.9	510	1040	740	400					460
0.9-1.5	400	570	490	410					460
3.0	400	550	570	410					460
4.6	420	740	780	410					460
6.1	530	950	970	410					460
7.6	640	1160	1210	410					460
9.1	760	1440	1550	410					460

2100 by 2100 by 200 mm

Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M _i ," mm
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}	
0<0.6	490	1270	660	400	510	410	410	400	
0.6<0.9	470	1080	780	400					460
0.9-1.5	400	590	510	400					460
3.0	400	570	610	400					460
4.6	400	760	800	400					460
6.1	490	970	1020	400					460
7.6	590	1190	1230	400					460
9.1	700	1480	1630	400					460

2400 by 1200 by 200 mm

Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M _i ," mm
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}	
0<0.6	720	1230	570	410	400	410	410	400	
0.6<0.9	780	1060	700	400					940
0.9-1.5	490	610	530	410					460
3.0	550	590	610	410					460
4.6	760	830	850	410					460
6.1	970	1060	1080	410					460
7.6	1210	1330	1350	410					910

2400 by 1500 by 200 mm

Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M _i ," mm
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}	
0<0.6	640	1310	640	400	490	410	410	400	
0.6<0.9	740	1140	780	400					460
0.9-1.5	420	660	550	400					460
3.0	490	640	680	400					460
4.6	680	890	910	400					460
6.1	870	1140	1190	400					460
7.6	1060	1500	1550	400					790

2400 by 1800 by 200 mm

Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M _i ," mm
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}	
0<0.6	590	1350	700	400	510	400	400	400	
0.6<0.9	680	1210	850	400					460
0.9-1.5	400	700	570	400					460
3.0	440	680	720	400					460
4.6	610	950	970	400					460
6.1	780	1210	1250	400					460
7.6	950	1630	1670	400					790

2400 by 2100 by 200 mm

Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M _i ," mm
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}	
0<0.6	570	1400	740	400	510	410	410	400	
0.6<0.9	610	1270	890	400					460
0.9-1.5	400	700	610	400					460
3.0	420	720	760	400					460
4.6	570	970	1040	400					460
6.1	720	1270	1310	400					460
7.6	890	1690	1780	400					790

2400 by 2400 by 200 mm									
Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M," mm
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}	
0<0.6	640	1440	760	400	530	400	400	400	
0.6<0.9	570	1290	910	400					460
0.9-1.5	400	720	660	400					460
3.0	400	740	800	400					460
4.6	530	1020	1080	400					460
6.1	680	1290	1380	400					460
7.6	830	1760	1840	400					790

2700 by 1500 by 225 mm									
Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M," mm
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}	
0<0.6	680	1250	610	470	470	460	460	470	
0.6<0.9	780	1140	740	470					460
0.9-1.5	470	680	550	470					460
3.0	590	700	720	470					460
4.6	800	950	970	470					460
6.1	1040	1230	1250	470					460
7.6	1270	1590	1630	470					840

2700 by 1800 by 225 mm									
Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M," mm
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}	
0<0.6	610	1310	660	470	460	460	460	470	
0.6<0.9	720	1210	800	470					460
0.9-1.5	470	720	590	470					460
3.0	550	740	780	470					460
4.6	740	1020	1060	470					460
6.1	930	1310	1350	470					460
7.6	1140	1740	1780	470					840

2700 by 2100 by 225 mm									
Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M," mm
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}	
0<0.6	570	1350	700	470	460	470	460	470	990
0.6<0.9	660	1270	870	470					460
0.9-1.5	470	740	640	470					460
3.0	510	780	830	470					460
4.6	680	1060	1120	470					460
6.1	870	1380	1420	470					460
7.6	1060	1840	1950	470					840

2700 by 2400 by 225 mm									
Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M," mm
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}	
0<0.6	590	1380	740	470	490	460	460	470	
0.6<0.9	610	1310	890	470					460
0.9-1.5	470	700	740	470					460
3.0	470	800	870	470					460
4.6	640	1100	1160	470					460
6.1	800	1400	1500	470					460
7.6	970	1910	2070	470					840

2700 by 2700 by 225 mm									
Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M," mm
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}	
0<0.6	660	1400	740	470	490	460	460	470	
0.6<0.9	570	1330	910	470					460
0.9-1.5	470	740	740	460					460
3.0	470	830	910	460					460
4.6	590	1120	1210	460					460
6.1	760	1440	1570	460					460
7.6	930	1970	2180	460					840

3000 by 1500 by 250 mm									
Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M," mm
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}	
0<0.6	700	1210	570	510	510	510	510	510	
0.6<0.9	830	1160	720	510					460
0.9-1.5	530	700	570	510					460
3.0	680	740	760	510					460
4.6	930	1020	1040	510					460
6.1	1210	1290	1330	510					460
7.6	1480	1650	1690	510					1020

3000 by 1800 by 250 mm									
Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M," mm
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}	
0<0.6	640	1270	640	510	510	510	510	510	
0.6<0.9	780	1230	780	510					460
0.9-1.5	510	740	610	510					460
3.0	640	780	830	510					460
4.6	850	1080	1120	510					460
6.1	1100	1400	1440	510					460
7.6	1350	1820	1930	510					890

3000 by 2100 by 250 mm									
Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M," mm
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}	
0<0.6	590	1310	680	510	510	510	510	510	
0.6<0.9	720	1270	850	510					460
0.9-1.5	510	760	660	510					460
3.0	590	830	890	510					460
4.6	780	1140	1190	510					460
6.1	1020	1460	1520	510					460
7.6	1230	1950	2140	510					890

3000 by 2400 by 250 mm									
Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M," mm
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}	
0<0.6	550	1330	720	510	510	510	510	510	
0.6<0.9	660	1310	890	510					460
0.9-1.5	510	780	720	510					460
3.0	550	870	930	510					460
4.6	740	1190	1250	510					460
6.1	930	1520	1590	510					460
7.6	1140	2050	2310	510					890

3000 by 2700 by 250 mm									
Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M," mm
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}	
0<0.6	610	1380	740	510	510	510	510	510	
0.6<0.9	610	1350	910	510					460
0.9-1.5	510	780	760	510					460
3.0	530	910	970	510					460
4.6	700	1230	1290	510					460
6.1	890	1570	1690	510					460
7.6	1080	2140	2460	510					890

3000 by 3000 by 250 mm									
Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M," mm
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}	
0<0.6	680	1380	780	510	510	510	510	510	
0.6<0.9	570	1380	930	510					460
0.9-1.5	510	780	800	510					460
3.0	510	930	1020	510					460
4.6	680	1250	1350	510					460
6.1	850	1610	1760	510					460
7.6	1040	2180	2560	510					890

3300 by 1200 by 275 mm									
Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M," mm
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}	
0<0.6	800	1100	550	560	560	560	560	550	460
0.6<0.9	950	1080	590	550					460
0.9-1.5	640	640	550	560					460
3.0	850	700	720	560					460
4.6	1190	970	990	560					460
6.1	1520	1250	1270	560					1070
7.6	1880	1520	1550	560					1120

3300 by 1800 by 275 mm									
Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M," mm
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}	
0<0.6	680	1230	610	560	560	560	560	550	
0.6<0.9	800	1230	760	550					460
0.9-1.5	550	740	640	560					460
3.0	720	830	870	560					460
4.6	990	1140	1190	560					460
6.1	1270	1460	1500	560					460
7.6	1550	1910	2050	560					910

3300 by 2400 by 275 mm									
Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M," mm
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}	
0<0.6	570	1310	700	550	560	560	560	550	
0.6<0.9	700	1330	870	550					460
0.9-1.5	550	800	740	550					460
3.0	640	930	990	550					460
4.6	870	1270	1330	550					460
6.1	1080	1630	1690	550					460
7.6	1330	2270	2540	550					910

3300 by 3000 by 275 mm									
Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M," mm
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}	
0<0.6	640	1350	760	550	560	560	560	550	
0.6<0.9	610	1380	910	550					460
0.9-1.5	550	800	830	550					160
3.0	590	990	1080	550					460
4.6	780	1350	1440	550					460
6.1	970	1740	1880	550					460
7.6	1190	2460	2860	550					910

3300 by 3300 by 275 mm									
Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M," mm
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}	
0<0.6	720	1350	830	550	560	560	560	550	
0.6<0.9	570	1400	950	550					460
0.9-1.5	550	830	890	560					460
3.0	570	1040	1140	560					460
4.6	740	1380	1500	560					460
6.1	930	1780	1970	560					460
7.6	1140	2500	2960	560					910

3600 by 1200 by 300 mm									
Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M," mm
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}	
0<0.6	830	1060	610	610	610	610	610	610	
0.6<0.9	1020	1080	610	610					460
0.9-1.5	700	640	610	610					460
3.0	970	740	760	610					460
4.6	1330	1020	1040	610					460
6.1	1710	1310	1330	610					1170
7.6	2120	1610	1630	610					1170

3600 by 1800 by 300 mm									
Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M," mm
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}	
0<0.6	700	1210	610	610	610	610	610	610	
0.6<0.9	850	1230	740	610					460
0.9-1.5	610	760	660	610					460
3.0	830	890	910	610					460
4.6	1120	1210	1250	610					460
6.1	1440	1550	1590	610					460
7.6	1760	1990	2160	610					1120

3600 by 2400 by 300 mm									
Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M," mm
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}	
0<0.6	610	1290	700	610	610	610	610	610	
0.6<0.9	740	1330	850	610					460
0.9-1.5	610	830	760	610					460
3.0	740	970	1040	610					460
4.6	970	1330	1400	610					460
6.1	1250	1710	1780	610					460
7.6	1520	2430	2730	610					970

3600 by 3000 by 300 mm									
Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M," mm
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}	
0<0.6	610	1330	760	610	610	610	610	610	
0.6<0.9	660	1400	910	610					460
0.9-1.5	610	850	870	610					460
3.0	680	1060	1160	610					460
4.6	890	1440	1550	610					460
6.1	1120	1840	1990	610					460
7.6	1350	2710	3110	610					970

3600 by 3600 by 300 mm									
Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M," mm
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}	
0<0.6	740	1350	870	700	610	610	610	610	
0.6<0.9	610	1420	1020	610					460
0.9-1.5	610	890	950	610					460
3.0	610	1120	1250	610					460
4.6	830	1500	1650	610					460
6.1	1020	1970	2180	610					460
7.6	1250	2840	3410	610					970

TABLE 2 Design Requirements for Precast Concrete Box Sections Under Earth Dead and Interstate Live Load Conditions

NOTE 1—Design earth covers and reinforcement areas are based on the weight of a column of earth over the width of the box section as defined in Appendix X1.

NOTE 2—Concrete design strength 35 MPa.

NOTE 3—The design earth cover indicated is the height of fill above the top of the box section. Design requirements are based on the material and soil properties, loading data, and typical section as included in Appendix X1. For alternative or special designs, see 7.2.

NOTE 4—Design steel area in square millimetres per linear metre of box section at those locations which are indicated on the typical section included in Appendix X1.

NOTE 5—The top section designation, for example, 900 by 600 by 100 mm, indicates (interior horizontal span in millimetres) by (interior vertical rise in millimetres) by (wall and slab thickness in millimetres).

NOTE 6—In accordance with the acceptance criteria in 7.2, the manufacturer may interpolate the steel area requirements for fill heights between noted increments or may submit independent designs.

900 by 600 by 100 mm										
Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M," mm	
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}		
0<0.6 ^A	360	830	470	210	400	360	360	300		
0.6<0.9	320	570	570	210					460	
0.9-1.5	210	250	250	210					460	
3.0	210	210	210	210					460	
4.6	210	300	300	210					460	
6.1	250	380	380	210					460	
7.6	300	470	470	210					460	
9.1	360	550	550	210					460	

^A Top slab 175 mm, bottom slab 150 mm.

900 by 900 by 100 mm										
Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M," mm	
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}		
0<0.6 ^A	360	870	490	210	420	360	360	300		
0.6<0.9	230	660	660	210					460	
0.9-1.5	210	300	300	210					460	
3.0	210	230	230	210					460	
4.6	210	320	340	210					460	
6.1	210	400	420	210					460	
7.6	210	510	510	210					460	
9.1	250	590	610	210					460	

^A Top slab 175 mm, bottom slab 150 mm.

1200 by 600 by 125 mm										
Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M," mm	
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}		
0<0.6 ^A	380	890	470	250	440	380	380	300		
0.6<0.9	510	610	530	250					460	
0.9-1.5	260	300	300	250					460	
3.0	250	250	250	250					460	
4.6	320	360	360	250					460	
6.1	400	440	440	250					460	
7.6	510	550	550	250					460	
9.1	620	660	660	250					460	

^A Top slab 162.5 mm, bottom slab 150 mm.

1200 by 900 by 125 mm										
Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M," mm	
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}		
0<0.6 ^A	380	970	530	250	490	380	380	300		
0.6<0.9	420	740	660	250					460	
0.9-1.5	250	360	360	250					460	
3.0	250	300	300	250					460	

4.6	250	400	420	250	460
6.1	320	530	530	250	460
7.6	380	640	660	250	460
9.1	440	760	760	250	460

^A Top slab 162.5 mm, bottom slab 150 mm.

1200 by 1200 by 125 mm										
Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M," mm	
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}		
0<0.6 ^A	380	1020	570	250	510	380	380	300		
0.6<0.9	340	800	720	250					460	
0.9-1.5	250	380	380	250					460	
3.0	250	320	340	250					460	
4.6	250	420	440	250					460	
6.1	250	550	570	250					460	
7.6	320	680	700	250					460	
9.1	380	800	830	250					460	

^A Top slab 162.5 mm, bottom slab 150 mm.

1500 by 900 by 150 mm										
Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M," mm	
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}		
0<0.6 ^A	420	990	640	300	470	410	410	360		
0.6<0.9	550	760	590	300					460	
0.9-1.5	300	400	400	300					460	
3.0	300	340	360	300					460	
4.6	360	470	490	300					460	
6.1	470	610	610	300					460	
7.6	570	740	760	300					460	
9.1	680	890	910	300					460	

^A Top slab 200 mm, bottom slab 175 mm.

1500 by 1200 by 150 mm										
Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M," mm	
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}		
0<0.6 ^A	410	1060	720	300	510	410	410	360		
0.6<0.9	470	870	700	300					460	
0.9-1.5	300	440	440	300					460	
3.0	300	380	400	300					460	
4.6	300	510	530	300					460	
6.1	380	660	680	300					460	
7.6	470	800	830	300					460	
9.1	550	970	990	300					460	

^A Top slab 200 mm, bottom slab 175 mm.

1500 by 1500 by 150 mm										
Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M," mm	
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}		
0<0.6 ^A	410	1100	760	300	510	410	410	360		
0.6<0.9	400	910	740	300					460	
0.9-1.5	300	470	470	300					460	
3.0	300	400	420	300					460	
4.6	300	550	570	300					460	
6.1	340	700	720	300					460	
7.6	400	850	870	300					460	
9.1	490	1020	1040	300					460	

^A Top slab 200 mm, bottom slab 175 mm.

1800 by 900 by 175 mm										
Design Earth Cover, m	Circumferential Reinforcement Areas, mm ² /m								"M," mm	
	A _{s1}	A _{s2}	A _{s3}	A _{s4}	A _{s5}	A _{s6}	A _{s7}	A _{s8}		
0<0.6 ^A	530	1020	680	360	440	410	410	360		
0.6<0.9	640	800	550	360					460	
0.9-1.5	360	420	360	360					460	
3.0	360	380	400	360					460	
4.6	490	530	550	360					460	