

# INTERNATIONAL STANDARD

Audio and audiovisual equipment – Digital audio parts – Basic measurement  
methods of audio characteristics –  
Part 2: Consumer use

IEC 61606-2:2009  
<https://standards.iteh.ai/catalog/standards/sist/3d179297-b90b-4740-b297-b6f3982690e0/iec-61606-2-2009>



## THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2009 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland  
Email: [inmail@iec.ch](mailto:inmail@iec.ch)  
Web: [www.iec.ch](http://www.iec.ch)

### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

### About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: [www.iec.ch/searchpub](http://www.iec.ch/searchpub)

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: [www.iec.ch/online\\_news/justpub](http://www.iec.ch/online_news/justpub)

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: [www.electropedia.org](http://www.electropedia.org)

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: [www.iec.ch/webstore/custserv](http://www.iec.ch/webstore/custserv)

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: [csc@iec.ch](mailto:csc@iec.ch)  
Tel.: +41 22 919 02 11  
Fax: +41 22 919 03 00



IEC 61606-2

Edition 2.0 2009-07

# INTERNATIONAL STANDARD

---

**Audio and audiovisual equipment – Digital audio parts – Basic measurement  
methods of audio characteristics –  
Part 2: Consumer use**

**ITeH STANDARD PREVIEW**  
**(standards.iteh.ai)**  
<https://standards.iteh.ai/catalog/standards/sist/3d179297-b90b-4740-b297-b6f3982690e0/iec-61606-2-2009>

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

PRICE CODE

W

ICS 33.160.01

ISBN 978-2-88910-548-9

## CONTENTS

FOREWORD.....	5
1 Scope.....	7
2 Normative references .....	7
3 Terms, definitions, explanations and rated values .....	7
3.1 Terms and definitions .....	7
3.2 Explanation of terms “jitter” .....	8
3.3 Digital interface for measurement.....	8
3.4 Rated values .....	8
4 Measuring conditions.....	8
4.1 General.....	8
4.2 Environmental conditions .....	8
4.3 Power supply.....	8
4.4 Test signal frequencies .....	8
4.5 Standard setting .....	8
4.6 Preconditioning .....	9
4.7 Measuring instruments .....	9
4.7.1 General .....	9
4.7.2 Digital level meter.....	9
4.7.3 Distortion meter.....	9
4.7.4 Analogue weighting filter.....	10
4.7.5 Digital weighting filter .....	10
4.7.6 Digital spectrum analyzer.....	10
5 Methods of measurement (digital-in/analogue-out).....	10
5.1 General.....	10
5.2 Input/output characteristics .....	10
5.2.1 Maximum output amplitude.....	10
5.2.2 Gain difference between channels .....	11
5.3 Frequency characteristics.....	11
5.3.1 Frequency response .....	11
5.3.2 Group delay (phase linearity).....	12
5.4 Noise characteristics .....	13
5.4.1 Signal-to-noise ratio .....	13
5.4.2 Dynamic range .....	13
5.4.3 Out-of-band noise ratio.....	14
5.4.4 Channel separation .....	15
5.5 Distortion characteristics .....	16
5.5.1 Level non-linearity .....	16
5.5.2 Distortion and noise.....	17
5.5.3 Intermodulation.....	17
6 Methods of measurement (analogue-in/digital-out) .....	18
6.1 General.....	18
6.2 Input/output characteristics .....	18
6.2.1 Analogue to digital level calibration .....	18
6.2.2 Maximum allowable input amplitude.....	20
6.2.3 Gain difference between channel and tracking error .....	21
6.3 Frequency characteristics.....	23

6.3.1	Frequency response .....	23
6.3.2	Group delay.....	24
6.4	Noise characteristics .....	25
6.4.1	Signal-to-noise ratio (idle channel noise).....	25
6.4.2	Dynamic range .....	27
6.4.3	Folded noise.....	28
6.4.4	Cross-talk .....	29
6.4.5	Channel separation .....	31
6.5	Distortion characteristics .....	33
6.5.1	Level non-linearity .....	33
6.5.2	Distortion and noise.....	34
6.5.3	Intermodulation.....	35
Figure 1	– Connection diagram of equipment.....	11
Figure 2	– Connection diagram of equipment.....	11
Figure 3	– Connection diagram of equipment.....	12
Figure 4	– Connection diagram of equipment.....	13
Figure 5	– Connection diagram of equipment.....	14
Figure 6	– Connection diagram of equipment.....	14
Figure 7	– Connection diagram of equipment.....	15
Figure 8	– Connection diagram of equipment.....	16
Figure 9	– Connection diagram of equipment.....	17
Figure 10	– Connection diagram of equipment.....	17
Figure 11	– Connection diagram of equipment.....	18
Figure 12	– Connection diagram of equipment.....	19
Figure 13	– Connection diagram of equipment.....	20
Figure 14	– Connection diagram of equipment.....	20
Figure 15	– Connection diagram of equipment.....	21
Figure 16	– Connection diagram of equipment.....	22
Figure 17	– Connection diagram of equipment.....	23
Figure 18	– Connection diagram of equipment.....	23
Figure 19	– Connection diagram of equipment.....	24
Figure 20	– Connection diagram of equipment.....	24
Figure 21	– Connection diagram of equipment.....	25
Figure 22	– Connection diagram of equipment.....	26
Figure 23	– Connection diagram of equipment.....	27
Figure 24	– Connection diagram of equipment.....	27
Figure 25	– Connection diagram of equipment.....	28
Figure 26	– Connection diagram of equipment.....	28
Figure 27	– Connection diagram of equipment.....	30
Figure 28	– Connection diagram of equipment.....	30
Figure 29	– Connection diagram of equipment.....	31
Figure 30	– Connection diagram of equipment.....	32
Figure 31	– Connection diagram of equipment.....	33
Figure 32	– Connection diagram of equipment.....	33

Figure 33 – Connection diagram of equipment ..... 34  
Figure 34 – Connection diagram of equipment ..... 34  
Figure 35 – Connection diagram of equipment ..... 35  
Figure 36 – Connection diagram of equipment ..... 36

Table 1 – Levels for measurement ..... 16  
Table 2 – Interfering frequency ..... 29

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[IEC 61606-2:2009](https://standards.iteh.ai/catalog/standards/sist/3d179297-b90b-4740-b297-b6f3982690e0/iec-61606-2-2009)

<https://standards.iteh.ai/catalog/standards/sist/3d179297-b90b-4740-b297-b6f3982690e0/iec-61606-2-2009>

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

**AUDIO AND AUDIOVISUAL EQUIPMENT –  
DIGITAL AUDIO PARTS –  
BASIC MEASUREMENT METHODS  
OF AUDIO CHARACTERISTICS –****Part 2: Consumer use**

## FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61606-2 has been prepared by IEC technical committee 100: Audio, video and multimedia systems and equipment.

This second edition cancels and replaces the first edition published in 2003. It constitutes a technical revision.

The significant technical changes with respect to the first edition are the following:

- changed the period of preconditioning;
- add A weighting filter in measuring instruments;
- correct the wrong reference number;
- some inappropriate descriptions have been improved.

The text of this standard is based on the following documents:

FDIS	Report on voting
100/1548/FDIS	100/1582/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This part is to be used in conjunction with IEC 61606-1, General.

A list of all parts of the IEC 61606 series, under the general title *Audio and audiovisual equipment – Digital audio parts – Basic measurement methods of audio characteristics*, can be found on the IEC website.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

**ITeH STANDARD PREVIEW**  
**(standards.iteh.ai)**

A bilingual version of this publication may be issued at a later date.

[IEC 61606-2:2009](#)

<https://standards.iteh.ai/catalog/standards/sist/3d179297-b90b-4740-b297-b6f3982690e0/iec-61606-2-2009>



# AUDIO AND AUDIOVISUAL EQUIPMENT – DIGITAL AUDIO PARTS – BASIC MEASUREMENT METHODS OF AUDIO CHARACTERISTICS –

## Part 2: Consumer use

### 1 Scope

This part of IEC 61606 is applicable to the basic measurement methods of the audio characteristics of the digital audio part of audio and audiovisual equipment for consumer use.

The common measuring conditions and methods are described in IEC 61606-1. This International Standard specifies conditions and methods of measurement for consumer equipment are given in this standard.

### 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60268-2, *Sound system equipment – Part 2: Explanation of general terms and calculation methods*

[IEC 61606-2:2009](https://standards.iteh.ai/catalog/standards/sist/3d179297-b90b-4740-b297-b63982690e0/iec-61606-2-2009)

[https://standards.iteh.ai/catalog/standards/sist/3d179297-b90b-4740-](https://standards.iteh.ai/catalog/standards/sist/3d179297-b90b-4740-b297-b63982690e0/iec-61606-2-2009)

IEC 60958 (all parts), *Digital audio interface*

[b297-b63982690e0/iec-61606-2-2009](https://standards.iteh.ai/catalog/standards/sist/3d179297-b90b-4740-b297-b63982690e0/iec-61606-2-2009)

IEC 61606-1:2009, *Audio and audiovisual equipment – Digital audio parts – Basic measurement methods of audio characteristics – Part 1: General*

IEC 61672-1, *Electroacoustics – Sound level meters – Part 1: Specifications*

IEC 61883-6, *Consumer audio/video equipment – Digital interface – Part 6: Audio and music data transmission protocol*

IEC 61938, *Audio, video and audiovisual systems – Interconnections and matching values – Preferred matching values of analogue signals*

### 3 Terms, definitions, explanations and rated values

#### 3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 61606-1 as well as the following apply.

##### 3.1.1

##### **analogue full-scale amplitude**

nominal signal level of an EUT corresponding to the digital full-scale level

NOTE In order to accommodate the EUT in an audio system, it is recommended that the analogue full scale amplitude has the value defined in IEC 61938. In the case of general purpose audio for consumer equipment, the amplitude is 2 V r.m.s.

### 3.1.2

#### **normal load impedance**

value defined in IEC 61938, or in the case of general purpose audio for consumer equipment, 22 k $\Omega$

### 3.1.3

#### **normal measuring level**

analogue signal level equal to –20 dB of analogue full-scale amplitude

### 3.1.4

#### **normal source impedance**

value defined in IEC 61938, or in the case of general purpose audio for consumer equipment, 2,2 k $\Omega$

## 3.2 Explanation of terms “jitter”

See 3.2 of IEC 61606-1.

## 3.3 Digital interface for measurement

This standard can be applied to IEC 60958 or IEC 61883-6.

Other interfaces having the same specification as in 3.1 of IEC 61606-1 may also be used.

## 3.4 Rated values

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)

For a full explanation of these terms, see IEC 60268-2. The following are rated conditions for digital audio equipment which should be specified by the manufacturer:

[IEC 61606-2:2009](https://standards.iteh.ai/catalog/standards/sist/3d179297-b90b-4740-b297-b6f3982690e0/iec-61606-2-2009)

- rated supply voltage; <https://standards.iteh.ai/catalog/standards/sist/3d179297-b90b-4740-b297-b6f3982690e0/iec-61606-2-2009>
- rated supply frequency;
- rated pre-emphasis and de-emphasis characteristics;
- rated digital input word length;
- rated sampling frequencies.

## 4 Measuring conditions

### 4.1 General

The measuring conditions applied in this part are the same as those given in IEC 61606-1, together with those given below.

### 4.2 Environmental conditions

As specified in 4.1 of IEC 61606-1.

### 4.3 Power supply

As specified in 4.2 of IEC 61606-1.

### 4.4 Test signal frequencies

As specified in 4.3 of IEC 61606-1.

### 4.5 Standard setting

As specified in 4.4 of IEC 61606-1.

## 4.6 Preconditioning

As specified in 4.5 of IEC 61606-1.

## 4.7 Measuring instruments

### 4.7.1 General

All specifications given in IEC 61606-1 are applicable, together with those given below.

### 4.7.2 Digital level meter

The r.m.s. signal level,  $V_{\text{total}}$  is calculated from the digital data within the in-band frequency range.

One method of calculation is as follows:

When the frequency components are calculated by the FFT method, the signal level is calculated as follows. All of the frequency components which are within the in-band frequency range are calculated using the following equation:

$$V_{\text{total}} = (V_{f1}^2 + V_{f2}^2 + V_{f3}^2 + \dots + V_{fn}^2)^{1/2}$$

The signal level  $S$  in dB<sub>FS</sub> is calculated from the following equation:

$$S \text{ dB}_{\text{FS}} = 20 \log_{10} (V_{\text{total}} / V_{\text{full}})$$

where  $V_{\text{full}}$  is the r.m.s. value of the full-scale amplitude of a 1 kHz signal.

The number of data points for the FFT calculation is greater than the value of  $f_s$ . The window used for the measurement shall be the minimum window having the following parameters:

$$W(t) = 1/L [a_0 + a_1 \cos(2\pi t/L) + a_2 \cos(4\pi t/L) + a_3 \cos(6\pi t/L)]$$

where

$L$  is the number of data points,

$$a_0 = 0,363\ 491\ 2,$$

$$a_1 = 0,489\ 268\ 2,$$

$$a_2 = 0,136\ 508\ 8,$$

$$a_3 = 0,010\ 731\ 8,$$

and  $t \leq L/2$ .

NOTE If the signal level is calculated directly using digital data, it should be filtered to the in-band frequency range before the calculation.

### 4.7.3 Distortion meter

Calculate the ratio of the total signal output to the noise and distortion component.

NOTE One measurement method is as follows.

The r.m.s. signal level,  $V_{\text{total}}$  is calculated from the resultant in-band frequency components of the fast Fourier Transformation (FFT) of the processed input signal:

$$V_{\text{total}} = (V_{f1}^2 + V_{f2}^2 + V_{f3}^2 + \dots + V_{fn}^2)^{1/2}$$

$V_N$ , is obtained by the FFT for frequency ranges from 4 Hz to  $f_L$ , which is 1/1,5 of the measuring frequency and  $f_H$  which is 1,5 times the measuring frequency to the upper limit frequency  $f_{\text{MAX}}$ ,  $V_N$  is derived from the following equation:

$$V_N = ((V_{f1}^2 + V_{f2}^2 + V_{f3}^2 + \dots + V_{fL}^2) + (V_{fH}^2 + V_{fH+1}^2 + V_{f\text{MAX}}^2))^{1/2}$$

The total distortion  $D$  is obtained from the equation:

$$D = V_N / V_{\text{total}} \times 100 \quad \%$$

The conditions for the measurement are the same as those for the digital level meter.

#### 4.7.4 Analogue weighting filter

The weighing filter used shall have A-weighting characteristics with tolerances  $\pm 1$  dB as specified for sound level measurements in IEC 61672-1.

#### 4.7.5 Digital weighting filter

The characteristics of weighing filter shall comply with A-weighting characteristics with tolerances  $\pm 1$  dB as specified for sound level measurements in IEC 61672-1.

#### 4.7.6 Digital spectrum analyzer IEC 61606-2:2009

A digital spectrum analyzer computes the Fast Fourier transform (FFT) of the input digital signal.

### 5 Methods of measurement (digital-in/analogue-out)

#### 5.1 General

The methods of measurement described in the following sub-clauses apply to the equipment where the input signal is a digital audio signal and the output signal is an analogue signal. All the specifications described in IEC 61606-1 which correspond to this standard are applied to these subclauses.

These subclauses specify the details of measurement methods for consumer use equipment.

If the EUT provides two or more channels, all channels should be measured in the same way. The word length and sampling frequency shall be stated in the expression of the results of the measurement.

#### 5.2 Input/output characteristics

##### 5.2.1 Maximum output amplitude

##### 5.2.1.1 Input signal

Frequency: 997 Hz

Signal level: full-scale level.

### 5.2.1.2 Procedures

Set the EUT to the standard setting specified in 4.5.


Apply the input signal to the EUT.

Adjust the level control and measure the maximum output voltage which does not show clipping and has total distortion of less than 1 %.

## 5.2.2 Gain difference between channels

### 5.2.2.1 Block diagram of measuring devices

Connect the EUT and measuring instrument as in Figure 1.



IEC 2407/03

**Figure 1 – Connection diagram of equipment**

### 5.2.2.2 Input signal

Frequency: 997 Hz.

Signal level: normal measuring level (-20 dBFS).

### 5.2.2.3 Procedure

[IEC 61606-2:2009](https://standards.iteh.ai/catalog/standards/sist/3d179297-b90b-4740-b297-b6f3982690e0/iec-61606-2-2009)

The following procedure applies. <https://standards.iteh.ai/catalog/standards/sist/3d179297-b90b-4740-b297-b6f3982690e0/iec-61606-2-2009>


- Set the EUT to the standard settings specified in 4.5.
- Adjust the gain control (if any) to the maximum position. Apply the same input signal to all channels to be measured, either simultaneously or in turn.
- Measure the output level of each channel.
- The gain difference between the channels is expressed in dB.

## 5.3 Frequency characteristics

### 5.3.1 Frequency response

#### 5.3.1.1 Block diagram of measuring devices

Connect the EUT and measuring instruments as shown in Figure 2.



IEC 2408/03

**Figure 2 – Connection diagram of equipment**

### 5.3.1.2 Input signal

The following characteristics apply.