

# PUBLICLY AVAILABLE SPECIFICATION

## PRE-STANDARD

Reed contact units –  
Part 2-1: Heavy-duty reed switches – Quality assessment specification

iTeh Standards  
(<https://standards.iteh.ai>)  
Document Preview

IEC/PAS 62246-2-1:2008

<https://standards.iteh.ai/catalog/standards/iec/10682cc5-0f78-482f-8a7c-615692891fc2/iec-pas-62246-2-1-2008>

WITHDRAWN



## THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2008 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland  
Email: [inmail@iec.ch](mailto:inmail@iec.ch)  
Web: [www.iec.ch](http://www.iec.ch)

### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

### About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: [www.iec.ch/searchpub](http://www.iec.ch/searchpub)

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: [www.iec.ch/online\\_news/justpub](http://www.iec.ch/online_news/justpub)

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: [www.electropedia.org](http://www.electropedia.org)

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.


- Customer Service Centre: [www.iec.ch/webstore/custserv](http://www.iec.ch/webstore/custserv)

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: [csc@iec.ch](mailto:csc@iec.ch)

Tel.: +41 22 919 02 11

Fax: +41 22 919 03 00



# PUBLICLY AVAILABLE SPECIFICATION

## PRE-STANDARD

---

**Reed contact units –  
Part 2-1: Heavy-duty reed switches – Quality assessment specification**

iTeh Standards  
(<https://standards.iteh.ai>)  
Document Preview

IEC PAS 62246-2-1:2008

<https://standards.iteh.ai/catalog/standards/iec/10682cc5-0f78-482f-8a7c-615692891fc2/iec-pas-62246-2-1-2008>

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

PRICE CODE

W

## CONTENTS

FOREWORD.....	3
1 Scope.....	5
2 Normative references .....	5
3 Test schedules .....	5
3.1 General .....	5
3.2 Qualification approval procedures .....	6
3.3 Quality conformance inspection.....	6
3.4 Formation of inspection lots.....	6
3.5 Intervals between tests.....	6
3.6 Standard conditions for testing .....	6
3.7 Mounting of test specimens during the test.....	6
3.8 General conditions for testing.....	6
4 Characteristic values of the heavy-duty reed switches.....	33
4.1 Standard test coil number for tests .....	33
4.2 Contact data.....	33
4.2.1 Contact reliability, electrical endurance, rated making and breaking current capacities and switching frequency.....	33
4.2.2 Static contact-circuit resistance.....	36
4.2.3 Mechanical endurance.....	36
4.3 Environmental data.....	36
5 Reliability – Failure rate data.....	36
6 Marking and documentation.....	37
6.1 Marking of the heavy-duty reed switch.....	37
6.2 Marking of the packaging.....	37
Annex A (normative) Mounting in a standard coil .....	38
Annex B (normative) Variants .....	39
Annex C (informative) Typical applications.....	40
Figure A.1 – Switch direction and position in a standard coil.....	38
Table 1 – Quality conformance inspection.....	7
Table 2 – Tests for qualification approval.....	15
Table 3 – Qualification approval.....	30
Table 4 – Characteristic values for general data .....	33
Table 5 – Standard test coil number for tests .....	33
Table 6 – Data for contact reliability, electrical endurance, making current capacity, breaking current capacity, and rated making and breaking capacities .....	34
Table 7 – Environmental data .....	36
Table 8 – Reliability data .....	36

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

## REED CONTACT UNITS –

Part 2-1: Heavy-duty reed switches –  
Quality assessment specification

## FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

A PAS is a technical specification not fulfilling the requirements for a standard, but made available to the public.

IEC/PAS 62246-2-1 has been processed by IEC Technical Committee 94: All-or-nothing electrical relays.

The text of this PAS is based on the following document:

This PAS was approved for publication by the P-members of the committee concerned as indicated in the following document

Draft PAS	Report on voting
94/264/NP	94/271/RVN

Following the publication of this PAS, which is a pre-standard publication, the technical committee or subcommittee concerned will transform it into an International Standard. It is intended to incorporate its contents into the next edition of IEC 62246-2 during the upcoming maintenance cycle for that standard.

This PAS shall remain valid for an initial maximum period of 3 years starting from the publication date. The validity may be extended for a single 3-year period, following which it shall be revised to become another type of normative document, or shall be withdrawn.

**Withdrawn**

iTeh Standards  
(<https://standards.iteh.ai>)  
Document Preview

[IEC PAS 62246-2-1:2008](https://standards.iteh.ai/cats/iec-standards/iec/106b2cc5-0f78-482f-8a7c-615692891fc2/iec-pas-62246-2-1-2008)

<https://standards.iteh.ai/cats/iec-standards/iec/106b2cc5-0f78-482f-8a7c-615692891fc2/iec-pas-62246-2-1-2008>

## REED CONTACT UNITS –

### Part 2-1: Heavy-duty reed switches – Quality assessment specification

#### 1 Scope

This PAS defines requirements and tests for heavy-duty reed switches intended to be incorporated into devices that can be used in various industrial applications.

This PAS is to be used in conjunction with IEC 62246-2.

This PAS selects from IEC 62246-2 and from other sources the appropriate test procedures to be used in detail specifications derived from this PAS.

Two different product variants (variant A and variant B) are specified depending on characteristic values and tests (see Annex B).

#### 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60068-2-11 (1981): *Environmental testing – Part 2: Tests. Test Ka: Salt mist*

IEC 60068-2-14 (1984): *Environmental testing – Part 2: Tests. Test N: Change of temperature*

IEC 60068-2-20 (1979): *Environmental testing. Part 2: Tests. Test T: Soldering*  
Amendment 2 (1987)

IEC 60068-2-21 (2006): *Environmental testing – Part 2-21: Tests – Test U: Robustness of terminations and integral mounting devices*

IEC 60068-2-29 (1987): *Environmental testing. Part 2: Tests. Test Eb and guidance: Bump*

IEC 60068-2-78 (2001): *Environmental testing – Part 2-78: Tests – Test Cab: Damp heat, steady state*

IEC 60127-2 (2003): *Miniature fuses – Part 2: Cartridge fuse-links*

IEC 61373 (1999): *Railway applications – Rolling stock equipment – Shock and vibration tests*

IEC 62246-1 (2002): *Reed contact units – Part 1: Generic specification*

IEC 62246-2 (2007): *Reed contact units – Part 2: Heavy-duty reed switches*

#### 3 Test schedules

##### 3.1 General

Test procedures are referenced in the corresponding subclauses of IEC 62246-2.

### 3.2 Qualification approval procedures

Qualification approval procedures are indicated in Table 2 and Table 3:

- sampling and test schedule are specified in Table 2 and Table 3;
- the tests specified and their order is mandatory;
- tests stated in Table 2 are mandatory for the variants except when otherwise specified;
- tests stated in Table 3 are mandatory only for the variants indicated.

### 3.3 Quality conformance inspection

Quality conformance inspection contains the tests stated in Table 1:

- Group A: routine tests;
- Groups A and B: lot-by-lot tests;
- Group C: periodic tests.

Unless otherwise stated in this PAS, all tests of Table 1 are mandatory.

Where a subgroup contains cumulative tests, the order of the tests is mandatory. Specimens that have been subjected to tests denoted as destructive (D) shall not be released for delivery. Specimens that have been subjected to tests denoted as non-destructive (ND) are permitted to be released for delivery.

### 3.4 Formation of inspection lots

The basis for determination of sample size for the quality conformance inspection is the heavy-duty reed switch quantity produced during one month.

### 3.5 Intervals between tests

The following are the intervals necessary between tests:

- Subgroup A0: at shipment;
- Subgroups A4 and B1: at least once a month;
- Subgroup C1: at least once a year;
- Subgroup C4: at least once every two years.

### 3.6 Standard conditions for testing

If not otherwise stated, all tests shall be performed under standard conditions for testing according to 3.3 of IEC 62246-1.

### 3.7 Mounting of test specimens during the test

The following requirement shall apply for shock and vibration tests:

The heavy-duty reed switch shall be mounted by its normal mounting method to the test fixture, where inherent resonances have been minimized so as not to invalidate the test.

### 3.8 General conditions for testing

Unless otherwise stated, the test coil number and when applicable its polarity specified in Table 5 shall be used for all tests. Unless otherwise stated in this PAS, the polarity shall be as specified by the manufacturer.



**Table 1 – Quality conformance inspection****Group A  
Subgroup A0**

For all tests in this subgroup: 100 % test.

Test No.	Test	Test conditions according to IEC 62246-2	Performance requirements
A0 – 1	Visual inspection and check of dimensions (ND)	Subclause 3.4	According to Table 4 Marking as specified in 6.1
A0 – 2	Functional tests (ND)	Subclause 3.5, Procedure 1 Application points and standard test coil number: Must-operate value: Saturate value: 150 % of must-operate Must-release value: Contact failure-to-make and failure-to-break by monitoring a current, typically 10 mA at 24 V d.c.	According to Table 5 According to Table 4
A0 – 3	Contact-circuit resistance (ND)	Subclause 3.7 Application points: terminals of closed contacts Standard test coil number: Test coil voltage: 150 % of must-operate Test voltage max.: 6 V d.c. Test current max.: 1 A	Initial value according to Table 4 According to Table 5
A0 – 4	Dielectric test (ND)	Subclause 3.8 Application points and test voltage. Duration of test: 1 min A shorter test with a higher voltage may be stated in the detail specification	According to Table 4 Maximum leakage current: 0,5 mA
A0 – 5	Operate, release, transfer or bridging and bounce times (ND)	Subclause 3.10 Application points and standard test coil number: Test coil voltage: 150 % of must-operate 1) operate time 2) release time 3) operate bounce time Contact failure-to-make and failure-to-break by monitoring a current, typically 10 mA at 24 V d.c.	According to Table 5 According to Table 4
A0 – 6	Sealing (ND)	Subclause 3.22 Application points and standard test coil number: Arc time during test: Test coil voltage: 150 % of must-operate Test voltage: 100 V – 110 V d.c. Test current: 0,5 A – 0,55 A Total number of operations required: 3	According to Table 5 According to Table 7

**Table 1 – Quality conformance inspection (continued)**

**Subgroup A4** (period: inspection lot refers to the production volume in one month)

Test No.	Test	Test conditions according to IEC 62246-2	IL	AQL	Performance requirements
1	Visual inspection and check of dimensions (ND)	Subclause 3.4			According to Table 4 Marking as specified in 6.1
2	Functional tests (ND)	Subclause 3.5, Procedure 1  Application points and standard test coil number:  Must-operate value: Saturate value: 150 % of must-operate Must-release value:  Contact failure-to-make and failure-to-break by monitoring a current, typically 10 mA at 24 V d.c.			According to Table 5  According to Table 4
3	Contact-circuit resistance (ND)	Subclause 3.7  Application points: terminals of closed contacts Standard test coil number:  Test coil voltage: 150 % of must-operate Test voltage max.: 6 V d.c. Test current max.: 1 A			Initial value according to Table 4  According to Table 5
4	Dielectric test (ND)	Subclause 3.8  Application points and test voltage:  Duration of test: 1 min  A shorter test with a higher voltage may be stated in the detail specification	S4	1,0	According to Table 4  Maximum leakage current: 0,5 mA
5	Operate, release, transfer or bridging and bounce times (ND)	Subclause 3.10  Application points and standard test coil number:  Test coil voltage: 150 % of must-operate  1) operate time: 2) release time: 3) operate bounce time:  Contact failure-to-make and failure-to-break by monitoring a current, typically 10 mA at 24 V d.c.			According to Table 5  According to Table 4
6	Sealing (ND)	Subclause 3.22  Application points and standard test coil number:  Arc time during test:  Test coil voltage: 150 % of must-operate  Test voltage: 100 V – 110 V d.c. Test current: 0,5 A – 0,55 A Total number of operations required: 3			According to Table 5  According to Table 7

**Table 1 – Quality conformance inspection (continued)****Subgroup B1** (period: inspection lot refers to the production volume of one month)

Test No.	Test	Test conditions according to IEC 62246-2	IL	AQL	Performance requirements
7	Contact reliability test (D)	Subclause 3.32 Test switch type and standard test coil number: Test coil voltage: 150 % of must-operate Coil suppression: N/A Duty cycle: 50 % Switching load conditions: Monitoring conditions: Final measurements: Test 3 – contact-circuit resistance Test 2 – functional tests	S3	2,5	According to Table 5 According to Table 6 According to Table 6 At each cycle during the test According to Table 4 According to Table 4

iTeh Standards  
 (https://standards.itih.ai)  
 Document Preview

IEC PAS 62246-2-1:2008

https://standards.itih.ai/catalog/standards/iec/10682cc5-0f78-482f-8a7c-615692891fc2/iec-pas-62246-2-1-2008

**Table 1 – Quality conformance inspection (continued)**

**Subgroup C1 (period: one year)**

Test No.	Test	Test conditions according to IEC 62246-2	Sample size	Acceptable number of failures	Performance requirements
8	Robustness of terminals (D)	<p>Subclause 3.12 (in accordance with IEC 60068-2-21)</p> <p>Procedure: test Ua1 – tensile</p> <p>Final measurements:</p> <p>Test 1 – visual inspection</p> <p>Test 2 – functional tests</p> <p>Test 6 – sealing</p>	6	0	<p>According to Table 4</p> <p>No breaking or loosening of terminals</p> <p>No cracks or other deterioration</p> <p>According to Table 4</p> <p>According to Table 7</p>
9	Soldering (D)	<p>Subclause 3.13 (in accordance with IEC 60068-2-20, test Ta, method 1)</p> <p>Temperature: (235 ± 5) °C</p> <p>Duration: (2 ± 0,5) s</p> <p>Application point: 5 mm from the glass-to-metal seals</p> <p>Subclause 3.13 (in accordance with IEC 60068-2-20, test Ta, method 2)</p> <p>Temperature: (350 ± 5) °C</p> <p>Duration: (3 ± 0,5) s</p> <p>Application point: 5 mm from the glass-to-metal seals</p> <p>Final measurements:</p> <p>Test 1 – visual test</p> <p>Test 2 – functional tests</p> <p>Test 6 – sealing</p>	5	0	<p>The dipped surface shall be 95 % covered with new solder coating, the remaining 5 % may contain only small pinholes</p> <p>No cracks or other deterioration</p> <p>According to Table 4</p> <p>According to Table 7</p>