



SLOVENSKI STANDARD
SIST EN 3290:2001
01-januar-2001

Aerospace series - Bearings, airframe rolling - Single row self-aligning roller bearings in steel - Diameter series 3 and 4 - Dimensions and loads

Aerospace series - Bearings, airframe rolling - Single row self-aligning roller bearings in steel - Diameter series 3 and 4 - Dimensions and loads

Luft- und Raumfahrt - Flugwerklager - Einreihige Tonnenlager - Einreihige Tonnenlager aus Stahl - Durchmesserreihen 3 und 4 - Maße und Belastungen

Série aérospatiale - Roulements pour structures d'aéronefs - Roulements en acier, à rotule, sur une rangée de rouleaux - Séries de diamètres 3 et 4 - Dimensions et charges

[https://standards.iteh.ai/catalog/standards/sist/bf0a79f6-10ca-43c1-b9ca-](https://standards.iteh.ai/catalog/standards/sist/bf0a79f6-10ca-43c1-b9ca-d79993724c60/sist-en-3290-2001)

Ta slovenski standard je istoveten z: EN 3290:1994

ICS:

49.035	Sestavni deli za letalsko in vesoljsko gradnjo	Components for aerospace construction
--------	--	---------------------------------------

SIST EN 3290:2001

en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 3290:2001](https://standards.iteh.ai/catalog/standards/sist/bf0a79f6-10ca-43c1-b9ca-d79993724c60/sist-en-3290-2001)

<https://standards.iteh.ai/catalog/standards/sist/bf0a79f6-10ca-43c1-b9ca-d79993724c60/sist-en-3290-2001>

EUROPEAN STANDARD

EN 3290

NORME EUROPÉENNE

EUROPÄISCHE NORM

June 1994

UDC 629.7.02:621.822.8.004.1:621.828:669.14

Descriptors: Aircraft industry, airframe bearings, self-aligning bearings, roller bearings, steel, dimensions, static loads

English version

**Aerospace series - Bearings, airframe rolling -
Single row self-aligning roller bearings in steel -
Diameter series 3 and 4 - Dimensions and loads**

Série aérospatiale - Roulements pour structures
d'aéronefs - Roulements en acier, à rotule, sur
une rangée de rouleaux - Séries de diamètres 3
et 4 - Dimensions et charges

Luft- und Raumfahrt - Flugwerkträger -
Einreihige Tonnenlager aus Stahl -
Durchmesserreihen 3 und 4 - Maße und
Belastungen

STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 3290:2001

<https://standards.iteh.ai/catalog/standards/sist/bf0a79f6-10ca-43c1-b9ca-d79993724c60/sist-en-3290-2001>

This European Standard was approved by CEN on 1994-06-07. CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CEN member.

The European Standards exist in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Central Secretariat has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.

CEN

European Committee for Standardization
Comité Européen de Normalisation
Europäisches Komitee für Normung

Central Secretariat: rue de Stassart, 36 B-1050 Brussels

Foreword

This European Standard has been prepared by the European Association of Aerospace Manufacturers (AECMA).

After inquiries and votes carried out in accordance with the rules of this Association, this Standard has successively received the approval of the National Associations and the Official Services of the member countries of AECMA, prior to its presentation to CEN.

This standard was submitted for Formal Vote, and the result was positive.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by December 1994, and conflicting national standards shall be withdrawn at the latest by December 1994.

According to the CEN/CENELEC Internal Regulations, the following countries are bound to implement this European Standard: Austria, Belgium, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland, United Kingdom.

SIST EN 3290:2001

https://standards.itec.org/standards/summary/0ca-43c1-b9ca-47992724c09/sist-en-3290-2001

STANDARD PREVIEW
(standards.itec.ai)

PREPARED BY TECHNICAL GROUP

1 Scope

This standard specifies the characteristics of single row self-aligning roller bearings in steel 1) of diameter series 3 and 4 2) designed to withstand only slow rotations, oscillations and/or swivelling under load.

They are intended for use between fixed and moving parts of the aircraft structure and their control mechanisms.

The airframe rolling bearings defined in this standard are used from $- 54\text{ °C}$ to $+ 150\text{ °C}$.

However, being lubricated with the following greases :

- very high pressure grease, ester type (code A), operational range $- 73\text{ °C}$ to $+ 121\text{ °C}$ or
- very high pressure grease, synthetic hydrocarbons, general purpose (code B), operational range $- 54\text{ °C}$ to $+ 177\text{ °C}$ (see EN 3280),

their field of application when lubricated with code A grease is limited to $+ 121\text{ °C}$.

2 Normative references

This European Standard incorporates by dated or undated reference provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this European Standard only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referred to applies.

ISO 15	Rolling bearings - Radial bearings - Boundary dimensions - General plan
ISO 1132	Rolling bearings - Tolerances - Definitions
EN 2031	Steel FE-PL31 - Hardened and tempered - Bars - Aerospace series 3)
EN 2221	Steel FE-PL31 - Hardened and tempered - Hollow bars $3,5\text{ mm} \leq a \leq 55\text{ mm}$ - Aerospace series 3)
EN 2222	Steel FE-PL31 - Hardened and tempered - Hand and die forgings - Aerospace series 3)
EN 3280	Aerospace series - Bearings, airframe rolling, rigid or self-aligning - Technical specification
EN 3292	Aerospace series - Bearings, airframe rolling - Single row self-aligning roller bearings in corrosion resisting steel - Diameter series 3 and 4 - Dimensions and loads

3 Definition

For the purposes of this standard, the following definition applies:

Bearing : full complement of rollers (without cage).

4 Symbols

The definitions of tolerances and clearances are given in ISO 1132.

Δ_{dmp}	=	single plane mean bore diameter deviation
Δ_{Dmp}	=	single plane mean outside diameter deviation
Δ_{ds}	=	deviation of a single bore diameter
Δ_{Ds}	=	deviation of a single outside diameter
G_a	=	axial internal clearance
G_r	=	radial internal clearance
K_{Ia}	=	radial runout of assembled bearing inner ring
K_{Oa}	=	radial runout of assembled bearing outer ring
$F_a\text{ max.}$	=	permissible static axial load
C_s	=	permissible static radial load
P_{or}	=	static equivalent radial load
F_a	=	bearing axial load, axial component of actual bearing load
F_r	=	bearing radial load, radial component of actual bearing load.

1) For new design, use preferably bearings in corrosion resisting steel, see EN 3292

2) See ISO 15

3) Published as AECMA Standard at the date of publication of this standard

5 Required characteristics

5.1 Dimensions - Tolerances - Clearances - Loads - Mass

Configuration : see figure 1 ; the bearings are fitted with either seals or shields.
Values : see table 1.

5.2 Surface roughness

Raceways and rolling elements : $R_a = 0,2 \mu\text{m}$

Bore, side faces and cylindrical outer surface : $R_a = 0,8 \mu\text{m}$.

5.3 Materials


Inner ring : EN 2031 or EN 2221 or EN 2222, 59 HRC to 64 HRC

Outer ring : EN 2031 or EN 2221 or EN 2222, 59 HRC to 64 HRC

Rollers : EN 2031, 59 HRC to 64 HRC

Shields : Corrosion resisting material

Seals : Polytetrafluoroethylene (PTFE) or polytetrafluoroethylene (PTFE) reinforced with fibreglass.



NOTE : The installation of seals and shields is at the manufacturer's option.

Figure 1

Table 1

Dimensions in millimetres

d		B	C	D	d1 min.	F max. 1)	G max. 1)	Tolerances μm				r	Mass kg/1000 parts \approx	
Code	Nominal	0 - 0,12	0 - 0,12					Δ_{dmp}	Δ_{Dmp}	Δ_{ds}	Δ_{Ds}			
08	8	17	14	30	14	14	24,9	0 - 8	0 - 9	+ 2 - 10	+ 2 - 11	0,3 to 0,8	58	
10	10	21	17	35	15,7	18	28		0 - 11	+ 3 - 11	+ 3 - 14		0,3 to 0,8	91
12	12			37	18		30,7							106
15	15			42	21,8		35,5							132
17	17			23	19		47							25,1
20	20	26	21	52	28	22	44,8	0 - 10	0 - 13	+ 3 - 13	+ 4 - 17	0,3 to 1	246	
25	25	29	24	62	34,5	25	53,3						397	
30	30	34	27	72	41,3	30	63						610	

d Code	Internal clearances μm				Runout tolerances radial max. μm		Starting torque 2) in mN.m		Permissible static loads 3) kN	
	Axial max. G_a		Radial G_r		Code P	Code E	Axial F_a max.	Radial C_s		
	Special group Code R	Group Code K	Special group Code R	Group Code K						
08	190	230	2 to 7	10 to 20	25	40	7	11	11,1	36,7
10							10	15,5	16,3	53,9
12	200	240	3 to 9				15	23	18,2	60,2
15							20	30	21,1	69,6
17							25	38	28,6	94,5
20	220	250	3 to 10				15 to 25	30	45	34,3
25	240	290		35	52	49		161,7		
30				40	60	65,3		215,6		

1) Dimensions of the shields are at the manufacturer's option within the limits of F and G.


2) Definition, see EN 3280.

3) $F_r + 3,3 F_a = P_{or}$; P_{or} shall be $\leq C_s$.

For ultimate static loads, see EN 3280.

6 Designation

EXAMPLE :



NOTE : If necessary, the code 19005 shall be placed between the description block and the identity block.

7 Marking

In addition to the manufacturer's own marking, each bearing shall be marked, on one side face only, using the identity block, see 6.

Marking position and method are at the manufacturer's option.

<https://standards.iteh.ai/catalog/standards/sist/bf0a79f6-10ca-43c1-b9ca-d79993724c60/sist-en-3290-2001>

8 Technical specification

See EN 3280.