

INTERNATIONAL STANDARD

NORME INTERNATIONALE



Electric appliances connected to the water mains – Avoidance of backsiphonage and failure of hose-sets

(<https://standards.iteh.ai>)

Appareils électriques raccordés au réseau d'alimentation en eau – Exigences pour éviter le retour d'eau par siphonnage et la défaillance des ensembles de raccordement

IEC 61770:2008

<https://standards.iteh.ai/catalog/standards/iec/50901656-831c-4870-b10b-e9220b4fdb7/iec-61770-2008>



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2015 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in 15 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

More than 60 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Catalogue IEC - webstore.iec.ch/catalogue

Application autonome pour consulter tous les renseignements bibliographiques sur les Normes internationales, Spécifications techniques, Rapports techniques et autres documents de l'IEC. Disponible pour PC, Mac OS, tablettes Android et iPad.

Recherche de publications IEC - www.iec.ch/searchpub

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études,...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire en ligne de termes électroniques et électriques. Il contient plus de 30 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans 15 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

Glossaire IEC - std.iec.ch/glossary

Plus de 60 000 entrées terminologiques électrotechniques, en anglais et en français, extraites des articles Termes et Définitions des publications IEC parues depuis 2002. Plus certaines entrées antérieures extraites des publications des CE 37, 77, 86 et CISPR de l'IEC.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: csc@iec.ch.

INTERNATIONAL STANDARD

NORME INTERNATIONALE



**Electric appliances connected to the water mains – Avoidance of
backsiphonage
and failure of hose-sets**

**Appareils électriques raccordés au réseau d'alimentation en eau – Exigences
pour éviter le retour d'eau par siphonnage et la défaillance des ensembles de
raccordement**

[IEC 61770:2008](https://standards.iteh.ai/IEC/61770/2008)

<https://standards.iteh.ai/catalog/standards/iec/50901656-831c-4870-b10b-e9220b4fdb7/iec-61770-2008>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 91.140.60, 97.030

ISBN 978-2-8322-2967-5

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

REDLINE VERSION

VERSION REDLINE



Electric appliances connected to the water mains – Avoidance of backsiphonage and failure of hose-sets

(<https://standards.iteh.ai>)

Appareils électriques raccordés au réseau d'alimentation en eau – Exigences pour éviter le retour d'eau par siphonnage et la défaillance des ensembles de raccordement

[IEC 61770:2008](#)

<https://standards.iteh.ai/catalog/standards/iec/50901656-831c-4870-b10b-e9220b4fdb7/iec-61770-2008>

CONTENTS

FOREWORD..... 3

1 Scope.....5

2 Normative references5

3 Terms and definitions5

4 General requirements6

5 General conditions for the tests7

6 Airgaps.....8

7 Pipe interrupters8

8 Dynamic backflow preventers9

9 Hose-sets 10

Annex A (normative) Backsiphonage test.....21

Figure 1 – Arrangement for the determination of "h" for pipe interrupters 14

Figure 2 – Arrangement for the determination of maximum and critical water levels for pipe interrupters 15

Figure 3 – Kinking test 16

Figure 4 – Arrangement for verifying the resistance of hose-sets to pulses 16

Figure 5 – Mandrel for testing coupling nuts 17

Figure 6 – Mandrel for ozone test on hose-sets 17

Figure 7 – Arrangement for the flexing test 18

Figure 8 – Arrangement for the bending test 19

Figure 9 – Detail for applying the bending moment to coupling tubes 19

Figure 10 – Detail for the impact test on coupling tubes 20

Table 1 – Tests applicable to different types of hoses 10

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ELECTRIC APPLIANCES CONNECTED TO THE WATER MAINS – AVOIDANCE OF BACKSIPHONAGE AND FAILURE OF HOSE-SETS

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This consolidated version of the official IEC Standard and its amendment has been prepared for user convenience.

IEC 61770 edition 2.1 contains the second edition (2008-07) [documents 61/3647/FDIS and 61/3687/RVD] and its amendment 1 (2015-10) [documents 61/4952/FDIS and 61/5004/RVD].

In this Redline version, a vertical line in the margin shows where the technical content is modified by amendment 1. Additions are in green text, deletions are in strikethrough red text. A separate Final version with all changes accepted is available in this publication.

International Standard IEC 61770 has been prepared by IEC technical committee 61: Safety of household and similar electrical appliances.

The principal changes in this edition as compared with the first edition are as follows (minor changes are not listed):

- normative references are updated;
- some notes have been converted to normative text (3.10, 5.2, 6.3, 7.2 and Annex A);
- the type of petroleum spirit has been specified (9.3).

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

NOTE 1 The following print types are used:

- requirements: in roman type;
- *test specifications: in italic type;*
- notes: in small roman type.

Words in **bold** in the text are defined in Clause 3. When a definition concerns an adjective, the adjective and the associated noun are also in bold.

The committee has decided that the contents of the base publication and its amendment will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

NOTE 2 The attention of National Committees is drawn to the fact that equipment manufacturers and testing organizations may need a transitional period following publication of a new, amended or revised IEC publication in which to make products in accordance with the new requirements and to equip themselves for conducting new or revised tests.

It is the recommendation of the committee that the content of this standard be adopted for implementation nationally not earlier than 12 months nor later than 36 months from the date of its publication.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

ELECTRIC APPLIANCES CONNECTED TO THE WATER MAINS – AVOIDANCE OF BACKSIPHONAGE AND FAILURE OF HOSE-SETS

1 Scope

This International Standard specifies requirements for appliances for household and similar purposes to prevent the backsiphonage of **non-potable water** into the water mains. It also specifies requirements for **hose-sets** used for connecting such appliances to the water mains that supply water at a pressure not exceeding 1 MPa.

NOTE 1 Examples of similar purposes are the installation of appliances in canteens, restaurants, laundrettes and communal flats.

NOTE 2 This standard does not apply to

- appliances used for dry cleaning;
- appliances for medical purposes;
- appliances intended for industrial purposes;
- water heaters that are an integral part of the water supply system;
- water coolers that are an integral part of the water supply system.

NOTE 3 The connection of the appliance to the water mains may be temporary or permanent.

NOTE 4 When reference is made to the water mains, water supplied from a cistern or similar system is also included.

NOTE 5 Many countries have requirements concerning the prevention of contamination of potable water as a result of contact with unsuitable materials upstream of a **backflow prevention device**.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60730-2-8, *Automatic electrical controls for household and similar use – Part 2: Particular requirements for electrically operated water valves, including mechanical requirements*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

potable water

water which is obtained directly from the potable water mains and remains in a closed system up to the **backflow prevention device**

3.2

non-potable water

water which leaves the closed system after having passed the **backflow prevention device**

3.3

backflow prevention device

means to prevent contamination of **potable water** by backflow of **non-potable water**

NOTE Examples are **airgaps**, **dynamic backflow preventers** and **pipe interrupters**.

3.4**airgap**

unobstructed free distance between the water inlet or the end of the feed pipe and the **critical water level**

NOTE A distance is considered to be unobstructed if the airflow into the feed pipe under vacuum conditions is not restricted by the construction of the appliance.

3.5**pipe interrupter**

device without movable or elastomeric parts, into which air can enter while water is passing through it

3.6**dynamic backflow preventer**

backflow prevention device which prevents backsiphonage by the use of moving parts

3.7**overflow**

means for discharging excess water from the appliance when the normal outlet is obstructed

3.8**maximum water level**

highest level of the **non-potable water** in any part of the appliance when it operates continuously under fault conditions

3.9**critical water level**

level to which the **non-potable water** is reduced from the **maximum water level** 2 s after water inlets have been closed

3.10**hose-set**

assembly consisting of a flexible hose and couplings and used for connecting the appliance to the water mains

Note 1 to entry: **Hose-sets need not be pre-assembled.** Couplings may be removable with or without the aid of a tool.

3.11**detachable part**

part which can be removed without the aid of a tool

4 General requirements

4.1 Appliances shall be provided with a **backflow prevention device**.

For appliances incorporating a water softener located upstream of an **airgap** or **pipe interrupter**, a **dynamic backflow preventer** shall be incorporated upstream of the water softener.

Other components presenting a potable water hazard, such as dispensers for adding cleaning, rinsing, softening or similar agents to the water, shall not be located upstream of the **backflow prevention device**.

Pipework containing **potable water** located upstream of a **backflow prevention device** shall not pass through **non-potable water** in the appliance.

Compliance is checked by inspection.

NOTE For a given point in a hydraulic system, "upstream" indicates the side from which the water flows and "downstream" indicates the side to which the water flows.

4.2 Backflow prevention devices shall be incorporated in, or fixed to, the appliance or they shall be incorporated in the inlet side of a **hose set**.

NOTE They may also be incorporated in the water inlet valves.

They shall be constructed so that

- their functional characteristics cannot be changed, even intentionally,
- they can only be removed with the aid of a tool,
- if omitted, the appliance is rendered inoperable or manifestly incomplete.

Compliance is checked by inspection and by manual tests.

4.3 Hose-sets for the connection of appliances to the water mains shall be constructed so that the risk of flooding is obviated as far as possible.

Compliance is checked by the tests of Clause 9.

4.4 Metallic parts of the water connection system of the appliance, the deterioration of which may cause the appliance to fail to comply with the requirements of this standard, shall be resistant to erosion, dezincification, oxidation or corrosion.

Compliance is checked by inspection.

NOTE Resistance to dezincification of brass can be checked in accordance with ISO 6509 ¹⁾.

5 General conditions for the tests

5.1 When reference is made to normal conditions, the following applies:

- the appliance is placed on a horizontal support;
- the appliance is connected to a water supply in accordance with the instructions for installation;
- the water supply has a static pressure not exceeding 1 MPa and a dynamic pressure not less than 0,6 MPa;
- the appliance is supplied at rated voltage;
- the appliance is tested without being loaded and without cleaning, rinsing or similar agents, doors and lids being closed.

NOTE When water pressures are stated, they are pressure differences from atmospheric pressure.

5.2 When reference is made to fault conditions, the appliance is inclined at an angle of 2° to the horizontal in the most unfavourable position. In addition to the normal conditions, the following fault conditions are applied one at a time, as far as is reasonable, consequential faults being taken into consideration:

- the connection between any dispenser intended for adding cleaning, rinsing, softening or similar agents to the water and other parts of the appliance is blocked, unless the cross-sectional area of the connection exceeds 10 cm² throughout its length with no dimension less than 10 mm;

¹⁾ ISO 6509, *Corrosion of metals and alloys – Determination of dezincification resistance of brass*

NOTE Dispenser connections are not blocked if they have cross-sections which are varied by user action each time the appliance is used, such as opening a detergent dispenser.

- **overflows** are blocked if they have
 - a circular cross-section not exceeding 5 cm²,
 - a non-circular cross-section with one dimension less than 3 mm and an area not exceeding 5 cm²,
- all magnetic valves upstream of a **backflow prevention device** which can be open simultaneously during the normal programme of the appliance are held open;
- all motors are disconnected from the supply mains and the normal drain outlet is blocked.

5.3 Unless otherwise specified, the tests are made in the order indicated and

- for appliances, **pipe interrupters** and **dynamic backflow preventers**, on a single sample as supplied, which shall withstand all the relevant tests;
- for **hose-sets**, on three samples. If one sample fails, the tests are repeated on a further set of three samples, all of which shall withstand the repeated tests.

Each of the tests of 9.1.9 to 9.1.11 is carried out on three new samples.

5.4 Tests on **airgaps**, **pipe interrupters** and **dynamic backflow preventers** are made on the appliance, unless this is impracticable or is otherwise specified.

5.5 When determining the **critical water level** of appliances having more than one water inlet, and a programme permitting simultaneous filling, each water inlet is closed in turn, other water inlets being open.

5.6 Unless otherwise specified, the tests are carried out at an ambient temperature of 20 °C ± 5 °C.

6 Airgaps

6.1 **Airgaps** shall be constructed so that the water can flow freely through the air section and that water downstream of the **airgap** cannot be drawn into the feed pipe.

Compliance is checked by inspection and by the tests of 6.2 and 6.3. The test of Annex A may be carried out instead of the test of 6.3.

6.2 The appliance is operated under fault conditions until the **maximum water level** is reached.

The water outlet of the feed pipe shall not come into contact with **non-potable water**.

6.3 The appliance is operated under fault conditions until the **critical water level** is reached.

The length of the **airgap** shall be at least twice the smallest diameter of the water supply system within the appliance, with a minimum of 20 mm. There shall also be a clear space of 20 mm between the outlet of the feed pipe and other parts in any downward direction. The thickness of any water film and the dimensions of waterdrops shall be taken into account.

7 Pipe interrupters

7.1 **Pipe interrupters** shall be constructed so that the air-inlet openings remain permanently free and open to the atmosphere. Water which may leak in normal use from an air-inlet opening shall flow into the container of the appliance but shall not reach a sufficient level for the vertical dimensions to be reduced below those specified in 7.3 and 7.4.

Pipe interrupters shall be protected against deliberate obstruction or manipulation which could affect the results of the tests.

The total cross-sectional area of the air-inlet openings shall not be less than the cross-sectional area of the water-inlet opening. The smallest dimension of each air-inlet opening shall be at least 3 mm. The dimensions are measured at right angles to the direction of the airflow.

Compliance is checked by inspection, measurement and by the tests and measurements of 7.2 to 7.4. However, if the measurements of 7.3 and 7.4 cannot be made due to the construction of the appliance, compliance is checked by the test of Annex A.

7.2 For separate **pipe interrupters**, a vertical tube of glass or other transparent material having approximately the same internal diameter and a length of at least 500 mm, is connected to the outlet of the **pipe interrupter**. The free end of the tube is immersed in water to a depth of at least 25 mm, as shown in Figure 1.

A vacuum pump is connected directly to the inlet of the **pipe interrupter** and a negative pressure of $65 \text{ kPa} \pm 15 \text{ kPa}$ is applied for at least 5 s. The distance h between the water level in the tube and the water level in the container is measured.

For **pipe interrupters** which are incorporated in the appliance downstream of a magnetic valve, the test is carried out in the appliance. The vacuum pump is connected directly to the water inlet of the appliance by means of the shortest possible length of tube.

The cross-sectional area of the connection of the vacuum pump shall be sufficient so that the airflow is not restricted.

NOTE If the inlet hose cannot be removed even with the aid of a tool, the vacuum pump is connected to the inlet of the hose.

7.3 The appliance is operated under fault conditions, until the **maximum water level** is reached.

The vertical distance between the **maximum water level** and the lowest rim of the air-inlet opening of the **pipe interrupter** is measured. It shall be at least equal to dimension h , shown in Figure 2.

7.4 Immediately after the test of 7.3, the water inlet is closed. The vertical distance between the **critical water level** and the lowest rim of the air inlet opening is measured. It shall be at least equal to $h + 20 \text{ mm}$.

The **critical water level** in the hoses connecting the **pipe interrupter** to a water softener downstream of a **dynamic backflow preventer** is also checked.

NOTE If the **critical water level** cannot be observed due to an opaque part or hose, this part or hose is replaced by a transparent part or transparent hose having the same shape and dimensions.

8 Dynamic backflow preventers

8.1 Dynamic backflow preventers shall be constructed so that wear or damage of movable parts, their supports or guides, or the removal of **detachable parts** does not allow backsiphonage. The movable parts shall operate each time the water passes through the device under conditions of normal use and failure of any of them shall render the appliance inoperable or shall be evident to the user.

*Compliance is checked by inspection and by operating the **dynamic backflow preventer** as described in 8.2, followed by the test of Annex A.*

The test of Annex A is carried out under the following conditions:

- with movable parts placed in the most unfavourable position, one at a time;
- after **detachable parts** have been removed;
- after simulating damage to movable parts, including their supports or guides, one at a time.

Only one of these three conditions is applied at any one time.

8.2 The device is operated for 5 000 cycles. Each cycle comprises a period of 3 s during which water flows through the device and a period of 3 s without water flow. The water is at a pressure of 0,2 MPa and has a temperature of

- 15 °C ± 5 °C, for **dynamic backflow preventers** in the cold water supply;
- 65 °C ± 5 °C, for **dynamic backflow preventers** in the hot water supply;
- 65 °C ± 5 °C, for **dynamic backflow preventers** if the inlet is unmarked.

The test is carried out 10 times with a 48 h rest period. Before each test, the **dynamic backflow preventer** is checked to ensure that movable parts operate when water flows through it.

9 Hose-sets

9.1 Hose-sets shall withstand the stresses to which they may be subjected in normal use.

Compliance is checked by the relevant tests specified in 9.1.1 to 9.1.9 as shown in Table 1 for different types of hoses and by the tests of 9.1.10 and 9.1.11 for couplings.

During the tests of 9.1.1 to 9.1.8, the hose shall not leak, burst or slip from its couplings.

NOTE 1 Deformation which does not impair the function of the **hose-set** is ignored.

NOTE 2 Flexible metal **hose-sets** having a length less than 1 m are not subjected to the tests of 9.1.2 and 9.1.3.

NOTE 3 For **hose-sets** which incorporate devices for protection against flooding and the hose of which is contained in a flexible tube, only the hose is subjected to the tests of 9.1.6 to 9.1.8.

NOTE 4 Hoses downstream of a magnetic valve are not subjected to the tests of 9.1.6 to 9.1.8 as long as they cannot come under pressure due to the operation of another magnetic valve.

Table 1 – Tests applicable to different types of hoses

Test	Type of hose				
	Non-thermoplastic	Non-thermoplastic with metal braiding	Thermoplastic	Thermoplastic with metal braiding	Flexible metal
Kinking	9.1.1	–	9.1.1	–	–
Flexing	–	–	–	–	9.1.2
Bending	–	–	–	–	9.1.3
Crushing	–	9.1.4	–	9.1.4	–
Low temperature	–	–	9.1.5	9.1.5	–
Ageing	9.1.6	9.1.6	9.1.6	9.1.6	–
Pulsing	9.1.7	9.1.7	9.1.7	9.1.7	9.1.7
Pressure	9.1.8	9.1.8	9.1.8	9.1.8	9.1.8
Ozone	9.1.9	9.1.9	–	–	–