

INTERNATIONAL STANDARD

NORME INTERNATIONALE



**Adjustable speed electrical power drive systems –
Part 7-204: Generic interface and use of profiles for power drive systems –
Profile type 4 specification**

**Entraînements électriques de puissance à vitesse variable –
Partie 7-204: Interface générique et utilisation de profils pour les entraînements
électriques de puissance – Spécification de profil de type 4**

<https://standards.iteh.ai/catalog/standards/iec/61800-7-204-2007>



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2007 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de la CEI ou du Comité national de la CEI du pays du demandeur.

Si vous avez des questions sur le copyright de la CEI ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de la CEI de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

Useful links:

IEC publications search - www.iec.ch/searchpub

The advanced search enables you to find IEC publications by a variety of criteria (reference number, text, technical committee,...).

It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available on-line and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary (IEV) on-line.

Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

A propos de la CEI

La Commission Electrotechnique Internationale (CEI) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications CEI

Le contenu technique des publications de la CEI est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente. un corrigendum ou amendement peut avoir été publié.

Liens utiles:

Recherche de publications CEI - www.iec.ch/searchpub

La recherche avancée vous permet de trouver des publications CEI en utilisant différents critères (numéro de référence, texte, comité d'études,...).

Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

Just Published CEI - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications de la CEI. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire en ligne au monde de termes électroniques et électriques. Il contient plus de 30 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans les langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (VEI) en ligne.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: csc@iec.ch.

INTERNATIONAL STANDARD

NORME INTERNATIONALE



**Adjustable speed electrical power drive systems –
Part 7-204: Generic interface and use of profiles for power drive systems –
Profile type 4 specification**

**Entraînements électriques de puissance à vitesse variable –
Partie 7-204: Interface générique et utilisation de profils pour les entraînements
électriques de puissance – Spécification de profil de type 4**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

PRICE CODE **XH**
CODE PRIX

ICS 29.200; 35.100.05

ISBN 978-2-8322-0877-9

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

CONTENTS

FOREWORD.....	35
INTRODUCTION.....	37
1 Scope.....	40
2 Normative references	40
3 Terms, definitions and abbreviated terms	40
3.1 Terms and definitions	40
3.2 Abbreviated terms	45
4 General.....	46
5 Data types.....	46
6 Short description of SERCOS data exchange	46
6.1 General.....	46
6.2 Synchronisation.....	47
7 Application function groups	47
7.1 General.....	47
7.2 Scaling of operation data.....	48
7.2.1 General	48
7.2.2 Scaling of position data	48
7.2.3 Scaling of velocity data.....	49
7.2.4 Scaling of torque/force data.....	51
7.2.5 Scaling of acceleration data and jerk data	53
7.2.6 Scaling of temperature data.....	55
7.3 Drive parameters.....	55
7.3.1 Velocity loop parameters	55
7.3.2 Position loop parameters	56
7.3.3 Current loop parameters	57
7.3.4 Drive limit values	57
7.3.5 General drive parameters	57
7.3.6 Spindle parameters	58
7.3.7 Spindle synchronous operation.....	58
7.4 Mechanics.....	59
7.4.1 Feedback systems.....	59
7.4.2 Feed constant.....	59
7.4.3 Gear train.....	60
7.4.4 Polarities	60
7.4.5 Parameter sets and gear ratios.....	61
7.4.6 Switching of parameter sets and gear ratio	62
7.5 Drive operation modes	62
7.5.1 General	62
7.5.2 Selection of the operation mode	63
7.5.3 Switching of the operation mode.....	64
7.6 Homing.....	66
7.6.1 General	66
7.6.2 Drive controlled homing procedure command	66
7.6.3 Control unit controlled homing procedure command	68
7.7 Measurements.....	71

7.8	Position spindle procedure command	72
7.8.1	General	72
7.8.2	Spindle Positioning when the function is started	73
7.8.3	New position values while the procedure command is active	74
7.8.4	Switching the positioning mode angle position/relative offset while the procedure command is active	74
7.9	Velocity window	75
7.10	Position switches	76
7.10.1	General	76
7.10.2	Position switch mode	77
7.10.3	Cam switch mode	77
7.11	PDS state machine control	78
7.11.1	Control and status word	78
7.11.2	Starting/stopping functions (State machine)	80
7.12	Park axis procedure command	83
7.13	Positive stop drive procedure command	83
7.14	Drive controlled synchronous operation procedure command	84
7.14.1	General	84
7.14.2	Synchronisation of the synchronous spindle to the lead spindle with a fixed angular offset	84
7.14.3	New synchronous position offset after synchronisation	85
7.14.4	New speed ratio after synchronisation	85
7.15	Drive controlled gear engaging procedure command	86
8	Identification numbers in numerical order	87
9	Description of identification numbers	100
9.1	IDN S-0-0005 Minimum feedback processing time (t_5)	100
9.1.1	Attributes	100
9.1.2	Description	101
9.2	IDN S-0-0007 Feedback acquisition capture point (t_4)	101
9.2.1	Attributes	101
9.2.2	Description	101
9.3	IDN S-0-0011 Class 1 diagnostic (C1D)	101
9.3.1	Attributes	101
9.3.2	Description	102
9.4	IDN S-0-0012 Class 2 diagnostic (C2D)	103
9.4.1	Attributes	103
9.4.2	Description	103
9.5	IDN S-0-0013 Class 3 diagnostic (C3D)	104
9.5.1	Attributes	104
9.5.2	Description	104
9.6	IDN S-0-0016 Configuration list of AT	105
9.6.1	Attributes	105
9.6.2	Description	105
9.7	IDN S-0-0017 IDN-list of all operation data	105
9.7.1	Attributes	105
9.7.2	Description	105
9.8	IDN S-0-0018 IDN-list of operation data for CP2	105
9.8.1	Attributes	105
9.8.2	Description	106

9.9	IDN S-0-0019 IDN-list of operation data for CP3.....	106
9.9.1	Attributes.....	106
9.9.2	Description.....	106
9.10	IDN S-0-0020 IDN-list of operation data for CP4.....	106
9.10.1	Attributes.....	106
9.10.2	Description.....	107
9.11	IDN S-0-0021 IDN-list of invalid operation data for CP2.....	107
9.11.1	Attributes.....	107
9.11.2	Description.....	107
9.12	IDN S-0-0022 IDN-list of invalid operation data for CP3.....	107
9.12.1	Attributes.....	107
9.12.2	Description.....	108
9.13	IDN S-0-0023 IDN-list of invalid operation data for CP4.....	108
9.13.1	Attributes.....	108
9.13.2	Description.....	108
9.14	IDN S-0-0025 IDN-list of all procedure commands.....	108
9.14.1	Attributes.....	108
9.14.2	Description.....	109
9.15	IDN S-0-0026 Configuration list for signal status word.....	109
9.15.1	Attributes.....	109
9.15.2	Description.....	109
9.16	IDN S-0-0027 Configuration list for signal control word.....	109
9.16.1	Attributes.....	109
9.16.2	Description.....	110
9.17	IDN S-0-0030 Manufacturer version.....	110
9.17.1	Attributes.....	110
9.17.2	Description.....	110
9.18	IDN S-0-0031 Hardware version.....	110
9.18.1	Attributes.....	110
9.18.2	Description.....	111
9.19	IDN S-0-0032 to S-0-0035 Primary operation mode, secondary operation modes 1 to 3.....	111
9.19.1	Attributes.....	111
9.19.2	Description.....	111
9.20	IDN S-0-0036 Velocity command value.....	111
9.20.1	Attributes.....	111
9.20.2	Description.....	112
9.21	IDN S-0-0037 Additive velocity command value.....	112
9.21.1	Attributes.....	112
9.21.2	Description.....	112
9.22	IDN S-0-0038 Positive velocity limit value.....	112
9.22.1	Attributes.....	112
9.22.2	Description.....	113
9.23	IDN S-0-0039 Negative velocity limit value.....	113
9.23.1	Attributes.....	113
9.23.2	Description.....	113
9.24	IDN S-0-0040 Velocity feedback value 1.....	113
9.24.1	Attributes.....	113
9.24.2	Description.....	114

9.25	IDN S-0-0041 Homing velocity.....	114
9.25.1	Attributes.....	114
9.25.2	Description.....	114
9.26	IDN S-0-0042 Homing acceleration.....	114
9.26.1	Attributes.....	114
9.26.2	Description.....	115
9.27	IDN S-0-0043 Velocity polarity parameter.....	115
9.27.1	Attributes.....	115
9.27.2	Description.....	115
9.28	IDN S-0-0044 Velocity data scaling type.....	116
9.28.1	Attributes.....	116
9.28.2	Description.....	116
9.29	IDN S-0-0045 Velocity data scaling factor.....	117
9.29.1	Attributes.....	117
9.29.2	Description.....	117
9.30	IDN S-0-0046 Velocity data scaling exponent.....	117
9.30.1	Attributes.....	117
9.30.2	Description.....	118
9.31	IDN S-0-0047 Position command value.....	118
9.31.1	Attributes.....	118
9.31.2	Description.....	118
9.32	IDN S-0-0048 Additive position command value.....	118
9.32.1	Attributes.....	118
9.32.2	Description.....	119
9.33	IDN S-0-0049 Positive position limit value.....	119
9.33.1	Attributes.....	119
9.33.2	Description.....	119
9.34	IDN S-0-0050 Negative position limit value.....	120
9.34.1	Attributes.....	120
9.34.2	Description.....	120
9.35	IDN S-0-0051 Position feedback value 1 (motor feedback).....	120
9.35.1	Attributes.....	120
9.35.2	Description.....	121
9.36	IDN S-0-0052 Reference distance 1.....	121
9.36.1	Attributes.....	121
9.36.2	Description.....	121
9.37	IDN S-0-0053 Position feedback value 2 (external feedback).....	121
9.37.1	Attributes.....	121
9.37.2	Description.....	122
9.38	IDN S-0-0054 Reference distance 2.....	122
9.38.1	Attributes.....	122
9.38.2	Description.....	122
9.39	IDN S-0-0055 Position polarity parameters.....	122
9.39.1	Attributes.....	122
9.39.2	Description.....	123
9.40	IDN S-0-0057 Position window.....	123
9.40.1	Attributes.....	123
9.40.2	Description.....	124
9.41	IDN S-0-0058 Reversal clearance.....	124

9.41.1	Attributes.....	124
9.41.2	Description.....	124
9.42	IDN S-0-0059 Position switch flag parameter.....	125
9.42.1	Attributes.....	125
9.42.2	Description.....	125
9.43	IDN S-0-0060 to S-0-0075 Position switch points on 1-16.....	125
9.43.1	Attributes.....	125
9.43.2	Description.....	126
9.44	IDN S-0-0076 Position data scaling type.....	126
9.44.1	Attributes.....	126
9.44.2	Description.....	126
9.45	IDN S-0-0077 Linear position data scaling factor.....	127
9.45.1	Attributes.....	127
9.45.2	Description.....	127
9.46	IDN S-0-0078 Linear position data scaling exponent.....	127
9.46.1	Attributes.....	127
9.46.2	Description.....	128
9.47	IDN S-0-0079 Rotational position resolution.....	128
9.47.1	Attributes.....	128
9.47.2	Description.....	128
9.48	IDN S-0-0080 Torque command value.....	129
9.48.1	Attributes.....	129
9.48.2	Description.....	129
9.49	IDN S-0-0082 Positive torque limit value.....	129
9.49.1	Attributes.....	129
9.49.2	Description.....	129
9.50	IDN S-0-0083 Negative torque limit value.....	130
9.50.1	Attributes.....	130
9.50.2	Description.....	130
9.51	IDN S-0-0084 Torque feedback value.....	130
9.51.1	Attributes.....	130
9.51.2	Description.....	130
9.52	IDN S-0-0085 Torque polarity parameter.....	131
9.52.1	Attributes.....	131
9.52.2	Description.....	131
9.53	IDN S-0-0086 Torque/force data scaling type.....	131
9.53.1	Attributes.....	131
9.53.2	Description.....	132
9.54	IDN S-0-0091 Bipolar velocity limit value.....	132
9.54.1	Attributes.....	132
9.54.2	Description.....	133
9.55	IDN S-0-0092 Bipolar torque limit value.....	133
9.55.1	Attributes.....	133
9.55.2	Description.....	133
9.56	IDN S-0-0093 Torque/force data scaling factor.....	133
9.56.1	Attributes.....	133
9.56.2	Description.....	134
9.57	IDN S-0-0094 Torque/force data scaling exponent.....	134
9.57.1	Attributes.....	134

9.57.2	Description	134
9.58	IDN S-0-0095 Diagnostic message	135
9.58.1	Attributes	135
9.58.2	Description	135
9.59	IDN S-0-0097 Mask class 2 diagnostic	135
9.59.1	Attributes	135
9.59.2	Description	135
9.60	IDN S-0-0098 Mask class 3 diagnostic	136
9.60.1	Attributes	136
9.60.2	Description	136
9.61	IDN S-0-0099 Reset class 1 diagnostic	136
9.61.1	Attributes	136
9.61.2	Description	137
9.62	IDN S-0-0100 Velocity loop proportional gain	137
9.62.1	Attributes	137
9.62.2	Description	137
9.63	IDN S-0-0101 Velocity loop integral action time	137
9.63.1	Attributes	137
9.63.2	Description	138
9.64	IDN S-0-0102 Velocity loop differential time	138
9.64.1	Attributes	138
9.64.2	Description	138
9.65	IDN S-0-0103 Modulo value	138
9.65.1	Attributes	138
9.65.2	Description	139
9.66	IDN S-0-0104 Position loop K_V -factor	139
9.66.1	Attributes	139
9.66.2	Description	140
9.67	IDN S-0-0105 Position loop integral action time	140
9.67.1	Attributes	140
9.67.2	Description	140
9.68	IDN S-0-0106 Current loop proportional gain 1	140
9.68.1	Attributes	140
9.68.2	Description	141
9.69	IDN S-0-0107 Current loop integral action time 1	141
9.69.1	Attributes	141
9.69.2	Description	141
9.70	IDN S-0-0108 Feedrate override	141
9.70.1	Attributes	141
9.70.2	Description	142
9.71	IDN S-0-0109 Motor peak current	142
9.71.1	Attributes	142
9.71.2	Description	142
9.72	IDN S-0-0110 Amplifier peak current	142
9.72.1	Attributes	142
9.72.2	Description	143
9.73	IDN S-0-0111 Motor continuous stall current	143
9.73.1	Attributes	143
9.73.2	Description	143

9.74	IDN S-0-0112 Amplifier rated current.....	143
9.74.1	Attributes.....	143
9.74.2	Description.....	144
9.75	IDN S-0-0113 Maximum motor speed.....	144
9.75.1	Attributes.....	144
9.75.2	Description.....	144
9.76	IDN S-0-0114 Load limit of the motor.....	144
9.76.1	Attributes.....	144
9.76.2	Description.....	145
9.77	IDN S-0-0115 Position feedback 2 type.....	145
9.77.1	Attributes.....	145
9.77.2	Description.....	145
9.78	IDN S-0-0116 Resolution of feedback 1.....	146
9.78.1	Attributes.....	146
9.78.2	Description.....	146
9.79	IDN S-0-0117 Resolution of feedback 2.....	146
9.79.1	Attributes.....	146
9.79.2	Description.....	147
9.80	IDN S-0-0118 Resolution of linear feedback.....	147
9.80.1	Attributes.....	147
9.80.2	Description.....	147
9.81	IDN S-0-0119 Current loop proportional gain 2.....	148
9.81.1	Attributes.....	148
9.81.2	Description.....	148
9.82	IDN S-0-0120 Current loop integral action time 2.....	148
9.82.1	Attributes.....	148
9.82.2	Description.....	149
9.83	IDN S-0-0121 Input revolutions of load gear.....	149
9.83.1	Attributes.....	149
9.83.2	Description.....	149
9.84	IDN S-0-0122 Output revolutions of load gear.....	149
9.84.1	Attributes.....	149
9.84.2	Description.....	150
9.85	IDN S-0-0123 Feed constant.....	150
9.85.1	Attributes.....	150
9.85.2	Description.....	150
9.86	IDN S-0-0124 Standstill window.....	150
9.86.1	Attributes.....	150
9.86.2	Description.....	151
9.87	IDN S-0-0125 Velocity threshold (n_x).....	151
9.87.1	Attributes.....	151
9.87.2	Description.....	151
9.88	IDN S-0-0126 Torque threshold (T_x).....	151
9.88.1	Attributes.....	151
9.88.2	Description.....	152
9.89	IDN S-0-0129 Manufacturer class 1 diagnostic.....	152
9.89.1	Attributes.....	152
9.89.2	Description.....	152
9.90	IDN S-0-0130 Probe value 1 positive edge.....	153

9.90.1	Attributes.....	153
9.90.2	Description.....	153
9.91	IDN S-0-0131 Probe value 1 negative edge.....	153
9.91.1	Attributes.....	153
9.91.2	Description.....	154
9.92	IDN S-0-0132 Probe value 2 positive edge.....	154
9.92.1	Attributes.....	154
9.92.2	Description.....	154
9.93	IDN S-0-0133 Probe value 2 negative edge.....	154
9.93.1	Attributes.....	154
9.93.2	Description.....	155
9.94	IDN S-0-0134 Master control word.....	155
9.94.1	Attributes.....	155
9.94.2	Description.....	155
9.95	IDN S-0-0135 Drive status word.....	155
9.95.1	Attributes.....	155
9.95.2	Description.....	156
9.96	IDN S-0-0136 Positive acceleration limit value.....	156
9.96.1	Attributes.....	156
9.96.2	Description.....	156
9.97	IDN S-0-0137 Negative acceleration limit value.....	156
9.97.1	Attributes.....	156
9.97.2	Description.....	157
9.98	IDN S-0-0138 Bipolar acceleration limit value.....	157
9.98.1	Attributes.....	157
9.98.2	Description.....	157
9.99	IDN S-0-0139 Park axis procedure command.....	157
9.99.1	Attributes.....	157
9.99.2	Description.....	158
9.100	IDN S-0-0140 Controller type.....	158
9.100.1	Attributes.....	158
9.100.2	Description.....	158
9.101	IDN S-0-0141 Motor type.....	158
9.101.1	Attributes.....	158
9.101.2	Description.....	159
9.102	IDN S-0-0142 Application type.....	159
9.102.1	Attributes.....	159
9.102.2	Description.....	159
9.103	IDN S-0-0144 Signal status word.....	159
9.103.1	Attributes.....	159
9.103.2	Description.....	160
9.104	IDN S-0-0145 Signal control word.....	160
9.104.1	Attributes.....	160
9.104.2	Description.....	160
9.105	IDN S-0-0146 Control unit controlled homing procedure command.....	160
9.105.1	Attributes.....	160
9.105.2	Description.....	161
9.106	IDN S-0-0148 Drive controlled homing procedure command.....	161
9.106.1	Attributes.....	161

9.106.2	Description	161
9.107	IDN S-0-0149 Positive drive stop procedure command	162
9.107.1	Attributes	162
9.107.2	Description	162
9.108	IDN S-0-0150 Reference offset 1	163
9.108.1	Attributes	163
9.108.2	Description	163
9.109	IDN S-0-0151 Reference offset 2	163
9.109.1	Attributes	163
9.109.2	Description	163
9.110	IDN S-0-0152 Position spindle procedure command	164
9.110.1	Attributes	164
9.110.2	Description	164
9.111	IDN S-0-0153 Spindle angle position	164
9.111.1	Attributes	164
9.111.2	Description	165
9.112	IDN S-0-0154 Spindle positioning parameter	165
9.112.1	Attributes	165
9.112.2	Description	165
9.113	IDN S-0-0155 Friction torque compensation	166
9.113.1	Attributes	166
9.113.2	Description	166
9.114	IDN S-0-0156 Velocity feedback value 2	166
9.114.1	Attributes	166
9.114.2	Description	167
9.115	IDN S-0-0157 Velocity window	167
9.115.1	Attributes	167
9.115.2	Description	167
9.116	IDN S-0-0158 Power threshold (P_x)	167
9.116.1	Attributes	167
9.116.2	Description	168
9.117	IDN S-0-0159 Monitoring window	168
9.117.1	Attributes	168
9.117.2	Description	168
9.118	IDN S-0-0160 Acceleration data scaling type	168
9.118.1	Attributes	168
9.118.2	Description	169
9.119	IDN S-0-0161 Acceleration data scaling factor	169
9.119.1	Attributes	169
9.119.2	Description	170
9.120	IDN S-0-0162 Acceleration data scaling exponent	170
9.120.1	Attributes	170
9.120.2	Description	170
9.121	IDN S-0-0163 Weight counterbalance	171
9.121.1	Attributes	171
9.121.2	Description	171
9.122	IDN S-0-0164 Acceleration feedback value 1	171
9.122.1	Attributes	171
9.122.2	Description	171

9.123	IDN S-0-0165 and S-0-0166 Distance-coded reference marks A and B	172
9.123.1	Attributes	172
9.123.2	Description	172
9.124	IDN S-0-0167 Frequency limit of feedback 1/S-0-0168 Frequency limit of feedback 2	172
9.124.1	Attributes	172
9.124.2	Description	172
9.125	IDN S-0-0169 Probe control parameter	173
9.125.1	Attributes	173
9.125.2	Description	173
9.126	IDN S-0-0170 Probing cycle procedure command	173
9.126.1	Attributes	173
9.126.2	Description	174
9.127	IDN S-0-0171 Calculate displacement procedure command	174
9.127.1	Attributes	174
9.127.2	Description	174
9.128	IDN S-0-0172 Displacement to the referenced system procedure command	175
9.128.1	Attributes	175
9.128.2	Description	175
9.129	IDN S-0-0173 Marker position A	176
9.129.1	Attributes	176
9.129.2	Description	176
9.130	IDN S-0-0174 Marker position B	176
9.130.1	Attributes	176
9.130.2	Description	177
9.131	IDN S-0-0176 Displacement parameter 2	177
9.131.1	Attributes	177
9.131.2	Description	177
9.132	IDN S-0-0177 Absolute distance 1	178
9.132.1	Attributes	178
9.132.2	Description	178
9.133	IDN S-0-0178 Absolute distance 2	178
9.133.1	Attributes	178
9.133.2	Description	178
9.134	IDN S-0-0179 Probe status	179
9.134.1	Attributes	179
9.134.2	Description	179
9.135	IDN S-0-0180 Spindle relative offset	180
9.135.1	Attributes	180
9.135.2	Description	180
9.136	IDN S-0-0181 Manufacturer class 2 diagnostic	180
9.136.1	Attributes	180
9.136.2	Description	180
9.137	IDN S-0-0182 Manufacturer class 3 diagnostic	181
9.137.1	Attributes	181
9.137.2	Description	181
9.138	IDN S-0-0183 Synchronisation velocity window	181
9.138.1	Attributes	181
9.138.2	Description	182

9.139	IDN S-0-0184 Synchronisation velocity error limit	182
9.139.1	Attributes	182
9.139.2	Description.....	182
9.140	IDN S-0-0189 Following distance.....	183
9.140.1	Attributes	183
9.140.2	Description.....	183
9.141	IDN S-0-0190 Drive controlled gear engaging procedure command	183
9.141.1	Attributes	183
9.141.2	Description.....	183
9.142	IDN S-0-0191 Cancel reference point procedure command.....	184
9.142.1	Attributes	184
9.142.2	Description.....	184
9.143	IDN S-0-0192 IDN-list of all backup operation data	184
9.143.1	Attributes	184
9.143.2	Description.....	185
9.144	IDN S-0-0193 Positioning jerk.....	185
9.144.1	Attributes	185
9.144.2	Description.....	185
9.145	IDN S-0-0194 Acceleration command value.....	185
9.145.1	Attributes	185
9.145.2	Description.....	186
9.146	IDN S-0-0195 Acceleration feedback value 2	186
9.146.1	Attributes	186
9.146.2	Description.....	186
9.147	IDN S-0-0196 Motor rated current.....	186
9.147.1	Attributes	186
9.147.2	Description.....	187
9.148	IDN S-0-0197 Set coordinate system procedure command	187
9.148.1	Attributes	187
9.148.2	Description.....	187
9.149	IDN S-0-0198 Initial coordinate value.....	187
9.149.1	Attributes	187
9.149.2	Description.....	188
9.150	IDN S-0-0199 Shift coordinate system procedure command.....	188
9.150.1	Attributes	188
9.150.2	Description.....	188
9.151	IDN S-0-0200 Amplifier warning temperature	189
9.151.1	Attributes	189
9.151.2	Description.....	189
9.152	IDN S-0-0201 Motor warning temperature.....	189
9.152.1	Attributes	189
9.152.2	Description.....	189
9.153	IDN S-0-0202 Cooling error warning temperature	190
9.153.1	Attributes	190
9.153.2	Description.....	190
9.154	IDN S-0-0203 Amplifier shut-down temperature	190
9.154.1	Attributes	190
9.154.2	Description.....	190
9.155	IDN S-0-0204 Motor shut-down temperature	190