

INTERNATIONAL STANDARD

Information technology – Small computer system interface (SCSI) –
Part 151: Serial attached SCSI-1.1 (SAS-1.1)
(standards.iteh.ai)

[ISO/IEC 14776-151:2010](https://standards.iteh.ai/catalog/standards/sist/1c057010-1cce-4831-a28c-d6ec968f3751/iso-iec-14776-151-2010)

<https://standards.iteh.ai/catalog/standards/sist/1c057010-1cce-4831-a28c-d6ec968f3751/iso-iec-14776-151-2010>



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2010 ISO/IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about ISO/IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland
Email: inmail@iec.ch
Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: www.iec.ch/online_news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: www.iec.ch/webstore/customerservice

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch
Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00



ISO/IEC 14776-151

Edition 1.0 2010-07

INTERNATIONAL STANDARD

Information technology – Small computer system interface (SCSI) –
Part 151: Serial attached SCSI-1.1 (SAS-1.1)

STANDARD PREVIEW
(standards.iteh.ai)

ISO/IEC 14776-151:2010
<https://standards.iteh.ai/catalog/standards/sist/1c057010-1cce-4831-a28c-d6ec968f3751/iso-iec-14776-151-2010>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE

XC

ICS 35.200

ISBN 978-2-88912-092-5

Contents

Page

Foreword	28
Introduction	29
1 Scope	31
2 Normative references.....	33
3 Terms, definitions, symbols, abbreviations, keywords and conventions.....	34
3.1 Terms and definitions	34
3.2 Symbols and abbreviations	54
3.3 Keywords.....	57
3.4 Editorial conventions	58
3.5 Class diagram and object diagram conventions.....	59
3.6 State machine conventions	64
3.6.1 State machine conventions overview.....	64
3.6.2 Transitions	64
3.6.3 Messages, requests, indications, confirmations, responses and event notifications.....	65
3.6.4 State machine counters, timers and variables.....	65
3.6.5 State machine arguments.....	65
3.7 Bit and byte ordering	65
3.8 Notation for procedures and functions	66
4 General	67
4.1 Architecture	67
4.1.1 Architecture overview.....	67
4.1.2 Physical links and phys.....	68
4.1.3 Ports (narrow ports and wide ports).....	71
4.1.4 SAS devices	74
4.1.5 Expander devices (edge expander devices and fanout expander devices).....	75
4.1.6 Service delivery subsystem	77
4.1.7 Domains.....	78
4.1.8 Expander device topologies.....	80
4.1.8.1 Expander device topology overview.....	80
4.1.8.2 Edge expander device set.....	80
4.1.8.3 Expander device topologies	81
4.1.9 Pathways	84
4.1.10 Connections.....	85
4.2 Names and identifiers.....	87
4.2.1 Names and identifiers overview.....	87
4.2.2 SAS address.....	87
4.2.3 Hashed SAS address	88
4.2.4 Device names	88
4.2.5 Port names	88
4.2.6 Port identifiers.....	88
4.2.7 Phy identifiers	89
4.3 State machines.....	90
4.3.1 State machine overview.....	90
4.3.2 Transmit data path.....	92
4.3.3 Receive data path.....	96
4.3.4 State machines and SAS device, SAS port and SAS phy classes	99
4.4 Resets	100
4.4.1 Reset overview	100
4.4.2 Hard reset	102
4.4.2.1 Hard reset overview	102
4.4.2.2 Additional hard reset processing by SAS ports.....	102
4.4.2.3 Additional hard reset processing by expander ports	102

iTeh STANDARD PREVIEW

(standards.iteh.ai)

ISO/IEC 14776-151:2010

<https://standards.iteh.ai/catalog/standards/sist/1c057010-1c0e-4831-a28c-d6e3968f3751/iso-iec-14776-151-2010>

4.5 I_T nexus loss	102
4.6 Expander device model	102
4.6.1 Expander device model overview	102
4.6.2 Expander ports	103
4.6.3 Expander connection manager (ECM).....	104
4.6.4 Expander connection router (ECR).....	104
4.6.5 Broadcast primitive processor (BPP)	104
4.6.6 Expander device interfaces	104
4.6.6.1 Expander device interface overview.....	104
4.6.6.2 Expander device interfaces detail	106
4.6.6.3 ECM interface.....	106
4.6.6.4 ECR interface	108
4.6.6.5 BPP interface	110
4.6.7 Expander device routing	110
4.6.7.1 Routing attributes and routing methods	110
4.6.7.2 Connection request routing	111
4.6.7.3 Expander route table.....	111
4.7 Discover process.....	112
4.7.1 Discover process overview	112
4.7.2 Allowed topologies	114
4.7.3 Discover process optimization	115
4.7.4 Expander route index order	116
4.8 Phy test functions	121
5 Physical layer.....	122
5.1 Physical layer overview.....	122
5.2 Passive interconnect	122
5.2.1 SATA connectors and cable assemblies.....	122
5.2.2 SAS connectors and cables.....	122
5.2.3 Connectors	126
5.2.3.1 Connectors overview.....	126
5.2.3.2 SAS internal connectors.....	127
5.2.3.2.1 SAS Drive connectors.....	127
5.2.3.2.1.1 SAS Drive plug connector	127
5.2.3.2.1.2 SAS Drive cable receptacle connector.....	127
5.2.3.2.1.3 SAS Drive backplane receptacle connector.....	128
5.2.3.2.1.4 SAS Drive connector pin assignments.....	128
5.2.3.2.2 SAS 4i connectors	130
5.2.3.2.2.1 SAS 4i cable receptacle connector	130
5.2.3.2.2.2 SAS 4i plug connector.....	130
5.2.3.2.2.3 SAS 4i connector pin assignments	131
5.2.3.2.3 Mini SAS 4i connectors.....	132
5.2.3.2.3.1 Mini SAS 4i cable plug connector	132
5.2.3.2.3.2 Mini SAS 4i receptacle connector	133
5.2.3.2.3.3 Mini SAS 4i connector pin assignments.....	134
5.2.3.3 SAS external connectors.....	136
5.2.3.3.1 SAS 4x connectors	136
5.2.3.3.1.1 SAS 4x cable plug connector	136
5.2.3.3.1.2 SAS 4x receptacle connector.....	136
5.2.3.3.1.3 SAS 4x connector pin assignments	138
5.2.3.3.2 Mini SAS 4x connectors.....	138
5.2.3.3.2.1 Mini SAS 4x cable plug connector	138
5.2.3.3.2.2 Mini SAS 4x receptacle connector	140
5.2.3.3.2.3 Mini SAS 4x connector pin assignments.....	143
5.2.4 Cable assemblies	143
5.2.4.1 SAS internal cable assemblies.....	143
5.2.4.1.1 SAS Drive cable assemblies.....	143
5.2.4.1.2 SAS internal symmetric cable assemblies.....	144
5.2.4.1.2.1 SAS internal symmetric cable assemblies overview	144
5.2.4.1.2.2 SAS internal symmetric cable assembly - SAS 4i.....	145

- 5.2.4.1.2.3 SAS internal symmetric cable assembly - Mini SAS 4i 146
- 5.2.4.1.2.4 SAS internal symmetric cable assembly - SAS 4i to Mini SAS 4i 147
- 5.2.4.1.3 SAS internal fanout cable assemblies 148
 - 5.2.4.1.3.1 SAS internal fanout cable assemblies overview 148
 - 5.2.4.1.3.2 SAS internal controller-based fanout cable assemblies 149
 - 5.2.4.1.3.3 SAS internal backplane-based fanout cable assemblies 151
- 5.2.4.2 SAS external cable assemblies 152
 - 5.2.4.2.1 SAS external cable assemblies overview 152
 - 5.2.4.2.2 SAS external cable assembly - SAS 4x 153
 - 5.2.4.2.3 SAS external cable assembly - Mini SAS 4x 154
 - 5.2.4.2.4 SAS external cable assembly - SAS 4x to Mini SAS 4x 156
- 5.2.5 Backplanes 156
- 5.2.6 Cable assembly and backplane specifications 157
- 5.3 Transmitter and receiver device electrical characteristics 161
 - 5.3.1 Compliance points 161
 - 5.3.2 Test loads 169
 - 5.3.2.1 Test loads overview 169
 - 5.3.2.2 Zero-length test load 170
 - 5.3.2.3 TCTF test load 171
 - 5.3.2.4 Low-loss TCTF test load 173
 - 5.3.3 General electrical characteristics 174
 - 5.3.4 Transmitter and receiver device transients 177
 - 5.3.5 Eye masks 177
 - 5.3.5.1 Eye masks overview 177
 - 5.3.5.2 Transmitter device eye mask 178
 - 5.3.5.3 Receiver device eye mask 178
 - 5.3.5.4 Receiver device jitter tolerance eye mask 179
 - 5.3.6 Transmitter device characteristics 180
 - 5.3.6.1 Transmitter device characteristics overview 180
 - 5.3.6.2 Transmitter device signal output characteristics as measured with the zero-length test load 181
 - 5.3.6.3 Transmitter device signal output characteristics as measured with each test load 181
 - 5.3.6.4 Transmitter device maximum jitter 183
 - 5.3.6.5 Transmitter device signal output levels for OOB signals 183
 - 5.3.7 Receiver device characteristics 183
 - 5.3.7.1 Receiver device characteristics overview 183
 - 5.3.7.2 Delivered signal (receiver device signal tolerance) characteristics 184
 - 5.3.7.3 Maximum delivered jitter 186
 - 5.3.7.4 Receiver device jitter tolerance 186
 - 5.3.8 Spread spectrum clocking 187
 - 5.3.9 Non-tracking clock architecture 187
- 5.4 READY LED signal electrical characteristics 187
- 6 Phy layer 189
 - 6.1 Phy layer overview 189
 - 6.2 8b10b coding 189
 - 6.2.1 8b10b coding overview 189
 - 6.2.2 8b10b coding introduction 189
 - 6.2.3 8b10b coding notation conventions 189
 - 6.3 Character encoding and decoding 190
 - 6.3.1 Introduction 190
 - 6.3.2 Transmission order 190
 - 6.3.3 Data and control characters 190
 - 6.3.4 Encoding characters in the transmitter 197
 - 6.3.5 Decoding characters in the receiver 197
 - 6.4 Dwords, primitives, data dwords and invalid dwords 197
 - 6.5 Bit order 198
 - 6.6 Out of band (OOB) signals 199
 - 6.6.1 OOB signals overview 199
 - 6.6.2 Transmitting OOB signals 200
 - 6.6.3 Receiving OOB signals 202

IT-ET STANDARD PREVIEW

(standards.iteh.ai)

ISO/IEC 14776-151:2010

[https://standards.iteh.ai/catalog/standards/sist/1c057010-1cce-4831-a28c-](https://standards.iteh.ai/catalog/standards/sist/1c057010-1cce-4831-a28c-d6cc9683751/iso-iec-14776-151-2010)

[d6cc9683751/iso-iec-14776-151-2010](https://standards.iteh.ai/catalog/standards/sist/1c057010-1cce-4831-a28c-d6cc9683751/iso-iec-14776-151-2010)

6.6.4	Transmitting the SATA port selection signal	204
6.7	Phy reset sequences	204
6.7.1	Phy reset sequences overview	204
6.7.2	SATA phy reset sequence	205
6.7.2.1	SATA OOB sequence	205
6.7.2.2	SATA speed negotiation sequence	205
6.7.3	SAS to SATA phy reset sequence	206
6.7.4	SAS to SAS phy reset sequence	207
6.7.4.1	SAS OOB sequence	207
6.7.4.2	SAS speed negotiation sequence	208
6.7.4.2.1	SAS speed negotiation sequence overview	208
6.7.4.2.2	Speed negotiation window	209
6.7.4.2.3	SAS speed negotiation sequence	210
6.7.5	Phy reset sequence after devices are attached	212
6.8	SP (phy layer) state machine	213
6.8.1	SP state machine overview	213
6.8.2	SP transmitter and receiver	215
6.8.3	OOB sequence states	216
6.8.3.1	OOB sequence states overview	216
6.8.3.2	SP0:OOB_COMINIT state	216
6.8.3.2.1	State description	216
6.8.3.2.2	Transition SP0:OOB_COMINIT to SP1:OOB_AwaitCOMX	217
6.8.3.2.3	Transition SP0:OOB_COMINIT to SP3:OOB_AwaitCOMINIT_Sent	217
6.8.3.2.4	Transition SP0:OOB_COMINIT to SP4:OOB_COMSAS	217
6.8.3.3	SP1:OOB_AwaitCOMX state	217
6.8.3.3.1	State description	217
6.8.3.3.2	Transition SP1:OOB_AwaitCOMX to SP0:OOB_COMINIT	217
6.8.3.3.3	Transition SP1:OOB_AwaitCOMX to SP4:OOB_COMSAS	217
6.8.3.4	SP2:OOB_NoCOMSASTimeout state	218
6.8.3.4.1	State description	218
6.8.3.4.2	Transition SP2:OOB_NoCOMSASTimeout to SP0:OOB_COMINIT	218
6.8.3.4.3	Transition SP2:OOB_NoCOMSASTimeout to SP4:OOB_COMSAS	218
6.8.3.5	SP3:OOB_AwaitCOMINIT_Sent state	218
6.8.3.5.1	State description	218
6.8.3.5.2	Transition SP3:OOB_AwaitCOMINIT_Sent to SP4:OOB_COMSAS	218
6.8.3.6	SP4:OOB_COMSAS state	218
6.8.3.6.1	State description	218
6.8.3.6.2	Transition SP4:OOB_COMSAS to SP5:OOB_AwaitCOMSAS_Sent	218
6.8.3.6.3	Transition SP4:OOB_COMSAS to SP6:OOB_AwaitNoCOMSAS	218
6.8.3.6.4	Transition SP4:OOB_COMSAS to SP7:OOB_AwaitCOMSAS	219
6.8.3.7	SP5:OOB_AwaitCOMSAS_Sent state	219
6.8.3.7.1	State description	219
6.8.3.7.2	Transition SP5:OOB_AwaitCOMSAS_Sent to SP6:OOB_AwaitNoCOMSAS	219
6.8.3.8	SP6:OOB_AwaitNoCOMSAS state	219
6.8.3.8.1	State description	219
6.8.3.8.2	Transition SP6:OOB_AwaitNoCOMSAS to SP0:OOB_COMINIT	219
6.8.3.8.3	Transition SP6:OOB_AwaitNoCOMSAS to SP8:SAS_Start	219
6.8.3.9	SP7:OOB_AwaitCOMSAS state	219
6.8.3.9.1	State description	219
6.8.3.9.2	Transition SP7:OOB_AwaitCOMSAS to SP2:OOB_NoCOMSASTimeout	219
6.8.3.9.3	Transition SP7:OOB_AwaitCOMSAS to SP6:OOB_AwaitNoCOMSAS	219
6.8.3.9.4	Transition SP7:OOB_AwaitCOMSAS to SP16:SATA_COMWAKE	219
6.8.3.9.5	Transition SP7:OOB_AwaitCOMSAS to SP26:SATA_SpinupHold	220
6.8.4	SAS speed negotiation states	220
6.8.4.1	SAS speed negotiation states overview	220
6.8.4.2	SP8:SAS_Start state	221
6.8.4.2.1	State description	221
6.8.4.2.2	Transition SP8:SAS_Start to SP0:OOB_COMINIT	222
6.8.4.2.3	Transition SP8:SAS_Start to SP9:SAS_RateNotSupported	222
6.8.4.2.4	Transition SP8:SAS_Start to SP10:SAS_AwaitALIGN	222

6.8.4.3 SP9:SAS_RateNotSupported state 222

- 6.8.4.3.1 State description 222
- 6.8.4.3.2 Transition SP9:SAS_RateNotSupported to SP14:SAS_Fail 222

6.8.4.4 SP10:SAS_AwaitALIGN state 222

- 6.8.4.4.1 State description 222
- 6.8.4.4.2 Transition SP10:SAS_AwaitALIGN to SP0:OOB_COMINIT 222
- 6.8.4.4.3 Transition SP10:SAS_AwaitALIGN to SP11:SAS_AwaitALIGN1 222
- 6.8.4.4.4 Transition SP10:SAS_AwaitALIGN to SP12:SAS_AwaitSNW 222
- 6.8.4.4.5 Transition SP10:SAS_AwaitALIGN to SP14:SAS_Fail 222

6.8.4.5 SP11:SAS_AwaitALIGN1 state 223

- 6.8.4.5.1 State description 223
- 6.8.4.5.2 Transition SP11:SAS_AwaitALIGN1 to SP0:OOB_COMINIT 223
- 6.8.4.5.3 Transition SP11:SAS_AwaitALIGN1 to SP12:SAS_AwaitSNW 223
- 6.8.4.5.4 Transition SP11:SAS_AwaitALIGN1 to SP14:SAS_Fail 223

6.8.4.6 SP12:SAS_AwaitSNW state 223

- 6.8.4.6.1 State description 223
- 6.8.4.6.2 Transition SP12:SAS_AwaitSNW to SP0:OOB_COMINIT 223
- 6.8.4.6.3 Transition SP12:SAS_AwaitSNW to SP13:SAS_Pass 223

6.8.4.7 SP13:SAS_Pass state 223

- 6.8.4.7.1 State description 223
- 6.8.4.7.2 Transition SP13:SAS_Pass to SP0:OOB_COMINIT 223
- 6.8.4.7.3 Transition SP13:SAS_Pass to SP8:SAS_Start 223
- 6.8.4.7.4 Transition SP13:SAS_Pass to SP15:SAS_PHY_Ready 224

6.8.4.8 SP14:SAS_Fail state 224

- 6.8.4.8.1 State description 224
- 6.8.4.8.2 Transition SP14:SAS_Fail to SP1:OOB_AwaitCOMX 224
- 6.8.4.8.3 Transition SP14:SAS_Fail to SP8:SAS_Start 224

6.8.4.9 SP15:SAS_PHY_Ready state 224

- 6.8.4.9.1 State description 224
- 6.8.4.9.2 Transition SP15:SAS_PHY_Ready to SP0:OOB_COMINIT 224

6.8.5 SATA host emulation states 225

- 6.8.5.1 SATA host emulation states overview 225
- 6.8.5.2 SP16:SATA_COMWAKE state 226
 - 6.8.5.2.1 State description 226
 - 6.8.5.2.2 Transition SP16:SATA_COMWAKE to SP17:SATA_AwaitCOMWAKE 227
- 6.8.5.3 SP17:SATA_AwaitCOMWAKE state 227
 - 6.8.5.3.1 State description 227
 - 6.8.5.3.2 Transition SP17:SATA_AwaitCOMWAKE to SP0:OOB_COMINIT 227
 - 6.8.5.3.3 Transition SP17:SATA_AwaitCOMWAKE to SP18:SATA_AwaitNoCOMWAKE 227
- 6.8.5.4 SP18:SATA_AwaitNoCOMWAKE state 227
 - 6.8.5.4.1 State description 227
 - 6.8.5.4.2 Transition SP18:SATA_AwaitNoCOMWAKE to SP0:OOB_COMINIT 227
 - 6.8.5.4.3 Transition SP18:SATA_AwaitNoCOMWAKE to SP19:SATA_AwaitALIGN 227
- 6.8.5.5 SP19:SATA_AwaitALIGN state 227
 - 6.8.5.5.1 State description 227
 - 6.8.5.5.2 Transition SP19:SATA_AwaitALIGN to SP0:OOB_COMINIT 227
 - 6.8.5.5.3 Transition SP19:SATA_AwaitALIGN to SP20:SATA_AdjustSpeed 227
- 6.8.5.6 SP20:SATA_AdjustSpeed state 227
 - 6.8.5.6.1 State description 227
 - 6.8.5.6.2 Transition SP20:SATA_AdjustSpeed to SP0:OOB_COMINIT 228
 - 6.8.5.6.3 Transition SP20:SATA_AdjustSpeed to SP21:SATA_TransmitALIGN 228
- 6.8.5.7 SP21:SATA_TransmitALIGN state 228
 - 6.8.5.7.1 State description 228
 - 6.8.5.7.2 Transition SP21:SATA_TransmitALIGN to SP0:OOB_COMINIT 228
 - 6.8.5.7.3 Transition SP21:SATA_TransmitALIGN to SP22:SATA_PHY_Ready 228
- 6.8.5.8 SP22:SATA_PHY_Ready state 228
 - 6.8.5.8.1 State description 228
 - 6.8.5.8.2 Transition SP22:SATA_PHY_Ready to SP0:OOB_COMINIT 228
 - 6.8.5.8.3 Transition SP22:SATA_PHY_Ready to SP23:SATA_PM_Partial 228
 - 6.8.5.8.4 Transition SP22:SATA_PHY_Ready to SP24:SATA_PM_Slumber 228

ISO STANDARD PREVIEW
(standards.iteh.ai)
ISO/IEC 14776-151:2010
<https://standards.iteh.ai/catalog/standards/sist/1c057010-1cce-4831-a28c-d6e968b3751/iso-iec-14776-151-2010>

6.8.5.9 SP23:SATA_PM_Partial state.....	228
6.8.5.9.1 State description.....	228
6.8.5.9.2 Transition SP23:SATA_PM_Partial to SP0:OOB_COMINIT.....	229
6.8.5.9.3 Transition SP23:SATA_PM_Partial to SP16:SATA_COMWAKE.....	229
6.8.5.9.4 Transition SP23:SATA_PM_Partial to SP18:SATA_AwaitNoCOMWAKE.....	229
6.8.5.10 SP24:SATA_PM_Slumber state.....	229
6.8.5.10.1 State description.....	229
6.8.5.10.2 Transition SP24:SATA_PM_Slumber to SP0:OOB_COMINIT.....	229
6.8.5.10.3 Transition SP24:SATA_PM_Slumber to SP16:SATA_COMWAKE.....	229
6.8.5.10.4 Transition SP24:SATA_PM_Slumber to SP18:SATA_AwaitNoCOMWAKE.....	229
6.8.6 SATA port selector state.....	229
6.8.6.1 State description.....	229
6.8.6.2 Transition SP25:SATA_PortSel to SP1:OOB_AwaitCOMX.....	229
6.8.7 SATA spinup hold state.....	230
6.8.7.1 State description.....	230
6.8.7.2 Transition SP26:SATA_SpinupHold to SP0:OOB_COMINIT.....	230
6.9 SP_DWS (phy layer dword synchronization) state machine.....	230
6.9.1 SP_DWS state machine overview.....	230
6.9.2 SP_DWS receiver.....	232
6.9.3 SP_DWS0:AcquireSync state.....	233
6.9.3.1 State description.....	233
6.9.3.2 Transition SP_DWS0:AcquireSync to SP_DWS1:Valid1.....	233
6.9.4 SP_DWS1:Valid1 state.....	233
6.9.4.1 State description.....	233
6.9.4.2 Transition SP_DWS1:Valid1 to SP_DWS0:AcquireSync.....	233
6.9.4.3 Transition SP_DWS1:Valid1 to SP_DWS2:Valid2.....	233
6.9.5 SP_DWS2:Valid2 state.....	233
6.9.5.1 State description.....	233
6.9.5.2 Transition SP_DWS2:Valid2 to SP_DWS0:AcquireSync.....	234
6.9.5.3 Transition SP_DWS2:Valid2 to SP_DWS3:SyncAcquired.....	234
6.9.6 SP_DWS3:SyncAcquired state.....	234
6.9.6.1 State description.....	234
6.9.6.2 Transition SP_DWS3:SyncAcquired to SP_DWS4:Lost1.....	234
6.9.7 SP_DWS4:Lost1 state.....	234
6.9.7.1 State description.....	234
6.9.7.2 Transition SP_DWS4:Lost1 to SP_DWS5:Lost1Recovered.....	234
6.9.7.3 Transition SP_DWS4:Lost1 to SP_DWS6:Lost2.....	234
6.9.8 SP_DWS5:Lost1Recovered state.....	234
6.9.8.1 State description.....	234
6.9.8.2 Transition SP_DWS5:Lost1Recovered to SP_DWS3:SyncAcquired.....	234
6.9.8.3 Transition SP_DWS5:Lost1Recovered to SP_DWS6:Lost2.....	234
6.9.9 SP_DWS6:Lost2 state.....	234
6.9.9.1 State description.....	234
6.9.9.2 Transition SP_DWS6:Lost2 to SP_DWS7:Lost2Recovered.....	234
6.9.9.3 Transition SP_DWS6:Lost2 to SP_DWS8:Lost3.....	235
6.9.10 SP_DWS7:Lost2Recovered state.....	235
6.9.10.1 State description.....	235
6.9.10.2 Transition SP_DWS7:Lost2Recovered to SP_DWS4:Lost1.....	235
6.9.10.3 Transition SP_DWS7:Lost2Recovered to SP_DWS8:Lost3.....	235
6.9.11 SP_DWS8:Lost3 state.....	235
6.9.11.1 State description.....	235
6.9.11.2 Transition SP_DWS8:Lost3 to SP_DWS9:Lost3Recovered.....	235
6.9.11.3 Transition SP_DWS8:Lost3 to SP_DWS0:AcquireSync.....	235
6.9.12 SP_DWS9:Lost3Recovered state.....	235
6.9.12.1 State description.....	235
6.9.12.2 Transition SP_DWS9:Lost3Recovered to SP_DWS6:Lost2.....	235
6.9.12.3 Transition SP_DWS9:Lost3Recovered to SP_DWS0:AcquireSync.....	235
6.10 Spin-up.....	235
7 Link layer.....	237

7.1 Link layer overview	237
7.2 Primitives	237
7.2.1 Primitives overview	237
7.2.2 Primitive summary	237
7.2.3 Primitive encodings	241
7.2.4 Primitive sequences	245
7.2.4.1 Primitive sequences overview	245
7.2.4.2 Single primitive sequence	245
7.2.4.3 Repeated primitive sequence	245
7.2.4.4 Continued primitive sequence	246
7.2.4.5 Triple primitive sequence	246
7.2.4.6 Redundant primitive sequence	247
7.2.5 Primitives not specific to type of connections	248
7.2.5.1 AIP (Arbitration in progress)	248
7.2.5.2 ALIGN	249
7.2.5.3 BREAK	250
7.2.5.4 BROADCAST	250
7.2.5.5 CLOSE	251
7.2.5.6 EOAF (End of address frame)	251
7.2.5.7 ERROR	251
7.2.5.8 HARD_RESET	251
7.2.5.9 NOTIFY	251
7.2.5.10 OPEN_ACCEPT	252
7.2.5.11 OPEN_REJECT	252
7.2.5.12 SOAF (Start of address frame)	254
7.2.6 Primitives used only inside SSP and SMP connections	255
7.2.6.1 ACK (Acknowledge)	255
7.2.6.2 CREDIT_BLOCKED	255
7.2.6.3 DONE	255
7.2.6.4 EOF (End of frame)	255
7.2.6.5 NAK (Negative acknowledgement)	255
7.2.6.6 RRDY (Receiver ready)	256
7.2.6.7 SOF (Start of frame)	256
7.2.7 Primitives used only inside STP connections and on SATA physical links	256
7.2.7.1 SATA_ERROR	256
7.2.7.2 SATA_PMACK, SATA_PMNAK, SATA_PMREQ_P and SATA_PMREQ_S (Power management acknowledgements and requests)	256
7.2.7.3 SATA_HOLD and SATA_HOLDA (Hold and hold acknowledge)	257
7.2.7.4 SATA_R_RDY and SATA_X_RDY (Receiver ready and transmitter ready)	257
7.2.7.5 Other primitives used inside STP connections and on SATA physical links	257
7.3 Clock skew management	257
7.4 Idle physical links	258
7.5 CRC	258
7.5.1 CRC overview	258
7.5.2 CRC generation	259
7.5.3 CRC checking	261
7.6 Scrambling	261
7.7 Bit order of CRC and scrambler	263
7.8 Address frames	266
7.8.1 Address frames overview	266
7.8.2 IDENTIFY address frame	268
7.8.3 OPEN address frame	270
7.9 Identification and hard reset sequence	272
7.9.1 Identification and hard reset sequence overview	272
7.9.2 SAS initiator device rules	272
7.9.3 Fanout expander device rules	273
7.9.4 Edge expander device rules	273
7.9.5 SL_IR (link layer identification and hard reset) state machines	273
7.9.5.1 SL_IR state machines overview	273
7.9.5.2 SL_IR transmitter and receiver	274

7.9.5.3 SL_IR_TIR (transmit IDENTIFY or HARD_RESET) state machine	275
7.9.5.3.1 SL_IR_TIR state machine overview	275
7.9.5.3.2 SL_IR_TIR1:Idle state	275
7.9.5.3.2.1 State description	275
7.9.5.3.2.2 Transition SL_IR_TIR1:Idle to SL_IR_TIR2:Transmit_Identify	275
7.9.5.3.2.3 Transition SL_IR_TIR1:Idle to SL_IR_TIR3:Transmit_Hard_Reset.....	275
7.9.5.3.3 SL_IR_TIR2:Transmit_Identify state.....	275
7.9.5.3.3.1 State description	275
7.9.5.3.3.2 Transition SL_IR_TIR2:Transmit_Identify to SL_IR_TIR4:Completed.....	275
7.9.5.3.4 SL_IR_TIR3:Transmit_Hard_Reset state	276
7.9.5.3.4.1 State description	276
7.9.5.3.4.2 Transition SL_IR_TIR3:Transmit_Hard_Reset to SL_IR_TIR4:Completed	276
7.9.5.3.5 SL_IR_TIR4:Completed state.....	276
7.9.5.4 SL_IR_RIF (receive IDENTIFY address frame) state machine.....	276
7.9.5.4.1 SL_IR_RIF state machine overview	276
7.9.5.4.2 SL_IR_RIF1:Idle state	276
7.9.5.4.2.1 State description	276
7.9.5.4.2.2 Transition SL_IR_RIF1:Idle to SL_IR_RIF2:Receive_Identify_Frame	276
7.9.5.4.3 SL_IR_RIF2:Receive_Identify_Frame state	276
7.9.5.4.3.1 State description	276
7.9.5.4.3.2 Transition SL_IR_RIF2:Receive_Identify_Frame to SL_IR_RIF3:Completed	277
7.9.5.4.4 SL_IR_RIF3:Completed state.....	277
7.9.5.5 SL_IR_IRC (identification and hard reset control) state machine	277
7.9.5.5.1 SL_IR_IRC state machine overview.....	277
7.9.5.5.2 SL_IR_IRC1:Idle state.....	277
7.9.5.5.2.1 State description	277
7.9.5.5.2.2 Transition SL_IR_IRC1:Idle to SL_IR_IRC2:Wait.....	277
7.9.5.5.3 SL_IR_IRC2:Wait state.....	277
7.9.5.5.3.1 State description	277
7.9.5.5.3.2 Transition SL_IR_IRC2:Wait to SL_IR_IRC3:Completed	278
7.9.5.5.4 SL_IR_IRC3:Completed state.....	278
7.10 Power management.....	278
7.11 SAS domain changes.....	278
7.12 Connections	279
7.12.1 Connections overview.....	279
7.12.2 Opening a connection.....	280
7.12.2.1 Connection request.....	280
7.12.2.2 Results of a connection request.....	280
7.12.3 Arbitration fairness.....	281
7.12.4 Arbitration and resource management in an expander device	282
7.12.4.1 Arbitration and resource management in an expander device overview.....	282
7.12.4.2 Arbitration status	283
7.12.4.3 Edge expander devices.....	283
7.12.4.4 Fanout expander devices	284
7.12.4.5 Partial Pathway Timeout timer	284
7.12.4.6 Pathway recovery.....	284
7.12.5 Aborting a connection request	285
7.12.6 Closing a connection	287
7.12.7 Breaking a connection	288
7.13 Rate matching	288
7.14 SL (link layer for SAS phys) state machines	291
7.14.1 SL state machines overview	291
7.14.2 SL transmitter and receiver.....	293
7.14.3 SL_RA (receive OPEN address frame) state machine.....	294
7.14.4 SL_CC (connection control) state machine	295
7.14.4.1 SL_CC state machine overview	295
7.14.4.2 SL_CC0:Idle state	296
7.14.4.2.1 State description.....	296
7.14.4.2.2 Transition SL_CC0:Idle to SL_CC1:ArbSel	296
7.14.4.2.3 Transition SL_CC0:Idle to SL_CC2:Selected.....	296

ITeP STANDARD PREVIEW

(standards.iteh.ai)

ISO/IEC 14776-151:2010

[https://standards.iteh.ai/catalog/standards/sist/1c057010-1cce-4831-a28c-](https://standards.iteh.ai/catalog/standards/sist/1c057010-1cce-4831-a28c-d6ec968b3751/iso-iec-14776-151-2010)

[d6ec968b3751/iso-iec-14776-151-2010](https://standards.iteh.ai/catalog/standards/sist/1c057010-1cce-4831-a28c-d6ec968b3751/iso-iec-14776-151-2010)

- 7.14.4.3 SL_CC1:ArbSel state 296
 - 7.14.4.3.1 State description 296
 - 7.14.4.3.2 Transition SL_CC1:ArbSel to SL_CC0:Idle 297
 - 7.14.4.3.3 Transition SL_CC1:ArbSel to SL_CC2:Selected 297
 - 7.14.4.3.4 Transition SL_CC1:ArbSel to SL_CC3:Connected 297
 - 7.14.4.3.5 Transition SL_CC1:ArbSel to SL_CC5:BreakWait 298
 - 7.14.4.3.6 Transition SL_CC1:ArbSel to SL_CC6:Break 298
- 7.14.4.4 SL_CC2:Selected state 298
 - 7.14.4.4.1 State description 298
 - 7.14.4.4.2 Transition SL_CC2:Selected to SL_CC0:Idle 298
 - 7.14.4.4.3 Transition SL_CC2:Selected to SL_CC3:Connected 299
 - 7.14.4.4.4 Transition SL_CC2:Selected to SL_CC6:Break 299
- 7.14.4.5 SL_CC3:Connected state 299
 - 7.14.4.5.1 State description 299
 - 7.14.4.5.2 Transition SL_CC3:Connected to SL_CC4:DisconnectWait 299
 - 7.14.4.5.3 Transition SL_CC3:Connected to SL_CC5:BreakWait 299
 - 7.14.4.5.4 Transition SL_CC3:Connected to SL_CC6:Break 299
 - 7.14.4.5.5 Transition SL_CC3:Connected to SL_CC7:CloseSTP 299
- 7.14.4.6 SL_CC4:DisconnectWait state 299
 - 7.14.4.6.1 State description 299
 - 7.14.4.6.2 Transition SL_CC4:DisconnectWait to SL_CC0:Idle 300
 - 7.14.4.6.3 Transition SL_CC4:DisconnectWait to SL_CC5:BreakWait 300
 - 7.14.4.6.4 Transition SL_CC4:DisconnectWait to SL_CC6:Break 300
- 7.14.4.7 SL_CC5:BreakWait state 300
 - 7.14.4.7.1 State description 300
 - 7.14.4.7.2 Transition SL_CC5:BreakWait to SL_CC0:Idle 300
- 7.14.4.8 SL_CC6:Break state 300
 - 7.14.4.8.1 State description 300
 - 7.14.4.8.2 Transition SL_CC6:Break to SL_CC0:Idle 300
- 7.14.4.9 SL_CC7:CloseSTP state 300
 - 7.14.4.9.1 State description 300
 - 7.14.4.9.2 Transition SL_CC7:CloseSTP to SL_CC0:Idle 301
- 7.15 XL (link layer for expander phys) state machine 301
 - 7.15.1 XL state machine overview 301
 - 7.15.2 XL transmitter and receiver 304
 - 7.15.3 XL0:Idle state 306
 - 7.15.3.1 State description 306
 - 7.15.3.2 Transition XL0:Idle to XL1:Request_Path 306
 - 7.15.3.3 Transition XL0:Idle to XL5:Forward_Open 306
 - 7.15.4 XL1:Request_Path state 306
 - 7.15.4.1 State description 306
 - 7.15.4.2 Transition XL1:Request_Path to XL0:Idle 307
 - 7.15.4.3 Transition XL1:Request_Path to XL2:Request_Open 307
 - 7.15.4.4 Transition XL1:Request_Path to XL4:Open_Reject 307
 - 7.15.4.5 Transition XL1:Request_Path to XL5:Forward_Open 308
 - 7.15.4.6 Transition XL1:Request_Path to XL9:Break 308
 - 7.15.5 XL2:Request_Open state 308
 - 7.15.5.1 State description 308
 - 7.15.5.2 Transition XL2:Request_Open to XL3:Open_Confirm_Wait 308
 - 7.15.6 XL3:Open_Confirm_Wait state 308
 - 7.15.6.1 State description 308
 - 7.15.6.2 Transition XL3:Open_Confirm_Wait to XL0:Idle 309
 - 7.15.6.3 Transition XL3:Open_Confirm_Wait to XL1:Request_Path 309
 - 7.15.6.4 Transition XL3:Open_Confirm_Wait to XL5:Forward_Open 309
 - 7.15.6.5 Transition XL3:Open_Confirm_Wait to XL7:Connected 309
 - 7.15.6.6 Transition XL3:Open_Confirm_Wait to XL9:Break 309
 - 7.15.6.7 Transition XL3:Open_Confirm_Wait to XL10:Break_Wait 309
 - 7.15.7 XL4:Open_Reject state 309
 - 7.15.7.1 State description 309
 - 7.15.7.2 Transition XL4:Open_Reject to XL0:Idle 310

IEEE STANDARD PREVIEW

(standards.iteh.ai)

ISO/IEC 14776-151:2010

<https://standards.iteh.ai/catalog/standards/sist/c057010-1c0e-4831-a28c-16cc96883751/iso-iec-14776-151-2010>

ISO/IEC 14776-151:2010

7.15.8 XL5:Forward_Open state.....	310
7.15.8.1 State description	310
7.15.8.2 Transition XL5:Forward_Open to XL6:Open_Response_Wait.....	310
7.15.9 XL6:Open_Response_Wait state	310
7.15.9.1 State description	310
7.15.9.2 Transition XL6:Open_Response_Wait to XL0:Idle.....	311
7.15.9.3 Transition XL6:Open_Response_Wait to XL1:Request_Path.....	311
7.15.9.4 Transition XL6:Open_Response_Wait to XL2:Request_Open	311
7.15.9.5 Transition XL6:Open_Response_Wait to XL7:Connected	311
7.15.9.6 Transition XL6:Open_Response_Wait to XL9:Break	312
7.15.9.7 Transition XL6:Open_Response_Wait to XL10:Break_Wait.....	312
7.15.10 XL7:Connected state	312
7.15.10.1 State description	312
7.15.10.2 Transition XL7:Connected to XL8:Close_Wait.....	312
7.15.10.3 Transition XL7:Connected to XL9:Break.....	312
7.15.10.4 Transition XL7:Connected to XL10:Break_Wait.....	312
7.15.11 XL8:Close_Wait state	313
7.15.11.1 State description	313
7.15.11.2 Transition XL8:Close_Wait to XL0:Idle.....	313
7.15.11.3 Transition XL8:Close_Wait to XL9:Break.....	313
7.15.11.4 Transition XL8:Close_Wait to XL10:Break_Wait.....	313
7.15.12 XL9:Break state	313
7.15.12.1 State description	313
7.15.12.2 Transition XL9:Break to XL0:Idle.....	313
7.15.13 XL10:Break_Wait state	314
7.15.13.1 State description	314
7.15.13.2 Transition XL10:Break_Wait to XL0:Idle	314
7.16 SSP link layer	314
7.16.1 Opening an SSP connection.....	314
7.16.2 Full duplex	314
7.16.3 SSP frame transmission and reception.....	314
7.16.4 SSP flow control	315
7.16.5 Interlocked frames	315
7.16.6 Breaking an SSP connection	317
7.16.7 Closing an SSP connection	317
7.16.8 SSP (link layer for SSP phys) state machines.....	318
7.16.8.1 SSP state machines overview.....	318
7.16.8.2 SSP transmitter and receiver	321
7.16.8.3 SSP_TIM (transmit interlocked frame monitor) state machine.....	322
7.16.8.4 SSP_TCM (transmit frame credit monitor) state machine.....	323
7.16.8.5 SSP_D (DONE control) state machine.....	323
7.16.8.6 SSP_TF (transmit frame control) state machine	324
7.16.8.6.1 SSP_TF state machine overview.....	324
7.16.8.6.2 SSP_TF1:Connected_Idle state	324
7.16.8.6.2.1 State description	324
7.16.8.6.2.2 Transition SSP_TF1:Connected_Idle to SSP_TF2:Tx_Wait.....	324
7.16.8.6.2.3 Transition SSP_TF1:Connected_Idle to SSP_TF4:Transmit_DONE.....	325
7.16.8.6.3 SSP_TF2:Tx_Wait state	325
7.16.8.6.3.1 State description	325
7.16.8.6.3.2 Transition SSP_TF2:Tx_Wait to SSP_TF3:Transmit_Frame.....	325
7.16.8.6.3.3 Transition SSP_TF2:Tx_Wait to SSP_TF4:Transmit_DONE.....	325
7.16.8.6.4 SSP_TF3:Transmit_Frame state	325
7.16.8.6.4.1 State description	325
7.16.8.6.4.2 Transition SSP_TF3:Transmit_Frame to SSP_TF1:Connected_Idle.....	326
7.16.8.6.5 SSP_TF4:Transmit_DONE state	326
7.16.8.7 SSP_RF (receive frame control) state machine.....	326
7.16.8.8 SSP_RCM (receive frame credit monitor) state machine.....	327
7.16.8.9 SSP_RIM (receive interlocked frame monitor) state machine.....	327
7.16.8.10 SSP_TC (transmit credit control) state machine	328
7.16.8.11 SSP_TAN (transmit ACK/NAK control) state machine.....	328

- 7.17 STP link layer 328
 - 7.17.1 STP frame transmission and reception 328
 - 7.17.2 STP initiator phy throttling 329
 - 7.17.3 STP flow control 329
 - 7.17.4 Continued primitive sequence 332
 - 7.17.5 Affiliations 332
 - 7.17.6 Opening an STP connection 333
 - 7.17.7 Closing an STP connection 334
 - 7.17.8 STP connection management examples 334
 - 7.17.9 STP (link layer for STP phys) state machines 336
 - 7.17.10 SMP target port support 337
- 7.18 SMP link layer 337
 - 7.18.1 SMP frame transmission and reception 337
 - 7.18.2 SMP flow control 337
 - 7.18.3 Closing an SMP connection 337
 - 7.18.4 SMP (link layer for SMP phys) state machines 337
 - 7.18.4.1 SMP state machines overview 337
 - 7.18.4.2 SMP transmitter and receiver 337
 - 7.18.4.3 SMP_IP (link layer for SMP initiator phys) state machine 338
 - 7.18.4.3.1 SMP_IP state machine overview 338
 - 7.18.4.3.2 SMP_IP1:Idle state 339
 - 7.18.4.3.2.1 State description 339
 - 7.18.4.3.2.2 Transition SMP_IP1:Idle to SMP_IP2:Transmit_Frame 339
 - 7.18.4.3.3 SMP_IP2:Transmit_Frame state 339
 - 7.18.4.3.3.1 State description 339
 - 7.18.4.3.3.2 Transition SMP_IP2:Transmit_Frame to SMP_IP3:Receive_Frame 340
 - 7.18.4.3.4 SMP_IP3:Receive_Frame state 340
 - 7.18.4.4 SMP_TP (link layer for SMP target phys) state machine 340
 - 7.18.4.4.1 SMP_TP state machine overview 340
 - 7.18.4.4.2 SMP_TP1:Receive_Frame state 341
 - 7.18.4.4.2.1 State description 341
 - 7.18.4.4.2.2 Transition SMP_TP1:Receive_Frame to SMP_TP2:Transmit_Frame 342
 - 7.18.4.4.3 SMP_TP2:Transmit_Frame state 342
- 8 Port layer 343
 - 8.1 Port layer overview 343
 - 8.2 PL (port layer) state machines 343
 - 8.2.1 PL state machines overview 343
 - 8.2.2 PL_OC (port layer overall control) state machine 345
 - 8.2.2.1 PL_OC state machine overview 345
 - 8.2.2.2 PL_OC1:Idle state 346
 - 8.2.2.2.1 PL_OC1:Idle state description 346
 - 8.2.2.2.2 Transition PL_OC1:Idle to PL_OC2:Overall_Control 347
 - 8.2.2.3 PL_OC2:Overall_Control state 347
 - 8.2.2.3.1 PL_OC2:Overall_Control state overview 347
 - 8.2.2.3.2 PL_OC2:Overall_Control state establishing connections 347
 - 8.2.2.3.3 PL_OC2:Overall_Control state connection established 350
 - 8.2.2.3.4 PL_OC2:Overall_Control state unable to establish a connection 350
 - 8.2.2.3.5 PL_OC2:Overall_Control state connection management 351
 - 8.2.2.3.6 PL_OC2:Overall_Control state frame transmission 352
 - 8.2.2.3.7 PL_OC2:Overall_Control state frame transmission cancellations 353
 - 8.2.2.3.8 Transition PL_OC2:Overall_Control to PL_OC1:Idle 353
 - 8.2.3 PL_PM (port layer phy manager) state machine 354
 - 8.2.3.1 PL_PM state machine overview 354
 - 8.2.3.2 PL_PM1:Idle state 356
 - 8.2.3.2.1 PL_PM1:Idle state description 356
 - 8.2.3.2.2 Transition PL_PM1:Idle to PL_PM2:Req_Wait 357
 - 8.2.3.2.3 Transition PL_PM1:Idle to PL_PM3:Connected 357
 - 8.2.3.3 PL_PM2:Req_Wait state 357
 - 8.2.3.3.1 PL_PM2:Req_Wait state overview 357

8.2.3.3.2 PL_PM2:Req_Wait establishing a connection.....	357
8.2.3.3.3 PL_PM2:Req_Wait connection established.....	357
8.2.3.3.4 PL_PM2:Req_Wait unable to establish a connection.....	358
8.2.3.3.5 PL_PM2:Req_Wait connection management.....	358
8.2.3.3.6 Transition PL_PM2:Req_Wait to PL_PM1:Idle.....	358
8.2.3.3.7 Transition PL_PM2:Req_Wait to PL_PM3:Connected.....	358
8.2.3.3.8 Transition PL_PM2:Req_Wait to PL_PM4:Wait_For_Close.....	359
8.2.3.4 PL_PM3:Connected state.....	359
8.2.3.4.1 PL_PM3:Connected state description.....	359
8.2.3.4.2 Transition PL_PM3:Connected to PL_PM1:Idle.....	361
8.2.3.5 PL_PM4:Wait_For_Close state.....	361
8.2.3.5.1 PL_PM4:Wait_For_Close state description.....	361
8.2.3.5.2 Transition PL_PM4:Wait_For_Close to PL_PM1:Idle.....	361
9 Transport layer.....	362
9.1 Transport layer overview.....	362
9.2 SSP transport layer.....	362
9.2.1 SSP frame format.....	362
9.2.2 Information units.....	364
9.2.2.1 COMMAND frame - Command information unit.....	364
9.2.2.2 TASK frame - Task Management Function information unit.....	366
9.2.2.3 XFER_RDY frame - Transfer Ready information unit.....	367
9.2.2.4 DATA frame - Data information unit.....	368
9.2.2.5 RESPONSE frame - Response information unit.....	369
9.2.2.5.1 RESPONSE frame - Response information unit overview.....	369
9.2.2.5.2 Response information unit - NO_DATA format.....	371
9.2.2.5.3 Response information unit - RESPONSE_DATA format.....	371
9.2.2.5.4 Response information unit - SENSE_DATA format.....	372
9.2.3 Sequences of SSP frames.....	372
9.2.3.1 Sequences of SSP frames overview.....	372
9.2.3.2 Task management function sequence of SSP frames.....	372
9.2.3.3 Non-data command sequence of SSP frames.....	373
9.2.3.4 Write command sequence of SSP frames.....	373
9.2.3.5 Read command sequence of SSP frames.....	374
9.2.3.6 Bidirectional command sequence of SSP frames.....	374
9.2.4 SSP transport layer handling of link layer errors.....	375
9.2.4.1 SSP transport layer handling of link layer errors overview.....	375
9.2.4.2 COMMAND frame - handling of link layer errors.....	375
9.2.4.3 TASK frame - handling of link layer errors.....	376
9.2.4.4 XFER_RDY frame - handling of link layer errors.....	376
9.2.4.4.1 XFER_RDY frame overview.....	376
9.2.4.4.2 XFER_RDY frame with transport layer retries enabled.....	376
9.2.4.4.3 XFER_RDY frame with transport layer retries disabled.....	377
9.2.4.5 DATA frame - handling of link layer errors.....	377
9.2.4.5.1 DATA frame overview.....	377
9.2.4.5.2 DATA frame with transport layer retries enabled.....	377
9.2.4.5.3 DATA frame with transport layer retries disabled.....	378
9.2.4.6 RESPONSE frame - handling of link layer errors.....	378
9.2.5 SSP transport layer error handling summary.....	378
9.2.5.1 SSP transport layer error handling summary introduction.....	378
9.2.5.2 SSP initiator port transport layer error handling summary.....	378
9.2.5.3 SSP target port transport layer error handling summary.....	379
9.2.6 ST (transport layer for SSP ports) state machines.....	380
9.2.6.1 ST state machines overview.....	380
9.2.6.2 ST_I (transport layer for SSP initiator ports) state machines.....	381
9.2.6.2.1 ST_I state machines overview.....	381
9.2.6.2.2 ST_IFR (initiator frame router) state machine.....	383
9.2.6.2.2.1 ST_IFR state machine overview.....	383
9.2.6.2.2.2 Processing transport protocol service requests.....	383
9.2.6.2.2.3 Processing Frame Received confirmations.....	384