

INTERNATIONAL STANDARD

NORME INTERNATIONALE

**Cable networks for television signals, sound signals and interactive services –
Part 1-2: Performance requirements for signals delivered at the system outlet in
operation**

**Réseaux de distribution par câbles destinés aux signaux de télévision, de
radiodiffusion sonore et aux services interactifs –
Partie 1-2: Exigences de qualité des signaux fournis à la prise murale, en
fonctionnement**



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2009 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de la CEI ou du Comité national de la CEI du pays du demandeur.

Si vous avez des questions sur le copyright de la CEI ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de la CEI de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland
Email: inmail@iec.ch
Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: www.iec.ch/online_news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: www.iec.ch/webstore/custserv

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch

Tel.: +41 22 919 02 11

Fax: +41 22 919 03 00

A propos de la CEI

La Commission Electrotechnique Internationale (CEI) est la première organisation mondiale qui élabore et publie des normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications CEI

Le contenu technique des publications de la CEI est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

- Catalogue des publications de la CEI: www.iec.ch/searchpub/cur_fut-f.htm

Le Catalogue en-ligne de la CEI vous permet d'effectuer des recherches en utilisant différents critères (numéro de référence, texte, comité d'études,...). Il donne aussi des informations sur les projets et les publications retirées ou remplacées.

- Just Published CEI: www.iec.ch/online_news/justpub

Restez informé sur les nouvelles publications de la CEI. Just Published détaille deux fois par mois les nouvelles publications parues. Disponible en-ligne et aussi par email.

- Electropedia: www.electropedia.org

Le premier dictionnaire en ligne au monde de termes électroniques et électriques. Il contient plus de 20 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans les langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International en ligne.

- Service Clients: www.iec.ch/webstore/custserv/custserv_entry-f.htm

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions, visitez le FAQ du Service clients ou contactez-nous:

Email: csc@iec.ch

Tél.: +41 22 919 02 11

Fax: +41 22 919 03 00

INTERNATIONAL STANDARD

NORME INTERNATIONALE

**Cable networks for television signals, sound signals and interactive services –
Part 1-2: Performance requirements for signals delivered at the system outlet in
operation**

**Réseaux de distribution par câbles destinés aux signaux de télévision, de
radiodiffusion sonore et aux services interactifs –
Partie 1-2: Exigences de qualité des signaux fournis à la prise murale, en
fonctionnement**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

PRICE CODE
CODE PRIX



ICS 33.120.10; 33.160; 35.110

ISBN 978-2-88912-401-5

CONTENTS

| | |
|--|----|
| FOREWORD..... | 4 |
| INTRODUCTION..... | 6 |
| 1 Scope..... | 7 |
| 2 Normative references..... | 8 |
| 3 Terms, definitions, symbols and abbreviations..... | 10 |
| 3.1 Terms and definitions..... | 10 |
| 3.2 Abbreviations..... | 15 |
| 4 Methods of measurement..... | 16 |
| 5 Subjective quality of television pictures in relation to the main impairments of the analogue composite television signal..... | 17 |
| 5.1 Subjective quality scale..... | 17 |
| 5.2 Subjective quality and objective parameters..... | 17 |
| 6 Summation of the impairments..... | 20 |
| 6.1 Impairments to be summed..... | 20 |
| 6.2 Summation laws..... | 21 |
| 6.2.1 General..... | 21 |
| 6.2.2 Voltage addition..... | 21 |
| 6.2.3 Power addition..... | 22 |
| 6.3 Examples..... | 22 |
| 7 Performance requirements in operation..... | 22 |
| 7.1 General..... | 22 |
| 7.2 Impedance..... | 23 |
| 7.3 Performance requirements at the terminal input..... | 23 |
| 7.3.1 Definition..... | 23 |
| 7.3.2 Signal level..... | 23 |
| 7.3.3 Other parameters..... | 23 |
| 7.4 Performance requirements at system outlets..... | 23 |
| 7.4.1 Minimum and maximum carrier levels..... | 23 |
| 7.4.2 Mutual isolation between system outlets..... | 23 |
| 7.4.3 Isolation between individual outlets in one household..... | 24 |
| 7.4.4 Isolation between forward and return path..... | 24 |
| 7.4.5 Long-term frequency stability of distributed carrier signals at any system outlet..... | 24 |
| 7.4.6 Carrier level differences at system outlet..... | 24 |
| 7.4.7 Frequency response within a television channel..... | 24 |
| 7.4.8 Random noise at system outlet..... | 24 |
| 7.4.9 Interference to television channels..... | 26 |
| Annex A (normative) RF carrier to noise ratio..... | 28 |
| Annex B (informative) Examples of summation of impairments..... | 31 |
| Bibliography..... | 33 |
| Figure 1 – CATV/MATV/SMATV cable network – Performance requirements..... | 8 |
| Figure 2 – Examples of location of HNI for various home network types..... | 13 |
| Figure 3 – Signal to echo ratio (dB) versus echo delay (μ s)..... | 20 |
| Figure A.1 – Example of a TV receiver IF filter (systems B and G)..... | 28 |

| | |
|--|----|
| Figure A.2 – Example of a demodulated TV signal (systems B and G) | 29 |
| Table 1 – Methods of measurement of IEC 60728-1 applicable in operation..... | 17 |
| Table 2 – Impairment units versus subjective quality..... | 17 |
| Table 3 – Impairment grade versus un-weighted white noise | 18 |
| Table 4 – Impairment grade versus differential gain | 19 |
| Table 5 – Impairment grade versus differential phase | 19 |
| Table 6 – Impairment grade versus short time linear distortion (2T pulse)..... | 19 |
| Table 7 – Impairment grade versus chrominance-luminance gain inequality..... | 19 |
| Table 8 – Impairment grade versus chrominance-luminance delay inequality..... | 19 |
| Table 9 – Impairment grade versus echo rating (1 μ s echo delay)..... | 20 |
| Table 10 – Correction factors to be applied for delays different than 1 μ s..... | 20 |
| Table 11 – Carrier-to-noise ratios and RF signal-to-noise ratios at system outlet (television) in operation | 25 |
| Table 12 – Carrier-to-noise ratios at system outlet (radio) in operation | 26 |
| Table B.1 – Examples of voltage addition | 31 |
| Table B.2 – Examples of power addition | 32 |

iTeh STANDARD PREVIEW
(standards.iteh.ai)

IEC 60728-1-2:2009

<https://standards.iteh.ai/catalog/standards/sist/602702c4-a7f4-4af8-b336-491fdceede5b/iec-60728-1-2-2009>

Withhold

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**CABLE NETWORKS FOR TELEVISION SIGNALS,
SOUND SIGNALS AND INTERACTIVE SERVICES –****Part 1-2: Performance requirements for signals
delivered at the system outlet in operation**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60728-1-2 has been prepared by technical area 5: Cable networks for television signals, sound signals and interactive services, of IEC technical committee 100: Audio, video and multimedia systems and equipment.

This bilingual version, published in 2011-03, corresponds to the English version.

The text of this standard is based on the following documents:

| FDIS | Report on voting |
|---------------|------------------|
| 100/1531/FDIS | 100/1562/RVD |

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

The French version of this standard has not been voted upon.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 60728 series, published under the general title *Cable networks for television signals, sound signals and interactive services*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[IEC 60728-1-2-2009](https://standards.iteh.ai/catalog/standards/sist/602702c4-a7f4-4af8-b336-491fdceede5b/iec-60728-1-2-2009)

<https://standards.iteh.ai/catalog/standards/sist/602702c4-a7f4-4af8-b336-491fdceede5b/iec-60728-1-2-2009>

Withdrawn

INTRODUCTION

Standards of the IEC 60728 series deal with cable networks including equipment and associated methods of measurement for headend reception, processing and distribution of television signals, sound signals and their associated data signals, and for processing, interfacing and transmitting all kinds of signals for interactive services using all applicable transmission media.

This includes

- CATV¹-networks,
- MATV-networks and SMATV-networks,
- individual receiving networks

and all kinds of equipment, systems and installations installed in such networks.

The extent of this standardization work is from the antennas and/or special signal source inputs to the headend or other interface points to the network up to the terminal input.

The standardization of any user terminals (i.e. tuners, receivers, decoders, multimedia terminals, etc.) as well as of any coaxial, balanced and optical cables and accessories thereof is excluded.

The reception of television signals inside a building requires an outdoor antenna and a distribution network to convey the signal to the TV receivers.

This part of IEC 60728 deals with the requirements that must be fulfilled at the system outlet or terminal input, when the CATV/MATV/SMATV system is in operation.

These performance requirements for signals at the system outlet or terminal input in operation are derived from considerations of the characteristics of the received signals at the input of the headend (see Clause 6 of IEC 60728-1) and the summation of the impairments produced by the headend, the CATV/MATV/SMATV network and the home network, when the requirements given in IEC 60728-1 and IEC 60728-1-1 are fulfilled.

This document gives the guidelines for calculation of the operational characteristics at system outlet, taking into account the performance requirements of the CATV/MATV/SMATV network, of the home networks and of the received signals, given in the International Standards IEC 60728-1 and 60728-1-1 prepared by TA 5: Cable networks for television signals, sound signals and interactive services, of IEC technical committee 100: Audio, video and multimedia systems and equipment.

¹ This word encompasses the Hybrid Fibre Coaxial (HFC) networks used nowadays to provide telecommunications services, voice, data, audio and video both broadcast and narrowcast.

CABLE NETWORKS FOR TELEVISION SIGNALS, SOUND SIGNALS AND INTERACTIVE SERVICES –

Part 1-2: Performance requirements for signals delivered at the system outlet in operation

1 Scope

This part of IEC 60728 provides the minimum performance requirements to be fulfilled in operation at the system outlet or terminal input and describes the summation criteria for the impairments present in the received signals and those produced by the CATV/MATV/SMATV cable network, including individual receiving systems.

NOTE 1 When a change of signal format is made at the headend, the summation of the impairments does not apply (see also Clause 7).

In a building divided into apartment blocks, the signals received by the antennas are distributed by the MATV/SMATV cable network up to the home network interface (HNI); the television signals are then distributed (inside the home) by home networks (HN) of various types up to the system outlet or terminal input. The cable network can support two way operation, from the system outlet (or terminal input) towards the headend.

The home network can use coaxial cables, balanced pair cables, fibre optic cables (glass or plastic) and also wireless links inside a room (or a small number of adjacent rooms) to replace wired cords.


This part of IEC 60728 is applicable to cable networks intended for television signals, sound signals and interactive services operating between about 5 MHz and 3 000 MHz. The frequency range is extended to 6 000 MHz for home distribution techniques that replace wired cords with a wireless two way communication inside a room (or a small number of adjacent rooms) that uses the 5 GHz to 6 GHz frequency band.

Figure 1 shows the main sections of a general CATV/MATV/SMATV system, indicating the parts of the IEC 60728-1 series documents where the relevant performance requirements are indicated.

- The requirements for the signals received at the headend are given in Clause 6 of IEC 60728-1.
- The requirements for the CATV/MATV/SMATV cable network, assuming an unimpaired input signal at the input of the headend, up to the system outlet are given in IEC 60728-1, Clause 5.
- The requirements for the CATV/MATV/SMATV cable network up to the home network interface (HNI) are given in IEC 60728-1, Clause 7, assuming an unimpaired input signal at the input of the headend.
- The specific requirements from HNI to the system outlet or terminal input are given in IEC 60728-1-1, Clause 5, assuming an unimpaired input signal at the HNI.
- The requirements at the system outlet in operation are given in Clause 7 of this standard.

The expression “in operation” means that the received signals, with their impairments, are applied to the headend input of the CATV/MATV/SMATV cable network. The requirements at the system outlet “in operation” are derived, therefore, by summing the impairments of the various cascaded parts of the system and of the input signal.

When a change of signal format from analogue to analogue (e.g. from FM to AM-VSB) or from digital to digital (e.g. from QPSK to QAM) or from digital to analogue (e.g. from DVB-S/S2 to AM-VSB or DVB-T to AM-VSB) is made at the headend, the summation of the impairments that produce a relaxation of requirements at system outlet does not apply. Such a case will be the equivalence of unimpaired signals applied at the headend input. Therefore the requirements at system outlet given in IEC 60728-1 apply.



IEC 1012/09

Diagram of the main sections of a CATV/MATV/SMATV cable network and the relevant parts of the IEC 60728-1 series where the requirements are indicated.

Figure 1 – CATV/MATV/SMATV cable network – Performance requirements

This standard also provides references for the basic methods of measurement of the operational characteristics of the downstream cable network in order to assess its performance.

All requirements refer to the performance limits to be achieved in operation at any system outlet when terminated in a resistance equal to the nominal load impedance of the system, unless otherwise specified. Where system outlets are not used, the above applies to the terminal input.

NOTE 2 If the home network is subdivided into a number of parts, using different transmission media (e.g. coaxial cabling, balanced cabling, optical cabling, wireless links) the accumulation of degradations should not exceed the figures given below.

NOTE 3 Performance requirements of return paths as well as special methods of measurement for the use of the return paths in cable networks are described in IEC 60728-10.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-705, *International Electrotechnical Vocabulary (IEV) – Chapter 705: Radio wave propagation*

IEC 60050-712, *International Electrotechnical Vocabulary (IEV) – Chapter 712: Antennas*

IEC 60050-725, *International Electrotechnical Vocabulary (IEV) – Chapter 725: Space radiocommunications*

IEC 60728-1:2007, *Cable networks for television signals, sound signals and interactive services – Part 1: System performance of forward paths*

IEC 60728-1-1 *Cable networks for television signals, sound signals and interactive services – Part 1-1: RF cabling for two way home networks*

IEC 60728-3, *Cable networks for television signals sound signals and interactive services – Part 3: Active wideband equipment for coaxial cable networks*

IEC 60966-2-4, *Radio frequency and coaxial cable assemblies – Part 2-4: Detail specification for cable assemblies for radio and TV receivers – Frequency range 0 MHz to 3 000 MHz, IEC 61169-2 connectors*

IEC 60966-2-5, *Radio frequency and coaxial cable assemblies – Part 2-5: Detail specification for cable assemblies for radio and TV receivers – Frequency range 0 MHz to 1 000 MHz, IEC 61169-2 connectors*

IEC 60966-2-6, *Radio frequency and coaxial cable assemblies – Part 2-6: Detail specification for cable assemblies for radio and TV receivers – Frequency range 0 MHz to 3 000 MHz, IEC 61169-24 connectors*

ITU-R Recommendation BT.500-7, *Methodology for the subjective assessment of the quality of television pictures*

ITU-R Recommendation BT.654, *Subjective quality of television pictures in relation to the main impairments of the analogue composite television signal*

ITU-R Recommendation BT.655, *Radio-frequency protection ratios for AM vestigial sideband terrestrial television systems interfered with by unwanted analogue vision signals and their associated sound signals*

ITU-T Recommendation J.61, *Transmission performance of television circuits designed for use in international connections*

ITU-T Recommendation J.63, *Insertion of test signals in the field-blanking interval of monochrome and colour television signals*

ETSI EN 300 421, *Digital Video Broadcasting (DVB); Framing structure, channel coding and modulation for 11/12 GHz satellite services*

ETSI EN 300 429, *Digital Video Broadcasting (DVB); Framing structure, channel coding and modulation for cable systems*

ETSI EN 300 473, *Digital Video Broadcasting (DVB); Satellite Master Antenna Television (SMATV) distribution systems*

ETSI EN 300 744, *Digital Video Broadcasting (DVB); Framing structure, channel coding and modulation for digital terrestrial television*

ETSI EN 302 307, *Digital Video Broadcasting (DVB); Second generation framing structure, channel coding and modulation systems for Broadcasting, Interactive Services, News Gathering and other broadband satellite applications*

3 Terms, definitions, symbols and abbreviations

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60050-705, IEC 60050-712 and IEC 60050-725 apply.

NOTE The most important definitions are repeated below.

3.1.1

active home network

home network that uses active equipment (for example, amplifiers) in addition to passive equipment such as splitters, taps, system outlets, cables and connectors up to the coaxial RF interface (input and/or output) of the terminal equipment for distributing and combining RF signals

3.1.2

antenna

that part of a radio transmitting or receiving system which is designed to provide the required coupling between a transmitter or a receiver and the medium in which the radio wave propagates

NOTE 1 In practice, the terminals of the antenna or the points to be considered as the interface between the antenna and the transmitter or receiver should be specified.

NOTE 2 If the transmitter or receiver is connected to its antenna by a feeder line, the antenna may be considered to be a transducer between the guided radio waves of the feeder line and the radiated waves in space.

[IEV 712-01-01]

3.1.3

attenuation

ratio of the input power to the output power of an equipment or system, expressed in decibels

3.1.4

balun

device for transforming an unbalanced voltage to a balanced voltage or vice-versa

NOTE The term is derived from "balanced to unbalanced transformer".

3.1.5

bit error ratio

BER

ratio between erroneous bits and the total number of transmitted bits

3.1.6

carrier-to-intermodulation ratio

C/I

difference in decibels between the carrier level at a specified point in a piece of equipment or a system and the level of a specified intermodulation product or combination of products

3.1.7**carrier-to-noise ratio****C/N**

difference in decibels between the vision or sound carrier level at a given point in a piece of equipment or a system and the noise level at that point (measured within a bandwidth appropriate to the television or radio system in use)

3.1.8**cross-modulation**

undesired modulation of the carrier of a desired signal by the modulation of another signal as a result of equipment or system non-linearities

3.1.9**decibel ratio**

ten times the logarithm to the base 10 of the ratio of two quantities of power P_1 and P_2 , that is

$$10 \lg \frac{P_1}{P_2} \quad \text{in dB}$$

NOTE 1 Quantities of power may also be expressed in terms of voltages for a common impedance value (e.g. 75 Ω).

$$20 \lg \frac{U_1}{U_2} \quad \text{in dB}$$

NOTE 2 The abbreviation "lg" in equations signifies " \log_{10} ".

3.1.10**directivity**

attenuation between output port and interface or tap port minus the attenuation between input port and interface or tap port, of any equipment or system

3.1.11**distribution amplifier**

amplifier designed to feed one or more branch or spur feeders

NOTE This is a general term embracing branch amplifier and spur amplifier.

3.1.12**DOCSIS****EuroDOCSIS**

standards defining interface specifications for cable modems and cable modem termination systems for high-speed data communication over RF cable networks

3.1.13**dwelling unit****DU**

home or office where television and sound signals are distributed and where there is access to interactive services

3.1.14**echo rating****E**

result of a system test with a 2T sine-squared pulse (as determined in ITU-T Recommendation J.61 and ITU-T Recommendation J.63) using the boundary line on a specified graticule (for example, Figure 29 of IEC 60728-1) within which all parts of the received pulse fall

NOTE The object of the graticule design is to ensure that the subjective effect of an echo of rating $E\%$ is the same as that of a single echo, with displacement greater than $12T$, of $(E/2)\%$ relative to the peak amplitude of the test pulse.

3.1.15

feeder

transmission path forming part of a cable network

NOTE 1 Such a path may consist of a metallic cable, optical fibre, waveguide, or any combination of them.

NOTE 2 By extension, the term is also applied to paths containing one or more radio links.

3.1.16

gain

ratio of the output power to the input power of any equipment or system, expressed in decibels

3.1.17

headend

equipment which is connected between receiving antennas or other signal sources and the remainder of the cable networks, to process the signals to be distributed

NOTE The headend may, for example, comprise antenna amplifiers, frequency converters, combiners, separators and generators.

3.1.18

headend input

interface of the headend where the signals received by antennas or individual feeder lines are applied for signal processing

3.1.19

home network

HN

RF cable network inside a single dwelling (one-family house or one unit of a multi-dwelling building) in the SOHO (Small Offices Home Offices) environments or in the rooms of hotels, hospitals, etc.; the preferred topology of this network is a star

NOTE This network carries television signals, sound signals and interactive services up to the coaxial RF interface (input and/or output) of the terminal equipment. It may comprise active equipment, passive equipment, cables and connectors.

3.1.20

home network interface

HNI

interface for access to the network for transmission of television signal, sound signals and interactive services inside a home (single dwelling); it is the first accessible point after the entrance of the network into an individual home (see Figure 2)

NOTE In some cases the home network interface may be coincident with the system outlet. In this case the performance requirements for a system outlet apply.




Figure 2 – Examples of location of HNI for various home network types

3.1.21 intermodulation

process whereby non-linearity of equipment in a system produces output signals (called intermodulation products) at frequencies which are linear combinations of those of the input signals

3.1.22 isolation

attenuation between two output, tap or interface ports of any equipment or system

3.1.23 level

decibel ratio of any power P_1 to the standard reference power P_0 , that is

$$10 \lg \frac{P_1}{P_0} \quad \text{in dB}$$

decibel ratio of any voltage U_1 to the standard reference voltage U_0 , that is

$$20 \lg \frac{U_1}{U_0} \quad \text{in dB}$$

NOTE This may be expressed in decibels (relative to 1 μV in 75 Ω) or more simply in dB(μV) if there is no risk of ambiguity and if based on a common impedance value (e.g. 75 Ω).

3.1.24 multiplex

signals from several separate sources assembled into a single composite signal for transmission over a common transmission channel