



## Guide for Fire Hazard Assessment of Rail Transportation Vehicles<sup>1</sup>

This standard is issued under the fixed designation E 2061; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

<sup>ε1</sup> NOTE—An editorial change was made in Note X2.2 in June 2001.

### INTRODUCTION

The traditional approach to codes and standards is the specification of individual fire-test-response requirements for each material, component, or product that is found in a given environment and is deemed important to maintain satisfactory levels of fire safety. This practice has been in place for so long that it gives a significant level of comfort; manufacturers know what is required to comply with the specifications and specifiers simply apply the requirements. The implicit assumptions are not stated, but they are that the use of the prescribed requirements ensures an adequate level of safety. There is no need to impose any change on those manufacturers who supply safe systems meeting existing prescriptive requirements; however, as new materials, components, and products are developed, manufacturers, designers, and specifiers often desire the flexibility to choose how overall safety requirements are to be met. It is the responsibility of developers of alternative approaches to state explicitly the assumptions being made which result in a design having an equivalent level of safety. One way to generate explicit and valid assumptions is to use a performance-based approach, based on test methods that provide data in engineering units, suitable for use in fire safety engineering calculations, as this guide provides.

This fire hazard assessment guide focuses on rail transportation vehicles. Such a fire hazard assessment requires developing all crucial fire scenarios that must be considered and consideration of the effect of all contents and designs within the rail transportation vehicle, which will potentially affect the resulting fire hazard. The intention of this guide is that rail transportation vehicles be designed either by meeting all the requirements of the traditional prescriptive approach or by conducting a fire hazard assessment, that needs to provide adequate margins of error, in which a level of safety is obtained that is equal to or greater than the level of safety resulting from the traditional approach.

### 1. Scope

1.1 This is a guide to developing fire hazard assessments for rail transportation vehicles. It has been written to assist professionals, including fire safety engineers, who wish to assess the fire safety of rail transportation vehicles, during or after their design (see also 1.6). This guide is not in itself a fire hazard assessment nor does it provide acceptance criteria; thus, it cannot be used for regulation.

1.2 Hazard assessment is a process that results in an estimate of the potential severity of the fires that can develop under defined scenarios, once defined incidents have occurred. Hazard assessment does not address the likelihood of a fire occurring. Hazard assessment is based on the premise that an ignition has occurred, consistent with a specified scenario, and

that potential outcomes of the scenario can be reliably estimated.

1.3 Consistent with 1.2, this guide provides methods to estimate whether particular rail passenger designs provide an equal or greater level of fire safety when compared to designs developed based on the traditional applicable fire-test-response characteristic approaches currently widely used in this industry. Such approaches have typically been based on prescriptive test methodologies, as exemplified by guidelines of the Federal Railroad Administration (FRA) and recommended practices of the Federal Transit Administration (FTA) (Table X1.1). Selective use of parts of the methodology in this guide and of individual fire-test-response characteristics from Table X1.1 does not satisfy the fire safety objectives of this guide or of the table. This guide shall be used in its entirety to develop a fire hazard assessment for rail transportation vehicles or to aid in the design of such vehicles.

1.4 This guide includes and applies accepted and clearly

<sup>1</sup> This guide is under the jurisdiction of ASTM Committee E05 on Fire Standards and is the direct responsibility of Subcommittee E05.17 on Transportation.

Current edition approved April 10, 2001. Published May 2001. Originally published as E 2061 – 00. Last previous edition E 2061 – 00b.

defined fire safety engineering techniques and methods consistent with both existing, traditional prescriptive codes and standards and performance based fire codes and standards under development throughout the world.

1.5 This guide provides recommended methods to mitigate potential damage from fires in rail transportation vehicles, by assessing the comparative fire hazard of particular products, assemblies, systems or overall designs intended for use in rail transportation vehicles. Such methods could include changes to the materials, components, products, assemblies, or systems involved in the construction of the rail transportation vehicle or changes in the design features of the vehicle, including the number and location of automatically activated fire safety devices present (see 4.4.4 for further details).

1.6 This guide is intended, among other things, to be of assistance to personnel addressing issues associated with the following areas.

1.6.1 Design and specification of rail transportation vehicles.

1.6.2 Fabrication of rail transportation vehicles.

1.6.3 Supply of assemblies, subassemblies, and component materials, for use in rail transportation vehicles.

1.6.4 Operation of rail transportation vehicles.

1.6.5 Provision of a safe environment for all occupants of a rail transportation vehicle.

1.7 The techniques provided in this guide are based on specific assumptions in terms of rail transportation vehicle designs, construction and fire scenarios. These techniques can be used to provide a quantitative measure of the fire hazards from a specified set of fire conditions, involving specific materials, products, or assemblies. Such an assessment cannot be relied upon to predict the hazard of actual fires, which involve conditions, or vehicle designs, other than those assumed in the analysis. In particular, the fire hazard may be affected by the anticipated use pattern of the vehicle.

1.8 This guide can be used to analyze the estimated fire performance of the vehicle specified under defined specific fire scenarios. Under such scenarios, incidents will begin either inside or outside a vehicle, and ignition sources can involve vehicle equipment as well as other sources. The fire scenarios to be used are described in detail in Section 5.3.

1.8.1 Fires with more severe initiating conditions than those assumed in an analysis may pose more severe fire hazard than that calculated using the techniques provided in this guide. For this reason severe fire conditions must be considered as part of an array of fire scenarios.

1.9 This guide is to be used to predict or provide a quantitative measure of the fire hazard from a specified set of fire conditions involving specific materials, products, or assemblies. This assessment does not necessarily predict the hazard of actual fires, which involve conditions other than those assumed in the analysis.

NOTE 1—While 1.9 is the standard caveat described in section F2.2.2.2 of the Form and Style for ASTM Standards manual for fire hazard assessment standards, this guide is a guide and cannot be used to provide quantitative measures.

## 2. Referenced Documents

### 2.1 ASTM Standards:

- C 542 Specification for Lock-Strip Gaskets<sup>2</sup>
- C 1166 Test Method for Flame Propagation of Dense and Cellular Elastomeric Gaskets and Accessories<sup>2</sup>
- D 123 Terminology Relating to Textiles<sup>3</sup>
- D 2724 Test Methods for Bonded, Fused, and Laminated Apparel Fabrics<sup>3</sup>
- D 3574 Test Methods for Flexible Cellular Materials—Slab, Bonded, and Molded Urethane Foams<sup>4</sup>
- D 3675 Test Method for Surface Flammability of Flexible Cellular Materials Using a Radiant Heat Energy Source<sup>4</sup>
- D 5424 Test Method for Smoke Obscuration of Insulating Materials Contained in Electrical or Optical Fiber Cables When Burning in a Vertical Cable Tray Configuration<sup>5</sup>
- D 5537 Test Method for Heat Release, Flame Spread and Mass Loss Testing of Insulating Materials Contained in Electrical or Optical Fiber Cables When Burning in a Vertical Cable Tray Configuration<sup>5</sup>
- D 6113 Test Method for Using a Cone Calorimeter to Determine Fire-Test-Response Characteristics of Insulating Materials Contained in Electrical or Optical Fiber Cables<sup>4</sup>
- E 119 Test Methods for Fire Tests of Building Construction and Materials<sup>2</sup>
- E 162 Test Method for Surface Flammability of Materials Using a Radiant Heat Energy Source<sup>2</sup>
- E 176 Terminology of Fire Standards<sup>2</sup>
- E 603 Guide for Room Fire Experiments<sup>2</sup>
- E 648 Test Method for Critical Radiant Flux of Floor-Covering Systems Using a Radiant Heat Energy Source<sup>2</sup>
- E 662 Test Method for Specific Optical Density of Smoke Generated by Solid Materials<sup>2</sup>
- E 906 Test Method for Heat and Visible Smoke Release Rates for Materials and Products<sup>2</sup>
- E 1321 Test Method for Determining Material Ignition and Flame Spread Properties<sup>2</sup>
- E 1354 Test Method for Heat and Visible Smoke Release Rates for Materials and Products Using an Oxygen Consumption Calorimeter<sup>2</sup>
- E 1355 Guide for Evaluating the Predictive Capability of Fire Models<sup>2</sup>
- E 1472 Guide for Documenting Computer Software for Fire Models<sup>2</sup>
- E 1474 Test Method for Determining the Heat Release Rate of Upholstered Furniture and Mattress Components or Composites Using a Bench Scale Oxygen Consumption Calorimeter<sup>2</sup>
- E 1537 Test Method for Fire Testing of Seating Upholstered Furniture<sup>2</sup>
- E 1546 Guide for the Development of Fire-Hazard-Assessment Standards<sup>2</sup>
- E 1590 Test Method for Fire Testing of Mattresses<sup>2</sup>
- E 1591 Guide for Data for Fire Models<sup>2</sup>
- E 1623 Test Method for Determination of Fire and Thermal Parameters of Materials, Products, and Systems Using an

<sup>2</sup> Annual Book of ASTM Standards, Vol 04.07.

<sup>3</sup> Annual Book of ASTM Standards, Vol 07.01

<sup>4</sup> Annual Book of ASTM Standards, Vol 08.02.

<sup>5</sup> Annual Book of ASTM Standards, Vol 10.02.

Intermediate Scale Calorimeter (ICAL)<sup>2</sup>  
 E 1740 Test Method for Determining the Heat Release Rate and Other Fire-Test-Resistance Characteristics of Wallcovering Composites Using a Cone Calorimeter<sup>2</sup>  
 2.2 *NFPA Standards:*<sup>6</sup>  
 NFPA 70 National Electrical Code  
 NFPA 130 Standard for Fixed Guideway Transit Systems  
 NFPA 262 Standard Method of Test for Flame Travel and Smoke of Wires and Cables for Use in Air-Handling Spaces  
 NFPA 265 Standard Methods of Fire Tests for Evaluating Room Fire Growth Contribution of Textile Wall Coverings  
 NFPA 901 Uniform Coding for Fire Protection  
 2.3 *ISO Standards:*<sup>7</sup>  
 ISO Guide 52: Glossary of Fire Terms and Definitions  
 ISO 4880: Burning Behaviour of Textiles and Textile Products  
 ISO 9705: Full Scale Room Fire Test for Surface Products  
 2.4 *Federal Aviation Administration Standards:*<sup>8</sup>  
 FAR 25.1359: Federal Aviation Administration 60° Bunsen Burner Test for Electric Wire  
 FAR 25.853 (a): Federal Aviation Administration Vertical Bunsen Burner Test  
 FAR 25.853 (c): Federal Aviation Administration Oil Burner Test for Seat Cushions  
 2.5 *Other Federal Standards:*<sup>9</sup>  
 Americans with Disabilities Act  
 FED STD 191A Textile Test Method 5830  
 2.6 *Underwriters Laboratories Standards:*<sup>10</sup>  
 UL 44: Standard for Safety for Thermoset-Insulated Wires and Cables  
 UL 83: Standard for Safety for Thermoplastic-Insulated Wires and Cables  
 UL 1581: Reference Standard for Electrical Wires, Cables, and Flexible Cords, 1080 (VW-1 (Vertical Wire) Flame Test)  
 UL 1581: Reference Standard for Electrical Wires, Cables, and Flexible Cords, 1160 Vertical Tray Flame Test  
 UL 1685: Standard Vertical Tray Fire Propagation and Smoke Release Test for Electrical and Optical Fiber Cables  
 UL 1975: Standard Fire Tests for Foamed Plastics Used for Decorative Purposes  
 2.7 *Canadian Standards Association Standards:*<sup>11</sup>

CSA Standard C22.2 No. 3, Test Methods for Electrical Wires and Cables, Vertical Flame Test—Cables in Cable Trays/FT4  
 2.8 *Institute of Electrical and Electronic Engineers Standards:*<sup>12</sup>  
 IEEE Standard 383, Standard for Type Tests of Class 1E Electric Cables, Field Splices, and Connections for Nuclear Power Generating Stations  
 2.9 *National Electrical Manufacturing Association Standards:*<sup>13</sup>  
 NEMA WC 3/ICEA S-19, Rubber-Insulated Wire and Cable for the Transmission and Distribution of Electrical Energy  
 2.10 *CA Standards:*<sup>14</sup>  
 CA Technical Bulletin 129, Flammability Test Procedure for Mattresses for Use in Public Buildings  
 CA Technical Bulletin 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies

### 3. Terminology

3.1 *Definitions*—For terms related to fire used in this guide, refer to Terminology E 176 and ISO Guide 52. In case of conflict, the terminology in Terminology E 176 shall prevail. For terms relating to textiles used in this guide, refer to Terminology D 123 or to ISO 4880. In case of conflict, the terminology in Terminology D 123 shall prevail.

3.1.1 *fire-characteristic profile, n*—array of fire-test-response characteristics, all measured using tests relevant to the same fire scenario, for a material, product, or assembly to address, collectively, the corresponding fire hazard.

3.1.1.1 *Discussion*—This array of fire-test response characteristics is a set of data relevant to the assessment of fire hazard in a particular fire scenario. In other words, all the fire tests used would have a demonstrated validity for the fire scenario in question, for example, by having comparable fire intensities. The fire-characteristic profile is intended as a collective guide to the potential fire hazard from a material, product, or assembly involved in a fire that could be represented by the laboratory test conditions.

3.1.2 *fire hazard, n*—the potential for harm associated with fire.

3.1.2.1 *Discussion*—A fire may pose one or more types of hazard to people, animals, or property. These hazards are associated with the environment and with a number of fire-test-response characteristics of materials, products, or assemblies including but not limited to ease of ignition, flame spread, rate of heat release, smoke generation and obscuration, toxicity of combustion products, and ease of extinguishment (see Terminology E 176).

3.1.3 *fire performance, n*—response of a material, product, or assembly in a specific fire, other than in a fire test involving controlled conditions (different from fire-test-response characteristics, q.v.)

<sup>6</sup> Available from the National Fire Protection Association (NFPA), 1 Batterymarch Park, Quincy, MA, 02269–9101.

<sup>7</sup> Available from International Standardization Organization, P.O. Box 56, CH-1211; Geneva 20, Switzerland or from the American National Standards Institute, 11 West 42nd Street, New York, NY 10046.

<sup>8</sup> Available from the Federal Aviation Administration, Technical Center, Atlantic City International Airport, Atlantic City, NJ 08405.

<sup>9</sup> Available from General Services Administration, Specifications Activity, Printed Materials Supply Division, Building 197, Naval Weapons Plant, Washington, DC 20407.

<sup>10</sup> Available from Underwriters Laboratories, Inc., 333 Pfingsten Rd., Northbrook, IL 60062.

<sup>11</sup> Available from the Canadian Standards Associations, 178 Rexdale Blvd., Rexdale, Ontario, Canada M9W 1R3.

<sup>12</sup> Available from the Institute of Electrical and Electronic Engineers, Inc., 345 East 47th Street, New York, NY 10017.

<sup>13</sup> Available from National Electrical Manufacturers Association, 1300 North 17th St., Ste 1847, Rosslyn, VA 22209.

<sup>14</sup> Available from California Bureau of Home Furnishings and Thermal Insulation, State of California, Department of Consumer Affairs, 3485 Orange Grove Avenue, North Highlands, CA 95660–5595.

3.1.3.1 *Discussion*—The ASTM policy on fire standards distinguishes between the response of materials, products, or assemblies to heat and flame “under controlled conditions,” which is fire-test-response characteristic, and “under actual fire conditions,” which is fire performance. Fire performance depends on the occasion or environment and may not be measurable. In view of the limited availability of fire-performance data, the response to one or more fire tests, approximately recognized as representing end-use conditions, is generally used as a predictor of the fire performance of a material, product, or assembly (see Terminology E 176).

3.1.4 *fire scenario, n*—a detailed description of conditions, including environmental, of one or more of the steps from before ignition to the completion of combustion in an actual fire, or in a full-scale simulation.

3.1.4.1 *Discussion*—The conditions describing a fire scenario, or a group of fire scenarios, are those required for the testing, analysis, or assessment that is of interest. Typically, they are those conditions that can create significant variation in the results. The degree of detail necessary will depend upon the intended use of the fire scenario. Environmental conditions may be included in a scenario definition but are not required in all cases. Fire scenarios often define conditions in the early steps of a fire while allowing analysis to calculate conditions in later steps (see Terminology E 176).

3.1.5 *flashover, n*—the rapid transition to a state of total surface involvement in a fire of combustible materials within an enclosure.

3.1.5.1 *Discussion*—Flashover occurs when the surface temperatures of an enclosure and its contents rise, producing combustible gases and vapors, and the enclosure heat flux becomes sufficient to heat these gases and vapors to their ignition temperatures. Flashover commonly occurs when the upper layer temperature reaches 600°C or when the radiant heat flux at the floor reaches 20 kW/m<sup>2</sup> (see Terminology E 176).

3.1.6 *smoke, n*—the airborne solid and liquid particulates and gases evolved when a material undergoes pyrolysis or combustion (see Terminology E 176).

### 3.2 Definitions of Terms Specific to This Standard:

3.2.1 *heat release rate, n*—the calorific energy released per unit time by the combustion of a material under specified test conditions.

3.2.2 *product, n*—material, component, or complete end-use product, in use in fixed guideway transportation vehicles.

## 4. Significance and Use

4.1 This guide is intended for use by those undertaking the development of fire hazard assessments for rail transportation vehicles and products contained within rail transportation vehicles.

4.2 This guide provides information on an approach to develop a fire hazard assessment, but fixed procedures are not established. Any limitations in the availability of data, of appropriate test procedures, of adequate fire models, or in the advancement of scientific knowledge, will place significant constraints upon the procedure for the assessment of fire hazard.

4.3 A fire hazard assessment developed following this guide

must specify all steps required to determine fire hazard measures for which safety thresholds or pass/fail criteria can be meaningfully set by responsible authorities. It is preferred that such exercises have input from various sources.

4.4 *Outcomes: Use and Application.* A fire hazard assessment developed as a result of using this guide should be able to assess a new product being considered for use in a certain rail transportation vehicle and reach one of the conclusions listed in 4.4.1-4.4.4.

4.4.1 *New Product Safer than Product Currently in Use.* The new product is safer, in terms of predicted fire performance, than the one in established use. In this case, the new product is desirable, from the point of view of fire safety.

4.4.2 *New Product Equivalent in Safety to Product Currently in Use.* There is no difference between the predicted fire safety of the new product and of the one in established use. In this case, use of the new product provides neither advantage nor disadvantage, from the point of view of fire safety.

4.4.3 *New Product Less Safe than Product Currently in Use.* The new product is less safe, in terms of predicted fire performance, than the one in established use. In this case, a direct substitution of products would provide a lower level of safety and the new product would be undesirable, and should not be used, from the point of view of fire safety, without other compensatory changes being made.

4.4.3.1 *New Product Different in Safety to Product Currently in Use.* A new product that is less safe, in terms of predicted fire performance, can nevertheless be made acceptable if, and only if, it is part of a complete, comprehensive, fire safety design for the rail transportation vehicle. Such redesign of the vehicle should include other features such as use of an alternative layout or increased use of automatic fire protection systems, that demonstrably produce the same or better safety for the complete design. In such cases, a more in-depth fire hazard assessment would have to be conducted to ensure that the entire design achieves the safety goals, and the new product would be acceptable only as part of the larger, approved design.

4.4.4 The new product could offer some safety advantages and some safety disadvantages over the item in established use. An example of such an outcome could be increased smoke obscuration with decreased heat release. In such cases, a more in-depth fire hazard assessment would have to be conducted to ensure that the advantages outweigh the disadvantages, and the resulting overall level of safety is no less than that provided by the traditional approach (see Table X1 and Appendix X1).

4.5 Following the analysis described in 4.4, a fire hazard assessment developed following this guide would reach a conclusion regarding the desirability of the new product studied. It is essential for the results of the assessment to lead to a design that is at least as safe as the one being replaced.

## 5. Procedure

### 5.1 Fire Safety Objectives

5.1.1 The primary fire safety objective is to ensure the safe (unharmful) evacuation of all occupants of a rail transportation vehicle in the event of a fire.

5.1.1.1 This is achieved if the time required, in the event of a fire, to evacuate the vehicle is less than the time for the fire to create untenable conditions, preferably for the fire not to

create conditions that cause harm to people, whenever possible, in the passenger compartment. The evacuation time includes the time required for the occupants to reach, or be transported, to a safe location and notification time.

5.1.1.2 The time to untenability shall be the shortest time until untenable conditions are created for any occupant starting at any location within the vehicle or along the evacuation path.

5.1.1.3 If the fire scenario involves a vehicular accident, then the assessment shall assume evacuation is achieved through rescue by emergency personnel. The fire hazard assessment needs to recognize that the accident may take place in an area (or at a time) when such rescue is difficult. Examples of conditions of difficult access are tunnels, bridges, remote locations, and unfavorable weather.

5.1.1.4 Tenability is assessed on the basis of fire effects on the occupants, including both direct effects, such as heat, toxic gases, or oxygen deprivation, and indirect effects, such as reduced visibility due to smoke obscuration. A tenable environment, therefore, will prevent loss of life and reduce the likelihood of harm, including nonfatal injury to individuals.

(1) Levels of tenability should be set by the developer of the fire hazard assessment generated from using this guide or by the specific.

NOTE 2—Investigations of the tenability in a fire scenario have shown the maximum temperatures which human beings can withstand (1-3),<sup>15</sup> the maximum convected heat humans can tolerate (4), the heat flux required to blister or burn skin (5-8), the restrictions to escape imposed by smoke obscuration (9, 10), the effects of the primary toxic gases (11-16), the overall effects of smoke toxicity (17-20) and various ways to combine one or more of these effects (4, 21 and 22).

(2) If no levels of tenability are chosen, the default tenability criteria should be the values specified in the documentation for HAZARD (21, 22)

5.1.2 A secondary fire safety objective is to prevent flash-over inside the rail transportation vehicle.

5.1.3 The user shall consider inclusion of a third fire safety objective, which is to maintain a safe working environment for safety personnel, including fire fighters.

## 5.2 Considerations of Design Factors in Calculations for Estimates of Fire Hazard

5.2.1 The issue of design of products or entire rail transportation vehicles can have significant impact on fire safety. Design specifications can be used as input into the calculation methods of a fire hazard assessment; however, for design specifications to be useful, they cannot be expressed in vague terms but must be expressed as either numerical values or as other instructions, for example, equations compatible with the fire hazard assessment calculation method used.

5.2.1.1 Once expressed as numerical or other specific values, design specifications are a source for input variables for fire hazard assessment. For example, design specifications will include specification of the materials or components to be used in the vehicle compartment linings, including ceilings, walls, and floors. The calculations required to assess whether flash-over will be prevented in the vehicle (an objective specified in

5.1.2) will require heat absorption parameters for the compartment linings. These heat absorption parameters will not be identical to the design specifications for the compartment lining materials but will be derivable from these specifications by reference to data from established test methods. Because this guide does not specify the models as calculation methods to be used, it follows that it cannot list the input variables that will be required or the appropriate procedures to use in deriving those input variables from design specifications.

5.2.1.2 A fire hazard assessment is an evaluation of a complete design that addresses certain fire safety objectives; therefore, the design specifications used must address and include all relevant products and design features used, including those specified by conventional prescriptive practices. A fire hazard assessment of a retrofit, rebuild, or repair cannot be limited to the parts of the design being changed. Rather, a fire hazard assessment of a retrofit carried out according to the practices presented in this guide must address the resulting car, including contents, in its entirety.

5.2.1.3 This guide does not address minor changes to vehicles designed using components or materials that are defined originally by property lists, such as those described in 5.7.8. In such cases, the techniques presented in this guide will have less applicability and may present fewer, if any, economic benefits than continuing the use of the lists described in 5.7.8.

5.2.2 In connection with this guide, the term “design” refers both to the general arrangement of the vehicle (for example, size, location of doors and windows, the nature of emergency exits, the number and configuration of levels and compartments) and to the materials, components, and products used to fabricate the vehicle. The development of such designs often involves decisions that include tradeoffs and ad-hoc benefit analyses and is a traditional approach.

5.2.2.1 An example of such a decision are trade-offs considered between using traditional glazing materials, which are not combustible but have high mass and low impact resistance. The use of these materials may compromise passenger and staff security, due to the hazard of projectiles. An alternative, to address hazards posed by projectiles to noncombustible, but friable, glazing is the use of more impact resistant materials, which are combustible.

NOTE 3—The use of plastic glazing materials with high impact resistance is a common practice in the transportation industry and has been since the 1970s.

5.2.3 Design specifications for materials, components, and products will include fire-test-performance characteristics. Appendix X1 and Appendix X4 provide a list of test methods from which the test methods to be used should be chosen. Alternative test methods are contained in Table X1 (23) and Appendix X1, and they generate fire-test-response characteristics, albeit ones that cannot be used for fire safety engineering calculations.

5.2.3.1 The test methods referenced include, but are not limited to, those required to measure the fire-test-response characteristics included in recommendations or requirements of NFPA 130, the Federal Railroad Administration (FRA) (24) AMTRAK (25), and the Federal Transit Administration (FTA) (26). A new FRA rule was issued in 1999, which incorporated

<sup>15</sup> The boldface numbers in parentheses refer to the list of references at the end of this standard.

the majority of the earlier FRA guidelines (27).

(1) The choice of any test method is nonmandatory, and the developer of a fire hazard assessment will need to provide evidence of its validity for use in testing of rail transportation system components or composites (see also 5.7.7.1). Design and quality control of component materials critically affects the precision of composite fire test results; therefore, manufacturers should ensure consistency in the fire performance of components which are assessed as part of a composite system, preferably by testing the components.

5.2.3.2 The test methods referenced in Appendix X4 have been designed to yield results in fire safety engineering units, which are appropriate for fire hazard assessment, and measure heat release rate, which has been demonstrated to be an essential component of fire hazard assessment (28, 29).

5.2.3.3 It is likely that design specifications of any finished product with different component materials will not be available normally (from the suppliers of the individual materials or components that go into them) in a form suitable for application of fire hazard assessment. Manufacturers of such products normally cannot be expected to have developed data on characteristics that are not part of existing sets of requirements or recommendations for their products. Similarly, suppliers of individual materials cannot be expected to identify or provide materials, components, or products, based exclusively on the kinds of design specifications required for fire hazard assessment; therefore, suppliers of such products may require the translation of the performance specifications into conventional specifications for the individual materials. A prescriptive approach to achieve fire safety objectives should always exist as an alternative. In the case of rail transportation vehicles, such an approach would be through use of the traditional methods as exemplified by the recommendations in Table X1 and Appendix X1. The hazard assessment approach becomes an option available to those manufacturers who prefer to seek alternative means of achieving acceptable levels of fire safety inside rail transportation vehicles.

### 5.3 Fire Scenarios

5.3.1 Fire Scenario 1 is a fire that originates within the rail transportation vehicle.

5.3.1.1 Fire Scenario 1a, specified as the highest-challenge likely scenario of this type, begins as an incendiary ignition involving the use of accelerants and prior damage exposing the fillings of the two upholstered seats nearest the point of ignition. Fire begins while the vehicle is in motion between stations, at the maximum distance from any station (see also Appendix X3).

5.3.1.2 Fire Scenario 1b, specified as one of the most common scenarios, is a trash fire that begins under a seat assembly and spreads to that seat assembly, in a passenger compartment.

5.3.1.3 If cooking is permitted on any passenger vehicle, an additional fire scenario, to be called Scenario 1c, also must be assessed. Fire Scenario 1c is a cooking fire originating at the cooking equipment and involving initial ignition of cooking fuel, if equipment is gas-fueled, or cooking oil, if equipment is not gas-fueled. Fire begins while the vehicle is in motion between stations, at the maximum distance from any station.

5.3.1.4 If there are one or more vehicles provided for overnight sleeping, fire scenario 1d also must be assessed, where Fire Scenario 1d is a small open-flame ignition of bedding in an unoccupied bed in a vehicle, with other beds occupied by sleeping people. Fire begins while the vehicle is in motion between stations, at the maximum distance between stations.

5.3.1.5 If there are one or more vehicles provided for cargo (or cargo storage space is provided within a passenger vehicle), Fire Scenario 1e also must be assessed, where Fire Scenario 1e consists of small open-flame ignition of a combustible, for example trash, in a fully-filled cargo vehicle. The assumed fuel load shall be the maximum allowed, including the highest quality of hazardous materials possible under the planned operating procedures. Openings connecting the cargo vehicle to an assumed adjacent passenger vehicle shall be assumed to be open to the maximum degree permitted by the design.

5.3.1.6 If the rail transportation vehicle overturns and then catches on fire, it is possible that different considerations apply as a function of the way the vehicle ends up. If it remains in its normal orientation, the earlier scenarios apply, but if it falls on its side or if it turns around completely, to end up upside down, they represent different scenarios. In both cases, fire begins while the vehicle is stationary between stations, at the maximum distance between stations.

5.3.2 Fire Scenario 2 is a fire that originates outside the rail transportation vehicle, penetrates the rail transportation vehicle, and endangers the evacuation route from the vehicle through the spread of flames or smoke into the evacuation route.

5.3.2.1 Fire Scenario 2a, specified as the highest-challenge likely scenario of this type, begins with ignition of a fuel spill following a collision with survivors. Fire begins in a tunnel, where the vehicle has stopped due to the collision, at a point maximally distant from any egress to the outside. Evacuation is to a place of safe refuge.

5.3.2.2 If the vehicles are individually electrically powered, Fire Scenario 2b must be assessed, where Fire Scenario 2b is an electrical fire that causes the vehicle to stop in a tunnel, at a point maximally distant from any egress to the outside. The interruption of electrical power also affects operation of the vehicle doors, in accordance with the vehicle's design. The point of origin is assumed to be whatever point in the electrical system will lead to the fastest spread of smoke and toxic gases to the vehicle interior.

5.3.3 The specification of fire scenarios included in this section assumes that other fire scenarios either are less severe, and therefore, will lead to achievement of fire safety objectives if the design achieves the objectives for the specified fire scenarios, or are sufficiently unlikely that they need not be considered as part of the overall fire hazard assessment, although they may be considered individually.

5.3.3.1 The fire scenarios that are appropriate for a certain rail system may not be adequate for a different rail system. Additional or different fire scenarios may be needed in certain cases.

### 5.4 Additional Model Assumptions

5.4.1 Occupancy of the rail transportation vehicle and any

other relevant occupiable spaces, such as the platform to which occupants may move to evacuate, shall be set for analysis purposes so as to pose the greatest challenge to the fire safety objectives. A logical assumption would be occupancy to capacity and a mix of occupants of different abilities, where some will have various physical or mental disabilities, and capabilities, for example, some will be assumed to be impaired by alcohol, or drugs, or by age-related limitations.

5.4.1.1 Assumptions regarding numbers and abilities of disabled persons shall incorporate relevant provisions of the Americans with Disabilities Act.<sup>9</sup>

5.4.1.2 Assumptions regarding age distributions of the occupants shall reflect data on age patterns among users of the rail system. Assumptions regarding the capabilities of older or younger occupants shall reflect patterns in the general population, or known applications to the specific rail transportation scenario chosen, if they differ, and shall be documented as to sources of data.

5.4.1.3 Assumptions regarding alcohol or drug impairment among occupants shall be documented as to source data and shall be based on patterns in the general population, weighted to reflect the age and economic distribution of users of the rail system. If such data are not available, conservatively assume that 10 % of adult occupants are impaired by alcohol.

5.4.1.4 If the rail vehicles provide sleeping accommodations, assume that fire occurs when the maximum number of occupants will be sleeping. If there are no data available to determine the maximum fraction of people sleeping, assume all passengers are sleeping.

#### 5.5 Required Calculations

5.5.1 The fire hazard assessment involves using one or more calculation procedures to determine whether the fire safety objectives in Section 5.1 will be met if the design specified in Section 5.2 experiences each of the fires of the scenarios specified in Section 5.3, and given the additional assumptions specified in Section 5.4.

5.5.1.1 This guide does not assign a specific choice of calculation procedure just as it does not assign a specific test method. It simply gives guidance on the types of procedures available and on the required output to generate a valid fire hazard assessment.

5.5.1.2 Use Guide E 1546 when developing the procedure.

5.5.1.3 Use NFPA 901 if needed for overall coding of materials or products.

5.5.2 Because the fire safety objectives are all stated in terms of specified fire effects by location and time, the fire hazard assessment calculation procedures must support the calculations in 5.5.2.1-5.5.2.5.

5.5.2.1 Translate the fire scenario specifications into a description of the fire in its initial stages, as a function of time in the initially involved space. The fire-test-response characteristics of the materials, components, or products initially involved that should be considered for such a description are rate of heat release, rate of mass loss, total heat release (if burned to completion, or cumulative heat release to end of burning otherwise), flame spread, cumulative full-scale smoke obscuration and toxic potency of the products of combustion released. A thorough analysis of the actual rail transportation

vehicle fire scenario should result in a final decision on the properties required for the fire hazard assessment. If the product under consideration is a structural component, assess also its fire endurance.

5.5.2.2 Assess and evaluate the vehicle design specifications to develop and describe foreseeable characteristics of the fuel load environment near the initial fire. Use these and the time-based description of the initial fire as a function of time to calculate the spread of fire to secondary items and the ignition of those secondary items.

5.5.2.3 For each space, or potential fire compartment, calculate the timing of major fire events, including the onset of flashover, as well as, fire spread from one space to an adjacent space, whether through barriers or not, particularly from outside a rail vehicle to inside the vehicle. The calculation of fire spread from one space to another will require measurement of barrier fire resistance characteristics.

5.5.2.4 For each potentially exposed occupant, calculate the time to reach safe refuge and compare it to the calculated time until exposure to an unacceptable potential for harm (hazard). The former requires calculation of occupant alerting response, travel speed, and other behavior. For occupants requiring rescue, calculations will need to estimate the size, capabilities, and arrival time of fire department or other rescue personnel. The latter can be calculated as time to exposure to an untenable cumulative dose of fire effects or conservatively calculated as time to first exposure to unacceptably hazardous fire conditions. Calculations will be required for the area of fire origin, any occupied spaces, and any spaces that are part of escape or rescue routes.

5.5.2.5 When making the calculations described in 5.5.2.3 and 5.5.2.4, incorporate the activation and effects of any fire protection systems, including automatic or manual fire suppression, detection, and smoke control systems. Consider that, once a collision has occurred, electrically-controlled detection and protection systems may be damaged.

5.5.3 For the fire safety objective of preventing flashover, flashover shall be calculated as occurring when the radiative heat flux at the center of the floor reaches 20 kW/m<sup>2</sup>. Other fire characteristics that are sometimes used as indicators of flashover, such as an upper layer temperature of 600°C, can be used in the calculations but are not to be used to assess achievement of the objective.

#### 5.6 Procedural Steps in Conducting a Fire Hazard Assessment

5.6.1 The detailed procedural steps for conducting a fire hazard assessment on a product in a rail transportation vehicle are given in Section 5.7, for the fire safety objectives, see Section 5.1. Conducting these procedures requires applying the design considerations in Section 5.2; for the scenarios considered, see Section 5.3; and, under the additional assumptions presented, see Section 5.4. Appendix X1 and Appendix X4 provide a list of test methods from which the test methods to be used should be chosen (see also X3.3). Some appropriate calculation methods are listed in Appendix X5 and Appendix X6.

5.6.2 Following the steps in Section 5.7, the final step in a fire hazard assessment procedure should be the development of

a detailed procedure to ensure consistent quality control over time.<sup>16</sup> In the absence of prescriptive small-scale tests that dictate the minimum fire-test response characteristics required for each material, component, or product, alternative means should be described so that the fire safety of the rail transportation vehicle can be ensured without having to conduct full rail transportation vehicle burn tests.

#### 5.7 Steps in Conducting a Fire Hazard Assessment

5.7.1 Fire hazard assessment begins by choosing fire safety objective(s) to be achieved. This step is described in Section 5.1.

5.7.2 Fire hazard assessment requires specification of the design to be assessed, in a form that permits the fire safety performance of the design to be tested and modeled. This step is described in Section 5.2.

5.7.3 Fire hazard assessment requires specification of the fire scenarios for which a design must meet the fire safety objectives. This step is described in Section 5.3.

5.7.4 Fire hazard assessment requires specification of any additional assumptions, such as conditions of the environment, in the assessment. This step is described in Section 5.3.

5.7.5 Fire hazard assessment finds a specified design to be acceptable if, under the specified assumptions, a vehicle built to the design will meet each of the objectives for each of the specified fire scenarios.

5.7.6 It is the intention of this standard to maintain or exceed the levels of fire safety in rail transportation vehicles associated with the traditional applicable fire-test-response characteristic requirements for rail transportation systems, including the recommendations from the Federal Transit Administration and the guidelines from the Federal Railroad Administration, while providing an alternative method of assessing designs to achieve equivalent safety. Appendix X7 (30, 31) illustrates the level of safety achieved in 1990–1991.

5.7.6.1 Fire hazard assessment requires the use of testing and calculation methods to determine whether the objectives will be met by a specified design for a specified fire scenario, under the specified assumptions. The calculations to be performed are described in Section 5.3, and the selection and qualifying of calculation methods for the assessment are described in Section 5.3.

5.7.7 For the fire hazard assessment procedure to be valid, it is necessary that the calculation methods and the fire-test-response characteristics used produce valid estimates of success or failure in achievement of the fire safety objectives, given the specified fire scenario(s).

5.7.7.1 It is advisable for the validity of the fire hazard assessment procedure to be confirmed by peer review.

5.7.8 One way in which acceptable levels of safety would be achieved is through a design that complies with the applicable fire-test-response characteristic requirements for rail transpor-

tation systems, including the traditional recommendations from the Federal Railroad Administration in 1989 (24), or those in NFPA 130. If a rail transportation vehicle is designed fully with materials, components, and products meeting those requirements or recommendations, that vehicle would not traditionally need to be subjected to the fire hazard assessment procedure described here.

5.7.8.1 A complete listing of the fire-test-response characteristics of a design, together with the corresponding Federal Railroad Administration recommendations for those characteristics (see Table X1 and Appendix X1), would constitute an acceptable design.

5.7.9 The recommendations cited in 5.7.8 should be used to set specific values in the fire safety objectives and in other qualified elements of the fire hazard assessment in any instance where those values are not specified by this guide. This should be done so as not to compromise the fire safety levels reflected in the statistics of fire incidents shown in Appendix X7. Any values or other assumptions specified by the user must be set explicitly and conservatively, that is, providing greater safety, with an explicitly stated rationale for the specific values or assumptions.

## 6. Selection and Qualification of Fire Hazard Calculation Methods

6.1 Because no applicable calculation methods have been adopted as ASTM standards, the choice of calculation methods is nonmandatory and must include written evidence of the validity of the method for this purpose. Use Guide E 1355 in order to evaluate the predictive capability of the fire model used. Guide E 1591 provides guidelines on how to obtain the appropriate input data, in particular material properties, that are needed for fire modeling. Guide E 1472 illustrates the type of documentation required for fire models to be satisfactory.

6.2 The user must provide guidance on safety factors needed to offset the uncertainties and biases associated with the method or with the data used by the method. Any valid calculation method is valid only for certain applications and within the limits of its own uncertainties and biases and the uncertainties of its source data; therefore, the evidence of validity required in 5.4.1 will provide the basis for specifying safety factors.

6.3 See Appendix X5 and Appendix X6 for candidate calculation methods.

6.4 Under the provisions in 5.7.8, a design fully complying with the existing requirements or recommendations based on fire-test-response characteristics is deemed to satisfy the fire hazard assessment. This is equivalent to stating that a fire-characteristic profile for the design is deemed to satisfy the fire hazard assessment if it satisfies the fire-test-response characteristic limits in Table X1 and Appendix X1. This does not constitute acceptance of the fire-characteristic profile in general as a simplification of the fire hazard assessment procedure. Any use of the fire-characteristic profile other than this specific application must be shown to be valid.

<sup>16</sup> One way to ensure consistent quality control is by listing materials, components, products, or assemblies.



APPENDIXES

(Nonmandatory Information)

X1. EXAMPLE OF FIRE-TEST-RESPONSE CHARACTERISTICS RECOMMENDATIONS

X1.1 Notes to Table X1.1 as set out by the Federal Railroad Administration (25):

X1.1.1 Test Methods D 3675 and E 162—Materials tested for surface flammability should not exhibit any flaming running or flaming dripping; window and light diffuser panels need not meet the running or dripping requirement.

X1.1.2 Cushions, Mattresses, Seat Upholstery, Mattress Ticking, and Covers, Curtains—The surface flammability and smoke emission characteristics of a material should be demonstrated to be permanent by washing, if appropriate, according to FED STD 191-A Textile Test Method 5830.<sup>17</sup>

X1.1.3 Seat Upholstery, Mattress Ticking, Covers, and Curtains—The surface flammability and smoke emission characteristics of a material should be demonstrated to be permanent by dry-cleaning, if appropriate, according to Test Methods D 2774. Materials that cannot be washed or dry-cleaned should

be so labeled and should meet the applicable performance criteria after being cleaned as recommended by the manufacturer.

X1.1.4 Window Panels— For double window glazing, only the interior glazing should meet the material recommendations specified herein; the exterior need not meet those recommendations.

X1.1.5 Test Method E 662—Test Method E 662 maximum test limits for smoke emission (specific optical density) should be measured in either the flaming mode or the nonflaming mode, depending on which mode generates the most smoke.

X1.1.6 Test Methods E 119—Structural flooring assemblies should meet the performance criteria during a nominal test period determined by the transit property. The nominal test period should be twice the maximum expected period of time, under normal circumstances, for a vehicle to come to a complete, safe stop from maximum speed, plus the time necessary to evacuate all passengers from a vehicle to a safe area. The nominal time period should not be less than 15 min. Only one specimen need be tested. A proportional reduction may be made in dimensions of the specimen provided that it represents a true test of its ability to perform as a barrier against undercar fires. Penetrations (ducts, etc.) should be designed against acting as passageways for fire and smoke.

<sup>17</sup> The American Association of Textile Chemists and Colorists (AATCC, P.O. Box 12215, Research Triangle Park, NC, 27709) has issued the Standard Laboratory Practice for Home Laundering Fabrics prior to Flammability Testing, to Differentiate Between Durable and Nondurable Finishes (May 1, 1991). Although no AATCC formal equivalent standard exists, the practice mentioned is likely to be useful as a replacement to the Federal Test Method, since the Federal standards are in the process of being withdrawn.

TABLE X1.1 U.S. Flammability and Smoke Emission Recommendations for Passenger Rail Vehicles (22)

Category	Function of Material	Flammability		Smoke Emission	
		Test Procedure	Performance Criteria	Test Procedure	Performance Criteria
Passenger seats, sleeping, and dining car components	Cushions, mattresses	ASTM D 3675	$I_s \leq 25$	ASTM E 662	$D_s(1.5) \leq 100$ : $D_s(4.0) \leq 175^A$
	Seat Frames, mattress frames	ASTM E 162	$I_s \leq 35$	ASTM E 662	$D_s(1.5) \leq 100$ ; $D_s(4.0) \leq 200$
	Seat and toilet shroud, food trays Seat upholstery, mattress ticking and covers, curtains	ASTM E 162 FAR 25.853 (a) (Vertical burner)	$I_s \leq 35$ Flame time $\leq 10$ s Burn length $\leq 6$ in	ASTM E 662 ASTM E 662 ASTM E 662	$D_s(1.5) \leq 100$ ; $D_s(4.0) \leq 200$ $D_s(4.0) \leq 250$ coated $D_s(4.0) \leq 200$ uncoated
Panels	Wall, ceiling, partition, tables and shelves, windscreen, HVAC ducting	ASTM E 162 ASTM E 119 ASTM E 162	$I_s \leq 35$ as appropriate <sup>B</sup> $I_s \leq 100$	ASTM E 662 ASTM E 662 ASTM E 662	$D_s(1.5) \leq 100$ ; $D_s(4.0) \leq 200$
	Structural	ASTM E 119	nominal evacuation time, at least 15 min	ASTM E 662	
	Flooring	Covering	ASTM E 648 ASTM E 162 <sup>C</sup>	C.R.F. $\geq 5$ kW/ $m^{2D,E}$ $I_s \leq 25$	ASTM E 662 ASTM E 662
Insulation	Thermal, acoustic	ASTM E 162	$I_s \leq 25$	ASTM E 662	$D_s(4.0) \leq 100$
Elastomers	Window gaskets, door nosing, diaphragms, roof mat	ASTM C 542	Pass	ASTM E 662	$D_s(1.5) \leq 100$ ; $D_s(4.0) \leq 200$
Exterior plastic components	End cap roof housings	ASTM E 162	$I_s \leq 35$	ASTM E 662	$D_s(1.5) \leq 100$ ; $D_s(4.0) \leq 200$
Component box covers	Interior, exterior boxes	ASTM E 162	$I_s \leq 35$	ASTM E 662	$D_s(1.5) \leq 100$ ; $D_s(4.0) \leq 200$

<sup>A</sup>NFPA 130 and FTA requirement is  $D_s(1.5) \leq 100$ ;  $D_s(4.0) \leq 200$

<sup>B</sup>Test criteria for floors or criteria appropriate to the physical locations and magnitude of the major ignition, energy, or fuel loading sources, may be used.

<sup>C</sup>NFPA 130 only.

<sup>D</sup>Amtrak requirement is C.R.F.  $\geq 6$  kW/m<sup>2</sup>

<sup>E</sup>Amtrak requirement is  $I_s \leq 35$ .

X1.1.7 *Floor Coverings*—Floor coverings should be tested in accordance with Test Method E 648 with its padding, if the padding is used in actual installation.

X1.1.8 *Seat or Mattress Frames*—Arm rests, if foamed plastic, are tested as cushions, and, if hard material, are tested as a seat back shroud.

X1.1.9 *Cushions and Mattresses*—Testing is performed without upholstery.

X1.1.10 *Wall and Ceiling Panels, Floor Coverings*—Carpeting on walls and ceilings are to be considered wall and ceiling panel materials, respectively.

X1.1.11 *Elastomers*—The fire test method in Specification C 542 is Test Method C 1166.

X1.2 Table X1.1 shows all of the materials and products addressed by the Federal Railroad Administration, and indicates the traditional approach to fire-test-response characteristic requirements for rail transportation systems.

X1.3 NFPA 130 requires that wiring materials and installations in fixed guideway transit systems, other than for

traction power, conform to the requirements of NFPA 70, the National Electrical Code. It also requires that wire and cable constructions intended for use in operating vital train circuits and power circuits to emergency fans and lights pass the flame propagating criteria of IEEE 383. AMTRAK also has issued separate specifications for wire and cable (32).

X1.3.1 IEEE 383 is substantially similar to the flame spread portion of Protocol A of Test Method D 5537. It is a vertical cable tray flame propagation test, with a 2.4-m (8-ft) long test sample.

X1.3.2 The National Electrical Code states that cables that meet a more severe fire test can be appropriately used in applications where a less severe test is required (see X4.12.7 for the applicable test methods).

X1.3.3 In comparison, the Federal Aviation Administration requires electric wire insulation to meet requirements based on a 60° angle test method [FAR 25.1359]. Average extinguishing time not to exceed 30 s; average drip extinguishing time not to exceed 3 s; average burn length not to exceed 76-mm (3-in.), and the wire shall not break during the test.

**X2. Federal Railroad Administration Rule**

X2.1 Table X2.1 shows the fire-test-response characteristic requirements for materials and products set out by the Federal Railroad Administration (29), provided as reference material. Explanatory notes to the table, taken directly from the Federal Railroad Administration rulemaking, are shown in the following sections.

X2.1.1 Materials tested for surface flammability should not exhibit any flaming running or flaming dripping.

X2.1.2 The Test Method E 662 maximum test limits for smoke emission (specific optical density) should be measured in either the flaming mode or the nonflaming mode, utilizing the mode which generates the most smoke.

X2.1.3 Testing of a complete seat assembly (including cushions, fabric layers, upholstery) according to Test Method E 1537 with application of pass/fail criteria of Cal TB 133 and of a complete mattress assembly (including cushions, fabric layers, upholstery) according to Test Method E 1590 with application of pass/fail criteria of Cal TB 129, shall be permitted in lieu of the test methods prescribed herein, provided the assembly component units remain unchanged or new (replacement) assembly components possess equivalent fire performance properties to the original components tested. A fire hazard analysis must also be conducted that considers the operating environment within which the seat or mattress

**TABLE X2.1 FRA Requirements for Commuter and Intercity Rail Vehicle Materials (29)**

Category	Function of Material	Flammability		Smoke Emission	
		Test Procedure	Performance Criteria	Test Procedure	Performance Criteria
Cushions, mattresses	All (1, 2, 3, 4, 5, 6, 7, 8) <sup>A</sup>	ASTM D 3675	$I_s \leq 25$	ASTM E 662	$D_s (1.5) \leq 100$ ; $D_s (4.0) \leq 175$
		Fabrics	All (1, 2, 3, 6, 7, 8)	FAR 25.853 (a) (vertical)	Flame time $\leq 10$ s Burn length $\leq 6$ in.
Vehicle components (9, 10, 11, 12)	All except flexible cellular foams, floor coverings, light transmitting plastics, and items addressed under other specific categories (1, 2)	ASTM E 162	$I_s \leq 35$	ASTM E 662	$D_s (1.5) \leq 100$
		Flexible cellular foams (1, 2)	ASTM D 3675	$I_s \leq 25$	ASTM E 662
	Floor covering (13, 14)	ASTM E 648	CRF $\leq 5$ kW/m <sup>2</sup>	ASTM E 662	$D_s (1.5) \leq 100$ $D_s (4.0) \leq 200$
	Light transmitting plastics (2, 15)	ASTM E 162	$I_s \leq 100$	ASTM E 662	$D_s (1.5) \leq 100$ $D_s (4.0) \leq 200$
	Elastomers (16)	ASTM C 1166	Pass	ASTM E 662	$D_s (1.5) \leq 100$ $D_s (4.0) \leq 200$
Wire and cable	Low voltage wire and cable	ICEA S-19/NEMA WC3 or UL 44 and UL 83 (17)	Pass	ASTM E 662	$D_s (4.0) \leq 200$ (flaming) $D_s (4.0) \leq 75$ (nonflaming)
	Power cable	IEEE Std 383 (18)	Pass	ASTM E 662	$D_s (4.0) \leq 200$ (flaming) $D_s (4.0) \leq 75$ (nonflaming)
Structural components (19)	Flooring (20), other (21)	ASTM E 119	Pass		

<sup>A</sup>The numbers in brackets refer to the corresponding subsections within X2.1.