

Edition 1.1 2018-11 CONSOLIDATED VERSION

INTERNATIONAL STANDARD colour inside Digital audio – Interface for non-linear PCM encoded audio bitstreams applying IEC 60958 -Part 11: MPEG-4 AAC and its extensions in LATM/LOAS



THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2018 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office 3, rue de Varembé CH-1211 Geneva 20 Switzerland Tel.: +41 22 919 02 11 info@iec.ch www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications, Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing \$1 000 terms and definitions in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (JEV) online.

IEC Glossary - std.iec.ch/glossary

87 p00 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

https://standards.iteh.ai/



Edition 1.1 2018-11 CONSOLIDATED VERSION

INTERNATIONAL STANDARD colour inside Digital audio – Interface for non-linear RCM encoded audio bitstreams applying IEC 60958 -Part 11: MPEG-4 AAC and its extensions in LATM/LOAS

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 33.160.30; 33.170

ISBN 978-2-8322-6217-7

Warning! Make sure that you obtained this publication from an authorized distributor.





IEC 61937-11:2010-05+AMD1:2018-11 CSV(en)

Edition 1.1 2018-11 CONSOLIDATED VERSION



CONTENTS

	FO	FOREWORD			
	INT	ROD	UCTION	5	
	INT	ROD	UCTION to Amendment 1	5	
	1	Scop	pe	6	
	2	Norr	mative references	6	
	3	Tern	ns, definitions and abbreviations	6	
		3.1	Terms and definitions	6	
		3.2	Abbreviations	8	
	4	Мар	ping of the audio bit stream on to IEC 61937-1	8	
		4.1	General	8	
		4.2	Burst-info for MPEG-4 AAC and its extensions in LATM/LOAS	8	
	5	Forn	nat of data-burst for MPEG-4 AAC and its extensions in LATMAOAS	9	
		5.1	General	9	
		5.2	Pause data-bursts for MPEG-4 AAC and its extensions in LATM/LOAS	9	
		5.3	Audio data-bursts	10	
			5.3.1 MPEG-4 AAC and its extensions in LATM/LOAS	10	
			5.3.2 LATM/LOAS framing	12	
	۸n		5.3.3 Latency	1Z 14	
	Am		(informative) Calculation of delay and data-buist repetition rates – guidelines	14	
Annex B (normative)			(normative) High-speed transmission	10	
Bibliography				17	
	Fig	ure 1	- Data-borst structure	10	
	Fig	ure 2	- Latency diagram for burst reception and decoding	3.7131-2010	
	Tab	ble 1 ·	- Values for data-type bits 0-4 and sub-data-type data-type bits 5-6	9	
	Table 2 - Repetition period of pause data-bursts			9	
Table 3 - Data type-dependent informat			- Data-type-dependent information	11	
	Table A.1 - Examples - Calculation of delay and data-burst repetition rates			14	
	Tab	ble B.	1 – Indication fields	16	
	Tab	ble B.	2 – Signalling example	16	

IEC 61937-11:2010+AMD1:2018 CSV © IEC 2018

INTERNATIONAL ELECTROTECHNICAL COMMISSION

DIGITAL AUDIO – INTERFACE FOR NON-LINEAR PCM ENCODED AUDIO BITSTREAMS APPLYING IEC 60958 –

Part 11: MPEG-4 AAC and its extensions in LATM/LOAS

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
 - 6) All users should ensure that they have the latest edition of this publication.
 - 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
 - 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
 - 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This consolidated version of the official IEC Standard and its amendment has been prepared for user convenience.

IEC 61937-11 edition 1.1 contains the first edition (2010-05) [documents 100/1491/CDV and 100/1580/RVC] and its amendment 1 (2018-11) [documents 100/2948/CDV and 100/3033/RVC].

In this Redline version, a vertical line in the margin shows where the technical content is modified by amendment 1. Additions are in green text, deletions are in strikethrough red text. A separate Final version with all changes accepted is available in this publication.

2010

- 3 -

International Standard IEC 61937-11 has been prepared by technical area 4: Digital system interfaces and protocols, of IEC technical committee 100: Audio, video and multimedia systems and equipment.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of IEC 61937, under the general title *Digital audio – Interface for non-linear PCM encoded audio bitstreams applying IEC 60958* can be found on the IEC website.

The committee has decided that the contents of the base publication and its amendment will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

2010

IEC 61937-11:2010+AMD1:2018 CSV - 5 - © IEC 2018

INTRODUCTION

Modern digital video broadcasting standards such as DVB include support for the MPEG-4 HE AAC and/or HE AAC v2 audio codecs as specified in ISO/IEC 14496-3. An increasing number of countries are adopting these new codecs for their standard definition and high definition digital video broadcasting services and have started with implementations.

For MPEG-2 AAC audio (ISO/IEC 13818-7) the specified framing format for the audio bit stream is ADTS and its transport over an IEC 60958 interface is specified in IEC 61937-6.

However, the MPEG-4 (ISO/IEC 14496-3) audio codecs introduce new features and capabilities that require a framing format that supports more flexible signaling and delivery mechanisms. Therefore, MPEG-2 Systems (ISO/IEC 13818-1) specifies the MPEG-4 LATM/LOAS framing format for MPEG-4 audio codecs to overcome the limitations of ADTS.

In order to be able to pass the MPEG-4 audio bit stream from a Set Top Box to an A/V receiver connected via the IEC 60958 interface without needing to reframe the audio bit stream within ADTS, the MPEG-4 LATM/LOAS framing format needs to be supported by IEC 61937.

INTRODUCTION to Amendment

The revision of IEC 61937-11:2010 has become necessary to specify the protocol where the interface does not carry an embedded sampling frequency clock. The purpose is primarily to support stereophonic multichannel audio applications increasing their channel counts. It is justified in that ARIB introduces 22.2(7.1 audio channel applications, as given in ITU-R BS.2051-0, into the market in 2018. This Amendment 1 contains the following significant technical changes with respect to IEC 61937-11:2010:

new Annex B specifies new high-speed transmission;

https://eta the term "Sub-data type" is discontinued. 956-1314-41ad-a0b2-d2802467b51d/iec-61937-11-2010

DIGITAL AUDIO – INTERFACE FOR NON-LINEAR PCM ENCODED AUDIO BITSTREAMS APPLYING IEC 60958 –

Part 11: MPEG-4 AAC and its extensions in LATM/LOAS

1 Scope

This part of IEC 61937 describes the method to convey non-linear PCM bitstreams encoded according to the MPEG-4 AAC format and its extensions spectral band replication, parametric stereo and MPEG surround, framed in MPEG-4 LATM/LOAS.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60958 (all parts), Digital audio interface

IEC 61937-1, Digital audio – Interface for non-linear PCM encoded audio bitstreams applying IEC 60958 – Part 1: General

IEC 61937-2, Digital audio Interface for non-linear PCM encoded audio bitstreams applying IEC 60958 – Part 2: Burst-info

ISO/IEC 14496-3.2009, Information technology – Coding of audio-visual objects – Part 3: Audio

3 Terms, definitions and abbreviations

For the purposes of this document the terms, definitions and abbreviations of IEC 61937-1, IEC 61937-2 and the following apply.

3.1 Terms and definitions

3.1.1

access unit

smallest entity to which timing information can be attributed; an access unit is the smallest individually decodable unit; a decoder consumes access units

3.1.2 AudioMuxElement(1)

LATM element that carries payload data for at least one audio elementary stream, related payload length information and multiplex configuration information

NOTE This element carries payload data in form of PayloadMux elements. The number in brackets indicates multiplexing configuration (StreamMuxConfig) is multiplexed into AudioMuxElements, that is in-band transmission.

3.1.3 AudioSpecificConfig

configuration structure used to convey parameters to initialize the MPEG-4 audio decoder

IEC 61937-11:2010+AMD1:2018 CSV © IEC 2018

3.1.4

low overhead MPEG-4 audio transport multiplex

LATM

multiplexing layer defined by ISO/IEC 14496-3; used for multiplexing of audio elementary streams

3.1.5 low overhead audio stream LOAS

synchronisation layer defined by ISO/IEC 14496-3; three different formats of LOAS are defined, each of which is designed to address the specific characteristics of the underlying transmission layer

3.1.6

MPEG-4 AAC profile

contains only the MPEG-4 AAC low complexity audio object type; MPEG-4 AAC low complexity object type is the counterpart to the MPEG-2 AAC low complexity profile; in addition to the MPEG-2 AAC LC profile the MPEG-4 AAC low complexity object type enables the usage of the PNS tool

NOTE The MPEG-4 AAC Low Complexity object type is used when there are restrictions on the usage of RAM and processing complexity.

3.1.7

MPEG-4 high efficiency AAC profile

contains the spectral band replication object type in conjunction with the MPEG-4 AAC low complexity object type

NOTE For further information please refer to ISONEC 14496-3. The MPEG-4 high efficiency AAC profile is a superset of the MPEG-4 AAC profile.

3.1.8

MPEG-4 high efficiency AAC profile version 2 11:2010

contains the parametric stereo object type and the spectral band replication object type in 2010 conjunction with the AAC low complexity object type

NOTE The MPEG-4 high efficiency AAC profile version 2 is a superset of the MPEG-4 high efficiency AAC profile.

3.1.9

MPEG surround

technology used for coding of multichannel signals based on a downmixed signal of the original multichannel signal, and associated spatial parameters

NOTE MPEG surround is defined in ISO/IEC 23003-1.

3.1.10

PayloadMux

payload data chunk in an AudioMuxElement that contains potentially multiplexed payload data for multiple audio elementary streams; in general PayloadMux elements can be concatenated inside AudioMuxElements

3.1.11

SpatialSpecificConfig

configuration structure used to initialize the MPEG surround decoder

3.1.12 StreamMuxConfig

configuration structure that describes the structure of the LATM payload multiplex

- 7 -

3.1.13

Sub-data-type

reference to the type of payload of the data-bursts defined for the use with the specified datatype

3.1.14 modified discrete cosine transformation MDCT

 $\ensuremath{\mathsf{transformation}}$ schema used by AAC

3.1.15

transformation length (of the AAC codec or core codec)

AAC can operate in two modes using either a 960 lines or 1 024 lines MDCT transformation for long blocks; an MDCT line is a spectral component described by frequency, amplitude and phase

3.2 Abbreviations

AAC	Advanced Audio Coding
AAC LC	MPEG-4 AAC Low Complexity
HE AAC	MPEG-4 High Efficiency AAC and MPEG-4 High Efficiency AAC Version 2
ADTS	Audio Data Transport Stream
DVB	Digital Video Broadcasting
MDCT	Modified Discrete Cosine Transformation
MPEG	Moving Picture Experts Group
MPS	MPEG Surround
PNS	Perceptual Noise Substitution
PS	Parametric Stereo
SBR	Spectral Band Replication 7-11:2010

https://TLndards.iteh.AAC/TransformationLength 956-1314-41ad-a0b2-d2802467b51d/iec-61937-11-2010

4 Mapping of the audio bit stream on to IEC 61937-1

4.1 General

The coding of the bit stream and data-burst is in accordance with IEC 61937-1 and IEC 61937-2.

4.2 Burst-info for MPEG-4 AAC and its extensions in LATM/LOAS

The 16-bit burst-info contains information about the data which will be found in the data-burst (see Table 1).