



Edition 1.0 2011-01

# INTERNATIONAL STANDARD





#### THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2011 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office 3, rue de Varembé CH-1211 Geneva 20 Switzerland

Email: inmail@iec.ch Web: www.iec.ch

#### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

#### **About IEC publications**

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

■ Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

■ IEC Just Published: www.iec.ch/online\_news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

Customer Service Centre: www.iec.ch/webstore/custserv

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch


Tel.: +41 22 919 02 11

Fax: +41 22 919 03 00



Edition 1.0 2011-01

# INTERNATIONAL STANDARD



Multimedia systems and equipment - Nolour measurement and management - Part 12-1: Metadata for identification of colour gamut (Gamut ID)



INTERNATIONAL ELECTROTECHNICAL COMMISSION

PRICE CODE

W

ICS 17.180.20; 33.160

ISBN 978-2-88912-309-4

### CONTENTS

FO	REWORD	4
INT	FRODUCTION	6
1	Scope	7
2	Normative references	7
3	Terms and definitions	8
4	Abbreviations	8
5	Overview	8
6	Header of Gamut ID metadata	9
7	Description of gamut geometry (full profile)	10
		10
	7.2 Gamut geometry	11
		12
	7.4 Gamut instances	14
	7.5 Gamut hulls	
	7.6 Gamut component	
	7.6.1 General 7.6.2 Packing of face indices	
	7.6.2 Packing of face indices	
	7.7.1 General	
	7.7.2 Packing of vertex indices	
	7.8 Vertices	
	7.8.1 General	
	7.8.2 Packing of colour space coordinates for vertices	
8	Description of gamut geometry (medium and simple profiles)	
	n8.1ds General (1and) ds/1.22 anaxc-e911-4ad0-b98b-51c9412fa4a6/iec-6196	
	8.2 Medium profile	
0	8.3 Simple profile	
9	Description of colour reproduction	
	nex A (Informative) Size of Gamut ID metadata	
	nex B (Informative) Motivation and requirements	
	nex C (informative) Use of profiles	
	nex D (informative) Example of Gamut ID metadata in simple profile	
Bib	liography	38
•	ure 1 – Logical structure of the description of gamut geometry (full profile)	
-	ure B.1 – Scope of Gamut ID – Generation and use of metadata are not specified	27
	ure B.2 – Example of a description of gamut geometry in CIEXYZ colour space asisting of a set of triangular faces	28
Fig	ure B.3 – Example of a gamut with identified ridge due to colorant channels	30
Fig	ure B.4 – Example of a non-convex gamut with two convex gamut hulls	31
Tab	ble 1 – Format of Gamut ID metadata	8
Tab	ble 2 – Header of Gamut ID metadata	9
Tab	ble 3 – Bit depth for encoding of a colour space coordinate	10

Table 4 – Description of gamut geometry	12
Table 5 – Header of description of gamut geometry	13
Table 6 – Gamut instances	14
Table 7 – <i>i</i> th Gamut instance	15
Table 8 – Gamut hulls	16
Table 9 – hth gamut hull	16
Table 10 – Definition of gamut components	17
Table 11 – $c$ th gamut component	17
Table 12 – Example for packing of gamut components	18
Table 13 – Definition of faces	18
Table 14 – Example for packing of faces	19
Table 15 – Vertices	20
Table 16 – Packing of 10-bit colour space coordinates	20
Table 17 – Packing of 12-bit colour space coordinates	21
Table 18 – Description of gamut geometry (simple profile)	22
Table 19 – Header of description of gamut geometry (simple profile)	22
Table 20 – Definition of vertices (simple profile)	22
Table B.1 – Requirements and Gamut 1D features(	29
Table C.1 – Profiles for the description of gamut geometry	32
Table D.1 – Colour gamut for digital cinema	34
Table D.2 – Example for the header	34
Table D.3 – Example for the header of description of gamut geometry	35
Table D.4 – Example of definition of vertices	35

https://standards.iteh.ai/ v//octandards/1c/2Nata8c-e911-4ad0-b98b-51c9412fa4a6/iec-61966-12-1-2011

#### INTERNATIONAL ELECTROTECHNICAL COMMISSION

## MULTIMEDIA SYSTEMS AND EQUIPMENT – COLOUR MEASUREMENT AND MANAGEMENT –

#### Part 12-1: Metadata for identification of colour gamut (Gamut ID)

#### **FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards. Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61966-12-1 has been prepared by technical area 2: Colour measurement and management, of IEC technical committee 100: Audio, video and multimedia systems and equipment.

The text of this standard is based on the following documents:

FDIS	Report on voting				
100/1757/FDIS	100/1776/RVD				

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 61966 series, published under the general title *Multimedia* systems and equipment – Colour measurement and management, can be found on the IEC website.

The committee has decided that the contents of this amendment and the base publication will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- · reconfirmed.
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this document may be issued at a later date.

IMPORTANT – The "colour inside" logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this publication using a colour printer.



#### INTRODUCTION

New technologies in capturing and displaying wide-gamut colour images enable a new market of wide-gamut video colour content creation. Recent video standards for wide gamut colour space encoding such as IEC 61966-2-4 (xvYCC) were established in order to be able to distribute content with a colour gamut that is extended with respect to classical colour gamuts such as defined by colorimetry standards ITU-R BT.601 (standard definition television) and ITU-R BT.709 (high definition television). With the increasing popularity of wide gamut and high dynamic range content and displays, the variety of colour gamuts of displays is expected to increase. This issue can be an obstacle for adopting wide-gamut video colour content in professional content creation since the compatibility of the content to the employed displays as well as the compatibility among different displays is not ensured. The term display includes here any video colour reproduction equipment, such as direct view displays and projectors. Thanks to improvements of technology, the variety of colour gamut and colour reproduction capacities of displays increases while the colour gamut and the colour encoding rules of existing colour space encoding standards are fixed.

To address this issue, the IEC standard Gamut ID (IEC 61966-12-1) specifies a colour gamut metadata scheme for video systems including information for colour reproduction. This metadata can amend a video content or a display. More specifically, improvements can be achieved if the wide-gamut colour content is created with the knowledge of the display colour gamut as well as if the colour reproduction in the display is done with the knowledge of the colour gamut of the pictorial content.

This standard enables video systems defining their own colour gamut. This standard defines necessary metadata that allows managing inhomogeneous video systems with different colour gamuts. This standard generalizes existing colour space encoding standards having a fixed colour gamut.

Med Preview

1965-12-1:2011

https://standards.iteh.ai/1/12/standa/ds//c/2/s148c-e911-4ad0-b98b-51c9412fa4a6/iec-61966-12-1-201

### MULTIMEDIA SYSTEMS AND EQUIPMENT – COLOUR MEASUREMENT AND MANAGEMENT –

#### Part 12-1: Metadata for identification of colour gamut (Gamut ID)

#### 1 Scope

This part of IEC 61966 defines the colour gamut metadata scheme for video systems and similar applications.

The metadata can be associated with wide gamut video colour content or to a piece of equipment to display the content.

When associated with content, the colour gamut metadata defines the gamut for which the content was created. It can be used by the display for controlled colour reproduction even if the display's colour gamut is different from that of the content.

When associated with a display, the colour gamut metadata defines the display colour gamut. It can be used during content creation to enable improved colour reproduction.

The colour gamut metadata may cover associated colour encoding information, which includes all information required for a controlled colour reproduction, when such information is not provided by the colour encoding specification.

The colour gamut metadata scheme provides scalable solutions. For example, more flexible solutions will be used for the professional use, while much simpler solutions will be used for consumer use with easier product implementation.

This part of IEC 6/1966 only defines the colour gamut metadata scheme. Vendor-specific solutions for creation and end-use of this metadata are allowed.

#### 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050(845):1987, International electrochnical vocabulary - Chapter 845: Lighting

IEC 61966-2-4:2006, Multimedia systems and equipment – Colour measurement and management – Part 2-4: Colour management – Extended-gamut YCC colour space for video applications – xvYCC

ISO 15076-1:2005 Image technology colour management – Architecture, profile format and data structure – Part 1: Based on ICC.1:2004-10

ISO 22028-1:2004, Photography and graphic technology – Extended colour encodings for digital image storage, manipulation and interchange – Part 1: Architecture and requirements

ITU-R BT.709-5:2002, Parameter values for the HDTV standards for production and international programme exchange

CIE 15:2004, Colorimetry

SMPTE 274M:2005, SMPTE Standard for Television - 1920 x 1080 Image Sample Structure, Digital Representation and Digital Timing Reference Sequences for Multiple Picture Rates

#### 3 Terms and definitions

For the purposes of this document, the following terms and definitions as well as the terms and definitions of colour space, illuminance, luminance, tristimulus, and other related lighting terms of IEC 60050(845) apply.

### 3.1 content

video content in production, post-production or consumption

#### 3.2 gamut

a solid in a colour space

#### 3.3

gamut boundary description

description of the boundary of a colour gamut

#### 3.4

radiometrically-linear colour space coordinates

colour space coordinates that are linear with respect to image radiance

#### 4 Abbreviations

GBD	Gamut Boundary Description
LSB	Least Significant Bit
MSBlards.iteh	Most Significant Bit \ \ \ \ 2 \ \ana8c-e911-4ad0-b98b-51c9412fa4a6/iec-61966-12-1-2011
GI	Gamut Instance
GH	Gamut Hull
GC	.Gamut Component

#### 5 Overview

This standard specifies metadata called "Gamut ID metadata" providing information on an actual colour gamut.

The Gamut ID metadata contains four parts and its format is summarized in Table 1.

Table 1 - Format of Gamut ID metadata

Byte # hex	Metadata content				
0h0000	Header of Gamut ID metadata				
ID_G	Description of gamut geometry				
ID_E	Description of colour reproduction				

Clause 6 specifies the header of Gamut ID metadata.

Clauses 7 and 8 specify the description of gamut geometry that corresponds to one of three profiles as listed below:

- full profile;
- medium profile;
- simple profile.

Clause 7 specifies the full profile of the description of gamut geometry. The medium and simple profiles are specified in Clause 8.

Clause 9 specifies the description of colour reproduction.

#### 6 Header of Gamut ID metadata

The Gamut ID metadata starts with the header shown in Table 2.

Table 2 - Header of Gamut ID metadata

Byte #	Size	Sym-	m							
hex	bytes	bols	Description				on	^	Values	
11.211			7 6	6 5	4	3	2	1	Q	
oo standards.	1 iteh.ai/	N, P	R	ID_PROFILE		ID_PRECISION	20	ID GBD_SPACE	eh	R = reserved = 0b0 (1bit) 1D PFOFILE (2 bits): 0b00: Full profile 0b01: Medium profile 0b10: Simple profile 0b11: Reserved ID_PRECISION (2 bits): 0b00: 8 bits 0b01: 10 bits 0b10: 12 bits 0b11: Reserved ID_GBD_SPACE (3bits): 0b000: ITU-R BT.709 RGB
01	2	ID_G	Byte	e # c	of sta	art of th	ie d	escript	ion	[0h0009;0hFFFF]
		_	of gamut geometry					•		
03	2	ID_E	Byte # of start of the description of colour reproduction					criptic	[0;0hFFFF]	
05	2		Reserved. Shall be zero.						0h0000	
07	2		Reserved. Shall be zero.				zero		0h0000	

ID\_PROFILE indicates the profile of the Gamut ID metadata and shall be one of

- 0b00: Full profile,
- 0b01:Medium profile,
- 0b11: Simple profile.

ID\_GBD\_SPACE indicates the colour space and the colour space encoding for colour vertices in the description of gamut geometry and shall be one of

- 0b000: ITU-R BT.709, RGB space, encoding according to SMPTE 274M,
- 0b001: xvYCC-601, YCbCr space, encoding according to IEC 61966-2-4 SD,
- 0b010: xvYCC-709, YCbCr space, encoding according to IEC 61966-2/4 HD,
- 0b011: XYZ; encoding shall use the XYZNumber format of ICC profiles specified in ISO 15076-1:2005 taking 12 bytes for one XYZ triple.

aID\_PRECISION and ID\_GBD\_SPACE specify according to Table 3 the number N of bits that are used per colour channel in order to define the coordinates of a colour in a colour space.

Table 3 - Bit depth for encoding of a colour space coordinate

ID_GBD_SPACE	ID_PRECISION (	Bit depth N
0b000 or	0b00	/8 poits
0b001 or	0601	10 b)ts
0b010	0b10	12 bits
27	0b11	Reserved
0b011	Any	32 bits
0b100 or	Ahy	Reserved
0b101 of	May Die	view
0b110 or		V IC W
0b111		

1965-12-1:2011

ID\_G indicates the offset in bytes from the beginning of Gamut ID metadata to the beginning of the description of gamut geometry.

If ID\_E is different from 0h0000, the Gamut ID metadata contains a description of colour reproduction and ID\_E indicates the offset in bytes from the beginning of the description of colour reproduction. If ID\_E has the value 0h0000, the Gamut ID metadata does not contain a description of colour reproduction.

#### 7 Description of gamut geometry (full profile)

#### 7.1 General

In the header of Gamut ID metadata, if ID\_PROFILE equals 0b00, the description of gamut geometry shall correspond to the full profile.