

INTERNATIONAL STANDARD

ISO
9194

First edition
1987-12-15



INTERNATIONAL ORGANIZATION FOR STANDARDIZATION
ORGANISATION INTERNATIONALE DE NORMALISATION
МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ

Bases for design of structures — Actions due to the self-weight of structures, non-structural elements and stored materials — Density

Bases de calculs des constructions — Actions dues au poids propre des structures, des éléments non structuraux et des matériaux entreposés — Masses volumiques

iTeh Standards
(<https://standards.itih.ai>)
Document Preview

ISO 9194:1987

<https://standards.itih.ai/catalog/standards/iso/3d40413f9ee7-4bae-831c-0f5d5e74d8c3/iso-9194-1987>

Reference number
ISO 9194:1987 (E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council. They are approved in accordance with ISO procedures requiring at least 75 % approval by the member bodies voting.

International Standard ISO 9194 was prepared by Technical Committee ISO/TC 98, *Bases for design of structures*.

Users should note that all International Standards undergo revision from time to time and that any reference made herein to any other International Standard implies its latest edition, unless otherwise stated.

ISO 9194:1987

<https://standards.iteh.ai/catalog/standards/iso/3d40413f9ee7-4bae-831c-0f5d5e74d8c3/iso-9194-1987>

Bases for design of structures — Actions due to the self-weight of structures, non-structural elements and stored materials — Density

0 Introduction

General principles on reliability of structures are given in ISO 2394.

Since at the moment, only insufficient statistical data of densities are available, the values given in this International Standard are deterministic ones. In general they may be interpreted as mean values of densities.

Even these mean values are in some cases different for the same material from one country to another. This is the reason for giving a range of two values for one material in this International Standard.

Each country in its relevant standards should use its traditional values which are in the indicated range.

1 Scope and field of application

This International Standard defines the actions due to the self-weight of structures, non-structural elements and stored materials. It gives the numerical values of their densities.

These actions are to be determined by multiplying the densities by the gravitational acceleration and by the actual volume. The actions caused by the weight of the earth placed on the structures are similarly calculated.

2 Reference

ISO 2394, *General principles on reliability of structures*.

3 General

3.1 The most important value in determining actions due to the self-weight of structures, non-structural elements and/or that of stored materials is the density.

3.2 For materials having all three dimensions of the same order of magnitude, the densities are expressed in kilograms per cubic metre (kg/m^3). For roofings (sheeting materials) having one dimension of smaller order of magnitude than the other two dimensions, the similar quantity will be surface

density, expressed in kilograms per square metre (kg/m^2) (mass related to surface area).

3.3 In some countries roofings are considered to be external load, causing pressure on the structure (by analogy with, for example, snow load) — consequently these are expressed in newtons per square metre (N/m^2) or in pascals¹⁾.

For this reason, roofings (see annex A) are given as surface pressures, together with the values of surface density.

3.4 Densities of stored materials substantially depend on how they are placed. Usually two methods of stocking are distinguished:

- a) disorderly storage of materials;
- b) orderly storage of materials.

Disorderly or bulky stored materials are stored without bales, forming a natural heap. Orderly stored materials are stored in stocks or piles with or without bales.

4 Density values

4.1 The representative value of the density of materials and/or components of structures, non-structural elements and stored materials is in general determined by the mean value.

The representative value is generally represented by a unique value. In actual design situations, densities may alter due to the difference in quality of workmanship, moisture content, etc. The representative value of the density of earth is represented in the same manner, bearing compactness in mind.

4.2 The representative values of densities of structures and non-structural elements are given in a table in annex A; the representative values of densities of stored materials and densities of earth placed on structures are similarly given in annex B.

4.3 Where the tables give only one density value for one material (or soil), this means that the corresponding nominal values do not normally differ significantly (up to $\pm 5\%$) in dif-

1) $1 \text{ Pa} = 1 \text{ N/m}^2$

ferent countries and the indicated mean value is the average of the nominal values. The range of two values of densities given in the annexes for one material indicates that the mean values of densities for different countries vary between the indicated ones.

This also refers to the angles of repose. However, it should be emphasized that in accordance with the national practice

of different countries, angles of repose differ up to $\pm 30\%$ from those indicated in annex B. Thus values of angles of repose given in annex B are approximate.

4.4 For the time being, only limited statistical data are available and the values given in annexes A and B are based on relevant national practice.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO 9194:1987](#)

<https://standards.iteh.ai/catalog/standards/iso/3d40413f9ee7-4bae-831c-0f5d5e74d8c3/iso-9194-1987>

Annex A

Representative values of densities of structural and of non-structural elements

(This annex forms an integral part of the Standard).

This annex gives representative values of the densities of structural and non-structural elements in the form of a table.

Material	Density kg/m ³	Material	Density kg/m ³
Wood and substitutes¹⁾ (air-dried, about 15 % humidity)		Building bricks and blocks	
Hardwood		Solid burnt clay brick	
Beech tree (<i>Fagus sylvatica</i>)	680	up to 14 MPa (inclusive) compressive strength	1 600
Oak tree (<i>Quercus</i>)	690	over 14 Mpa compressive strength	1 800
Peduncular oak (<i>Quercus robur</i>)	640	Perforated brick (holes through the brick exceed 25 % of its volume)	
Brazilian rosewood (<i>Dalbergia nigra</i>)	800	hollow brick	820 to 1 350
Turkey oak (<i>Quercus cerris</i>)	640 to 770	perforated brick	1 150 to 1 450
Yew tree (<i>Taxus baccata</i>)	640	Lime-sand brick	1 700
Australian hardwood		Cob brick, adobe	1 600
Box, grey (<i>Eucalyptus microcarpa</i>)	1 120	Refractory brick for general purposes	
Penda, brown (<i>Xanthostemon chrysanthus</i>)	1 120	fireclay	1 850
Softwood		high-strength fireclay	2 100
Black pine (<i>Pinus laricio</i>)	570	silica (dinas)	1 800
Larch tree (<i>Larix decidua</i>)	550	magnesite	2 800
Norway spruce (<i>Picea</i>)	430	chrome magnesite	3 000
Spruce fir (<i>Pinus eccelsa</i>)	380 to 440	corundum	2 600
Scotch pine (<i>Pinus silvestris</i>)	490	Covering bricks	
White willow (<i>Salix alba</i>)	330	inside wall-covering	1 600
Giant poplar (<i>Populus alba</i>)	410	outside façade covering	1 800
Trembling poplar (<i>Populus tremula</i>)	450	clinker brick	2 000
Ocume (<i>Ocume</i>)	410	Gas silicate block	
Conifers	400 to 600	with 2 MPa compressive strength	500
Extruded chipboard	500 to 750	with 5 MPa compressive strength	700
Fibreboard		with 7,5 MPa compressive strength	900
hard	900 to 1 100	Acid-resistant brick	2 000
medium-hard	600 to 850	Tuff block with 5 MPa compressive strength	1 100
porous insulating	250 to 400	Glass brick, double-walled	870 to 1 100
Plywood	750 to 850	Mortars	
Coreboard	450 to 650	Lime mortar	1 200 to 1 800
Natural building stones		Lime cement mortar	1 750 to 2 000
Magmatic plutonic rocks	2 650 to 3 000	Cement mortar (with 2,5 MPa or greater compressive strength)	2 100
Magmatic vulcanites	2 500 to 2 850	Rock floor mortar	1 600
Volcanic tuffs	1 400 to 2 000	Gypsum mortar	1 200 to 1 800
Sedimentary rocks		Fireclay mortar	1 900
sandstone	2 700	Pearlite mortar	
marl	2 300	lime	340
porous limestone	1 700 to 2 200	gypsum	370
fresh-water limestone	2 400	cement	440
compact limestone	2 650 to 2 800	Bitumen mortar with river sand	1 700
dolomite	2 800	Concrete²⁾	
Transformed rocks		Gravel concrete	2 250 to 2 500
clay slate	2 600	Basalt concrete	2 300 to 2 500
marble	2 700		

Material	Density kg/m ³	Material	Density kg/m ³
Crushed rock concrete C3-C35	2 300 to 2 500	Tuff concrete, medium size building block	1 200
Blast furnace foam slag concrete C3-C10	1 600 to 1 900	Gas silicate, medium size building block 1,5 to 2,5 MPa compressive strength	600 to 800
Aerated and gas concrete C1,5-C5	600 to 1 500	2,5 to 5 MPa compressive strength	800 to 1 100
Expanded clay gravel concrete C1,5-C16	700 to 1 700	5 to 10 MPa compressive strength	900 to 1 300
Perlite concrete C1,5-C2	350 to 700	10 to 20 MPa compressive strength	1 000 to 1 600
Tuff concrete C3-C6	1 400 to 1 600	Inside wall-covering brick	1 700
Lightweight aggregate concrete using sintered pulverized fuel ash aggregates	1 600 to 1 850	Outside façade brick	1 900
Heat insulating gas concrete	300 to 900	Clinker brick	2 000
Heat insulating perlite brick and pipseshell	260	Fireclay brick (in fireclay mortar)	2 000
Aggregates and fillers		Acid-resistant brick (in bitumen mortar)	1 900
Sand	1 550	Glass brick, double-walled (in cement mortar)	1 100
Sand gravel of 0 to 40 mm grain size	1 700	Glass brick, coupled on one side (in cement mortar)	870
Gravel	1 500 to 1 600	Metals for structures	
Blast furnace foam slag	1 700	Structural steel	7 850
Blast furnace slag, granulated	1 200	Cast iron structure	7 100
Crushed slag stone of 5 to 40 mm grain size	1 500	Aluminium	2 700
Aerated silicate	1 000	Covering and other building material	
Pulverized fuel ash (pozzolan) for use as a cementitious component in concrete (bulk density)	800 to 1 050	Asphalt, pure	2 200
Lightweight concrete aggregate (Lytag) (bulk density)	750 to 1 000	Bitumen	1 000 to 1 400
Lightweight aggregate using sintered pulverized fuel ash/natural sand	1 700 to 2 000	Tar (pitch)	1 100 to 1 400
Masonry from natural stones		Asbestos cement roofing and covering board	1 800 to 2 100
Rocks of initial setting		Asbestos cement corrugated board	1 600
basalt malphir, diorit, gabbro	3 000	Asbestos cement pipe	1 800
basalt lava	2 400	Cellulose acetate panel	1 300
diabase	2 900	Cement tile	2 400
granite, syngenit, porphyt	2 800	Mosaic tile	2 200
trachyt	2 600	Concrete flagstone	2 200
Sedimentary rock		Tile	1 750 to 2 000
graywacke, sandstone, puddingstone	2 700	Face brick (hard façade brick)	2 500
dense limestone, dolomite, shell limestone and marble	2 800	Stoneware tile	2 400
limestone conglomerate (e.g. travertin, etc.)	2 600	Soft covering brick	
volcanic tuff	2 000	holed	1 350
Transformed rocks		solid	1 600
gneiss, granulite	3 000	Epoxy resin	
slate	2 800	without filler	1 150
serpantine	2 700	with mineral matter	2 000
Brick masonry³⁾		with fibreglass	1 800
Ordinary brick	1 500	Fenoplast	1 500
Solid burnt clay brick		Rubber floor	1 800
up to 14 MPa (inclusive) compressive strength	1 500 to 1 700	Plastic tile	1 100
over 14 MPa compressive strength	1 900	Polyamide (e.g. diamid)	1 100
Walls made from brick with holes or ceramic blocks (depending on the type of brick and blocks used)	1 150 to 1 450	Polyester resin, without filler	1 350
		Polyethylene	930
		Polyisobutylene-base board	1 350
		Polymethylacrylate	1 150
		Polypropylene	930
		PVC hardboard	1 400
		PVC flooring board	1 600
		PVC flooring tile	1 700
		Flat glass	2 600
		Armoured glass	3 000