

SLOVENSKI STANDARD SIST ISO 9224:1999

01-oktober-1999

Korozija kovin in zlitin - Korozivnost atmosfer - Vodilne vrednosti za kategorizacijo korozivnosti

Corrosion of metals and alloys -- Corrosivity of atmospheres -- Guiding values for the corrosivity categories

iTeh STANDARD PREVIEW

Corrosion des métaux et alliages + Corrosivité des atmosphères -- Valeurs de référence relatives aux classes de corrosivité

SIST ISO 9224:1999

Ta slovenski standard je istoveten z: 09224:1992

ICS:

77.060 Korozija kovin Corrosion of metals

SIST ISO 9224:1999 en

SIST ISO 9224:1999

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ISO 9224:1999 https://standards.iteh.ai/catalog/standards/sist/5600368c-ac3d-4b2b-b654-5f15cc8a6309/sist-iso-9224-1999 SIST ISO 9224:1999

INTERNATIONAL STANDARD

ISO 9224

First edition 1992-02-15

Corrosion of metals and alloys — Corrosivity of atmospheres — Guiding values for the corrosivity categories

iTeh Standard des métaux et alliages — Corrosivité des atmosphères — Valeurs directrices relatives aux catégories de corrosivité

SIST ISO 9224:1999 https://standards.iteh.ai/catalog/standards/sist/5600368c-ac3d-4b2b-b654-5fl 5cc8a6309/sist-iso-9224-1999



ISO 9224:1992(E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75% of the member bodies casting a vote.

International Standard ISO 9224 was prepared by Technical Committee ISO/TC 156, Corrosion of metals and alloys.

<u>SIST ISO 9224:1999</u> https://standards.iteh.ai/catalog/standards/sist/5600368c-ac3d-4b2b-b654-5fl 5cc8a6309/sist-iso-9224-1999

© ISO 1992

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization
Case Postale 56 ● CH-1211 Genève 20 ● Switzerland
Printed in Switzerland

ISO 9224:1992(E)

Introduction

The "corrosivity category" established in ISO 9223 is a general term suitable for engineering purposes, which describes the corrosion properties of atmospheres based on current knowledge of atmospheric corrosion.

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST ISO 9224:1999</u> https://standards.iteh.ai/catalog/standards/sist/5600368c-ac3d-4b2b-b654-5f15cc8a6309/sist-iso-9224-1999 SIST ISO 9224:1999

iTeh This page Intentionally left blank EVIEW (standards.iteh.ai)

<u>SIST ISO 9224:1999</u> https://standards.iteh.ai/catalog/standards/sist/5600368c-ac3d-4b2b-b654-5f15cc8a6309/sist-iso-9224-1999

Corrosion of metals and alloys — Corrosivity of atmospheres — Guiding values for the corrosivity categories

1 Scope

This International Standard specifies guiding corrosion values and the characteristics of corrosion for the corrosivity categories defined in ISO 9223.

Guiding corrosion values give corrosion rates for standard structural materials and can be used for engineering calculations. The guiding corrosion values specify the technical content of each of the individual corrosivity categories for these standard metals.

This International Standard can be used to predict the service life for metals, alloys and, in some 9224:1 cases, for metallic coatings used in atmospheres corresponding to different corrosivity categories (see table 1). The guiding corrosion values also provide a technical basis for determining the need for protective measures and other engineering purposes.

The guiding corrosion values are based on experience obtained from a large number of site exposures and service performances. Corrosion rates expected for a given corrosivity category may be exceeded in the vicinity of special design features which cause localized or galvanic corrosion.

2 Normative reference

The following standard contains provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the edition indicated was valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent edition of the standard indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 9223:1992, Corrosion of metals and alloys — Corrosivity of atmospheres — Classification.

3 Definitions

For the purposes of this International Standard, the following definitions apply.

3.1 guiding corrosion value: Corrosion rates (average and steady state), mass loss, penetration or other corrosion characteristics expressing the expected corrosive action of the atmospheric environment of a given corrosivity category towards standard materials.

3.2 average corrosion rate, r_{av} : The corrosion rate during the first 10 years of atmospheric exposure of a metal, given by the equation

$$r_{\rm av} = \frac{\Delta h_1}{t_1 - t_0} \tag{1}$$

where

 Δh_1 is the corrosion depth, in micrometres, after the first 10 years of exposure;

 t_0 is the time at which the exposure starts;

 t_1 is the time at which the exposure ends.

3.3 steady state corrosion rate, $r_{\rm lin}$: The corrosion rate derived from a long term atmospheric exposure of a metal, not including the initial period. For the purpose of this International Standard, the corrosion rate after 10 years of exposure is considered as constant.

The steady state corrosion rate, $r_{\rm lin}$, is given by the equation

$$r_{\rm lin} = \frac{\Delta h_2}{t_2 - t_1} \tag{2}$$

where

- Δh_2 is the corrosion depth, in micrometres, for the considered time interval:
- t_1 and t_2 are the times (longer than 10 years) in the linear region of the curve of uniform corrosion as a function of time.

4 Long term corrosive action of atmospheres belonging to different corrosivity categories

- **4.1** The long term corrosive action of atmospheres belonging to different corrosivity categories is characterized for different metals and their groups by
- a) the average corrosion rate for the first 10 years of exposure;

- b) the steady state corrosion rate;
- c) the form of corrosion attack.
- **4.2** For most metals, the initial corrosion rate exceeds the steady state corrosion rate. The total extent of corrosion must therefore be calculated by multiplying the average corrosion rate for the first 10 years by 10 and adding the product of the remaining service life and the steady state corrosion rate in subsequent years.
- **4.3** Average corrosion rates for the first 10 years of exposure, and steady state corrosion rates of carbon steel, zinc, copper, aluminium and weathering steels are given in table 1.

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ISO 9224:1999

https://standards.iteh.ai/catalog/standards/sist/5600368c-ac3d-4b2b-b654-5f15cc8a6309/sist-iso-9224-1999