



Standard Specification for Performance of Engine Oils¹

This standard is issued under the fixed designation D 4485; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

This standard has been approved for use by agencies of the Department of Defense.

INTRODUCTION

This document covers all the currently active American Petroleum Institute (API) engine oil performance categories that have been defined in accordance with the ASTM consensus process. There are other organizations with specifications not subject to this process, such as the International Lubricant Standardization and Approval Committee (ILSAC), and the Association des Constructeurs Européens d'Automobiles (ACEA). Their specifications are not covered in this document.

In the ASTM system, a specific API designation is assigned to each category. The system is open-ended, that is, new designations are assigned for use with new categories as each new set of oil performance characteristics are defined. Oil categories may be referenced by engine builders in making lubricant recommendations, and used by lubricant suppliers and customers in identifying products for specific applications. Where applicable, candidate oil programs are conducted in accordance with the Chemical Manufacturers Association (CMA) Petroleum Additives Product Approval Code of Practice.

Other service categories not shown in this document have historically been used to describe engine oil performance (SA, SB, SC, SD, SE, SF, SG and CA, CB, CC, CD, CD-II, CE [see 3.1.2]). SA is not included because it does not have specified engine performance requirements. SG is not included because it was a category that could not be licensed for use in the API Service Symbol after December 31, 1995. The others are not included because they are based on test methods for which engine parts, test fuel, or reference oils, or a combination thereof, are no longer available. Also, the ASTM 5-Car and Sequence VI Procedures are obsolete and have been deleted from the category Energy Conserving and Energy Conserving II (defined by Sequence VI). Information on excluded older categories and obsolete test requirements can be found in [SAE J183](#).

1. Scope

1.1 This specification covers engine oils for light-duty and heavy-duty internal combustion engines used under a variety of operating conditions in automobiles, trucks, vans, buses, and off-highway farm, industrial, and construction equipment.

1.2 This specification is not intended to cover engine oil applications such as outboard motors, snowmobiles, lawn mowers, motorcycles, railroad locomotives, or ocean-going vessels.

1.3 This specification is based on engine test results that generally have been correlated with results obtained on reference oils in actual service engines operating with gasoline or diesel fuel. It should be recognized that not all aspects of

engine oil performance are evaluated by the engine tests in this specification. In addition, when assessing oil performance, it is desirable that the oil be evaluated under actual operating conditions.

1.4 This specification includes bench tests that help evaluate some aspects of engine oil performance not covered by the engine tests in this specification.

1.5 The values stated in SI units are to be regarded as the standard. The values in inch-pound units are provided for information only.

1.6 The test procedures referred to in this specification that are not yet standards are listed in [Table 1](#).

2. Referenced Documents

2.1 *ASTM Standards:*

[D 92 Test Method for Flash and Fire Points by Cleveland Open Cup](#)²

² *Annual Book of ASTM Standards*, Vol 05.01.

¹ This specification is under the jurisdiction of ASTM Committee D-2 on Petroleum Products and Lubricants and is the direct responsibility of Subcommittee D02.B on Automotive Lubricants.

Current edition approved Nov. 10, 2000. Published November 2000. Originally published as D 4485 – 85. Last previous edition D 4485 – 99b.

TABLE 1 Test Procedures

Test Procedure	ASTM Publications ^A
T-6	RR: D02-1219 ^B
T-7	RR: D02-1220 ^C
1K	RR: D02-1273 ^D
1M-PC	RR: D02-1320 ^E
1N	RR: D02-1321 ^F
Oil Aeration	RR: D02-1379 ^G
EOFT (Modified)	under development ^H
1P	RR: D02-1441 ^I
M11	RR: D02-1439 ^J

^AResearch Reports are available from ASTM Headquarters. Request by Research Report No.

^BMulticylinder Engine Test Procedure for the Evaluation of Lubricants—Mack T-6.

^CMulticylinder Engine Test Procedure for the Evaluation of Lubricants—Mack T-7.

^DCaterpillar 1K Test ASTM Research Report.

^ESingle Cylinder Piston Deposit Test CAT 1M-PC.

^FSingle Cylinder Piston Deposit Test, CAT 1N.

^GNavistar Engine Oil Test.

^HEngine Oil Filterability Test under development by ASTM D02.06.

^ICaterpillar 1P Test

^JCummins M11 High Soot Test

- D 93 Test Methods for Flash Point by Pensky-Martens Closed Cup Tester²
- D 130 Test Method for Detection of Copper Corrosion from Petroleum Products by the Copper Strip Tarnish Test²
- D 892 Test Method for Foaming Characteristics of Lubricating Oils²
- D 2887 Test Method for Boiling Range Distribution of Petroleum Fractions by Gas Chromatography³
- D 3244 Practice for Utilization of Test Data to Determine Conformance with Specifications³
- D 4684 Test Method for Determination of Yield Stress and Apparent Viscosity of Engine Oils at Low Temperature⁴
- D 4951 Test Method for Determination of Additive Elements in Lubricating Oils by Inductively Coupled Plasma Atomic Emission Spectrometry⁴
- D 5119 Test Method for Evaluation of Automotive Engine Oils in the CRC L-38 Spark-Ignition Engine⁴
- D 5133 Test Method for Low Temperature, Low Shear Rate, Viscosity/Temperature Dependence of Lubricating Oils Using a Temperature-Scanning Technique⁴
- D 5185 Test Method for the Determination of Additive Elements, Wear Metals, and Contaminants in Used Lubricating Oils and Determination of Selected Elements in Base Oils by Inductively Coupled Plasma Atomic Emission Spectrometry (ICP-AES)⁴
- D 5290 Test Method for Measurement of Oil Consumption, Piston Deposits, and Wear in a Heavy-Duty High-Speed Diesel Engine—NTC-400 Procedure⁵
- D 5302 Test Method for Evaluation of Automotive Engine Oils for Inhibition of Deposit Formation and Wear in a Spark-Ignition Internal Combustion Engine Fueled with Gasoline and Operated Under Low-Temperature, Light-Duty Conditions⁴

- D 5480 Test Method for Motor Oil Volatility by Gas Chromatography⁴
- D 5533 Test Method for Evaluation of Automotive Engine Oils in the Sequence III Spark-Ignition Engine⁴
- D 5800 Test Method for Evaporation Loss of Lubricating Oils by the Noack Method⁴
- D 5844 Test Method for Evaluation of Automotive Engine Oils for Inhibition of Rusting (Sequence IID)⁴
- D 5862 Test Method for Evaluation of Engine Oils in the Two-Stroke Cycle Turbo-Supercharged 6V92TA Diesel Engine⁴
- D 5966 Test Method for Evaluation of Engine Oils for Roller Follower Wear in Light-Duty Diesel Engine⁶
- D 5967 Test Method for Evaluation of Diesel Engine Oils in the T8 Diesel Engine⁶
- D 5968 Test Method for Evaluation of Corrosiveness of Diesel Engine Oil⁶
- D 6082 Test Method for High Temperature Foaming Characteristics of Lubricating Oils⁶
- D 6202 Test Method for Measurement of the Effects of Automotive Engine Oils on the Fuel Economy of Passenger Cars and Light-Duty Trucks in the Sequence VIA Spark Ignition Engine⁶
- D 6278 Test Method for the Shear Stability of Polymer-Containing Fluids Using a European Diesel Injector Apparatus⁶
- D 6335 Test Method for Determination of High Temperature Deposits by Thermo-Oxidation Engine Oil Simulation Test⁶
- D 6417 Test Method for Estimation of Engine Oil Volatility by Capillary Gas Chromatography⁶
- D 6483 Test Method For Evaluation of Diesel Engine Oils in the T-9 Diesel Engine⁶
- E 29 Practice for Using Significant Digits in Test Data to Determine Conformance with Specifications⁷
- E 178 Practice for Dealing with Outlying Observations⁷
- 2.2 *Society of Automotive Engineers Standards*:⁸
 - SAE J183 Engine Oil Performance and Engine Service Classification
 - SAE J300 Engine Oil Classification
 - SAE J1423 Passenger Car and Light-Duty Truck Energy-Conserving Engine Oil Classification
- 2.3 *American Petroleum Institute Publication*:⁹
 - API 1509 Engine Oil Licensing and Certification System (EOLCS)
- 2.4 *Government Standard*:¹⁰
 - Federal Test Method Standard No. 791C, Method 3470
- 2.5 *General Motors Corporation Engineering Standard*:¹¹
 - GM9099-P Engine Oil Filterability Test (EOFT)

⁶ *Annual Book of ASTM Standards*, Vol 05.04.

⁷ *Annual Book of ASTM Standards*, Vol 14.02.

⁸ Available from Society of Automotive Engineers (SAE), 400 Commonwealth Dr., Warrendale, PA 15096.

⁹ Available from American Petroleum Institute (API), 1220 L Street NW, Washington, DC 20005.

¹⁰ Available from Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20036.

¹¹ Available from General Motors Corporation, CPE-Engineering Standards, W-3, Warren, MI 48090.

³ *Annual Book of ASTM Standards*, Vol 05.02.

⁴ *Annual Book of ASTM Standards*, Vol 05.03.

⁵ Discontinued; see 1997 *Annual Book of ASTM Standards*, Vol 05.03.

2.6 *Chemical Manufacturers Association Code*:¹²
CMA Petroleum Additives Product Approval Code of Practice

3. Terminology

3.1 Definitions:

3.1.1 *classification, n*— in engine oils, the systematic arrangement into categories in accordance with different levels of performance in specified engine tests.

3.1.2 *category, n*—in engine oils, a designation such as SH, SJ, CF-4, CF, CF-2, CG-4, Energy Conserving, and so forth for a given level of performance in specified engine tests.

3.1.3 *automotive, adj*—descriptive of equipment associated with self-propelled machinery, usually vehicles driven by internal combustion engines.

3.1.4 *engine oil, n*—a liquid that reduces friction and wear between the moving parts within an engine, and also serves as a coolant.

3.1.4.1 *Discussion*—It can contain additives to enhance certain properties. Inhibition of engine rusting, deposit formation, valve train wear, oil oxidation, and foaming are examples.

3.1.5 *light-duty, adj*— in internal combustion engine operation, characterized by average speeds, power output, and internal temperatures that are generally much lower than the potential maximums.

3.1.6 *lugging, adj*—in internal combustion engine operation, characterized by a combined mode of relatively low-speed and high-power output.

3.1.7 *heavy duty, adj*— in internal combustion engine operation, characterized by average speeds, power output, and internal temperatures that are generally close to the potential maximums.

3.1.8 *light-duty engine, n*— in internal combustion engine types, one that is designed to be normally operated at substantially less than its peak output.

3.1.8.1 *Discussion*—This type of engine is typically installed in automobiles and small trucks, vans, and buses.

3.1.9 *heavy-duty engine, n*— in internal combustion engine types, one that is designed to allow operation continuous at or close to its peak output.

3.1.9.1 *Discussion*—This type of engine is typically installed in large trucks and buses as well as farm, industrial, and construction equipment.

3.2 Definitions of Terms Specific to This Standard:

3.2.1 *S category, n*—the group of engine oils that are intended primarily for use in automotive gasoline engine applications, such as passenger cars, light-duty trucks, and vans.

3.2.2 *C category, n*—the group of engine oils that are intended primarily for use in diesel and certain gasoline-powered vehicles.

3.2.3 *Energy Conserving category, n*—the group of engine oils that have demonstrated fuel economy benefits and are intended primarily for use in automotive gasoline engine applications, such as passenger cars, light-duty trucks, and vans.

4. Performance Classification

4.1 Automotive engine oils are classified in three general arrangements, as defined in Section 3; that is, S, C, and Energy Conserving. These arrangements are further divided into categories with performance measured as follows:

4.1.1 *SH*—Oil meeting the performance requirements measured in the following gasoline engine tests and bench tests:

4.1.1.1 Test Method D 5844D 5844, the Sequence IID gasoline engine test, has been correlated with vehicles used in short-trip service prior to 1978,¹³ particularly with regard to rusting.

4.1.1.2 Test Method D 5533D 5533, the Sequence IIIE gasoline engine test, has been correlated with vehicles used in high-temperature service prior to 1988,¹⁴ particularly with regard to oil thickening and valve train wear.

4.1.1.3 Test Method D 5302D 5480, the Sequence VE gasoline engine test, has been correlated with vehicles used in stop-and-go service prior to 1988,¹⁵ particularly with regard to sludge and valve train wear.

4.1.1.4 Test Method D 5119D 5119, the L-38 gasoline engine test, is used to measure copper-lead bearing weight loss under high-temperature operating conditions.

4.1.1.5 In addition to passing performance in the engine tests, specific viscosity grades shall also meet bench test requirements (see Table 2), which are discussed in the following subsections:

(a) The volatility of engine oils relates to engine oil consumption.

(b) The EOFT screens for the formation of precipitates that can cause oil filter plugging.

(c) Phosphorus compounds can cause glazing of automotive catalysts and exhaust gas oxygen sensors and, thereby, deactivate them. Control of the phosphorus level in the engine oil may reduce this tendency.

(d) The flash point can indicate if residual solvents and low-boiling fractions remain in the finished oil.

(e) Foaming in engine oil can cause valve lifter collapse and a loss of lubrication due to the presence of air in the oil. The foam test indicates an oil's foaming tendency.

(f) The H and M Test indicates the compatibility of an oil with standard test oils.

(g) The L-38 Shear Stability Test indicates the ability of an oil to resist permanent viscosity loss due to shearing in an engine.

TABLE 2 S Engine Oil Category

Category	Test Method	Rated or Measured Parameter	Primary Performance Criteria
SH	D 5844 (Sequence IID)	Average engine rust rating, ^A min Number stuck lifters	8.5 none

¹³ Available from ASTM in *STP 3151 (Part 1)*. Also available from the Society of Automotive Engineers as Technical Paper No. 780931.⁷

¹⁴ Available from ASTM Headquarters. Request RR:D02-1225.

¹⁵ Available from ASTM Headquarters. Request RR:D02-1226.

¹² Available from Chemical Manufacturers Association (CMA), 1300 Wilson Blvd., Arlington, VA 22209.

TABLE 2 Continued

Bench Test and Measured Parameter (effective January 1, 1992)	Viscosity Grade Performance Criteria ^F			Cam wear, μm Average, max Maximum, max	D 5119 (L-38) Bearing weight loss, mg, max	Viscosity Grade Performance Criteria
	SAE 5W-30	SAE 10W-30	SAE 15W-40			
Test Method D 5800 volatility loss, % max ^F	25	20	18			20 ^N
Test Method D 2887D 2887 volatility loss at 371°C (700°F), % max ^F	20	17	15			15 ^N
General Motors 9099P EOFT, % flow reduction, max	50	50	N.R. ^G			50
Test Method D 4951 or D 5185D 4951D 5185, phosphorus % mass, max	0.12	0.12	N.R.			NR ^G
Test Method D 92D 92 flash point, °C, min ^H	200	205	215			200
Test Method D 93D 93 flash point, °C, min ^H	185	190	200			185
Test Method D 892D 892 foaming tendency (Option A)						
Sequence I, max, foaming/settling ^J	10/0	10/0	10/0			10/0
Sequence II, max, foaming/settling ^J	50/0	50/0	50/0			50/0
Sequence III, max, foaming/settling ^J	10/0	10/0	10/0			10/0
High temperature foaming ^J	report ^K	report ^K	report ^K			report
Federal Test Method 791C, Method 3470.1, homogeneity and miscibility	L	L	L			L
L-38 shear stability	M	M	M			M
Test Method D 5800 volatility loss, % max ^O	22					22
Test Method D 2887D 2887 (Extended) volatility loss at 371°C (700°F), % max ^O	17					17
Test Method D 5480D 5480 volatility loss at 371°C (700°F), % max ^O	17					17
General Motors 9099P EOFT, % flow reduction, max	Report					Report
Standard procedure	50					50
Modified procedure with 0.6 % H2O	Report					Report
Modified procedure with 1.0 % H2O	Report					Report
Modified procedure with 2.0 % H2O	Report					Report
Modified procedure with 3.0 % H2O	Report					Report
Test Method D 4951 or D 5185D 4951D 5185, phosphorus % mass, max	0.10 ^P					NR ^G
Test Method D 92D 92 flash point, °C, min ^H	200					NR ^G
Test Method D 93D 93 flash point, °C, min ^H	185					NR ^G
Test Method D 892D 892 foaming tendency (Option A)						
Sequence I, max, foaming/settling ^Q	10/0					10/0
Sequence II, max, foaming/settling ^Q	50/0					50/0
Sequence III, max, foaming/settling ^Q	10/0					10/0
Test Method D 6082D 6082 (optional blending required) static foam max, Tendency/Stability	200/50 ^R					200/50 ^R
Federal Test Method 791C, Method 3470.1, homogeneity and miscibility	L					L
L-38 shear stability	M					M
High temperature deposits (TEOST), deposit wt mg, max	60					60
Gelation Index (Test Method D 5133D 5133), max	12					NR ^G

^ACRC Rust Rating Manual No. 7, available from Coordinating Research Council, 219 Perimeter Center Pkwy., Atlanta, GA 30346.

^BCRC Sludge Rating Manual No. 12, available from Coordinating Research Council, 219 Perimeter Center Pkwy., Atlanta, GA 30346.

^CCRC Varnish Rating Manual No. 14, available from Coordinating Research Council, 219 Perimeter Center Pkwy., Atlanta, GA 30346.

^DAn oil-related stuck ring occurs on a piston with an individual oil ring land deposit rating <2.6.

^EPassing bench test performance is only required for SAE 5W-30, SAE 10W-30, and SAE 15W-40 viscosity grades as defined in SAE J300.

^FEither Test Method D 5800 or Test Method D 2887D 2887 volatility requirement shall be met.

^GN.R. stands for Not Required.

^HEither Test Method D 92D 92 or Test Method 93 flash point requirement shall be met.

^ISettling volume determined at 5 min.

^JFollow Test Method D 892D 892 Sequence I (Option A) methodology using Mott metal diffuser, 200 ± 5 ml/min dry air flow volume, and 150 ± 1°C bath temperature.

^KKinetic foam volume; ml/static foam volume, and ml/collapse time in seconds.

^LHomogeneous with SAE reference oils.

^MTen-hour stripped kinematic viscosity (oil shall remain in original viscosity grade).

^NPassing volatility loss performance only required for 15W-40 oils.

^OVolatility requirement shall be met in either Test Method D 5800, D 5480, or D 2887 (Extended). A passing result in only one of these procedures is required. The extended Test Method D 2887D 2887 involves (a) system calibration up to C₆₀, with a final boiling point of 615°C (1139°F), (b) sample injection into a cool GC port, (c) GC oven temperature ramp of ≤10°/min, and (d) final GC oven temperature just high enough to get C₆₀ off of the GC column; this excluded the use of high temperature simulated distillation programs.

^PThis is a non-critical specification as described in Practice D 3244D 3244.

^QSettling volume determined at 10 min.

^aSettling volume determined at 1 min.

4.1.1.6 Licensing of the API SH category requires that candidate oils meet the performance requirements in this specification, and that the oils be tested in accordance with the protocols described in the CMA Petroleum Additives Product Approval Code of Practice. The methodology detailed in the CMA Code will help ensure that an engine oil meets its intended performance specification.

4.1.2 *SJ*—Oil meeting the performance requirements measured in the following gasoline engine tests and bench tests:

4.1.2.1 Test Method D 5844 **D 5844**, the Sequence IID, gasoline engine test has been correlated with vehicles used in short-trip service prior to 1978, particularly with regard to rusting.

4.1.2.2 Test Method D 5533 **D 5533**, the Sequence IIIE gasoline engine test, has been correlated with vehicles used in high-temperature service prior to 1988, particularly with regard to oil thickening and valve train wear.

4.1.2.3 Test Method D 5302 **D 5302**, the Sequence VE gasoline engine test, has been correlated with vehicles used in stop-and-go service prior to 1988, particularly with regard to sludge and valve train wear.

4.1.2.4 Test Method D 5119 **D 5119**, the L-38 gasoline engine test, is used to measure copper-lead bearing weight loss under high-temperature operating conditions.

4.1.2.5 In addition to passing performance in the engine tests, specific viscosity grades shall also meet bench test requirements (see [Table 2](#)), which are discussed in the following subsections:

(a) The volatility of engine oils is one of several factors that relates to engine oil consumption.

(b) The EOFT screens for the formation of precipitates and gels that form in the presence of water that can cause oil filter plugging.

(c) Phosphorus compounds in excessive amounts can cause glazing of automotive catalysts and exhaust gas oxygen sensors and, thereby, deactivate them. Control of the phosphorus level in the engine oil may reduce this tendency.

(d) The flash point may indicate if residual solvents and low-boiling fractions remain in the finished oil.

(e) Excessive foaming in engine oil can cause valve lifter collapse and a loss of lubrication due to the presence of air in the oil. The foam test indicates an oil's foaming tendency.

(f) The H and M Test indicates the compatibility of an oil with standard test oils.

(g) The L-38 Shear Stability Test indicates the ability of an oil to resist permanent viscosity loss due to shearing in an engine.

(h) Newer engines designed to provide increased power and improved driveability and to meet future federal emissions and

fuel economy requirements may be sensitive to internal deposits caused by elevated engine operating temperatures. The TEOST test may be useful in determining the deposit control of oils recommended for these engines.

(i) The Gelation Index technique might identify oils susceptible to air binding and might provide low temperature protection not adequately measured by the Test Method D 4684 **D 4684**.

4.1.2.6 Licensing of the API SJ category requires that candidate oils meet the performance requirements in this specification, and that the oils be tested in accordance with the protocols described in the CMA Petroleum Additives Product Approval Code of Practice. The methodology detailed in the CMA Code will help ensure that an engine oil meets its intended performance specification.

4.1.3 *CF-4*—Oil meeting the performance requirements in the following diesel and gasoline engine tests:

4.1.3.1 The 1K diesel engine test has been correlated with vehicles equipped with engines used in high-speed operation prior to 1989,¹⁶ particularly with regard to deposits, oil consumption, and ring wear.

4.1.3.2 The T-6 has been correlated with vehicles equipped with engines used in high-speed operation prior to 1980,¹⁷ particularly with regard to deposits, oil consumption, and ring wear.

4.1.3.3 The T-7 test has been correlated with vehicles equipped with engines operated largely under lugging conditions prior to 1984,¹⁸ particularly with regard to oil thickening.

4.1.3.4 Test Method D 5968, the bench corrosion test, has been shown to predict corrosion of engine oil-lubricated copper, lead, or tin-containing components used in diesel engines.¹⁹ Test Method D 5290 **D 5290**, the NTC-400 diesel engine test, has been correlated with vehicles equipped with engines in highway operation prior to 1983,²⁰ particularly with regard to oil consumption control, deposits, and wear. Test Method D 5290 **D 5290** is not listed in [Table 3](#), as calibrated test stands are no longer available due to unavailability of critical test parts. It has been demonstrated that the 1K test, in combination with Test Method D 5968, can be substituted for the NTC-400 test as an acceptable means to demonstrate performance against this category; however, data from NTC-400 tests, run in calibrated stands, can be used to support this category in accordance with the provisions of Specification D 4485 – 94.

¹⁶ Available from ASTM Headquarters. Request RR: D02-1273.

¹⁷ Available from ASTM Headquarters. Request RR: D02-1219.

¹⁸ Available from ASTM Headquarters. Request RR: D02-1220.

¹⁹ Available from ASTM Headquarters. Request RR: D02-1322.

²⁰ Available from ASTM Headquarters. Request RR: D02-1194.

TABLE 3 C Engine Oil Categories

Category	Test Method	Rated or Measured Parameter	Primary Performance Criteria			
CF-4	D 5119 (L-38) T-6	Bearing weight loss, mg, max	50			
		Merit rating ^A , min	90			
	or					
	D 6483 (T-9) ^B	Top piston ring weight loss ^C , average, mg, max	150			
		Linear wear, μm , max	40			
	T-7	Average rate of kinematic viscosity increase during last 50 h, mm^2/s at 100°C/h, max	0.040			
		Average rate of kinematic viscosity increase from 100 to 150 h, mm^2/s at 100°C/h, max	0.20			
	D 5967 (T-8A) ^B	Copper, mg/kg (ppm) increase, max	20			
		Lead, mg/kg (ppm) increase, max	60			
		Tin, mg/kg (ppm) increase, max	report			
Copper corrosion ^E , max		3				
1K	A 1K test program ^F with a minimum of two tests, acceptable according to the limits shown in the columns to the right, is required to demonstrate performance for this category.					
		Weighted demerits (WDK), ^{G,H} max	332	339	342	
		Groove No. 1 (top) carbon fill (TGF), ^G % volume, max	24	26	27	
		Top land heavy carbon (TLHC), ^G % max	4	4	5	
		Average oil consumption, g/kW-h, (0-252 h), max	0.5	0.5	0.5	
		Final Oil consumption, g/kW-h, (228-252 h) max	0.27	0.27	0.27	
		Scuffing, piston-rings-liner				
		Number of tests allowed	none	none ^I	none ^I	
		Piston ring sticking	none	none	none	
	CF	1M-PC	Top groove fill (TGF) ^G , volume, max	70 ^J		
Weighted total demerits (WTD) ^{G,K} , max			240 ^J			
		Ring side clearance loss ^G mm, max	0.013 ^J			
		Piston ring sticking	none			
		Piston, ring and liner scuffing	none			
			First-Test	Two-Test ^L	Three-Test ^L	
	D 5119 (L-38)	Bearing weight loss, mg, max	43.7	48.1	50.0	
CF-2	1M-PC	Weighted total demerits (WTD) ^{G,K}	100 ^J			
			First-Test	Two-Test ^M	Three-Test ^M	
	D 5862 (6V 92TA)	Cylinder liner scuffing area, % max	45.0			
		Cylinder liner port plugging area, Average, % max	2			
		Single cylinder, % max	5			
		Piston rings face distress demerits				
		No. 1 (fire ring), max	0.23	0.24	0.26	
		Average of No. 2 and 3	0.20	0.21	0.22	
	D 5119 (L-38)	Bearing weight loss, mg, max	43.7	48.1 ^L	50.0 ^L	
			First-Test	Two-Test ^N	Three-Test ^N	
CG-4	1N	Weighted demerits—1N (WDN) ^{G,O}	286.2			
		Top groove fill (TGF) ^G , % volume, max	20			
		Top land heavy carbon (TLHC) ^G , % max	3			
		Oil consumption, g/kW-h, (0-252 h) max	0.5			
		Scuffing, piston-rings-liner				
		Number of tests allowed	none	none	none ^I	
		Stuck rings	none	none	none	
	D 5967 (T-8)	Viscosity increase at 3.8 % soot, cSt, max	11.5			
		Filter plugging, differential pressure, kPa (psi), max	138 (20)			
		Oil consumption, g/kW-h, max	0.304			
lb/bhp-h, max		(0.0005)				
D 5533 (Sequence IIIE)	Hours to 375 % viscosity increase, min	65.5				
	D 5119 (L-38)	Bearing weight loss, mg, max	43.7			
	Used oil viscosity, cSt greater than SAE J300 lower limit for grade, min ^P	0.5				
D 5966 (RFWT)	Wear, μm , max	11.4				
	mils, max	(0.45)				
D 892 (Option A not allowed)	Foaming characteristics					
	Foaming/settling, ml, max ^Q					
	Sequence I	10/0				
	Sequence II	20/0				