

INTERNATIONAL STANDARD

NORME INTERNATIONALE



Fibre optic interconnecting devices and passive components – Performance standard –

Part 087-2: Non-connectorized single-mode bidirectional 1 310 nm upstream and 1 490 nm downstream WDM devices for category C – Controlled environment

<https://standards.iteh.ai/catalog/standards/sist/a7380941-3f60-413f-9204-1ec61753-087-2/iec-61753-087-2:2010>

Dispositifs d'interconnexion et composants passifs à fibres optiques – Norme de performance –

Partie 087-2: Dispositifs WDM unimodaux non connectés bidirectionnels 1 310 nm en voie montante et 1 490 nm en voie descendante et pour la catégorie C – Environnement contrôlé



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2010 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de la CEI ou du Comité national de la CEI du pays du demandeur.

Si vous avez des questions sur le copyright de la CEI ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de la CEI de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland
Email: inmail@iec.ch
Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

■ Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

■ IEC Just Published: www.iec.ch/online_news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

■ Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

■ Customer Service Centre: www.iec.ch/webstore/custserv

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch

Tel.: +41 22 919 02 11

Fax: +41 22 919 03 00

A propos de la CEI

La Commission Electrotechnique Internationale (CEI) est la première organisation mondiale qui élabore et publie des normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications CEI

Le contenu technique des publications de la CEI est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

■ Catalogue des publications de la CEI: www.iec.ch/searchpub/cur_fut-f.htm

Le Catalogue en-ligne de la CEI vous permet d'effectuer des recherches en utilisant différents critères (numéro de référence, texte, comité d'études,...). Il donne aussi des informations sur les projets et les publications retirées ou remplacées.

■ Just Published CEI: www.iec.ch/online_news/justpub

Restez informé sur les nouvelles publications de la CEI. Just Published détaille deux fois par mois les nouvelles publications parues. Disponible en-ligne et aussi par email.

■ Electropedia: www.electropedia.org

Le premier dictionnaire en ligne au monde de termes électroniques et électriques. Il contient plus de 20 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans les langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International en ligne.

■ Service Clients: www.iec.ch/webstore/custserv/custserv_entry-f.htm

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions, visitez le FAQ du Service clients ou contactez-nous:

Email: csc@iec.ch

Tél.: +41 22 919 02 11

Fax: +41 22 919 03 00

INTERNATIONAL STANDARD

NORME INTERNATIONALE



Fibre optic interconnecting devices and passive components – Performance standard –

Part 087-2: Non-connectorized single-mode bidirectional 1 310 nm upstream and 1 490 nm downstream WDM devices for category C – Controlled environment

<https://standards.iteh.ai/catalog/standards/sist/a7380941-3f60-413f-9204-166ba5091225/iec-61753-087-2-2010>

Dispositifs d'interconnexion et composants passifs à fibres optiques – Norme de performance –

Partie 087-2: Dispositifs WDM unimodaux non connectés bidirectionnels 1 310 nm en voie montante et 1 490 nm en voie descendante et pour la catégorie C – Environnement contrôlé

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

PRICE CODE
CODE PRIX

M

ICS 33.180.20

ISBN 978-2-88912-300-1

CONTENTS

FOREWORD.....	3
1 Scope.....	5
2 Normative references.....	5
3 Test.....	6
4 Test report.....	6
5 Performance requirements.....	6
5.1 Reference components.....	6
5.2 Dimensions.....	7
5.3 Sample size.....	7
5.4 Test details and requirements.....	7
Annex A (normative) Sample size.....	11
Annex B (informative) General information for 1310 nm upstream and 1490 nm downstream PON WWDM device.....	12
Bibliography.....	13
Figure B.1 – Example for 1 490 nm downstream and 1 310 nm upstream WWDM at central office and customer side.....	12
iTeh STANDARD PREVIEW (standards.iteh.ai)	
Table 1 – Test details and requirements.....	7
Table A.1 – Sample size.....	11

[IEC 61753-087-2:2010](https://standards.iteh.ai/catalog/standards/sist/a7380941-3f60-413f-9204-61611aa5bc44/iec-61753-087-2-2010)

<https://standards.iteh.ai/catalog/standards/sist/a7380941-3f60-413f-9204-61611aa5bc44/iec-61753-087-2-2010>

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**FIBRE OPTIC INTERCONNECTING
DEVICES AND PASSIVE COMPONENTS –
PERFORMANCE STANDARD –**

**Part 087-2: Non-connectorized single-mode bidirectional 1 310 nm
upstream and 1 490 nm downstream WDM devices for category C –
Controlled environment**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61753-087-2 has been prepared by subcommittee 86B: Fibre optic interconnecting devices and passive components, of IEC technical committee 86: Fibre optics.

The text of this standard is based on the following documents:

FDIS	Report on voting
86B/3095/FDIS	86B/3133/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

Future standards in this series will carry the new general title as cited above. Titles of existing standards in this series will be updated at the time of the next edition.

A list of all parts in the IEC 61753 series, under the general title *Fibre optic interconnecting devices and passive components performance standards*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

ITeH STANDARD PREVIEW
(standards.iteh.ai)

[IEC 61753-087-2:2010](#)

<https://standards.iteh.ai/catalog/standards/sist/a7380941-3f60-413f-9204-61611aa5bc44/iec-61753-087-2-2010>

FIBRE OPTIC INTERCONNECTING DEVICES AND PASSIVE COMPONENTS – PERFORMANCE STANDARD –

Part 087-2: Non-connectorized single-mode bidirectional 1 310 nm upstream and 1 490 nm downstream WWDM devices for category C – Controlled environment

1 Scope

This part of IEC 61753 contains the minimum initial performance, test and measurement requirements and severities which a fibre optic pigtailed 1 310 nm upstream and 1 490 nm downstream wide wavelength division multiplexing (WWDM) passive optical network (PON) device must satisfy in order to be categorized as meeting the requirements of category C (controlled environments), as defined in Annex A of IEC 61753-1:2007.

Annex B of this standard provides information concerning the function of the 1 310 nm upstream and 1 490 nm downstream WWDM.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60793-2-50, *Optical fibre cables – Part 2-50: Indoor cables – Family specification for simplex and duplex cables for use in terminated cable assemblies*

IEC 61300-2-1, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-1: Tests – Vibration (sinusoidal)*

IEC 61300-2-4, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-4: Tests – Fibre/cable retention*

IEC 61300-2-9, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-9: Tests – Shock*

IEC 61300-2-14, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-14: Tests – Optical power handling and damage threshold characterization*

IEC 61300-2-17, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-17: Tests – Cold*

IEC 61300-2-18, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-18: Tests – Dry heat – High temperature endurance*

IEC 61300-2-19, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-19: Tests – Damp heat (steady state)*

IEC 61300-2-22, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-22: Tests – Change of temperature*

IEC 61300-2-42, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-42: Tests - Static side load for connectors*

IEC 61300-2-44, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-44: Tests – Flexing of the strain relief of fibre optic devices*

IEC 61300-3-2, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-2: Examinations and measurements – Polarization dependent loss in a single-mode fibre optic device*

IEC 61300-3-6, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-6: Examinations and measurements – Return loss*

IEC 61300-3-7, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-7: Examinations and measurements – Wavelength dependence of attenuation and return loss of single mode components*

IEC 61300-3-20, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-20: Examinations and measurements – Directivity of fibre optic branching devices*

IEC 61753-1:2007, *Fibre optic interconnecting devices and passive components performance standard – Part 1: General and guidance for performance standards*

3 Test

Unless otherwise specified, all test methods are in accordance with the IEC 61300 series. Each test defines the number of samples to be evaluated. The samples used for each test are intended to be previously unstressed new samples but may also be selected from previously used samples if desired. The samples shall have pigtails of single-mode fibres as per IEC 60793-2-50 type B 1.1 or B 1.3 in either coated fibres (primary and secondary) or reinforced cable format. All measurements shall be carried out at normal room conditions, unless otherwise stated.

All tests shall be carried out over the operating wavelength ranges of 1 260 nm to 1 360 nm, 1 480 nm to 1 500 nm, unless otherwise specified.

NOTE 1 310 nm and 1 490 nm are the nominal or centre wavelengths, stated for the ranges 1 260 nm to 1 360 nm and 1 480 nm to 1 500 nm as defined in ITU-T Recommendations G.983.3 and G.984.2 and IEEE standard 802.3ah-2004.

4 Test report

Fully documented test reports and supporting evidence shall be prepared and be available for inspection as evidence that the tests have been carried out and complied with.

5 Performance requirements

5.1 Reference components

The testing for these components does not require the use of reference components.

5.2 Dimensions

Dimensions shall comply with either an appropriate IEC interface standard or with those given in appropriate manufacturers drawings, where the IEC interface standard does not exist or cannot be used.

5.3 Sample size

Sample sizes for the tests are defined in Annex A of this document.

5.4 Test details and requirements

For test details and requirements please see Table 1.

Table 1 – Test details and requirements

No.	Test	Requirement	Details	
1	Insertion loss (Attenuation) IEC 61300-3-7	≤ 0,8 dB Insertion loss shall be met over the operating wavelength ranges.	Launch patchcord length: Source type: Launch conditions: Other requirements:	≥ 2 m Unpolarised The wavelength of the source shall be longer than cut-off wavelength of the fibre. Test results shall be obtained under measurement uncertainty of 0,1 dB.
2	Wavelength isolation IEC 61300-3-7	≥ 20 dB between wavelength ranges 1 260 nm to 1 360 nm and 1 480 nm to 1500 nm; https://standards.itech.ai/catalog/standards/sist/a7387541-3f50-413f-9214-61611aa5bc44/iec-61753-087-2-2010	Launch patchcord length: Source type: Launch conditions: Other requirements:	≥ 2 m Unpolarised The wavelength of the source shall be longer than cut-off wavelength of the fibre. Test results shall be obtained under measurement uncertainty of 1 dB.
3	Directivity IEC 61300-3-20	≥ 50 dB Grade U Directivity shall be met over the operating wavelength ranges.	Source: Other requirements:	Laser diode (LD) Test results shall be obtained under measurement uncertainty of 1 dB. All ports not under test shall be terminated to avoid unwanted reflections contributing to the measurement. The directivity shall be measured between any pair of input or output ports.
4	Return loss IEC 61300-3-6	≥ 50 dB Grade U Return loss shall be met over the specified wavelength ranges.	Source: Other requirements:	LD Test results shall be obtained under measurement uncertainty of 1 dB. All ports not under test shall be terminated to avoid unwanted reflections contributing to the measurement.

Table 1 (continued)

No.	Test	Requirement	Details	
5	Polarisation Dependent Loss (PDL) IEC 61300-3-2	≤ 0,2 dB Polarisation dependent loss shall be met over the specified wavelength ranges.	Launch patchcord length: Source type: Other requirements:	≥ 2 m LD Test results shall be obtained under measurement uncertainty of 0,05 dB.
6	Optical power handling and damage threshold characterization IEC 61300-2-14 method 2	≥ 300 mW (sum of power at the two wavelength ranges at the same time) During and on completion of the test the insertion loss limits of Test No. 1 shall be met. After the test the isolation limits of Test No. 2 shall be met. During and on completion of the test the return loss limits of Test No. 4 shall be met.	Source type Max. power to be applied at wavelength ranges 1 480 nm to 1 500 nm and 1 260 nm to 1 360 nm: Power increments: Test duration: Other requirements:	LD 300 mW (~ +25 dBm) 3 dB 0,5 h at each power level. Test results shall be obtained under insertion loss measurement uncertainty of 0,1 dB. Test results shall be obtained under return loss measurement uncertainty of 1 dB.
7	Cold IEC 61300-2-17	During and on completion of the test the insertion loss limits of Test No. 1 shall be met. After the test the isolation limits of Test No. 2 shall be met. During and on completion of the test the return loss limits of Test No. 4 shall be met.	Temperature: Duration of the exposure: Maximum sampling interval during the test: Measurements required:	- 10 °C 2 °C 96 h 1 h Insertion loss shall be measured before, during and after the test. Return loss shall be measured before, during and after the test.
8	Dry heat – High temperature endurance IEC 61300-2-18	During and on completion of the test the insertion loss limits of Test No. 1 shall be met. After the test the isolation limits of Test No. 2 shall be met. During and on completion of the test the return loss limits of Test No. 4 shall be met.	Temperature: Duration of the exposure: Maximum sampling interval during the test: Measurements required:	+ 60 °C 2 °C 96 h 1 h Insertion loss shall be measured before, during and after the test. Return loss shall be measured before, during and after the test.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

https://standards.iteh.ai/catalog/standards/sist/61753-087-2-2010/iec-61753-087-2-2010

Table 1 (continued)

No.	Test	Requirement	Details	
9	Change of temperature IEC 61300-2-22	During and on completion of the test the insertion loss limits of Test No. 1 shall be met. After the test the isolation limits of Test No. 2 shall be met. During and on completion of the test the return loss limits of Test No. 4 shall be met.	High temperature:: Low temperature: Number of cycles: Rate of temperature change: Duration at extreme temperatures: Maximum sampling interval during the test: Measurements required:	+ 60 °C 2 °C - 10 °C 2 °C 5 1 °C/min 1 h 0,5 h Insertion loss shall be measured before, during and after the test. Return loss shall be measured before, during and after the test.
10	Damp heat (steady state) IEC 61300-2-19	During and on completion of the test the insertion loss limits of Test No. 1 shall be met. After the test the isolation limits of Test No. 2 shall be met. During and on completion of the test the return loss limits of Test No. 4 shall be met.	Temperature: Humidity: Duration of the exposure: Maximum sampling interval during the test: Measurements required:	+ 40 °C 2 °C 93 % RH + 2 % RH, - 3 % RH 96 h 1 h Insertion loss shall be measured before, during and after the test. Return loss shall be measured before, during and after the test.
11	Vibration IEC 61300-2-1	After the test the insertion loss limits of Test No. 1 shall be met. After the test the isolation limits of Test No. 2 shall be met. After the test the return loss limits of Test No. 4 shall be met.	Frequency range: Constant vibration amplitude: Number of cycles (10 Hz - 55 Hz - 10 Hz): Frequency change: Number of axes: Duration per axis: Measurements required:	10 Hz - 55 Hz 0,75 mm 15 1 octave/min 3 orthogonal 0,5 h Insertion loss shall be measured before and after the test. Return loss shall be measured before and after the test.
12	Shock IEC 61300-2-9	After the test the insertion loss limits of Test No. 1 shall be met. After the test the isolation limits of Test No. 2 shall be met. After the test the return loss limits of Test No. 4 shall be met.	Acceleration force: Number of axes: Duration shock: Pulse: Number of shocks: Measurements required:	500 g _n 3 main axes, perpendicular on each other 1 ms Half sine 2 per axis and direction (two in each direction) Insertion loss shall be measured before and after the test. Return loss shall be measured before and after the test.

Table 1 (continued)

No.	Test	Requirement	Details	
13	Fibre/cable retention IEC 61300-2-4	After the test the insertion loss limits of Test No. 1 shall be met. After the test the isolation limits of Test No. 2 shall be met. After the test the return loss limits of Test No. 4 shall be met.	Magnitude of the load: Load application point: Load rate: Duration of the load: Measurements required:	10 N 1 N for reinforced cable 5,0 N 0,5 N for secondary coated fibre 2,0 N 0,2 N at 0,5 N/s for primary coated fibre 0,3 m from the end of device 5 N/s for reinforced cable 0,5 N/s for coated fibre 120 s at 10 N 60 s at 5 N and 2 N Insertion loss shall be measured before and after the test. Return loss shall be measured before and after the test.
14	Flexing of the strain relief of fibre optic devices IEC 61300-2-44	After the test the insertion loss limits of Test No. 1 shall be met. After the test the isolation limits of Test No. 2 shall be met. After the test the return loss limits of Test No. 4 shall be met.	Magnitude of the load: Rate of load application: Load application point: Number of cycles: Measurements required:	2,0 N 0,2 N for reinforced cable 0,5 N/s for reinforced cable 0,2 m from end of device 30 cycles Insertion loss shall be measured before and after the test. Return loss shall be measured before and after the test.
15	Static side load IEC 61300-2-42	After the test the insertion loss limits of Test No. 1 shall be met. After the test the isolation limits of Test No. 2 shall be met. After the test the return loss limits of Test No. 4 shall be met.	Magnitude of the load: Load application point: Load rate: Duration of the load: Measurements required:	1,0 N 0,1 N for reinforced cable 0,2 N 0,1 N for secondary coated fibres 0,3 m from the end of device 0,5 N/s 1 h at 1N 5 min at 0,2 N Insertion loss shall be measured before and after the test. Return loss shall be measured before and after the test.

iTech STANDARD PREVIEW
(standards.iteh.ai)

IEC 61753-087-2:2010
<https://standards.iteh.ai/standards/sis/a7380941-3f60-413f-9204-61611aa5bc44/iec-61753-087-2-2010>