

INTERNATIONAL STANDARD

NORME INTERNATIONALE

**Low-voltage fuses –
Part 2: Supplementary requirements for fuses for use by authorized persons
(fuses mainly for industrial application) – Examples of standardized systems of
fuses A to J**

**Fusibles basse tension –
Partie 2: Exigences supplémentaires pour les fusibles destinés à être utilisés par
des personnes habilitées (fusibles pour usages essentiellement industriels) –
Exemples de systèmes de fusibles normalisés A à J**



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2010 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de la CEI ou du Comité national de la CEI du pays du demandeur.

Si vous avez des questions sur le copyright de la CEI ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de la CEI de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland
Email: inmail@iec.ch
Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

- Catalogue of IEC publications: www.iec.ch/searchpub

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

- IEC Just Published: www.iec.ch/online_news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

- Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

- Customer Service Centre: www.iec.ch/webstore/custserv

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch
Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00

A propos de la CEI

La Commission Electrotechnique internationale (CEI) est la première organisation mondiale qui élabore et publie des normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications CEI

Le contenu technique des publications de la CEI est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

- Catalogue des publications de la CEI: www.iec.ch/searchpub/cur_fut-f.htm

Le Catalogue en-ligne de la CEI vous permet d'effectuer des recherches en utilisant différents critères (numéro de référence, texte, comité d'études,...). Il donne aussi des informations sur les projets et les publications retirées ou remplacées.

- Just Published CEI: www.iec.ch/online_news/justpub

Restez informé sur les nouvelles publications de la CEI. Just Published détaille deux fois par mois les nouvelles publications parues. Disponible en-ligne et aussi par email.

- Electropedia: www.electropedia.org

Le premier dictionnaire en ligne au monde de termes électroniques et électriques. Il contient plus de 20 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans les langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International en ligne.

- Service Clients: www.iec.ch/webstore/custserv/custserv_entry-f.htm

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions, visitez le FAQ du Service clients ou contactez-nous:

Email: csc@iec.ch
Tél.: +41 22 919 02 11
Fax: +41 22 919 03 00

INTERNATIONAL STANDARD

NORME INTERNATIONALE

**Low-voltage fuses –
Part 2: Supplementary requirements for fuses for use by authorized persons
(fuses mainly for industrial application) – Examples of standardized systems of
fuses A to J**

**Fusibles basse tension –
Partie 2: Exigences supplémentaires pour les fusibles destinés à être utilisés
par des personnes habilitées (fusibles pour usages essentiellement industriels)
– Exemples de systèmes de fusibles normalisés A à J**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

PRICE CODE
CODE PRIX

XH

CONTENTS

FOREWORD.....	14
INTRODUCTION.....	16
1 General scope.....	17
1.2 Normative references	18
Fuse system A – Fuses with fuse-links with blade contacts (NH fuse system)	19
1 General.....	19
1.1 Scope.....	19
2 Terms and definitions	19
3 Conditions for operation in service.....	19
4 Classification.....	20
5 Characteristics of fuses	20
5.2 Rated voltage.....	20
5.3.1 Rated current of the fuse-link.....	20
5.3.2 Rated current of the fuse-holder	20
5.5 Rated power dissipation of a fuse-link and rated/acceptable power dissipation of a fuse-holder	20
5.6 Limits of time-current characteristics.....	21
5.6.1 Time-current characteristics, time-current zones and overload curves	21
5.6.2 Conventional times and currents.....	21
5.6.3 Gates	21
5.7.2 Rated breaking capacity.....	21
6 Marking.....	22
6.1 Markings of fuse-holders	22
6.2 Markings of fuse-links.....	22
7 Standard conditions for construction.....	22
7.1 Mechanical design.....	23
7.1.2 Connections, including terminals	23
7.1.3 Fuse-contacts.....	23
7.1.6 Construction of fuse-bases	23
7.1.7 Construction of a fuse-link	24
7.2 Insulating properties.....	24
7.7 I^2t characteristics	24
7.8 Overcurrent discrimination of "gG" fuse-links.....	25
7.9 Protection against electric shock	25
8 Tests.....	25
8.1.4 Arrangement of the fuse and dimensions	26
8.1.6 Testing of fuse-holders.....	26
8.2.4 Acceptability of test results.....	27
8.2.5 Resistance to tracking	27
8.3 Verification of temperature rise and power dissipation	27
8.3.1 Arrangement of the fuse	27
8.3.2 Measurement of the temperature rise	28
8.5.8 Acceptability of test results.....	29
8.7.4 Verification of overcurrent discrimination	29

8.9	Verification of resistance to heat	31
8.9.1	Fuse-base	31
8.9.2	Fuse-links with gripping lugs of moulded material or of metal fixed in moulded material	31
8.10	Verification of non-deterioration of contacts and direct terminal clamps	32
8.10.1	Arrangement of the fuse	32
8.10.2	Test method	34
8.10.3	Acceptability of test results	35
8.11	Mechanical and miscellaneous tests	36
Annex AA (informative) Special test for cable overload protection		58
Fuse system B – Fuses with striker fuse-links with blade contacts (NH fuse system)		59
1	General	59
1.1	Scope	59
2	Terms and definitions	59
3	Conditions for operation in service	59
4	Classification	59
5	Characteristics of fuses	59
5.2	Rated voltage	59
5.3.1	Rated current of the fuse-link	59
5.3.2	Rated current of the fuse-holder	60
5.5	Rated power dissipation of a fuse-link and rated acceptable power dissipation of a fuse-holder	60
5.6	Limits of time-current characteristics	60
5.7.2	Rated breaking capacity	60
6	Marking	60
7	Standard conditions for construction	60
7.1	Mechanical design	60
7.1.2	Connections, including terminals	60
7.1.3	Fuse-contacts	60
7.1.7	Construction of a fuse-link	61
7.2	Insulating properties and suitability for insulation	61
7.7	I^2t characteristics	61
7.8	Overcurrent discrimination of "gG" fuse-links	61
7.9	Protection against electric shock	61
8	Tests	61
8.1.6	Testing of fuse-holders	61
8.3	Verification of temperature rise and power dissipation	61
8.7.4	Verification of overcurrent discrimination	62
8.9	Verification of resistance to heat	62
8.9.1	Fuse-base	62
Fuse system C – Fuse-rails (NH fuse system)		71
1	General	71
1.1	Scope	71
2	Terms and definitions	71

3	Conditions for operation in service.....	71
4	Classification.....	71
5	Characteristics of fuses	71
5.2	Rated voltage	71
5.3.2	Rated current	71
5.5.1	Rated acceptable power dissipation.....	71
6	Markings	71
7	Standard conditions for construction.....	72
7.1	Mechanical design.....	72
7.1.2	Connections, including terminals	72
7.2	Insulating properties.....	72
8	Tests.....	72
8.1.6	Testing of fuse-holders.....	73
8.3	Verification of temperature rise and power dissipation.....	73
8.3.1	Arrangement of the fuse	73
8.10	Verification of non-deterioration of contacts and direct terminal clamps.....	74
8.10.1	Arrangement of the fuse	74
Fuse system D – Fuse-bases for busbar mounting (40 mm system) (NH fuse system)		79
1	General.....	79
1.1	Scope.....	79
2	Terms and definitions.....	79
3	Conditions for operation in service.....	79
4	Classification.....	79
5	Characteristics of fuses	79
5.2	Rated voltage.....	79
5.3.2	Rated current	79
5.5.2	Rated acceptable power dissipation of tandem fuse-bases	80
6	Markings.....	80
7	Standard conditions for construction.....	80
7.1	Mechanical design.....	80
7.1.2	Connections, including terminals	80
7.1.5	Construction of a fuse-base for busbar mounting.....	80
7.2	Insulating properties and suitability for insulation	81
8	Tests.....	81
8.3	Verification of temperature rise and power dissipation.....	81
8.3.1	Arrangement of the fuse	81
8.9.1	Fuse-base	82
8.10	Verification of non-deterioration of contacts and direct terminal clamps.....	82
8.10.1	Arrangement of the fuse	82
8.10.2	Test method	82
8.11	Mechanical and miscellaneous tests.....	82
Fuse system E – Fuses with fuse-links for bolted connections (BS bolted fuse system)		91
1	General.....	91

1.1	Scope.....	91
2	Terms and definitions	91
3	Conditions for operation in service.....	91
4	Classification.....	91
5	Characteristics of fuses	91
5.3.1	Rated current of the fuse-link.....	91
5.3.2	Rated current of the fuse-holder	91
5.5	Rated power dissipation of a fuse-link and rated acceptable power dissipation of a fuse-holder	91
5.6	Limits of time-current characteristics	92
5.6.1	Time-current characteristics, time-current zones and overload curves	92
5.6.2	Conventional times and currents.....	92
5.6.3	Gates	92
5.7.2	Rated breaking capacity	92
6	Markings	92
6.1	Markings of fuse-holders	92
6.2	Markings of fuse-links.....	92
7	Standard conditions for construction.....	93
7.1	Mechanical design.....	93
7.1.2	Connections including terminals	93
7.2	Insulating properties and suitability for insulation	93
7.9	Protection against electric shock	93
8	Tests.....	93
8.3	Verification of temperature rise and power dissipation	93
8.3.1	Arrangement of the fuse	93
8.3.3	Measurement of the power dissipation of the fuse-link.....	93
8.4	Verification of operation	93
8.4.1	Arrangement of the fuse	93
8.5	Verification of breaking capacity.....	93
8.5.1	Arrangement of the fuse	93
8.5.8	Acceptability of test results.....	93
8.9	Verification of resistance to heat	94
8.10	Verification of non-deterioration of contacts.....	94
8.10.1	Arrangement of the fuse	94
8.10.2	Test method	94
8.10.3	Acceptability of the results.....	94
8.11	Mechanical and miscellaneous tests.....	94
Fuse system F – Fuses with fuse-links having cylindrical contact caps (NF cylindrical fuse system)		105
1	General	105
1.1	Scope.....	105
2	Terms and definitions	105
3	Conditions for operation in service.....	105
4	Classification.....	105
5	Characteristics of fuses	105
5.2	Rated voltage.....	105

5.3.1	Rated current of the fuse-link.....	105
5.3.2	Rated current of the fuse-holder	106
5.5	Rated power dissipation of a fuse-link and rated acceptable power dissipation of a fuse-holder	106
5.6	Limits of time-current characteristics	107
5.6.1	Time-current characteristics, time-current zones and overload curves	107
5.6.2	Conventional times and currents.....	107
5.6.3	Gates	107
5.7.2	Rated breaking capacity	107
6	Marking	108
6.1	Markings of fuse-holders	108
6.2	Markings of fuse-links.....	108
7	Standard conditions for construction.....	108
7.1	Mechanical design.....	108
7.1.2	Connections including terminals	108
7.2	Insulating properties and suitability for insulation.....	109
7.7	I^2t characteristics	109
7.8	Overcurrent discrimination of "gG" fuse-links.....	109
7.9	Protection against electric shock	109
8	Tests	110
8.1.6	Testing of fuse-holders.....	110
8.3.1	Arrangement of the fuse	110
8.7.4	Verification of overcurrent discrimination.....	112
8.9	Verification of resistance to heat	113
8.10	Verification of non-deterioration of contacts.....	113
8.10.1	Arrangement of the fuse	113
8.10.2	Test method	114
8.10.3	Acceptability of test results.....	114
Fuse system G – Fuses with fuse-links with offset blade contacts (BS clip-in fuse system)		
1	General.....	119
1.1	Scope.....	119
2	Terms and definitions	119
3	Conditions for operation in service.....	119
4	Classification.....	119
5	Characteristics of fuses	119
5.2	Rated voltage	119
5.3.1	Rated current of the fuse-link.....	120
5.3.2	Rated current of the fuse-holder	120
5.5	Rated power dissipation of a fuse-link and rated acceptable power dissipation of a fuse-holder	120
5.6.1	Time-current characteristics, time-current zones	120
5.6.2	Conventional times and currents.....	120
5.6.3	Gates	120
5.7.2	Rated breaking capacity	120
6	Markings	121
6.1	Markings of fuse-holders	121

6.2	Markings of fuse-links.....	121
7	Standard conditions for construction.....	121
7.1	Mechanical design.....	121
7.1.2	Connections including terminals	121
7.2	Insulating properties and suitability for insulation	121
7.7	I^2t characteristics	121
7.9	Protection against electric shock	122
8	Tests.....	122
8.3.3	Measurement of the power dissipation of the fuse-link.....	122
8.4.1	Arrangement of the fuse	122
8.5.1	Arrangement of the fuse	122
8.7.4	Verification of overcurrent discrimination	122
8.9	Verification of resistance to heat	123
8.10	Verification of non-deterioration of contacts.....	123
8.10.1	Arrangement of the fuse	123
8.10.2	Test method	123
8.10.3	Acceptability of test results.....	123
8.11	Mechanical and miscellaneous tests.....	123
Fuse system H – Fuses with fuse-links having "gD" and "gN" characteristics (class J, class T, and class L time delay and non time delay fuse types)		
1	General	129
1.1	Scope.....	129
2	Terms and definitions.....	129
3	Conditions for operation in service.....	129
4	Classification.....	129
5	Characteristics of fuses	129
5.2	Rated voltage.....	129
5.3.1	Rated current of the fuse-link.....	130
5.3.2	Rated current of the fuse-holder	130
5.5	Rated power dissipation of a fuse-link and rated acceptable power dissipation of a fuse-holder	130
5.6	Limits of the time-current characteristics	130
5.6.1	Time-current characteristics, time-current zones	130
5.6.2	Conventional times and currents.....	130
5.6.3	Gates	130
5.7.2	Rated breaking capacity	131
6	Markings	131
6.1	Markings of fuse-holders	131
6.2	Markings of fuse-links.....	131
7	Standard conditions for construction.....	131
7.1	Mechanical design.....	131
7.2	Insulating properties and suitability for insulation	131
7.5	Breaking Capacity	131
7.6	Cut-off current characteristics.....	131
7.7	I^2t characteristics	132
7.8	Overcurrent discrimination.....	132
7.9	Protection against electric shock	132

8	Tests	133
8.3	Verification of temperature rise and power dissipation	133
8.3.1	Arrangement of the fuse	133
8.4	Verification of operation	133
8.4.1	Arrangement of the fuse	133
8.5.4	Recovery voltage	134
8.6	Verification of cut-off current characteristics	134
8.7	Verification of I^2t characteristics and overcurrent discrimination	134
8.9	Verification of resistance to heat	135
8.10	Verification of non-deterioration of contacts	135
8.10.1	Arrangement of the fuse	135
8.10.2	Test method	135
8.10.3	Acceptability of test results	136
8.11	Mechanical and miscellaneous tests	136
8.11.2	Miscellaneous tests	136
	Fuse system I – gU fuse-links with wedge tightening contacts	151
1	General	151
1.1	Scope	151
2	Terms and definitions	151
3	Conditions for operation in service	151
3.9	Discrimination of fuse-links	151
4	Classification	152
5	Characteristics of fuses	152
5.2	Rated voltage	152
5.3.1	Rated current of the fuse-link	152
5.5	Rated power dissipation of a fuse-link	152
5.6.1	Time-current characteristics, time-current zones	152
5.6.2	Conventional times and currents	152
5.6.3	Gates	152
5.7.2	Rated breaking capacity	153
5.8	Cut-off current and I^2t characteristics	153
6	Markings	153
6.1	Markings of fuse-holders	153
6.2	Markings of fuse-links	153
7	Standard conditions for construction	153
7.1	Mechanical design	153
7.2	Insulating properties and suitability for insulation	153
7.5	Breaking capacity	153
7.7	I^2t characteristics	153
7.8	Overcurrent discrimination of the fuse-links	154
8	Tests	154
8.1.1	Kind of tests	154
8.3.1	Arrangement of the fuse	154
8.3.3	Measurement of the power dissipation of the fuse-link	155
8.4.1	Arrangement of the fuse	155
8.5.1	Arrangement of the fuse	155

8.5.2	Characteristics of the test circuit.....	155
8.5.5	Test method	155
8.5.8	Acceptability of test results.....	155
8.7.3	Verification of compliance for fuse-links at 0,01 s	156
8.9	Verification of resistance to heat	156
8.11	Mechanical and miscellaneous tests.....	156
Fuse system J – Fuses with fuse-links having "gD class CC" and "gN class CC" characteristics (Class CC time delay and non-time delay fuse types)		165
1	General	165
1.1	Scope.....	165
2	Terms and definitions	165
3	Conditions for operation in service.....	165
4	Classification	165
5	Characteristics of fuses	165
5.2	Rated voltage	165
5.3.1	Rated current of the fuse-link.....	166
5.3.2	Rated current of the fuse-holder	166
5.5	Rated power dissipation of a fuse-link and rated acceptable power dissipation of a fuse-holder	166
5.6	Limits of the time-current characteristics	166
5.6.1	Time-current characteristics, time-current zones	166
5.6.2	Conventional times and currents.....	166
5.6.3	Gates	166
5.7.2	Rated breaking capacity.....	166
6	Markings	167
6.1	Markings of fuse-holders	167
6.2	Markings of fuse-links.....	167
7	Standard conditions for construction.....	167
7.1	Mechanical design.....	167
7.2	Insulating properties and suitability for insulation	167
7.5	Breaking Capacity	167
7.6	Cut-off current characteristics.....	167
7.7	I^2t characteristics	167
7.8	Overcurrent discrimination.....	168
7.9	Protection against electric shock	168
8	Tests	168
8.3	Verification of temperature rise and power dissipation	168
8.3.1	Arrangement of the fuse	168
8.4	Verification of operation	169
8.4.1	Arrangement of the fuse	169
8.5.4	Recovery voltage.....	169
8.6	Verification of cut-off current characteristics	169
8.7	Verification of I^2t characteristics and overcurrent discrimination	170
8.9	Verification of resistance to heat	170
8.10	Verification of non-deterioration of contacts.....	171
8.10.1	Arrangement of the fuse	171
8.10.2	Test method	171

8.10.3 Acceptability of test results.....	171
8.11 Mechanical and miscellaneous tests.....	171
8.11.2 Miscellaneous tests	172
Bibliography.....	181
Figure 101 – Fuse-links with blade contacts.....	39
Figure 102 – Fuse-bases for fuse-links with blade contacts.....	42
Figure 103 – Replacement handle.....	45
Figure 104 – Time-current zones for "gG" fuse-links	46
Figure 105 – Dummy fuse-link according to 8.3.4.1, 8.9.1 and 8.10	51
Figure 106 – Measuring points according to 8.3.4 of IEC 60269-1, 8.3.4.1, 8.3.4.2 and 8.10.2 of fuse system A	52
Figure 107 – Test knife according to 8.5.5.1.2	52
Figure 108 – Example of a measuring device for determining the withdrawal forces according to 8.9.1 and 8.11.1.2.....	53
Figure 109 – Facility for verifying the mechanical strength of gripping lugs (see 8.11.1.8).....	54
Figure 110 – Measuring points according to 8.10.2.....	55
Figure 111 – Reference fuse-base	56
Figure 112 – Design mark for isolated gripping-lugs.....	57
Figure 201 – Fuse-links with blade contacts with striker.....	64
Figure 202 – Fuse-bases for fuse-links with blade contacts with striker.....	68
Figure 301 – Fuse-rails for fuse-links with blade contacts	75
Figure 302 – Test arrangement for fuse-rails	77
Figure 401 – Busbar mounting bases, 1 pole.....	84
Figure 402 – Busbar mounting bases, 3 pole.....	85
Figure 403 – Busbar mounting base, size 00, 2 × 3 pole (tandem fuse-base).....	86
Figure 404 – Test arrangement for single-pole and triple-pole fuse-bases for busbar-mounting according to 8.3.1.....	87
Figure 405 – Test arrangement for two single-pole and six single-pole fuse-bases in tandem arrangement for busbar-mounting according to 8.3.1.....	88
Figure 406 – Test arrangement for the verification of the peak withstand current	89
Figure 407 – Dummy fuse-link	90
Figure 501 – Fuse-links for bolted connection – Sizes A, B, C and D	96
Figure 502 – Fuse-links for bolted connection – Sizes A and B	97
Figure 503 – Typical fuse-holder.....	98
Figure 504 – Time-current zones for "gG" fuse-link	100
Figure 505 – Time-current zones for "gG" fuse-link	101
Figure 506 – Power dissipation test rig	102
Figure 507 – Breaking capacity test rig for fuse-links for bolted connection.....	103
Figure 601 – Fuse-links with cylindrical caps	115
Figure 602 – Fuse-links with cylindrical contact caps with striker – Additional dimensions for sizes 14 × 51 and 22 × 58 only.....	116
Figure 603 – Base for fuse-links with cylindrical caps	117
Figure 701 – Fuse-links having offset blade contacts, sizes E1, F1, F2 and F3.....	124

Figure 702 – Typical fuse-holder.....	125
Figure 703 – Time-current zones for "gG" fuse-links	126
Figure 704 – Time-current zones for "gG" fuse-links	127
Figure 705 – Power dissipation test rig	128
Figure 801 – Class J fuse-links (1 – 600 A).....	137
Figure 802 – Class L fuse-links (700 – 6 000 A).....	138
Figure 803 – Fuse-base and contacts for Class J fuse-links 1 – 600 A.....	139
Figure 804 – Fuse-base and contacts for Class L fuse-links 700 – 6 000 A.....	140
Figure 805 – Class T fuse-links (1-1200 A).....	141
Figure 806 – Fuse-base and contacts for Class T fuse-links 1-1200 A.....	142
Figure 807 – Class J Dummy fuse-link dimensions	143
Figure 808 – Class T Dummy fuse-link Dimensions.....	143
Figure 809 – Temperature test arrangement.....	144
Figure 810 – Time-current zones for "gN" fuse-links	145
Figure 811 – Time-current zones for "gN" fuse-links	146
Figure 812 – Time-current zones for "gN" fuse-links	147
Figure 813 – Time-current zones for "gD" fuse-links	148
Figure 814 – Time-current zones for "gD" fuse-links	149
Figure 815 – Time-current zones for "gD" fuse-links	150
Figure 901 – Time-current zones for current ratings 100 A, 200 A, 355 A and 630 A.....	157
Figure 902 – Time-current zones for current ratings 160 A and 315 A.....	158
Figure 903 – Time-current zones for current ratings 250 A and 500 A.....	159
Figure 904 – Time-current zones for current ratings 200 A and 400 A.....	160
Figure 905 – Dimensions for fuse-links with L type and U type tags	161
Figure 906 – Power dissipation test rig	162
Figure 907 – Breaking capacity test rig.....	163
Figure 1001 – Class CC Fuse-links (1-30 A).....	172
Figure 1002 – Fuse-base and contacts for Class CC fuse-links 1-30 A.....	172
Figure 1003 – Class CC Dummy Fuse-link Dimensions.....	173
Figure 1004 – Temperature Test arrangement	174
Figure 1005 – Time-current zones for class CC "gN" fuses	175
Figure 1006 – Time-current zones for class CC "gN" fuses	176
Figure 1007 – Time-current zones for class CC "gN" fuses	177
Figure 1008 – Time-current zones for class CC "gD" fuses	178
Figure 1009 – Time-current zones for class CC "gD" fuses	179
Figure 1010 – Time-current zones for class CC "gD" fuses	180
Table 101 – Conventional time and current for "gG" fuse-links with rated current lower than 16 A.....	21
Table 102 – Gates for specified pre-arcing and operating times of "gG" fuse-links	21
Table 103 – Minimum rated breaking capacities.....	22
Table 104 – Marking of fuse-links	22
Table 105 – Minimum cross-sectional ranges of unprepared conductors	23

Table 106 – Pre-arcing and operating I^2t values at 0,01 s for "gG" fuse-links	24
Table 107 – Maximum operating I^2t values for "aM" fuse-links	25
Table 108 – Pre-arcing I^2t values for discrimination	25
Table 109 – Survey of tests on fuse-holders and number of fuse-holders to be tested	26
Table 110 – Rated impulse withstand voltage	27
Table 111 – Torque to be applied to the terminal screws	28
Table 112 – Test currents	29
Table 113 – Test currents and I^2t limits for discrimination test	30
Table 114 – Torques to be applied when no values are given by the manufacturer	33
Table 115 – Cross-sectional area of aluminium conductors for tests corresponding to 8.10	33
Table 116 – Test sequence for direct terminal clamps.....	35
Table 117 – Permissible changes of the resistance.....	36
Table 118 – Force to withdraw the fuse-link from the fuse-base contacts.....	37
Table 201 – Position and force of the striker	61
Table 301 – Minimum cross-sectional ranges of unprepared conductors for fuse-rails.....	72
Table 302 – Survey of complete tests on fuse-rails and number of fuse-rails to be tested	73
Table 401 – Minimum cross-sectional ranges of unprepared conductors for fuse-bases for busbar mounting.....	80
Table 402 – Torques to be applied to contact making screws.....	81
Table 403 – Test currents	82
Table 404 – Force to withdraw the fuse-link from the fuse-base contacts.....	83
Table 501 – Conventional time and current for "gG" fuse-links	92
Table 502 – Gates for specified pre-arcing times of "gG" fuse-links	92
Table 601 – Maximum rated current of fuse-links with cylindrical caps	106
Table 602 – Maximum rated current of fuse-holders.....	106
Table 603 – Maximum values of the rated power dissipation of a fuse-link	106
Table 604 – Rated acceptable power dissipation of a fuse-holder	107
Table 605 – Conventional time and current for "gG" fuse-links with rated current lower than 16 A.....	107
Table 606 – Gates for specified pre-arcing and operating times of "gG" fuse-links with rated current lower than 16 A.....	107
Table 607 – Minimum rated breaking capacities.....	108
Table 608 – Colours of marking	108
Table 609 – Minimum range of cross-sections for rigid copper conductors	109
Table 610 – Pre-arcing and operating I^2t values at 0,01 s for "gG" fuse-links	109
Table 611 – Maximum operating I^2t values for "aM" fuse-links	109
Table 612 – Survey of tests on fuse-holders and number of fuse-holders to be tested	110
Table 613 – Torque to be applied to the terminal screws	111
Table 614 – Test currents	112
Table 615 – Test currents and I^2t limits for discrimination test	113
Table 701 – Conventional time and current for "gG" fuse-links	120
Table 702 – Gates for specified pre-arcing times of "gG" fuse-links	120

Table 703 – Sizes of copper conductors	121
Table 704 – Pre-arcing I^2t values at 0,01 s for "gG" fuse-links	122
Table 801 – Conventional time and current for "gD" and "gN" fuse-links	130
Table 802 – Gates for specified pre-arcing times of "gD" and "gN" fuse-links	131
Table 803 – Pre-arcing I^2t values at 0,01 s for "gD" and "gN" fuse-links.....	132
Table 804 – Cross-sectional area of copper conductors for tests corresponding to 8.3 and 8.4	133
Table 805 – Maximum cut-off current (I_C) for "gD" and "gN" fuse-links at 200 kA prospective current	134
Table 806 – Maximum operating I^2t values for "gD" and "gN" fuse-links at 200 kA prospective current	135
Table 901 – Maximum power dissipation values.....	152
Table 902 – Pre-arcing I^2t values for gU fuse-links at 0,01 s	154
Table 903 – Cross-sectional area of conductors for power dissipation and temperature-rise tests	155
Table 1001 – Conventional time and current for "gD class CC " and "gN class CC " fuse-links	166
Table 1002 – Gates for specified pre-arcing times of "gD class CC " and "gN class CC " fuse-links.....	166
Table 1003 – Pre-arcing I^2t values at 0,01 s for "gD class CC " and "gN class CC " fuse-links	168
Table 1005 – Maximum cut-off current (I_C) for "gD class CC " and "gN class CC " fuse-links at 200 kA prospective current	170
Table 1006 – Maximum operating I^2t values for "gD class CC " and "gN class CC " fuse-links at 200 kA prospective current.....	170