



Edition 1.0 2008-11

PUBLICLY AVAILABLE SPECIFICATION

PRE-STANDARD Directly heated negative temperature coefficient thermistors -Part 1-1: Blank detail specification – Sensing application – Assessment level EZ



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2008 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office 3, rue de Varembé CH-1211 Geneva 20 Switzerland Email: inmail@iec.ch

Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Rease make sure that you have the latest edition, a corrigenda or an amendment might have been published.

■ Catalogue of IEC publications: <u>www.iec.ch/searchpub</u>

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

■ IEC Just Published: www.iec.ch/online news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

Electropedia: www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

Customer Service Centre: www.ies.ch/webstore/custserv

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:

Email: csc@iec.ch Tel.: +41 22 919 02 11 Fax: +41 22 919 03 00



IEC/PAS 60539-1-1


Edition 1.0 2008-11

PUBLICLY AVAILABLE SPECIFICATION

PRE-STANDARD

Directly heated negative temperature coefficient thermistors –

Part 1-1: Blank detail specification – Sensing application – Assessment level EZ



INTERNATIONAL ELECTROTECHNICAL COMMISSION

PRICE CODE

M

ICS 31.040.30

ISBN 978-2-88910-790-2

CONTENTS

FOI	REWC	PRD	. 3
INT	RODU	JCTION	. 5
1	General data		6
	1.1	Method(s) of mounting (to be inserted)	. 6
	1.2	Dimensions	
	1.3	Coating	.6
	1.4	Terminations	.6
	1.5	Flammability	. 6
	1.6	Resistance to solvents	. 6
	1.7	Packaging	. 6
	1.8	Electrical data/Ratings and characteristics	. 6
	1.9	Normative references	. 7
	1.10	Marking	7
	1.11	Ordering information	
		Additional information (not for inspection purposes)	. 7
	1.13	Additional or increased severities or requirements to those specified in the generic sectional specification	7
2	Inspection requirements		
	2.1	Procedures	.7
Tab	le 1 –	Test schedule for quality conformance inspection: lot-by-lot	
Tab	le 2 –	Test schedule for quantity conformance inspection: periodic	10

INTERNATIONAL ELECTROTECHNICAL COMMISSION

DIRECTLY HEATED NEGATIVE TEMPERATURE COEFFICIENT THERMISTORS –

Part 1-1: Blank detail specification – Sensing application – Assessment level EZ

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held esponsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

A PAS is a technical specification not fulfilling the requirements for a standard, but made available to the public.

This PAS shall be read in conjunction with IEC 60539-1:2008.

IEC-PAS 60539-1-1 has been processed by IEC technical committee 40: Capacitors and resistors for electronic equipment.

The text of this PAS is based on the following document:

This PAS was approved for publication by the P-members of the committee concerned as indicated in the following document

Draft PAS	Report on voting
40/1927/PAS	40/1934/RVD

Following publication of this PAS, which is a pre-standard publication, the technical committee or subcommittee concerned may transform it into an International Standard.

This PAS shall remain valid for an initial maximum period of 3 years starting from the publication date. The validity may be extended for a single 3-year period, following which it shall be revised to become another type of normative document, or shall be withdrawn.



DIRECTLY HEATED NEGATIVE TEMPERATURE COEFFICIENT THERMISTORS –

Part 1-1: Blank detail specification – Sensing application – Assessment level EZ

INTRODUCTION

Blank detail specification

A blank detail specification is a supplementary document to the generic specification and contains requirements for style and layout and minimum content of detail specifications. Detail specifications not complying with these requirements shall not be considered as being in accordance with IEC specifications nor shall they so be described.

In the preparation of detail specifications, the content of 1.1 of the generic specification shall be taken into account.

The numbers between brackets on the first page correspond to the following information which shall be inserted in the position indicated.

Identification of the detail specification

- [1] The "International Electrotechnical Commission" or the National Standards Organization under whose authority the detail specification is drafted.
- [2] The IEC or National Standards number of the detail specification, date of issue and any further information required by the national system.
- [3] The number and issue number of the IEC or national generic specification.
- [4] The IEC number of the blank detail specification.

Identification of the thermistor

- [5] A short description of the type of thermistor.
- [6] Information on typical construction (if applicable).

NOTE When the thermistor is not designed for use on printed boards, this should clearly be stated in the detail specification in this position.

- [7] Outline drawing with main dimensions which are of importance for interchangeability and/or reference to the national or international documents for outlines. Alternatively, this drawing may be given in an annex to the detail specification.
- [8] Application or group of applications covered and/or assessment level.
- [9] Reference data on the most important properties, to allow comparison between the various thermistor types.

1 General data

1.1 Method(s) of mounting (to be inserted)

(See 4.4 of IEC 60539-1:2008.)

1.2 Dimensions

(All dimensions are in millimetres or inches and millimetres; it shall be stated which dimensions are suitable for gauging.)

Dimensioned drawing(s) shall be given in the detail specification. If necessary, the dimensions may be listed in tabular form with reference to styles or codes.

1.3 Coating

The detail specification shall state:

- a) whether the thermistor is insulated or non insulated;
- b) the material:
- c) the colour, if applicable.

1.4 Terminations

The detail specification shall state whether the terminations are suitable for soldering. If they are not, suitable methods of connection shall be stated for example: welding, clamping or crimping.

1.5 Flammability

The detail specification shall state whether the thermistor is actively or passively flammable, if applicable. The test method shall be given in the test schedule.

1.6 Resistance to solvents

The detail specification shall state whether the coating and the marking of the thermistor are solvent resistant, if applicable. The test methods shall be given in the test schedule.

1.7 Packaging

The detail specification shall give the following information (if required):

- a) whether bulk packed or taped and if taped, drawing or references;
- b) the dimensions of the immediate packaging and the number of thermistors packed;
- c) the dimensions of the outer package and the number of immediate packages;
- d) methods of disposal of the packaging material.

1.8 Electrical data/Ratings and characteristics

The detail specification shall give units and tolerances or limiting values for the following parameters. If necessary, electrical data may be listed in tabular form, with reference to styles and codes.

Upper/Lower category temperatures ($\theta_{max}/\theta_{min}$);

Maximum current at ambient temperature θ ($I_{max \theta}$);

Zero-power resistance (R_T) ;

Resistance-temperature characteristics;

Maximum power dissipation at ambient temperature θ ($P_{max \theta R}$);

B-value;

Isolation voltage (insulated thermistors only);

etc.

1.9 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60539-1:2008, Directly heated negative temperature coefficient thermistors – Part 1: Generic specification

1.10 Marking

The marking of the thermistors and package containing the thermistors shall be in accordance with the requirements of 4.5.2 of IEC 60539-1:2008.

The details of the marking of the thermistors and package containing the thermistor shall be given in full in the detail specification.

1.11 Ordering information

Orders for thermistors covered by this specification shall contain, in clear or in coded form, the following minimum information:

- a) style reference;
- b) maximum current at ambient temperature;
- c) number and issue reference of the detail specification;
- d) maximum dissipation power at ambient temperature;
- e) B-value.
- 1.12 Additional information (not for inspection purposes)
- 1.13 Additional or increased severities or requirements to those specified in the generic sectional specification

NOTE Additions or increased requirements should be specified only when essential.

2 Inspection requirements

2.1 Procedures

- **2.1.1** For qualification approval, the procedures shall be in accordance with the generic specification, IEC 60539-1:2008, 3.4.
- **2.1.2** For quality conformance inspection, the test schedules (see Tables 1 and 2) include sampling, periodicity, severities and requirements. The formation of inspection lots is covered by the generic specification IEC 60539-1:2008, 3.5.

The following list applies to the test schedules developed in Tables 1 and 2:

- 1) Subclause numbers of tests and performance requirements refer to the generic specification IEC 60539-1 and Clause 1 of this Blank Detail Specification.
- 2) Number to be tested: sample size as directly allotted to the code letter for IL in table IIA of IEC 60410:1973 (Single sampling plans for normal inspection).

- 3) In these tables: p is the periodicity (in months)
 - n is the sample size
 - c is the acceptance criterion (permitted number of non-conforming items)
 - D indicates a destructive test
 - ND indicates a non-destructive test
 - L is the inspection level
- 4) The temperature at which the zero-power resistance shall be measured is the temperature specified in the detail specification. This temperature shall be stated, where required, in the test schedule.
- 5) The specimens used for this group may, at the discretion of the manufacturer, be used for any subsequent group which is identified as being "destructive".
- 6) The soldering solderability and soldering resistance to heat tests shall only be applied where the thermistor has terminations which are appropriate for soldering.
- 7) Where the terminations are stated to be suitable for printed wiring applications, the appropriate test conditions in IEC 60068-2-58 shall apply.
- 8) The thermistors shall be mounted by their normal means.
- 9) The bump test and the shock test are alternatives. The test selected in the detail specification shall be used.
- 10) The detail specification shall specify which test is appropriate to the construction and application of the thermistor for measuring the thermal time constant.
- 11) Any deviation from Annex B of the generic specification shall be given in the detail specification.
- 12) 100 % testing shall be followed by re-inspection by sampling in order to monitor outgoing quality level by non-conforming items per million (\times 10⁻⁶). The sampling level shall be established by the manufacturer. For the calculation of \times 10⁻⁶ values, any parametric failure shall be counted as a non-conforming item. In case one or more non-conforming items occur in a sample, this lot shall be rejected.