

### SLOVENSKI STANDARD SIST EN 61755-3-5:2007

01-september-2007

Cdhj bjja Ygb]\_j'nUcdhj bY'\_cbY\_hcf^Y'Ë'!) "XY'. 'Cdhj bjja Ygb]\_'Ë'7j`]bXf] bY dc`]\_UfVcbUhbY'\_ca dcn]hbY'hi`\_Y'g'dfYa Yfca '&z) 'a a ']b'% a z z\_j'i dcfUV`^U'c n`]hjbc'7i!Bj'nUcVcX'j`U\_bUzYbcfcXbc'j`U\_bc'fl97'\*%))!'!).&\$\$\*\L

Fibre optic connector optical interfaces -- Part 3-5: Optical Interface - 2,5 mm and 1,25 mm diameter cylindrical PC composite ferrule using Cu-Ni-alloy as fibre surrounding material, single mode fibre (IEC 61755-3-5:2006)

Optische Schnittstellen von Lichtwellenleiter-Steckverbindern -- Teil 3-5: Optische Schnittstelle - Zylindrische PC-Composite-Ferrulen mit 2,5 mm und 1,25 mm Durchmesser für Einmodenfaser, mit Cu-Ni-Legierung als Material für die Faserfassung (IEC 61755-3-5:2006)

SIST EN 61755-3-5:2007

https://standards.iteh.ai/catalog/standards/sist/239017b4-34a0-471f-b266-8326a9f44242/sist-en-61755-3-5-2007

Interfaces optiques de connecteurs pour fibres optiques -- Partie 3-5: Interfaces optiques -- Férules PC composites cylindriques de diametre 2,5 mm et 1,25 mm, utilisant un alliage Cu-Ni comme matériau entourant la fibre, fibres unimodales (IEC 61755-3-5:2006)

Ta slovenski standard je istoveten z: EN 61755-3-5:2006

ICS:

33.180.20 Ú[ç^: [çæ] ^Áæ] læç^Áæ Fibre optic interconnecting

[]  $(\tilde{a})$   $(\tilde{a})$   $(\tilde{a})$   $(\tilde{a})$   $(\tilde{a})$   $(\tilde{a})$ 

SIST EN 61755-3-5:2007 en,fr,de

# iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN 61755-3-5:2007</u> https://standards.iteh.ai/catalog/standards/sist/239017b4-34a0-471f-b266-8326a9f44242/sist-en-61755-3-5-2007

## **EUROPEAN STANDARD**

### EN 61755-3-5

### NORME FUROPÉENNE

## **EUROPÄISCHE NORM**

December 2006

ICS 33.180.20

#### **English version**

### Fibre optic connector optical interfaces Part 3-5: Optical interface -2.5 mm and 1,25 mm diameter cylindrical PC composite ferrule using Cu-Ni-alloy as fibre surrounding material, single mode fibre (IEC 61755-3-5:2006)

Interfaces optiques de connecteurs pour fibres optiques Partie 3-5: Interfaces optiques -Férules PC composites cylindriques de diamètre 2,5 mm et 1,25 mm, utilisant un alliage Gu-Ni comme matériau R D Pfür Einmodenfaser, mit Cu-Ni-Legierung entourant la fibre, fibres unimodales (CEI 61755-3-5:2006)

Optische Schnittstellen von Lichtwellenleiter-Steckverbindern Teil 3-5: Optische Schnittstelle -Zylindrische PC-Composite-Ferrulen mit 2,5 mm und 1,25 mm Durchmesser als Material für die Faserfassung (standards.itehed)61755-3-5:2006)

SIST EN 61755-3-5:2007 https://standards.iteh.ai/catalog/standards/sist/239017b4-34a0-471f-b266-8326a9f44242/sist-en-61755-3-5-2007

This European Standard was approved by CENELEC on 2006-12-01. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

## **CENELEC**

European Committee for Electrotechnical Standardization Comité Européen de Normalisation Electrotechnique Europäisches Komitee für Elektrotechnische Normung

Central Secretariat: rue de Stassart 35, B - 1050 Brussels

#### **Foreword**

The text of document 86B/2258/CDV, future edition 1 of IEC 61755-3-5, prepared by SC 86B, Fibre optic interconnecting devices and passive components, of IEC TC 86, Fibre optics, was submitted to the IEC-CENELEC Parallel Unique Acceptance Procedure and was approved by CENELEC as EN 61755-3-5 on 2006-12-01.

The following dates were fixed:

 latest date by which the EN has to be implemented at national level by publication of an identical national standard or by endorsement

(dop) 2007-09-01

 latest date by which the national standards conflicting with the EN have to be withdrawn

(dow) 2009-12-01

#### **Endorsement notice**

The text of the International Standard IEC 61755-3-5:2006 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

IEC 61753-1 NOTE Harmonized as EN 61753-1:2001 (not modified)./

IEC 61755-3 NOTE Harmonized in EN 61755-3 series (not modified).

SIST EN 61755-3-5:2007 https://standards.iteh.ai/catalog/standards/sist/239017b4-34a0-471f-b266-8326a9f44242/sist-en-61755-3-5-2007

## NORME INTERNATIONALE INTERNATIONAL STANDARD

CEI IEC 61755-3-5

> Première édition First edition 2006-11

Interfaces optiques de connecteurs pour fibres optiques –

Partie 3-5:

Interfaces optiques -

Férules PC composites cylindriques de diamètre 2,5 mm et 1,25 mm, utilisant un alliage Cu-Ni comme matériau entourant la fibre, fibres unimodales

https://standards.iteh.ai/catalog/standards/sist/239017b4-34a0-471f-b266-8326a9f44242/sist-en-61755-3-5-2007

Fibre optic connector optical interfaces -

Part 3-5:

Optical interface -

2,5 mm and 1,25 mm diameter cylindrical PC composite ferrule using Cu-Ni-alloy as fibre surrounding material, single mode fibre

© IEC 2006 Droits de reproduction réservés — Copyright - all rights reserved

Aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'éditeur.

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



CODE PRIX PRICE CODE



#### **CONTENTS**

FOREWORD		5	
1	Scope	9	
2	Description	9	
3	Interface parameters	11	
An	nnex A (informative)	17	
Rik	bliography	19	

## iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 61755-3-5:2007 https://standards.iteh.ai/catalog/standards/sist/239017b4-34a0-471f-b266-8326a9f44242/sist-en-61755-3-5-2007

#### INTERNATIONAL ELECTROTECHNICAL COMMISSION

#### FIBRE OPTIC CONNECTOR OPTICAL INTERFACES -

## Part 3-5: Optical interface – 2,5 mm and 1,25 mm diameter cylindrical PC composite ferrule using Cu-Ni-alloy as fibre surrounding material, single mode fibre

#### **FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.

  8326a9f44242/sist-en-61755-3-5-2007
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61755-3-5 has been prepared by subcommittee 86B: Fibre optic interconnecting devices and passive components, of IEC technical committee 86: Fibre optics.

The text of this standard is based on the following documents:

CDV	Report on Voting
86B/2258/CDV	86B/2338/RVC

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 61755 series, published under the general title *Fibre optic connector optical interfaces*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed;
- withdrawn;
- · replaced by a revised edition, or
- amended.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 61755-3-5:2007 https://standards.iteh.ai/catalog/standards/sist/239017b4-34a0-471f-b266-8326a9f44242/sist-en-61755-3-5-2007

#### FIBRE OPTIC CONNECTOR OPTICAL INTERFACES -

## Part 3-5: Optical interface – 2,5 mm and 1,25 mm diameter cylindrical PC composite ferrule using Cu-Ni-alloy as fibre surrounding material, single mode fibre

#### 1 Scope

This part of IEC 61755 defines dimensional limits and material properties of a 2,5 mm and a 1,25 mm diameter cylindrical composite ferrule optical interface to meet specific requirements for PC fibre-to-fibre interconnection. The composite ferrule uses different materials in the end face contact zone and in the ferrule to sleeve contact zone. The specified materials for each zone are Zirconia (ZrO<sub>2</sub>) for the ferrule to sleeve contact zone and Cu-Ni-alloy for the end face contact zone. Ferrules made from the material specified in this document are suitable for use in categories C, U and O as defined in IEC 61753-1.

NOTE If mated within the same family (cylindrical PC ferrule) the ferrules specified in this document are intended to have the same optical attenuation performance grade for connections with all ferrules described in IEC 61755-3 documents.

### 2 Description iTeh STANDARD PREVIEW

The performance of a cylindrical ferrule optical interface is determined by the accuracy with which the optical datum targets of two mating ferrules are aligned with each other. There are three conditions affecting the alignment of two optical datum targets, lateral offset, angular offset and longitudinal offset.

SIST EN 61755-3-5:2007

https://standards.iteh.ai/catalog/standards/sist/239017b4-34a0-471f-b266-

Parameters influencing the lateral and angular offset of the optical fibre axes include

- ferrule outside diameter;
- fibre hole concentricity relative to the ferrule outside diameter;
- fibre hole angle relative to outside diameter axis;
- fibre cladding diameter to fibre hole clearance;
- alignment sleeve inside diameter;
- fibre core concentricity relative to the cladding diameter;
- fibre core orientation relative to keying feature.

Parameters influencing the longitudinal offset of the optical fibre axes include

- end face spherical radius;
- · end face spherical radius apex offset;
- fibre undercut;
- axial force on ferrule end face;
- ferrule and fibre material physical constants;
- alignment sleeve frictional force;
- keying accuracy.