



SLOVENSKI STANDARD  
SIST EN 3479:2009

01-maj-2009

5 YfcbUj h\_U!>Y`c': 9!DA%,\$&fL) 7 fBJ7i %!) Ł!DfYU^Ybc`g`hUJ]bc`YY\_fcxXc`!  
pUf^Ybc`j`hcd]i`]b`i hf^Ybc`!D`cy U!\*`a a `0`U@&\$`a a `!`%\$+\$`ADU@Fa`@%&&\$  
ADU

Q^|[·] æ^Á^!a·ÄÜc^|ÄÖËÜT Fí €GÁYÍ Ô!PáD` Fí Ę DĚŮ [ ]· { æ|Á^|&d[ á^Á^ { ^|c`á  
ÄÜ [ ] c` } Á^æ`á/æ`áÁ`!^&á`ää` } Á^æ`áÄÜ|æ`ÄÄ`Á { Á`Á`m`GEÁ { ÄZÄĚĚ ĘT Ú`m  
Ü { m`F`ÄGGEÁT Úæ

**ITeH STANDARD PREVIEW**  
(Standard not for publication)

Š`-Ä` } áÜæ { -æ@ÄÜcæ@ÄÖËÜT Fí €GÁYÍ Ô!PáD` Fí Ę DĚÄ` á^|a`c`^!`^@^ } á!  
Ò^|d[ á^Á { \*^·&@ [ | : ^ } ÄS4·` } \*·^\* > @Ä` } á/æ`·^æ`!`ÄÜ|æ` } ÄÄ`Á { Á`Á`m`GE  
{ { ÄZÄĚĚ ĘT Ú`mÜ { m`F`ÄGGEÁT Úæ

SIST EN 3479:2009

<https://standards.iteh.ai/catalog/standards/sist/988a5544-f2c3-4eab-bc26-615c9f401838/en-147-1100>

Ü..!á`æ..! [·] ææ`ÄÖBá`|ÄÖËÜT Fí €GÁYÍ Ô!PáD` Fí Ę DĚÜ^| } á`Ä`AC|^&d[ á^  
& }·[ { { æ|Á^|ÄÄ`á`Á`|`c` } Á`c`á`|ÄÜ|æ`~^·ÄÄ`Á { Á`Á`m`GEÁ { ÄZÄĚĚ ĘT Ú`mÜ {  
m`F`ÄGGEÁT Úæ

Ta slovenski standard je istoveten z: EN 3479:2007

**ICS:**

49.025.10      Jekla      Steels

**SIST EN 3479:2009**      en,de

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST EN 3479:2009

<https://standards.iteh.ai/catalog/standards/sist/988a5544-f2c3-4eab-bc26-b53218428480/sist-en-3479-2009>

EUROPEAN STANDARD  
NORME EUROPÉENNE  
EUROPÄISCHE NORM

**EN 3479**

March 2007

ICS 49.025.10

English Version

**Aerospace series - Steel FE-PM1802 (X5CrNiCu15-5) -  
Consumable electrode remelted - Solution treated and  
precipitation treated - Plate - 6 mm < a ≤ 20 mm - 1 070 MPa ≤  
Rm ≤ 1 220 MPa**

Série aérospatiale - Acier FE-PM1802 (X5CrNiCu15-5) -  
Refondu à l'électrode consommable - Mis en solution et  
vieilli - Plaques 6 mm < a ≤ 20 mm - 1 070 MPa ≤ Rm ≤ 1  
220 MPa

Luft- und Raumfahrt - Stahl FE-PM1802 (X5CrNiCu15-5) -  
Mit selbstverzehrender Elektrode umgeschmolzen -  
Lösungsgeglüht und ausgelagert - Platten - 6 mm < a ≤ 20  
mm - 1 070 MPa ≤ Rm ≤ 1 220 MPa

This European Standard was approved by CEN on 5 October 2006.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN Management Centre has the same status as the official versions.

[SIST EN 3479:2009](https://standards.iteh.ai/catalog/standards/sis/988a5544-fc3-4eab-bc26-11d182849a1c/en/en-3479:2007)

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION  
COMITÉ EUROPÉEN DE NORMALISATION  
EUROPÄISCHES KOMITEE FÜR NORMUNG

**Management Centre: rue de Stassart, 36 B-1050 Brussels**

## Foreword

This document (EN 3479:2007) has been prepared by the Aerospace and Defence Industries Association of Europe - Standardization (ASD-STAN).

After enquiries and votes carried out in accordance with the rules of this Association, this Standard has received the approval of the National Associations and the Official Services of the member countries of ASD, prior to its presentation to CEN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by September 2007, and conflicting national standards shall be withdrawn at the latest by September 2007.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

**IT'S STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST EN 3479:2009](https://standards.iteh.ai/catalog/standards/sist/988a5544-f2c3-4eab-bc26-b53218428480/sist-en-3479-2009)

<https://standards.iteh.ai/catalog/standards/sist/988a5544-f2c3-4eab-bc26-b53218428480/sist-en-3479-2009>

## Introduction

This standard is part of the series of EN metallic material standards for aerospace applications. The general organization of this series is described in EN 4258.

This standard has been prepared in accordance with EN 4500-5.

## 1 Scope

This standard specifies the requirements relating to:

Steel FE-PM1802 (X5CrNiCu15-5)  
Consumable electrode remelted  
Solution treated and precipitation treated  
Plate  
6 mm < a ≤ 20 mm  
1 070 MPa ≤ R<sub>m</sub> ≤ 1 220 MPa

for aerospace applications.

iTech STANDARD PREVIEW  
(standards.iteh.ai)

## 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 2043, *Aerospace series — Metallic materials — General requirements for semi-finished product qualification (excluding forgings and castings)*. <sup>1)</sup>

EN 2951, *Aerospace series — Metallic materials — Test method — Micrographic determination of content of non-metallic inclusions*. <sup>1)</sup>

EN 4050-4, *Aerospace series — Test method for metallic materials — Ultrasonic inspection of bars, plates, forging stock and forgings — Part 4: Acceptance criteria*. <sup>1)</sup>

EN 4258, *Aerospace series — Metallic materials — General organization of standardization — Links between types of EN standards and their use*.

EN 4500-5, *Aerospace series — Metallic materials — Rules for drafting and presentation of material standards — Part 5: Specific rules for steels*. <sup>1)</sup>

EN 4700-1, *Aerospace series — Steel and heat resisting alloy — Wrought products — Technical specification — Part 1: Plate, sheet and strip*. <sup>1)</sup>

---

<sup>1)</sup> Published as ASD Prestandard at the date of publication of this standard.

## EN 3479:2007 (E)

1	Material designation		Steel FE-PM1802 (X5CrNiCu15-5)										
2	Chemical composition %	Element	C	Si	Mn	P	S	Cr	Mo	Ni	Cu	Nb + Ta	Fe
		min.	-	-	-	-	-	14,0	-	3,5	2,5	5 × C	Base
		max.	0,07	1,00	1,00	0,030	0,005	15,5	0,50	5,5	4,5	0,45	
3	Method of melting		Consumable electrode remelted										
4.1	Form		Plate										
4.2	Method of production		-										
4.3	Limit dimension(s)	mm	6 < a ≤ 20										
5	Technical specification		EN 4700-1										

6.1	Delivery condition		Solution treated				Solution treated and precipitation treated					
	Heat treatment		1 025 °C ≤ θ ≤ 1 055 °C / t ≥ 30 min / AC or faster + cool to θ ≤ 30 °C				1 025 °C ≤ θ ≤ 1 055 °C / t ≥ 30 min / AC or faster + cool to θ ≤ 30 °C + 535 °C ≤ θ ≤ 565 °C / t ≥ 4 h / AC					
6.2	Delivery condition code		W				U					
7	Use condition		Solution treated and precipitation treated				Delivery condition					
	Heat treatment		Delivery condition + 535 °C ≤ θ ≤ 565 °C / t ≥ 4 h / AC				-					

iTech STANDARD PREVIEW

Characteristics

8.1	Test sample(s)		See EN 4700-1.										
8.2	Test piece(s)		See EN 4700-1.										
8.3	Heat treatment		Solution treated				Use condition						
9	Dimensions concerned	mm	6 < a ≤ 20				6 < a ≤ 20						
10	Thickness of cladding on each face	%	-				-						
11	Direction of test piece		-				L		T				
12	Temperature	θ	°C		-				Ambient		Ambient		
13	Proof stress	R <sub>p0,2</sub>	MPa		-				≥ 1 000		≥ 1 000		
14	T Strength	R <sub>m</sub>	MPa		-				1 070 ≤ R <sub>m</sub> ≤ 1 220		1 070 ≤ R <sub>m</sub> ≤ 1 220		
15	Elongation	A	%		-				≥ 11		≥ 7		
16	Reduction of area	Z	%		-				≥ 45		≥ 27		
17	Hardness		HB ≤ 363				321 ≤ HB ≤ 375		321 ≤ HB ≤ 375				
18	Shear strength	R <sub>c</sub>	MPa		-				-		-		
19	Bending	k	-		-				-		-		
20	Impact strength		Impact strength + KV ≥ 25 J				KV ≥ 80 J; Notch direction T + KV ≥ 35 J, at - 30 °C; Notch direction T		KV ≥ 55 J; Notch direction L + KV ≥ 25 J, at - 30 °C; Notch direction L				
21	Temperature	θ	°C		-								
22	Time		h		-								
23	Stress	σ <sub>a</sub>	MPa		-								
24	Elongation	a	%		-								
25	Rupture stress	σ <sub>R</sub>	MPa		-								
26	Elongation at rupture	A	%		-								
27	Notes (see line 98)		-										

30	Microstructure	–	See EN 4700-1.
		7	The $\delta$ ferrite content shall not exceed 2 %
34	Grain size	–	See EN 4700-1.
		7	$G \geq 5$
44	External defects	–	See EN 4700-1.
		1	Visual
50	Cleanliness/inclusion content (micro-cleanness)	–	See EN 4700-1.
		1	EN 2951
		7	Category 4
61	Internal defects	–	See EN 4700-1.
		1	EN 4050-4
		7	Class 3
<p><b>iTeh STANDARD PREVIEW</b>  <b>(standards.iteh.ai)</b></p> <p>SIST EN 3479:2009  <a href="https://standards.iteh.ai/catalog/standards/sist/988a5544-f2c3-4eab-bc26-b53218428480/sist-en-3479-2009">https://standards.iteh.ai/catalog/standards/sist/988a5544-f2c3-4eab-bc26-b53218428480/sist-en-3479-2009</a></p>			
95	Marking inspection	–	See EN 4700-1.
96	Dimensional inspection	–	See EN 4700-1.
98	Notes	–	–
99	Typical use	–	–

## EN 3479:2007 (E)

100	-	Product qualification	-	See EN 2043.
				Qualification programme to be agreed between manufacturer and purchaser.
<p><b>iTeh STANDARD PREVIEW</b> <b>(standards.iteh.ai)</b></p> <p><u>SIST EN 3479:2009</u> <a href="https://standards.iteh.ai/catalog/standards/sist/988a5544-f2c3-4eab-bc26-b53218428480/sist-en-3479-2009">https://standards.iteh.ai/catalog/standards/sist/988a5544-f2c3-4eab-bc26-b53218428480/sist-en-3479-2009</a></p>				