

# SLOVENSKI STANDARD **SIST EN ISO 15136-2:2007** 01-januar-2007

±bXiglf]′UˈbUZhY´]bʻnYaY´g\_Y[Uˈd`]bU'!`J]′Ub]′fdUʻb]ʻg]ghYa]ʻnUʻdfYfdUjUb^YʻbU dcj fý]bc'!'&"XY'. 'Dcj fý]bg\_]'dc[ cbg\_]'g]ghYa ]'fIGC') %% \*!&&\$\$\*L

Petroleum and natural gas industries - Progressing cavity pump systems for artificial lift -Part 2: Surface-drive systems (ISO 15136-2:2006)

Erdöl- und Erdgasindustrie - Exzenterschneckentiefpump-Fördersysteme - Teil 2: Übertage-Antriebssysteme (ISO 15136-2:2006)

# iTeh STANDARD PREVIEW

Industries du pétrole et du gaz naturel Pompes de fond à cavité progressive pour activation des puits - Partie 2: Systemes d'entraînement en surface (ISO 15136-2:2006)

https://standards.iteh.ai/catalog/standards/sist/66582b2b-6590-4576-Ta slovenski standard je istoveten zeb/sist-ENoISO315136-2:2006

ICS:

75.180.10 Oprema za raziskovanje in

Exploratory and extraction equipment

odkopavanje

SIST EN ISO 15136-2:2007 en,fr

# iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN ISO 15136-2:2007 https://standards.iteh.ai/catalog/standards/sist/66582b2b-6590-4576-bb2f-2ff91df6f8eb/sist-en-iso-15136-2-2007

# **EUROPEAN STANDARD**

# **EN ISO 15136-2**

# NORME EUROPÉENNE EUROPÄISCHE NORM

June 2006

ICS 75.180.10

#### **English Version**

# Petroleum and natural gas industries - Progressing cavity pump systems for artificial lift - Part 2: Surface-drive systems (ISO 15136-2:2006)

Industries du pétrole et du gaz naturel - Pompes de fond à cavité progressive pour activation des puits - Partie 2: Systèmes d'entraînement en surface (ISO 15136-2:2006)

Erdöl- und Erdgasindustrie - Exzenterschneckentiefpump-Fördersysteme - Teil 2: Übertage-Antriebssysteme (ISO 15136-2:2006)

This European Standard was approved by CEN on 19 May 2006.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Central Secretariat has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy: Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdomst/66582b2b-6590-4576-bb2f-

2ff91df6f8eb/sist-en-iso-15136-2-2007



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

## **Foreword**

This document (EN ISO 15136-2:2006) has been prepared by Technical Committee ISO/TC 67 "Materials, equipment and offshore structures for petroleum and natural gas industries" in collaboration with Technical Committee CEN/TC 12 "Materials, equipment and offshore structures for petroleum, petrochemical and natural gas industries", the secretariat of which is held by AFNOR.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by December 2006, and conflicting national standards shall be withdrawn at the latest by December 2006.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

#### **Endorsement notice**

The text of ISO 15136-2:2006 has been approved by CEN as EN ISO 15136-2:2006 without any modifications.

(standards.iteh.ai)

<u>SIST EN ISO 15136-2:2007</u> https://standards.iteh.ai/catalog/standards/sist/66582b2b-6590-4576-bb2f-2ff91df6f8eb/sist-en-iso-15136-2-2007

# INTERNATIONAL STANDARD

ISO 15136-2

First edition 2006-06-01

# Petroleum and natural gas industries — Progressing cavity pump systems for artificial lift —

Part 2: Surface-drive systems

iTeh STANDARD PREVIEW
Industries du pétrole et du gaz naturel — Pompes de fond à cavité
(progressive pour activation des puits —

Partie 2: Systèmes d'entraînement en surface

<u>SIST EN ISO 15136-2:2007</u> https://standards.iteh.ai/catalog/standards/sist/66582b2b-6590-4576-bb2f-2ff91df6f8eb/sist-en-iso-15136-2-2007



#### PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

# iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN ISO 15136-2:2007 https://standards.iteh.ai/catalog/standards/sist/66582b2b-6590-4576-bb2f-2ff91df6f8eb/sist-en-iso-15136-2-2007

#### © ISO 2006

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents		Page	
Forewo	ord	iv	
Introdu	ıction	v	
1	Scope	1	
2	Normative references	1	
3	Terms and definitions	2	
4	Abbreviated terms		
5 5.1 5.2 5.3 5.4	Functional specification  General  Surface-drive system type selection  Functional characteristics  Environmental compatibility	6 6 6 7	
5.5 5.6	Compatibility with related well equipment		
5.6 5.7	Design validation and product functional testing		
6 6.1 6.2 6.3 6.4 6.5 6.6 6.7 6.8 6.9	Technical specification General requirements. STANDARD PREVIEW Technical characteristics Design criteria. (Standards.iteh.ai) Design verification Design validation Product functional test Additional testing. 219740038607815136-2-2007 Allowable design changes Design scaling.	8 10 10 10 11	
7 7.1 7.2 7.3 7.4 7.5 7.6	Supplier requirements  General  Documentation and data control  Product identification  Quality control documentation  Design verification  Product functional testing	11 11 13 13	
8	Repair	17	
9	Preparation for shipment	17	
10	Product application changes	17	
Annex	A (normative) Requirements for elastomers and non-metallic materials	18	
Annex	B (informative) Brake system evaluation method	20	
Annex	C (informative) Installation guidelines	34	
Annex	D (informative) Operation guidelines	36	
Annex	E (informative) Equipment selection guidelines	38	
Annex	F (informative) User/purchaser functional specification form	39	
Annex	G (informative) Brake system test methods	41	
Annex	H (informative) Selection and use of sucker rods in PCP rotary pumping applications	44	
Riblion	rranhy	40	

# **Foreword**

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 15136-2 was prepared by Technical Committee ISO/TC 67, Materials, equipment and offshore structures for petroleum, petrochemical and natural gas industries, Subcommittee SC 4, Drilling and production equipment.

Teh STANDARD PREVIEW

ISO 15136 consists of the following parts: (standards.iteh.ai)

- Petroleum and natural gas industries progressing cavity pump systems for artificial lift Part 2: Surface-drive systems

# Introduction

This part of ISO 15136 has been developed by users/purchasers and suppliers/manufacturers of progressing cavity pump surface-drive systems and is intended for use in the petroleum and natural gas industry worldwide. ISO 15136-2 provides requirements and information to both parties in the selection, manufacturing, testing, and using progressing cavity pump surface-drive systems as defined in the scope. Further, ISO 15136-2 addresses supplier requirements, which set the minimum parameters with which suppliers shall comply to claim conformity with this International Standard.

ISO 15136-2 has been structured to allow for grades of increased requirements in quality control documentation. These variations allow the user/purchaser to select the grade that is required for a specific application.

There are two quality control documentation grades, which provide the user/purchaser the choice of requirements to meet their preference or application. Quality control documentation grade Q2 is the standard grade offered and quality control documentation grade Q1 provides additional documentation. Additional requirements can be specified by the user/purchaser as supplemental requirements.

Users of this International Standard should be aware that requirements above those outlined in this International Standard may be needed for individual applications. This International Standard is not intended to inhibit a supplier/manufacturer from offering, or the user/purchaser/from accepting, alternative equipment or engineering solutions. This may be particularly applicable where there is innovative or developing technology. Where an alternative is offered, the vendor should identify any variations from this part of ISO 15136-2 and provide details.

<u>SIST EN ISO 15136-2:2007</u> https://standards.iteh.ai/catalog/standards/sist/66582b2b-6590-4576-bb2f-2ff91df6f8eb/sist-en-iso-15136-2-2007

# iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN ISO 15136-2:2007 https://standards.iteh.ai/catalog/standards/sist/66582b2b-6590-4576-bb2f-2ff91df6f8eb/sist-en-iso-15136-2-2007

# Petroleum and natural gas industries — Progressing cavity pump systems for artificial lift —

# Part 2:

# **Surface-drive systems**

# Scope

This part of ISO 15136 provides requirements for the design, design verification and validation, manufacturing and data control, performance ratings and repair of progressing cavity pump surface-drive systems for use in the petroleum and natural gas industry. This part of ISO 15136 is applicable to those products meeting the definition of surface-drive systems. Additionally, informative annexes provide information on brake system selection, installation, and operation; and sucker rod selection and use.

Equipment not covered by this part of ISO 15136, unless integral by design, includes bottom drive systems, sucker rods, polished rod clamps, stuffing boxes, electrical controls, instrumentation, external power transmission devices, auxiliary equipment, such as belts, sheaves and equipment guards. These items might or might not be covered by other International Standards (e.g., 21)

# SIST EN ISO 15136-2:2007

Normative references iteh.ai/catalog/standards/sist/66582b2b-6590-4576-bb2f-

2ff91df6f8eb/sist-en-iso-15136-2-2007

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 2859-1, Sampling procedures for inspection by attributes — Part 1: Sampling schemes indexed by acceptance quality level (AQL) for lot-by-lot inspection

ISO 2859-2, Sampling procedures for inspection by attributes — Part 2: Sampling plans indexed by limiting quality (LQ) for isolated lot inspection

ISO 3601-1, Fluid power systems — O-rings — Part 1: Inside diameters, cross-sections, tolerances and size identification code

ISO 3601-3, Fluid power systems — O-rings — Part 3: Quality acceptance criteria

ISO 6506-1, Metallic materials — Brinell hardness test — Part 1: Test method

ISO 6507-1, Metallic materials — Vickers hardness test — Part 1: Test method

ISO 6508-1, Metallic materials — Rockwell hardness test — Part 1: Test method (Scales A, B, C, D, E, F, G, H, K, N, T)

ISO 9000, Quality management systems — Fundamentals and vocabulary

ISO 9712, Non-destructive testing — Qualification and certification of personnel

# ISO 15136-2:2006(E)

ISO 15156 (all parts), Petroleum and natural gas industries — Materials for use in  $H_2$ S-containing environments in oil and gas production

ASTM A370, Standard Test Methods and Definitions for Mechanical Testing of Steel Products

ASTM D1415, Standard Test Method for Rubber Property — International Hardness

ASTM D2240, Standard Test Method for Rubber Property — Durometer Hardness

ASTM E140, Standard Hardness Conversion Tables for Metals Relationship Among Brinell Hardness, Vickers Hardness, Rockwell Hardness, Superficial Hardness, Knoop Hardness, and Scleroscope Hardness

MIL STD 105E, Sampling Procedures and Tables for Inspection by Attributes

## 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 9000 and the following apply.

#### 3.1

#### applied torque

torque that is applied to the top of the drive string by the surface-drive system

#### 3.2

#### auxiliary equipment

equipment or components that are outside the scope of this part of ISO 15136 and are typically selected and/or installed by the user/purchaser; examples are sheaves and belts, motors, polished rod clamps, guards, motor controllers and torque limiting devices

#### 3.3 <u>SIST EN ISO 15136-2:2007</u>

## axial-load capacity https://stand

https://standards.iteh.ai/catalog/standards/sist/66582b2b-6590-4576-bb2f-

maximum allowable load that can be supported by the structure independent of auxiliary equipment capabilities

# 3.4

#### backspin

process by which the progressing cavity pump, the drive string and the power train turn in the direction opposite to normal operation and which is driven by the release of the torsional and fluid potential energy

#### 3.5

#### backspin-resisting torque

torque applied to the drive string to resist backspin

#### 3.6

#### brake-engagement speed

rotational speed at which the brake system engages during backspin

## 3.7

#### bottom-drive system

PCP drive system utilizing a downhole prime mover

# 3.8

#### brake system

system that provides controlled resistance to backspin

#### 3.9

# drive string

device transmitting power (usually sucker rods) between the surface-drive system and the PCP

#### 3.10

#### dynamic fluid level

depth from the wellhead to the top of the liquid column in the casing-tubing annulus under dynamic conditions

#### 3.11

#### direct drive

type of surface-drive system with no internal gear reduction

#### 3.12

#### driver sheave

pulley mounted on the prime mover shaft in belt driven surface-drive systems

#### 3.13

#### driven sheave

pulley mounted on the main shaft in belt-driven surface-drive systems

#### 3.14

#### flow rate

volume of fluid pumped per unit of time

#### 3.15

# fluid potential energy

energy stored in the production system due to the difference in fluid levels between the production tubing and the tubing-casing annulus

# 3.16 iTeh STANDARD PREVIEW

#### fluid head

pressure exerted by the fluid above the downhole pump ten.ai)

# 3.17

#### friction torque

SIST EN ISO 15136-2:2007

resistance to rotation of the drive string (inside the tubing) and the rotor (inside the stator) that is dependent upon factors including (but not limited to) well depth and trajectory, pump geometry and interference fit between rotor and stator, and stuffing box characteristics

# 3.18

#### gear-reduction drive

type of surface-drive system with an internal gear reduction

# 3.19

#### heat capacity

total energy absorbed by the surface-drive system divided by the change in surface-drive system temperature

## 3.20

# heat dissipation rate

rate at which energy is dissipated from the surface-drive system to its surroundings in the form of heat

#### 3.21

# hydraulic drive

type of surface-drive system powered by a hydraulic prime mover

#### 3.22

# hydraulic torque

torque induced by the differential pressure across the PCP acting on its effective cross-sectional area

#### 3.23

## input power rating

maximum allowable power, which may be supplied to the surface-drive system

#### 3.24

#### job lot

batch of material or components that have undergone the same process or series of processes

#### 3.25

## job-lot traceability

the ability of parts to be identified as originating from a job lot which identifies the included heat(s)

#### 3.26

## main shaft

central shaft of the surface drive that is connected to the drive string

#### 3.27

# maximum backspin speed

maximum speed allowed at the main shaft that will not compromise the integrity of the surface-drive system or auxiliary equipment

#### 3.28

#### maximum dynamic fluid level

maximum operating fluid level in the annulus as measured from the surface that ensures that, after a shutdown, the rotating speed does not exceed the maximum backspin speed for the surface-drive system

#### 3.29

### maximum operating torque

maximum allowable operating torque applied at the main shaft as specified by the supplier/manufacturer

# iTeh STANDARD PREVIEW

#### 3.30

#### moment of inertia

# (standards.iteh.ai)

ratio of the torque applied to the rotating components of the surface-drive system divided by the angular acceleration of those components about a common axis

SIST EN ISO 15136-2:2007

# 3.31 operating speed range

2ff91df6f8eb/sist-en-iso-15136-2-2007

range defined by the minimum and maximum operating speeds for the surface-drive system as specified by the supplier/manufacturer

#### 3.32

## operating temperature range

range defined by the minimum and maximum operating temperatures for the surface-drive system as specified by the supplier/manufacturer

### 3.33

#### polished-rod stick-up

length of polished rod extending above the top of the polished rod clamp

#### 3.34

#### power train

components of the surface-drive system and auxiliary equipment which transmit power from the prime mover into the drive string

NOTE Includes belts, sheaves, gears, direct coupling or other combinations to achieve the required output.

#### 3.35

#### prime mover

motor (typically hydraulic, electric or internal combustion) providing the torque to the power train

#### 3.36

#### production system

assembly of equipment that includes the downhole pump, drive string, production tubing, well casing, surfacedrive system, and auxiliary equipment

#### 3.37

#### progressing cavity pump

pump consisting of a stator and rotor whose geometry of assembly is such that it creates two or more series of lenticular, spiral, separated cavities

#### 3.38

#### repair

activities that include disassembly, re-assembly and testing with or without the replacement of parts and can include, machining, welding, heat treating or other manufacturing operations

#### 3.39

#### surface-drive system

assembly of equipment that, when installed, transmits torque from a prime mover into a progressing cavity pump drive string, supports the loads transmitted by the drive string and controls backspin of the drive string as applicable

#### 3.40

#### thrust bearing

device within a surface-drive system that supports the axial load transmitted by the drive string while allowing it to rotate

# iTeh STANDARD PREVIEW

#### 3.41

#### thrust-bearing rating

# (standards.iteh.ai)

2ff91df6f8eb/sist-en-iso-15136-2-2007

bearing manufacturer's published statistical ratings that serve as guidelines in the prediction of bearing life expectancies under given conditions

SIST EN ISO 15136-2:2007

https://standards.iteh.ai/catalog/standards/sist/66582b2b-6590-4576-bb2f-

# torque-limiting device

device that prevents the surface-drive system from applying a torque to the drive string greater than a prescribed value

#### 3.43

## torsional energy

energy stored in the drive string due to torque-induced elastic deformation

#### 4 Abbreviated terms

ANSI American National Standards Institute

ASME American Society of Mechanical Engineers

ASTM American Society for Testing and Materials

AQL Acceptance quality limit

IEC International Electrotechnical Commission

mo month

NACE National Association of Corrosion Engineers

NDE Nondestructive examination

PCP Progressing cavity pump

© ISO 2006 – All rights reserved