INTERNATIONAL STANDARD



14

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION MEXCHYPAPOCHAR OPPAHUSALUR TO CTAHCAPTUSALUR ORGANISATION INTERNATIONALE DE NORMALISATION

Straight-sided splines for cylindrical shafts — Nominal dimensions

Cannelures cylindriques à flancs parallèles — Dimensions nominales

First edition - 1978-07-01

Ref. No. ISO 14-1978 (E)

FOREWORD

ISO (the International Organization for Standardization) is a worldwide federation of national standards institutes (ISO member bodies). The work of developing International Standards is carried out through ISO technical committees. Every member body interested in a subject for which a technical committee has been set up has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council.

International Standard ISO 14 was developed by Technical Committee ISO/TC 32, Splines and serrations.

It was submitted directly to the ISO Council, in accordance with clause 6.13.1 of the Directives for the technical work of ISO. It cancels and replaces ISO Recommendation R 14-1955, which had been approved by the member bodies of the following countries:

Austria	India	Spain			
Belgium	Israel	Sweden			
Canada	Italy	Switzerland			
Chile	Japan	United Kingdom			
Denmark	New Zealand	U.S.A.			
Finland	Pakistan	Yugoslavia			
France	Portugal				
Germany	South Africa, Rep. of				

No member body had expressed disapproval of the document.

Straight-sided splines for cylindrical shafts — Nominal dimensions

1 SCOPE AND FIELD OF APPLICATION

This International Standard lays down nominal dimensions, in millimetres, of straight-sided splines for cylindrical shafts, light series and medium series.


2 DIMENSIONS

The values given in the table for d, D and B are the nominal dimensions common to shaft and hub.

3 DESIGNATION

The profile of a splined shaft or hub shall be designated by stating, in the following order: the number of splines N, the minor diameter d and the outside diameter D, these three numbers being separated by the sign \times ; for example:

Shaft (or hub) $6 \times 23 \times 26$



d	Light series			Medium series				
	Designation	~	D	В	Designation	N	D	В
11					6 × 11 × 14	6	14	3
13					6× 13× 16	6	16	3,5
16					6 × 16 × 20	6	20	4
18					6× 18× 22	6	22	5
21					6 × 21 × 25	6	25	5
23	6 × 23 × 26	6	26	6	6 × 23 × 28	6	28	6
26	6 × 26 × 30	6	30	6	6 × 26 × 32	6	32	6
28	6 × 28 × 32	6	32	7	6 × 28 × 34	6	34	7
32	8 × 32 × 36	8	36	6	8 × 32 × 38	8	38	6
36	8 × 32 × 40	8	40	7	8 × 36 × 42	8	42	. 7
42	8 × 42 × 46	8	46	8	8 × 42 × 48	8	48	8
46	8 × 46 × 50	8	50	9	8 × 46 × 54	8	54	9
52	8 × 52 × 58	8	58	10	8 × 52 × 60	8	60	10
56	8 × 56 × 62	8	62	10	8 × 56 × 65	8	65	10
62	8 × 62 × 68	8	68	12	8 × 62 × 72	8	72	12
72	10 × 72 × 78	10	78	12	10 × 72 × 82	10	82	12
82	10 × 82 × 88	10	88	12	10 × 82 × 92	10	92	12
92	10 × 92 × 98	10	98	14	10 × 92 × 102	10	102	14
102	10×102×108	10	108	16	10 × 102 × 112	10	112	16
112	10 × 112 × 120	10	120	18	10 ×112 ×125	10	125	18